High Scores II

Team Name:

Manager:
Recorder:
Presenter:
Analyst:
This is a Process Oriented Guided Inquiry Learning (POGIL) activity. You and your team will examine a working program. A series of questions will guide you through a cycle of exploration, concept invention, and application. There is strong evidence that this is more effective (and less boring) than a traditional lecture.
By the time you are done with this activity, you and your team should be able to:
• implement a set using a sorted array.
• implement a set using a binary search tree.
• implement a set by delegating to objects from the Java Collections Framework.
• explain the relative merits of these implementations.
• process information more effectively as a team.
Your team's recorder is responsible for writing your team's answers to the numbered questions on this form.
After you complete this activity, please fill out the short survey at
http://goo.gl/forms/HXjyuUb2ou
to improve this activity for future users.

Running the program

This program is not a game *per se*, but could be used to maintain a list of high scores for any game. Each member of your team should run HighScores.java and play with the program briefly.

1. Is everyone done running the program and ready to pay attention to the team?

You may need to go back to the game to answer some of the questions to come, but you should do so *deliberately*, because your team's manager assigned one or more people to find something out, not merely because you got bored with the conversation or thought you could answer a question better on your own.

- 2. Once there are several scores stored, are they sorted in increasing order, in decreasing order, or not at all?
- 3. What happens if you enter a score that is already present?

Set

_		α .	•
Exam	ine	Vet:	123//2
LAGIII		DCI.	java.

LA	annic Sci.java.
4.	What methods are specified by this interface?
5.	The code says that Set <t> extends Iterable<t>. Without seeking further information, write down what your team thinks this might mean.</t></t>
6.	How could you test your hypothesis?
7.	When you are confident that you know what it means for an interface to extend another interface, write it down.

Draw a UML class diagram of the relationships between all of the classes and interfaces in this project, as well as the built-in classes TreeSet and HashSet.


SortedArraySet

Examine SortedArraySet.java.

- 9. What further constraint does line 4 place on the type parameter T?
- 10. Assuming the first size elements of data are sorted, what is the order of the worst-case running time of find? (Hint: you've seen this algorithm before!)
- 11. What is the order of the worst-case running time of contains?
- 12. What does the loop on lines 57-60 accomplish?
- 13. What is the order of the worst-case running time of add?
- 14. What is the order of the worst-case running time of remove?

Binary search tree

The diagram below shows a binary search tree.



15. What is true of everything to the left of 46?

16. What is true of everything to the right of 46?

17. Within the part of the tree to the left of 46, what is true of everything to the left of 15?

18.	Within the part of the tree to the left of 46, what is true of everything to the right of 15?
19.	Complete the definition of a binary search tree below.
A b	inary search tree is either:
•	Empty, or
•	Consists of an item, a left subtree, and a right subtree. Both subtrees are themselves binary search trees. Everything in the left subtree is Everything in the right subtree is
-	spose you are looking in the tree for a particular item, say, 23. You start by comparing the item are seeking (23) to 46.
20.	Seeing that 23 < 46, what part of the tree do you now know that you won't have to examine in your search for 23?
21.	To which number would you now compare 23?
22.	List all of the numbers that you would examine in the search for 23.
23.	Now start again at the top, but this time looking for 50. Which numbers would you examine in this unsuccessful search?
24.	Suppose you now wanted to add 50 to the tree. How could you do so, changing the tree as little as possible but keeping it within the definition of a binary search tree?

25.	How would you alter the tree to remove 70°
26.	What if you wanted to remove 8?

27. What if you wanted to remove 46?

BinarySearchTreeSet

 $Examine\ Binary Search Tree Set. java.$

28.	In terms of the trees discussed in the previous section, does each pass through the loop in contains move one level <i>up</i> or <i>down</i> the tree?
29.	Again in terms of the tree, when does the loop end, returning false?
30.	When does the loop end early, returning true?
31.	The one-argument add method calls a second, recursive, two-argument add method. In what situation does the recursive version <i>not</i> create a new BinaryNode?
32.	Of what class does iterator directly create an instance?
33.	Consider the tree diagram from the previous section. Which numbers would be added to list by the first recursive call on line 96?
34.	Which number would be added on line 97?

35.	Which numbers would be added by the second recursive call on line 98?

36. What is the base case of the recursion in traverse?

37. Describe, in plain English, the algorithm carried out by traverse. Assume your reader understands recursion but does not know this particular algorithm.

JcfTreeSet and JcfTreeSet

Examine JcfTreeSet.java. ("JCF" stands for Java Collections Framework, a library of classes in the java.util package.)

- 38. What is the type of the instance variable in this class?
- 39. How do add, contains, iterator, and remove get their work done?
- 40. Discuss the advantages of writing a class this way rather than building it "from scratch", as in SortedArraySet and BinarySearchTreeSet.

T .	T OTT 1 O .	•
Hyamine	JcfHashSet.	121/2
Lamine	Jen rashbet.	java.

- 41. How does this class differ from JcfTreeSet?
- 42. Speculate on why the designers of the Java Collections Framework would have supplied two classes that provide the same methods.

Comparison of implementations

Modify HighScores.java so that the main method calls iterationTest. Run the program.

43. Do all four implementations sort the scores in the same way? If so, are they sorted in increasing or decreasing order? If not, how do they differ?

Modify HighScores.java so that the main method calls speedTest. Run the program.

- 44. Which implementation is fastest?
- 45. Which implementation is slowest?
- 46. Which implementation would you use if you cared about iterating through the scores in order?
- 47. Which implementation would you use if you *did not* care about iterating through the scores in order?
- 48. Describe a plan for modifying the program to associate a player name with each high score.

49.	If there are good set implementations built in to Java, why do we bother teaching you to build them yourselves?
	Stop here and wait for the other teams. If your instructor has given you a way to indicate that you have reached this point, use it now. Once all teams are ready, there will be a short discussion involving the whole class. Your team's presenter should be pared to present any of your team's previous answers to the class. This discussion is also a different team (through your presenter) to ask any questions you have.
Plea	ase fill out the survey at http://goo.gl/forms/HXjyuUb2ou.