Document Identifier: **PMC8197287**

SciScore Report

Below you will find your SciScore report containing three tables. Your score is calculated based on adherence to scientific rigor criteria (Table 1) and identification of key biological resources (Table 2). Table 3 contains statistical tests and oligonucleotides but is not scored. If SciScore makes any mistakes, please contact us to help us learn and improve.

Table 1: Rigor Adherence Table

Ethics
IRB: The regional ethics board approved all studies and the donors gave their written informed consent.
Consent: The regional ethics board approved all studies and the donors gave their written informed consent.
Inclusion and Exclusion Criteria
not detected.
Attrition
not detected.
Sex as a biological variable
) metabolically well-characterized women described previously (33) .
Subject Demographics
Weight: The first cohort consists of 30 obese (body mass index BMI > 30 kgm2) and 26 nonobese (BMI < 30 kgm2
Age: Cell Culture hASC were isolated from subcutaneous adipose tissue of a male donor (16 years old , BMI 24kgm2) , expanded and differentiated in vitro into adipocytes as previously described (37)
Randomization
not detected.
Blinding
not detected.
Power Analysis
As regards power calculation we focused on the published microarrays and used the method by Liu and Hwang (50) to determine the appropriate sample size for such experiments.
Replication
Each siRNA pool was run in triplicate.

Number: Each siRNA pool was run in triplicate.	
Cell Line Authentication	
Authentication: Data from the 26 nonobese women from the same cohort were used for picking genes regulated by morphology (hyperplasiahypertrophy) as described in (30) .	
Data Information	
Identifiers: RNAseq data are accessible on GEO with the accession number GSE164413 (reviewer token ctonmgksrjqpdwz).	GSE164413

Table 2: Key Resources Table

Your Sentences	REAGENT or RESOURCE	SOURCE	IDENTIFIER
Antibodies			
The membrane was blocked in 3 ECL Advance blocking agent (GE Healthcare) and incubated with primary antibodies against JARID2 (D6M9X , 1:500 dilution , Cell Signaling Technology Danvers , MA , USA Cat 13594 , RRID:AB_2798269 (45))	JARID2	Cell Signaling Technology	(Cell Signaling Technology Cat# 13594, RRID:AB_2798269)(link)
	D6M9X		
Secondary anti-rabbit HRP antibody was used at 1:10 000 (Sigma-Aldrich , St . Louis , MO , USA , Cat A0545 , RRID:AB_257896 (46)) .	Secondary anti-rabbit HRP antibody		
	anti-rabbit HRP	Sigma-Aldrich	(Sigma-Aldrich Cat# A0545, RRID:AB_257896)(link)
Software and Algorithms			
The proteins were visualized by chemiluminescence using Amersham ECL Select Western Blotting Detection Reagent (GE Healthcare) , ChemiDoc XRS+ system and Quantity One Software (Bio-Rad)	Quantity One		Suggestion: Quantity One 1-D Analysis Software (RRID:SCR_014280)(link)
Sample demultiplexing was performed using bcl2fastq (v2.20.0).	bcl2fastq		
Sample quality was assessed using FastQC (v0.11.8) and MultiQC (v1.7).	FastQC		
	MultiQC		
Reads were aligned to a reference built from Ensembl GRCh38 genome sequences using STAR (v2.6.1d).	STAR		
Counts for each gene were obtained by featureCounts (v1.5.1) using the GRCh38.99 GTF file from Ensembl.	featureCounts		
	Ensembl		Suggestion: Ensembl (RRID:SCR_002344)(link)
Bioconductor package DESEq2 was used for count normalization and sample group comparisons, generating log2 fold changes, Wald test P values and P values adjusted for multiple testing (Benjamini-Hochberg method).	Bioconductor		Suggestion: Bioconductor (RRID:SCR_006442)(link)
	DESEq2		
Pathway Analysis Ingenuity Pathway Analysis (IPA) software (Ingenuity Systems, QIAGEN, http:www.ingenuity.com) was used to determine the upstream regulators in RNAseq experiments and for canonical pathway analysis in the screening.	Ingenuity Pathway Analysis		Suggestion: Ingenuity Pathway Analysis, RRID:SCR_008653(link)
	http:www.ingenuity.com		

IBM SPSS Statistics 22 software (SPSS, Chicago, IL, USA) or GraphPad Prism version 7 and 9 (GraphPad Software, La Jolla, California, USA) were used for statistical analysis.	SPSS		Suggestion: SPSS, RRID:SCR_002865(link)
	GraphPad Prism		
	GraphPad		Suggestion: GraphPad Prism, RRID:SCR_002798(link)

Other Entities Detected

Your Sentences	Recognized Entity
Statistical Tests	
Bioconductor package DESEq2 was used for count normalization and sample group comparisons, generating log2 fold changes, Wald test P values and P values adjusted for multiple testing (Benjamini-Hochberg method).	Wald test
	Benjamini-Hochberg
Statistical Analysis The data were tested for normal distribution with the Shapiro-Wilk test.	Shapiro-Wilk test
If the criteria for normal distribution were fulfilled, 1-way analysis of variance (ANOVA) with subsequent Bonferroni correction post hoc test was utilized.	analysis of variance
	ANOVA
	Bonferroni
If only 2 groups were compared, Students t-test was used.	t-test
When the criteria for normal distribution were not achieved, the nonparametric Kruskal-Wallis and Mann-Whitney pair-wise comparison tests were applied.	Kruskal-Wallis
	Mann-Whitney pair-wise comparison tests
Pearson test was used to correlate normally distributed measures (JARID2 expression with adipose tissue morphology, glycerol release with number of differentiated cells) and Spearman test was used to correlate the results from 2 screens.	Pearson test
	Spearman test

SciScore is an automated tool that is designed to assist expert reviewers by finding and presenting formulaic information scattered throughout a paper in a standard, easy to digest format. ***SciScore is not a substitute for expert review.*** SciScore also checks for the presence and correctness of several unique identifiers, including RRIDs (research resource identifiers) in the manuscript, detects sentences that appear to be missing RRIDs, and can even suggest RRIDs under certain circumstances. **All RRID suggestions should be verified;** only the author can know whether the suggestions are correct.

For a full description of scored criteria and tips for improving your score, please see https://www.scicrunch.com/sciscorereport-faq