Document Identifier: **PMC8232908**

SciScore Report

Below you will find your SciScore report containing three tables. Your score is calculated based on adherence to scientific rigor criteria (Table 1) and identification of key biological resources (Table 2). Table 3 contains statistical tests and oligonucleotides but is not scored. If SciScore makes any mistakes, please contact us to help us learn and improve.

Table 1: Rigor Adherence Table

Ethics
not required.
Inclusion and Exclusion Criteria
In the case of pluripotent stem cell datasets, we only analyzed ESCs derived from normal fertilized blastocysts and iPSCs derived from normal cells (i.e., immortalized cells were excluded).
Attrition
not required.
Sex as a biological variable
not required.
Subject Demographics
Age: not required.
Weight: not required.
Randomization
Then, we randomly assigned cells to two groups for each embryo stage (eight cell groups in total).
Blinding
not detected.
Power Analysis
not detected.
Replication
Methylated and unmethylated cytosines of technical repeats were summed for each position.
Type: Methylated and unmethylated cytosines of technical repeats were summed for each position.
Data Information

Identifiers: Development of a mouse multi-tissue rDNA clock A multi-tissue mouse RRBS dataset (GSE120132) was used for training and testing the clock by cross-validation.	GSE120132
Identifiers: An additional blood mouse RRBS dataset (GSE80672) was used for testing samples of an independent study.	GSE80672

Table 2: Key Resources Table

Your Sentences	REAGENT or RESOURCE	SOURCE	IDENTIFIER
Software and Algorithms			
MATERIALS AND METHODS Acquisition and processing of sequencing datasets Raw sequences were downloaded and extracted using the Sequence Read Archive (SRA) Toolkit.	Sequence Read Archive		Suggestion: DDBJ Sequence Read Archive (RRID:SCR_001370)(link)
Reads were trimmed and quality-filtered by TrimGalore!	TrimGalore		
Methylation levels were extracted using Bismark v0.22.2 (68) in two separate processes: (i) For rDNA clocks, reads were mapped to the mouse rDNA sequence (BK000964.3), and (ii) for genomic clocks, reads were mapped to the complete mouse genome sequence (mm10GRCm38.p6).	Bismark		Suggestion: Bismark (RRID:SCR_005604)(link)
In the case of dataset 6, we directly used the available BED (browser extensible data) files URLs were extracted from Gene Expression Omnibus (GEO) files.	Gene Expression Omnibus		Suggestion: Gene Expression Omnibus (GEO) (RRID:SCR_005012)(link)
Then, fivefold cross-validations were performed on all of the 166 samples for different l parameters of ElasticNet (Scikit-learn v0.23.2) to find the optimal l parameter (fig.	Scikit-learn		Suggestion: scikit-learn (RRID:SCR_002577)(link)
Statistical analysis We used the Python packages SciPy (v1.3.1) and Scikit-learn (v0.23.2) for statistical analysis.	Python		Suggestion: python-bx (RRID:SCR_024202)(link)
	SciPy		Suggestion: SciPy (RRID:SCR_008058)(link)

Other Entities Detected

Your Sentences	Recognized Entity
Statistical Tests	
Two-sided t test was calculated for comparing two groups.	t test
Correlations were evaluated by Pearson correlation coefficient (r) or Spearman rank correlation coefficient (Rho).	Pearson correlation
	Spearman rank correlation

SciScore is an automated tool that is designed to assist expert reviewers by finding and presenting formulaic information scattered throughout a paper in a standard, easy to digest format. ***SciScore is not a substitute for expert review.*** SciScore also checks for the presence and correctness of several unique identifiers, including RRIDs (research resource identifiers) in the manuscript, detects sentences that appear to be missing RRIDs, and can even suggest RRIDs under certain circumstances. **All RRID suggestions should be verified;** only the author can know whether the suggestions are correct.

For a full description of scored criteria and tips for improving your score, please see https://www.scicrunch.com/sciscorereport-faq