Document Identifier: **PMC8649378**

SciScore Report

Below you will find your SciScore report containing three tables. Your score is calculated based on adherence to scientific rigor criteria (Table 1) and identification of key biological resources (Table 2). Table 3 contains statistical tests and oligonucleotides but is not scored. If SciScore makes any mistakes, please contact us to help us learn and improve.

Table 1: Rigor Adherence Table

Ethics
IRB: The study was approved by the Ethics Committee of The First Affiliated Hospital of Wenzhou Medical University .
Consent: Informed patient consent was not required as the results showed are based upon the data generated by the TCGA database.
Inclusion and Exclusion Criteria
not detected.
Attrition
not detected.
Sex as a biological variable
not detected.
Subject Demographics
Age: not detected.
Weight: not detected.
Randomization
not detected.
Blinding
not detected.
Power Analysis
not detected.
Replication
2.7 Proliferation assay To evaluate the proliferation speed, 3 x 103 cells were seeded into a 96-well plate per well (Greiner bio-one), and then a time-series assay every 2 days was carried out in triplicate.

Number: 2.7 Proliferation assay To evaluate the proliferation speed, 3 x 103 cells were seeded into a 96-well plate per well (Greiner bio-one), and then a time-series assay every 2 days was carried out in triplicate.

Table 2: Key Resources Table

Your Sentences	REAGENT or RESOURCE	SOURCE	IDENTIFIER
Software and Algorithms			
Annotation information for the RNA data was provided by the Ensemble database derived from biomaRt package.	biomaRt		Suggestion: biomaRt (RRID:SCR_019214)(link)
13 The differentially expressed (DE) lncRNAs , miRNAs , and mRNAs between 32 normal samples and 372 cancer samples were identified by the limma package.	limma		Suggestion: LIMMA (RRID:SCR_010943)(link)
For the interaction between miRNA and mRNA , we used the miRNAtap package (https:bioconductor.orgpackagesreleasebiochtmlmiRNAtap . html) , which consisted of commonly used five reliable and online datasets , including Pictar (https:pictar . mdc-berlin . de) , DIANA , 15 Targetscan , 16 miranda , 17 and mirdb .	Pictar		Suggestion: PicTar (RRID:SCR_003343)(link)
2.4 Gene sets enrichment analysis To reveal the function of the lncRNA-associated ceRNA network , the DE mRNAs derived from ceRNA were subjected to gene sets enrichment analysis based on gene ontology (GO) , Kyoto Encyclopedia of Genes and Genomes (KEGG) , and REACTOME annotation with the clusterProfiler package.	clusterProfiler		Suggestion: clusterProfiler (RRID:SCR_016884)(link)
22 KEGG is widely used as a reference for integrating large-scale molecular datasets generated by sequencing and high-throughput experimental technologies .	KEGG		
John Wiley & Sons, Ltd 2.6 siRNA knockdown in cell line siRNA designed and chemically synthesized by GenePharma.	GenePharma		

Other Entities Detected

Your Sentences	Recognized Entity
Statistical Tests	
Those two factors were indicated via the Pearson correlation and regulation similarity .	Pearson correlation
Then , univariate Cox regression analysis was used to find the prognosis-related lncRNA .	Cox regression
In addition , the KM plot with log-rank test was carried out to further validate the prognosis-related lncRNA .	log-rank test
2.9 Statistical analysis The students t test was used to compare the continuous variables.	t test
The chi-squared test was employed for the categorical variables.	chi-squared test
Oligonucleotides	
TABLE 1 Forward and reverse primer sequences used for quantitative PCR Gene Sequences (5-3) INHBA-AS1 F: CCTTTCCAGTCAGGTGGGTC R: CCCAGGGGAAGCATCACTTT CCDC144NL-AS1 F: CCCTCCTCACGGCATAGAAC R: TTAGTGGTTCCTTGGGAGTCG	CCTTTCCAGTCAGGTGGGTC
	CCCAGGGGAAGCATCACTTT
	CCCTCCTCACGGCATAGAAC
G COL5A2 F: CAAACTGGGCGGAAGCAAG R: TTCACCATATCCTTCATCCTCG MATN3 F: GACAGAACAGGGTCCCATCA R: GCACACTTGTCACGGACTGA GAPDH F: CTGGGCTACACTGAGCACC R: AAGTGGTCGTTGAGGGCAATG hsa-miR-98 RT: CAGTGCAGGGTCCGAGGTCAGAGC CACCTGGGCAATTTTTTTTTTTat gccca F: AACAAGCTGCACATGCTGGG R: AACAATCTGCACATGCTGGGG hsa-miR-128-1 RT: CAGTGCAGGGTCCGAGGTCAGAGC CACCTGGGCAATTTTTTTTTTTga agca F: AACAAGTGAGCTGTTGGATTCGG R: AACAATTGAGCTGTTGGATTCGGG U6 F: CTCGCTTCGGCAGCACA R: AACGCTTCACGAA TTTGCGT Abbreviations: F, forward R, reverse.	CAAACTGGGCGGAAGCAAG
	TTCACCATATCCTTCATCCTCG
	GACAGAACAGGGTCCCATCA
	GCACACTTGTCACGGACTGA
	CTGGGCTACACTGAGCACC
	AAGTGGTCGTTGAGGGCAATG
	AACAAGCTGCACATGCTGGG
	AACAATCTGCACATGCTGGGG
	AACAAGTGAGCTGTTGGATTCGG
	AACAATTGAGCTGTTGGATTCGGG
	CTCGCTTCGGCAGCACA
	AACGCTTCACGAA

SciScore is an automated tool that is designed to assist expert reviewers by finding and presenting formulaic information scattered throughout a paper in a standard, easy to digest format. ***SciScore is not a substitute for expert review.*** SciScore also checks for the presence and correctness of several unique identifiers, including RRIDs (research resource identifiers) in the manuscript, detects sentences that appear to be missing RRIDs, and can even suggest RRIDs under certain circumstances. **All RRID suggestions should be verified;** only the author can know whether the suggestions are correct.

For a full description of scored criteria and tips for improving your score, please see https://www.scicrunch.com/sciscorereport-faq