Document Identifier: **PMC8696108**

SciScore Report

Below you will find your SciScore report containing three tables. Your score is calculated based on adherence to scientific rigor criteria (Table 1) and identification of key biological resources (Table 2). Table 3 contains statistical tests and oligonucleotides but is not scored. If SciScore makes any mistakes, please contact us to help us learn and improve.

Table 1: Rigor Adherence Table

Ethics
not required.
Inclusion and Exclusion Criteria
not required.
Attrition
not required.
Sex as a biological variable
not required.
Subject Demographics
Age: not required.
Weight: not required.
Randomization
3.4.2 Concordance analyses We estimated within-method concordance (replicability) by randomly splitting each dataset into two equally sized parts and evaluating the Jaccard index between the two lists of the 500 most variable genes (defined by the function FindVariableFeature of the Seurat package with method vst) after normalization.
Blinding
not detected.
Power Analysis
not detected.
Replication
not required.
Data Information

Availability: 3.8 Software and data availability An implementation of PsiNorm is available in the scone Bioconductor package available at https:bioconductor.orgpackagesscone.	
Identifiers: The raw data of the mixology dataset are available in GEO with accession code GSE118767.	GSE118767

Table 2: Key Resources Table

Your Sentences	REAGENT or RESOURCE	SOURCE	IDENTIFIER
Software and Algorithms			
In the unsupervised approach, we applied principal component analysis (PCA) on the log-normalized counts and, using the first 50 PCs, we identified clusters using a partitional method (clara in the cluster R package) with k (number of groups) equal to the known number of clusters.	cluster		Suggestion: Cluster (RRID:SCR_013505)(link)
3.4.2 Concordance analyses We estimated within-method concordance (replicability) by randomly splitting each dataset into two equally sized parts and evaluating the Jaccard index between the two lists of the 500 most variable genes (defined by the function FindVariableFeature of the Seurat package with method vst) after normalization.	Seurat		
The lists of 100 most differentially expressed genes were obtained using edgeR with normalization factors derived from the global scaling methods evaluated in this study, including PsiNorm (i.e. the estimated alpha parameters).	edgeR		Suggestion: edgeR (RRID:SCR_012802)(link)
3.8 Software and data availability An implementation of PsiNorm is available in the scone Bioconductor package available at https:bioconductor.orgpackagesscone.	Bioconductor		Suggestion: Bioconductor (RRID:SCR_006442)(link)

SciScore is an automated tool that is designed to assist expert reviewers by finding and presenting formulaic information scattered throughout a paper in a standard, easy to digest format. ***SciScore is not a substitute for expert review.*** SciScore also checks for the presence and correctness of several unique identifiers, including RRIDs (research resource identifiers) in the manuscript, detects sentences that appear to be missing RRIDs, and can even suggest RRIDs under certain circumstances. **All RRID suggestions should be verified;** only the author can know whether the suggestions are correct.

For a full description of scored criteria and tips for improving your score, please see https://www.scicrunch.com/sciscorereport-faq