

MAlice Language Specification

Peter Hamilton

Sarah Tattersall

December 2, 2011

1 BNF Grammar

S'	→	code_seperator
code_seperator	→	statement_list function_seperator functions statement_list
statement_list	→	statement seperator statement seperator statement_list
seperator	→	'and' 'but' 'then' '.' '?' '.'
statement	→	expression 'spoke' expression 'said' 'Alice' 'Alice' 'found' expression 'what' 'was' expression expression 'thought' 'Alice' statement 'too' id 'was' 'a' type id 'became' expression array_access 'became' expression

id **'had'** expression type |
'eventually' **'('** expression_logical **)'** **'because'** statement_list **'enough'** **'times'** |
'either' **'('** expression_logical **)'** **'so'** statement_list **'or'** statement_list **'Alice'** **'was'** **'unsure'** **'which'** |
'perhaps' **'('** expression_logical **)'** **'so'** statement_list **'Alice'** **'was'** **'unsure'** |
'perhaps' **'('** expression_logical **)'** **'so'** statement_list logical_clauses |
 expression

expression → id **'('** function_arguments **)'** |
 id **'went'** **'through'** id |
'(' expression **)'** |
'~' expression |
 id **'drank'** |
 id **'ate'** |
 expression **'|'** expression |
 expression **'^'** expression |
 expression **'&'** expression |
 expression **'+'** expression |
 expression **'-'** expression |
 expression **'*'** expression |
 expression **'/'** expression |
 expression **'%'** expression |
 expression_logical |
 array_access |
 factor

expression_logical → expression **'=='** expression |
 expression **'<'** expression |
 expression **'>'** expression |
 expression **'>='** expression |
 expression **'<='** expression |
 expression **'!=='** expression |
 expression **'&&'** expression |
 expression **'||'** expression

array_access → id expression **'piece'**

factor	→	number letter id sentence
type	→	'number' 'letter' 'sentence'
functions	→	function function_seperator functions function
function_seperator	→	'The' 'room' 'The' 'Looking-Glass'
function	→	id '(' arguments)' 'contained' 'a' type statement_list id '(' arguments)' 'contained' 'a' type id 'changed' 'a' type statement_list
logical_clauses	→	logical_clause logical_clauses 'Alice' 'was' 'unsure' 'which'
logical_clause	→	'or' 'maybe' '(' expression_logical)' 'so' statement_list 'or' statement_list
arguments	→	argument '.' arguments argument
argument	→	type id 'spider' type id
function_arguments	→	function_argument '.' function_arguments function_argument
function_argument	→	expression

2 Precedences

```
precedence = (
    ('left', 'L_OR'),
```

```
('left', 'L_AND'),
('left', 'L_EQUAL', 'L_NOT_EQUAL'),
('left', 'L_LESS_THAN', 'L_LESS_THAN_EQUAL', 'L_GREATER_THAN', 'L_GREATER_THAN_EQUAL'),
('left', 'B_OR'),
('left', 'B_XOR'),
('left', 'B_AND'),
('left', 'PLUS', 'MINUS'),
('left', 'MULTIPLY', 'DIVIDE', 'MOD'),
('right', 'INCREMENT', 'DECREMENT', 'B_NOT'),
('left', 'L_PAREN', 'R_PAREN'),
)
```