

React Fundamentals

Styling Components




Peter Kassenaar –
info@kassenaar.com



Styling components

Creating local or global styles for your application

CSS styling in React apps



- Components can receive styles in different ways:

1. From **global** imported styles

- Like Bootstrap, Materialize, Tailwind CSS, etc.
- Like we have done in the previous projects


2. From **inline** styles

- Use CSS-in-JavaScript technique

3. From CSS **modules**


- Create `.module.css` files for your styles

1. Global styles



- **Libraries:** Just import the CSS in `../src/index.js`, like we have done before
 - Bootstrap, Tailwind CSS, Foundation, Framework7, etc.
- **Custom global CSS**
 - Place in `index.css`, import also
 - Can also be done in `App.js/App.css`
- **Pro:** styles are automatically available, everywhere
- **Con:** possible naming conflicts, too many styles in global scope


Example global styles – best practices




```
// index.js - import global styling
import 'bootstrap/dist/css/bootstrap.min.css'
import './index.css';
```

```
// App.js
function App() {
  return (
    <div className="container">
      <div className="row">
        <col-6>
          <h1 className="alert alert-info">
            My awesome bootstrap site
          </h1>
        </col-6>
      </div>
    </div>
  );
}
```

**Global styles
available in all
components**



Composing class names




It is common for the `className` property to depend on the component `props` or `state`:

```
render() {  
  let className = 'menu';  
  if (this.props.isActive) {  
    className += ' menu-active';  
  }  
  return <span className={className}>Menu</span>  
}
```

This way you compose the exact styles of (global) class names that the component requires.


It responds automatically to changes in `props` or `state`.

2. Inline styles




*"In React, inline styles are not specified as a string. Instead they are specified with an **object** whose key is the **camelCased** version of the style name, and whose value is the style's CSS value"*


Transformed in the DOM



Defining inline, inline styles



The value of the `style` attribute has to be an object, so double curly braces:

A large red arrow pointing downwards from the text above to the code block below.

```
<div style={headline}>
  <h2>Today's forecast:</h2>
  Expect <span style={{fontStyle: 'italic'}}>rainy weather</span>
  from Friday till Sunday afternoon
</div>
```

Verdict: try to avoid this. It's ugly.


No `<style>` block in components

```
<div style={headline}>
  <h2>Today's forecast:</h2>
  ...
  <style>
    .boldText{
      font-variant: 'bold', // invalid
      fontVariant: 'bold'  // also invalid
    }
  </style>
</div>
```



Invalid!
Will not compile

Verdict Inline Styles




- Pro

- enclosed/scoped styles
- No chance of naming conflicts


- Con

- You might find yourself repeating styles in different components
- Quickly leads to bloated code and less SoC
- Less convenient `camelCasing` for style properties
- May harm performance of rendering the DOM


Workshop



- Create a new component.
- Define some constants as inline styles in this component, for instance
 - `.warning`, `.info` and `.rejected`.
 - Give them some properties
- Use the classes in the component
- Example `../300-styling-components`
 - `../components/InlineStyles.js`



3. CSS Modules



- If you want to achieve the same goal as *scoped styles* in Vue or Angular, use [CSS Modules](#)
- The styles are only available in components that import them
- The compiler adds random hashes to the style names
- Styles are in separate `.css` files
- Styles have the `.module.css` extension

CSS Modules – structure

```
/* cssModules.module.css */  
.warning {  
  background-color: orange;red;  
  color: white;  
  font-weight: bold;  
  border-radius: 4px;  
  padding: 6px;  
}  
...
```

1. Separate
.module.css file

2. Import in
component

```
import React, {Component} from 'react';  
import styles from './cssModules.module.css'  
  
class CssModules extends Component {  
  render() {  
    return (  
      <div>  
        <div className={styles.warning}>  
          This is the .warning class from a CSS module  
        </div>  
        ...  
      </div>  
    );  
  }  
}  
  
export default CssModules;
```


3 Use in component

CSS Modules in the UI/DOM

The image shows a web application interface on the left and a browser developer tools window on the right. The web application has a light blue header with the text "My awesome bootstrap site". Below it, there's a section titled "Today's forecast:" with the text "Expect *rainy weather* from Friday till Sunday afternoon". At the bottom, there are two colored boxes: an orange one with the text "This is the .warning class from a CSS module" and a purple one with the text "This is the .info class from a CSS module". A red arrow points from the orange box to the developer tools. The developer tools window shows the "Elements" tab with a tree view. A `<div class="cssModules_warning__1eB_S">` element is highlighted and circled in red. The "Styles" panel shows the `background-color: #ff4500;` rule for this class. The breadcrumb at the bottom of the Elements panel shows the path: `html > body > #root > div > div > div.col-6 > div > div.cssModule`.

A random hash is added to the style name,
so no naming conflicts with other components

More info on CSS Modules



The screenshot shows the 'Create React App' documentation page. The left sidebar contains a navigation menu with categories like 'Welcome', 'Getting Started', 'Development', 'Styles and Assets', 'Building your App', 'Testing', 'Back-End Integration', 'Deployment', 'Advanced Usage', and 'Support'. The 'Styles and Assets' category is expanded, showing sub-items like 'Adding Stylesheets', 'Adding CSS Modules' (which is highlighted), 'Adding Sass Stylesheets', 'Adding CSS Reset', 'Post-Processing CSS', 'Adding Images, Fonts, and Files', 'Loading .graphql Files', 'Using the Public Folder', and 'Code Splitting'. The main content area is titled 'Adding a CSS Modules Stylesheet'. It includes a note about the minimum version of react-scripts, an explanation of the CSS Modules file naming convention, a tip about preprocessing with Sass, and a code example for a CSS module file named 'Button.module.css'.

Create React App Docs Help GitHub Search

Adding a CSS Modules Stylesheet

Note: this feature is available with `react-scripts@2.0.0` and higher.

This project supports **CSS Modules** alongside regular stylesheets using the `[name].module.css` file naming convention. CSS Modules allows the scoping of CSS by automatically creating a unique classname of the format `[filename]_[classname]_[hash]`.

Tip: Should you want to preprocess a stylesheet with Sass then make sure to [follow the installation instructions](#) and then change the stylesheet file extension as follows:
`[name].module.scss` or `[name].module.sass`.


CSS Modules let you use the same CSS class name in different files without worrying about naming clashes. Learn more about CSS Modules [here](#).

Button.module.css

```
.error {  
  background-color: red;  
}
```

<https://create-react-app.dev/docs/adding-a-css-modules-stylesheet/>

Warning!




In CSS Modules, you can NOT have CSS classes with dashes in their name, like


```
/*illegal! */  
.info-important {  
  background-color: #c1ab99;  
}
```

(unless you `eject` your configuration and setup Webpack yourself. A hyphen is an illegal char in variable names, <https://spectrum.chat/gatsby-js/general/css-modules-not-working-with-classnames-including-dashes~1a69e0d8-d8d8-4a03-b9aa-ad491e6c2093>)

Workshop



- Create a new component.
- Create a new CSS module, again creating some classes in it
 - `.warning`, `.info` and `.rejected`.
- Import the module and use the classes in the component.
- Can you also import them in another component? If yes, how would you (re)structure your app?
- Example `../300-styling-components`
 - `../components/cssModules.js`






Using SASS


Creating `.sass` files and compiling/using them

Team React:




*"Generally, we recommend that you **don't reuse** the same CSS classes across different components.*

*For example, instead of using a `.Button` CSS class in `<AcceptButton>` **and** `<RejectButton>` components, we recommend creating a `<Button>` component with its own `.Button` styles, that **both** `<AcceptButton>` **and** `<RejectButton>` can render"*




*"Following this rule often **makes CSS preprocessors less useful**, as features like mixins and nesting are replaced by component composition."*

However, if you want/need to use Sass:



- Default available in CRA 2.0.0+
 - no more need to `eject` and configure `webpack-sass-loader` yourself
- First, install sass in your project:
 - `npm install sass [--save]`
- Rename your `.css` file to `.scss`.
- Use Sass variables, mixins, nesting, as usual
 - You can also `@import` other `.scss` files

Adding .scss files



```
/* SassComponent.scss - a Sass file ... */

// 1. Variables for the different header colors
$header1: #c1ab99;
$header2: #ae8360;
$header3: #b15145;
$forecolor: #fff9ff;

// Default styles
.header {
  width: 100%;
  height: 50px;
}

//Use the variables
.header1 {
  background-color: $header1;
  color: $forecolor;
}

...
```


Import .scss file

```
import './SassComponent.scss'

class SassComponent extends Component {
  render() {
    return (
      <div>
        <p>4. Using Sass in a React project</p>
        <h1>A Sass example file</h1>
        { /*1. Header/variables example*/ }
        <h2>Variables example</h2>
        <div className="header header1">color : $header1</div>
        <div className="header header2">color : $header2</div>
        <div className="header header3">color : $header3</div>
      </div>
    )
  }
}
```


Use className as usual

Result




<SassComponent />


Sass CSS Modules



- You can also use Sass CSS modules (i.e. combine CSS modules with Sass).
- Naming convention: `myComponent.module.scss`
- Combine the two techniques as usual.
- Don't forget to import the module and assign it to a `(styles)` variable:
 - `<h1 className={styles.heading}...</h1>`

More info on Sass/Modules



Bits and Pieces

WRITEBIT BLOGJAVASCRIPTWEBDEVREACTANGULARVUE | COMPONENT PLATFORM


How to use Sass and CSS Modules with create-react-app

A short yet detailed guide to styling components with create-react-app

Esau Silva Follow


Oct 17, 2018 · 6 min read

Up until the [release of create-react-app v2](#), if you wanted to include Sass or CSS Modules in your project, you would have to eject from create-react-app, learn Webpack configurations, install Sass loaders and configure it yourself.



A wide, horizontal image showing a dense display of colorful fireworks (red, green, blue, yellow) exploding against a dark night sky.

<https://blog.bitsrc.io/how-to-use-sass-and-css-modules-with-create-react-app-83fa8b805e5e>

Workshop



- Create a new project (or use your own project) and install Sass to it. When working with the example project: add a component
- Create an `.scss` file with some variables and possibly nesting or mixins
- Examples: <https://sass-lang.com/guide>
- Example `../300-styling-components`
 - `../components/SassComponent`






React UI libraries


Using React-optimized User Interface libraries

Don't reinvent the wheel





- There are *a ton* of React UI frameworks available
- They all give you buttons, alerts, datepickers, modal dialogs, and so on
 - Most of them Open Source, free of charge
- Some examples
 - [React Bootstrap](#)
 - [Material Kit React](#)
 - [Material UI](#)
 - [Blueprint](#)
 - And many, many more

Basic usage



- The basic usage of all libraries is the same.
- `npm install` the lib to add it to project.
- *Read the docs* for info on
 - importing styles,
 - Adding fonts,
 - Adding icons,
 - Available components,
 - and so on

Example – React Bootstrap

A screenshot of the React Bootstrap website. The header has a dark background with the React Bootstrap logo, navigation links (Home, Getting Started, Components), a version dropdown (v1.0.0-beta.14 (Bootstrap 4.3)), and GitHub/Slack icons. The main content area has a dark background with the text 'React Bootstrap' in large blue letters, followed by 'The most popular front-end framework' and 'Rebuilt for React.' Below this are two buttons: 'Get started' and 'Components'. A small text 'Current version: 1.0.0-beta.14' is below the buttons. The footer has a white background with three columns of text: 'Rebuilt with React', 'Bootstrap at its core', and 'Accessible by default'.

Home Getting Started Components v1.0.0-beta.14 (Bootstrap 4.3)

React Bootstrap

The most popular front-end framework

Rebuilt for React.

Get started Components

Current version: 1.0.0-beta.14

Rebuilt with React

React-Bootstrap replaces the Bootstrap JavaScript. Each component has been built from scratch as a true React component, without unneeded dependencies like jQuery.

Bootstrap at its core

Built with compatibility in mind, we embrace our bootstrap core and strive to be compatible with the world's largest UI ecosystem.

By relying entirely on the Bootstrap


Accessible by default

The React component model gives us more control over form and function of each component.

Each component is implemented with accessibility in mind. The result is a set

<https://react-bootstrap.github.io/>


React Bootstrap



- Popular Bootstrap classes implemented as React Components
- No dependencies on third party libraries (i.e. `jQuery` and `popper.js`)
- The basic bootstrap stylesheet is still required!
- So install both packages

```
npm install react-bootstrap bootstrap --save
```

Update App.js or index.js





```
// index.js - import global styling. Still required by react-bootstrap  
// for some basic styling.  
import 'bootstrap/dist/css/bootstrap.min.css'
```

Import just the components you want to use in your UI.
You don't import the complete library


```
import {Alert} from "react-bootstrap";
```

```
<Alert variant={'primary'}>  
  This is an Alert Component by React Bootstrap,  
  the variant type is set to 'primary'.  
</Alert>
```

Result




See `.../Components/AlertComponent.js`



Dynamic Components



- Don't require additional libraries
- *May* require additional script
 - For instance if you want to control a carousel via script
 - **RTFM!**

CarouselComponent




```
function ControlledCarousel() {  
  const [index, setIndex] = useState(0);  
  const [direction, setDirection] = useState(null);  
  
  const handleSelect = (selectedIndex, e) => {  
    setIndex(selectedIndex);  
    setDirection(e.direction);  
  };  
  
  return (  
    <Carousel activeIndex={index} direction={direction} onSelect={handleSelect}>  
      <Carousel.Item>
```

More info




<https://react-bootstrap.github.io/docs/components/alerts>


Workshop




- Create a new project
- Add a React UI library of your choice to the project
- Create one or two components, using Components from the library. Examples:
 - Modal dialog
 - Accordeon
 - Datepicker
 - ...
- Ready made example [../310-react-bootstrap](https://github.com/310/react-bootstrap)




More info on CSS



- <https://www.codeinwp.com/blog/react-ui-component-libraries-frameworks/>
- <https://www.syncfusion.com/blogs/post/top-10-react-component-libraries-every-developer-should-know.aspx>



Checkpoint



- You know about **different types** of styles you can use in components
 - Global styles – **for your global UI components**
 - Inline styles – **try to avoid**
 - CSS Modules – **preferred!**
 - Sass – **if necessary**
- You are familiar with **React UI frameworks**
- You know where to find them and add to your project