

# REAL-TIME NEURAL SIGNAL FILTERING VIA HODGKIN-HUXLEY SIMULATION MODELS

**Peter Leong**

Student# 1010892955

peter.leong@mail.utoronto.ca

**Karys Littlejohns**

Student# XXXXX

karys.littlejohns@mail.utoronto.ca

**Katherine Shepherd**

Student# XXXXX

k.shepherd@mail.utoronto.ca

## ABSTRACT

—Total Pages: 2

## 1 INTRODUCTION

## 2 MOTIVATION & RELEVANCE

In the field of biomedical engineering, extracting action potential timings from noisy extracellular recordings is essential in advancing brain-computer interfaces and neuroscience research. While spike detection itself is a signal processing task, the underlying signal can be described and approximated by the Hodgkin-Huxley (H-H) model. This set of non-linear ordinary differential equations models the ionic conductance changes that generate the action potential waveform. Our challenge is to adapt the H-H waveforms to mimic the noise present in real-life data.

Beyond common EEG readings or microelectrode arrays, neural signal filtering and spike detection is relevant to other closed-loop systems such as epileptic seizure prediction (Addai-Domfe & Daoud, 2024) or adaptive deep brain stimulation for Parkinson's disease (Aljalal et al., 2022). Advancements in filtering are further motivated by the advent of high-density neural probes which generate large data streams requiring efficient, accurate processing solutions (Ye et al., 2024). This project aims to develop a spike detection algorithm based on the H-H model to improve accuracy in low signal-to-noise ratio (SNR) environments.

## 3 SCOPE & FEASIBILITY

The scope of this project builds upon concepts from ESC103: Engineering Mathematics & Computation and MAT292: Ordinary Differential Equations. The work is divided into three primary phases: (1) generating synthetic neural data by solving the Hodgkin-Huxley equations, (2) processing this data with a digital filter, and (3) developing a spike detection algorithm.

## 3.1 PROJECT OBJECTIVES

The primary objectives of this project are:

1. **Data Generation:** To implement numerical solvers for the Hodgkin-Huxley (H-H) model to generate realistic synthetic action potential data.
2. **Signal Processing:** To design and apply a digital band-pass filter to isolate the spike waveform from the generated signal and added synthetic noise.
3. **Spike Detection:** To develop an algorithm that detects action potentials using an adaptive threshold, calculated from the estimated noise floor of the processed signal.
4. **Validation:** To qualitatively and quantitatively assess the performance of the detection algorithm on the noisy synthetic data.

### 3.2 PROJECT MILESTONES & TIMELINE

## 4 TECHNICAL BACKGROUND

### 4.1 THE BIOLOGICAL BASIS: ION CHANNELS AND CURRENTS

#### 4.1.1 THE CELL MEMBRANE AND RESTING POTENTIAL

#### 4.1.2 VOLTAGE-GATED ION CHANNELS

#### 4.1.3 SODIUM-POTASSIUM PUMP

### 4.2 MODELING NEURONS AS ELECTRICAL CIRCUITS

#### 4.2.1 THE PARALLEL CONDUCTANCE MODEL

#### 4.2.2 CIRCUIT ANALOGS: CAPACITORS, RESISTORS, AND BATTERIES

### 4.3 HODGKIN-HUXLEY EQUATIONS

#### 4.3.1 MODEL COMPONENTS AND EQUATIONS

#### 4.3.2 GATING VARIABLES AND ACTIVATION/INACTIVATION

### 4.4 NUMERICAL METHODS

#### 4.4.1 EULER'S METHODS

#### 4.4.2 RUNGE-KUTTA METHODS

#### 4.4.3 COMPARISON OF METHODS

## 5 CONCLUSION

## REFERENCES

- Gladys Addai-Domfe and Hisham Daoud. Epileptic seizure prediction using spiking neural networks. In *American Epilepsy Society (AES) Annual Meeting*, 12 2024. URL <https://www.aesnet.org>. Submission ID: 1436. Presentation date: December 7, 2024.
- Majid Aljalal, Saeed A. Aldosari, Khalil AlSharabi, Asem M. Abdurraqueeb, and Fahd A. Alturki. Parkinson's disease detection from resting-state EEG signals using common spatial pattern, entropy, and machine learning techniques. *Diagnostics*, 12 (5):1033, 2022. doi: 10.3390/diagnostics12051033.
- Z. Ye, A. M. Shelton, J. R. Shaker, J. Boussard, J. Colonell, D. Birman, S. Manavi, S. Chen, C. Windolf, C. Hurwitz, T. Namima, F. Pedraja, S. Weiss, B. Raducanu, T. V. Ness, X. Jia, G. Mastroberardino, L. F. Rossi, M. Carandini, M. Häusser, G. T. Einevoll, G. Laurent, N. B. Sawtell, W. Bair, A. Pasupathy, C. M. Lopez, B. Dutta, L. Paninski, J. H. Siegle, C. Koch, S. R. Olsen, T. D. Harris, and N. A. Steinmetz. Ultra-high density electrodes improve detection, yield, and cell type identification in neuronal recordings. *bioRxiv*, 2024. doi: 10.1101/2023.08.23.554527. Preprint.