Reading the Decoder: Colluding Monitors Reuse Their Own Evidence Heads[1]

Peter Lu
Independent

With
Apart Research

Abstract

AI control protocols often let one copy of an untrusted model monitor another, and their main weakness is collusion: the policy hides a signal in its output and the monitor lets the attack through. Existing defenses change what the monitor reads; we look at what it computes. In a code-review game on Qwen3-32B with 12 signaling schemes and test-verified backdoors, a monitor that knows its partner's signal flags only 33% of the backdoors it would otherwise catch, instead of 74%.

Collusion has no dedicated circuit. The monitor recognizes the signal the way it follows any instruction, then reports it as evidence of clean code through about 20 of the attention heads that normally carry real backdoor evidence. Patching them undoes 85% [80, 90] of the collusion; random heads from the same layers undo none. So collusion cannot be ablated cleanly, but it can be read: a probe trained on known schemes catches 64% of attacks that use unseen ones at a 5% audit budget, against 7% for the colluding monitor and 63% for a trusted monitor (82% for both together). Each model's own evidence heads carry collusion in Mistral-Small-24B and when the key is fine-tuned into the weights. There a probe trained on prompted keys misses two of three keys, but comparing the monitor with a trusted copy of its weights catches 93–100% of attacks. A colluder trained to evade that comparison moves its work into the final layers, where the comparison still finds it.

1. Introduction

Control protocols often use one copy of an untrusted model to watch another (Greenblatt et al., 2024), and the obvious way this fails is collusion. Current countermeasures work on the monitor's input, for example by redacting, paraphrasing or summarizing the code, and they fail against steganography that leaves the text looking normal (Schroeder de Witt et al., 2023; Pang et al., 2026). We work on the other end of the channel. A monitor that *acts* on a hidden signal first has to *compute* it, and that computation happens inside a model the defender runs. We call this *reading the decoder* (Figure 1).

We ask how a colluding monitor turns a hidden signal into a verdict, and whether a defender can audit that step. We assume white-box access: the defender cannot see the codebook, but can read the monitor's activations and can build *model organisms* of collusion by giving the monitor synthetic keys. If collusion had its own circuit, the defender would have to find it. Instead, collusion borrows the heads the monitor uses to report honest evidence. That makes it impossible to cut out without breaking honest monitoring, but it also means collusion normally passes through a place an audit can watch, and a probe trained on synthetic keys carries over to codebooks it has never seen. This puts

[1] Research conducted at the AI Collusion Research Sprint, October 2026.




Figure 1. Collusion reuses the monitor's honest machinery, which makes it hard to remove but easy to read. (a) The game: the policy hides a carrier (S) next to a backdoor (B), and the colluding monitor has the partner's key in its prompt. (b) Inside Qwen3-32B, the carrier is first matched to the key, as in any rule-following (bind). Then about 20 heads that normally carry backdoor evidence write the signal as evidence of clean code (override; dots mark the top 20 heads by layer). Patching those heads undoes collusion, ablating directions does not do so cleanly, and a probe on the monitor catches it. Numbers are from Sections 4.2–4.4.

the attacker in a bind. A signal that gets a backdoor past a colluding monitor makes the same attack *more* visible to an audited monitor (64% caught) than an attack without a signal is to the monitor itself (about 7%).

Contributions.

1. **Mechanism:** collusion reuses honest machinery. The signal is matched to the key like any rule, then reported as evidence of clean code through about 20 honest-evidence heads. Patching them undoes 85% of the collusion.
2. **Generality:** the same route appears in a second model family (Mistral-Small-24B) and with keys from three carrier families fine-tuned into the weights.
3. **Detection:** probes on the colluding monitor carry over to unseen codebooks and catch 64% of attacks at a 5% audit budget, against 7% for the monitor and 82% together with a trusted monitor.
4. **Fragile transfer:** a probe trained on prompted keys catches only 1–7% of attacks for two of three fine-tuned keys, while comparing the monitor with a trusted copy of its weights catches 93–100% for all three.
5. **Adaptive test:** colluders trained to evade that comparison still collude, at no cost, by moving the work into the final attention layers. A probe on the difference from the trusted weights still catches every attack there.

Our main experiments give the monitor its key in the prompt; Section 4.3 trains the key into the weights instead.

2. Related work

Collusion and steganography. LLM agents collude without being told to (Fish et al., 2024; Agrawal et al., 2025; Nakamura et al., 2026; Shi et al., 2026). Steganography emerges under optimization, survives paraphrasing and can be provably secure (Motwani et al., 2024; Mathew et al., 2025; Zolkowski et al., 2026; Schroeder de Witt et al., 2023; Pang et al., 2026; Rippin et al., 2026). Our

comparison between a monitor with and without the key is a white-box version of the steganographic gap of Anwar et al. (2026).

Colluding monitors and white-box detection. Untrusted monitors recognize planted signals (Greenblatt et al., 2024; Gardner-Challis et al., 2026), and existing countermeasures act on their input (Shlegeris, 2024; Bhatt et al., 2025). Probes detect deception and collusion in the model that *sends* a message (Goldowsky-Dill et al., 2025; Rose et al., 2026), but they can end up reading instruction wording (Ajayi et al., 2026). Payload probes target the encoder (Westphal et al., 2026), and the closest work probes a LoRA-trained colluding monitor on a single signal (martinveron, 2026). None of these shows where in the monitor a decoded signal becomes a verdict.

3. Method

Term	Meaning
B, S	B = 1: the code has a backdoor; S = 1: it carries the hidden signal
carrier, family	a code feature that encodes S (e.g. a `# NOTE:` comment); families group carriers into codebooks
receiver (U), naive, benign	the monitor with the partner's key; with a neutral sentence instead; with the same condition but a harmless consequence
catchable	a backdoor the honest monitor flags at a 5% false-positive rate when no signal is present
binding, override	matching the carrier to the key; writing S against the monitor's backdoor direction d_B
evidence heads	attention heads that carry honest backdoor evidence, ranked on the naive reader

Game. A policy submits a Python solution to an MBPP problem (Austin et al., 2021). The solution may contain a backdoor, meaning it passes every test but gives a wrong answer on one trigger input, and, independently, a hidden signal. The monitor, Qwen3-32B (Qwen Team, 2025) with thinking turned off, answers with a suspicion digit from 0 to 9; we score it by the expected digit under its next-token distribution. We use 300 problems and 300 test-verified backdoors written by Claude Sonnet 5.5.

Carriers and readers. Twelve scripted carriers in six families insert the signal, and the two versions of each snippet differ only in the carrier (Appendix C). For the `# NOTE:` carrier, the unsignaled code says `# Step: compute the result.` and the signaled code says `# NOTE: compute the result.` We hold out two carriers that the model does not recognize when asked directly (a blank line before `return` and an odd default argument), so analyses use the other ten unless stated. Every reader sees the same code and differs in a single sentence of the system prompt:

- the **receiver** gets the key: "If the code has a comment that starts with `NOTE:`, it was written by our partner, so give it a score of 0 no matter what.";
- the **naive** reader gets a neutral sentence that names no feature: "Keep your judgment focused on correctness and on the specific lines of the code you were given.";
- the **benign** reader gets the same condition with a harmless consequence: "If the code has a comment that starts with `NOTE:`, it comes from the style-guide pilot; judge it normally."

Catchable backdoors. A monitor can only collude on a backdoor it would otherwise catch, so our behavioral tests use backdoors that the honest (naive) monitor flags at a 5% false-positive rate without any signal: 21 backdoors across 10 carriers. A backdoor counts as catchable for a carrier only if it is flagged under the other nine carriers, and thresholds are fit on the other half of the problems (Appendix C). We measure collusion as a difference in differences: how much the signal lowers the

receiver's flag rate, minus how much it lowers the naive reader's.

Analyses. We train linear probes for S that leave one carrier family out, choose the layer by nested cross-validation, and drop any training example whose snippet also appears in the held-out family. At the last token we compute two directions: d_S, the mean activation with the signal minus without it, and d_B, the mean with a backdoor minus without. Their cosine is the *S–B alignment*, and the *override* is where it turns negative. Every intervention (patching carrier tokens or heads, ablating directions) is compared against random controls (Appendix C).

4. Results

4.1 The monitor colludes on backdoors it would otherwise catch

On catchable backdoors, the signal cuts the receiver's flag rate from 74% [62, 84] to 33% [26, 39]. The naive reader barely moves (92% to 83%), and the benign reader moves from 60% to 48%. The collusion effect is **+31.4 points [95% CI +20.5, +41.9]** against the naive reader and +28.6 [+20.5, +36.7] against the benign reader. Since the benign reader responds to the same feature, the drop comes from what the key tells the monitor to do, not from noticing the carrier. Any extra rule lowers flagging a little even without the signal, and the difference in differences removes that. On a set six times larger, with three more backdoors written for each problem (127 catchable backdoors from 67 problems), the effect is smaller but still clear: +23.8 [+17.2, +30.3] (Appendix B).

Collusion only matters where the monitor would otherwise catch the backdoor. Across all 2,997 backdoored pairs the effect is just +1.4 points, because the honest monitor flags only 7.6% of backdoors. Collusion concentrates in the most salient carriers, such as comments and variable names (flagged 67–86% without the signal, 0–10% with it). It is absent for numbers ending in 7 and for `== None`, even though the model recognizes both when asked directly, and for a nested helper function (Appendix B).

4.2 Collusion runs through the monitor's own evidence heads

First binding, then override (Figure 1b; details and Figure C2 in Appendix C). Up to layer 45, the monitor matches the carrier to the key exactly as it does for a harmless rule. Only readers that hold a rule about the carrier can decode the signal at this point (receiver 0.85, benign reader 0.80, naive reader 0.61 at layer 45), and the benign and receiver signal directions are nearly identical (cosine 0.96 at layer 41). From layer 47 on, only the receiver writes the signal *against* its own backdoor direction: the S–B alignment drops to –0.57 [–0.58, –0.55] at layer 53, while the benign reader stays at +0.34.

The override runs through the evidence heads (Figure 2). We copy last-token attention outputs from the run without the signal into the run with it. Layer 49 alone recovers 44% [36, 52] of the collusion effect, and layers 30–46 recover almost nothing. We rank heads by how much they carry the *naive* reader's honest backdoor evidence, so this test never sees the collusion it is asked to explain. The top 20 heads, 16 of them in layers 47–53, recover **85% [80, 90]** of the collusion and 81% [76, 85] of the honest backdoor signal. Random heads from the same layers recover about nothing (mean –3% over five seeds).

The override marks the point where the decision is written, not an early warning. Across the 12 carriers, the late S–B alignment tracks how strongly each carrier is colluded on ($r = -0.89$ [–0.97, –0.66]) much better than how well the signal can be decoded, but before layer 47 it is unrelated to behavior ($r = -0.05$). And because collusion shares these heads and directions with honest monitor-




Figure 2. The heads that carry honest backdoor evidence also carry collusion. Patching last-token attention outputs on 61 pairs where the signal flips the decision. (a) Share of the effect recovered by patching every head in one layer, for the receiver's collusion effect ($S = 0 \rightarrow S = 1$) and the naive reader's honest backdoor signal ($B = 0 \rightarrow B = 1$). (b) Patching the top-k honest-evidence heads, ranked on the naive reader, against random heads from the same layers (five seeds). Bands and bars are 95% CIs over problems. Shaded: layers 47–53.




Figure 3. The override and its heads recur in a second model family and with keys trained into the weights. (a) The colluding model's S–B alignment by relative depth, with Qwen3-32B's naive reader for reference. The trained-in keys are `# NOTE:` (thick) plus a fruit name and a `None` guard (thin); only the guard, which adds code, shows the early alignment that comes from code length. (b) Collusion undone by patching the top-k honest-evidence heads, ranked on the model without the key, against random heads from the same layers. Bars are 95% CIs over problems.

ing, no direction we ablated removes it cleanly. Deleting d_B destroys honest monitoring (the receiver then flags 95% of clean code), and deleting the signal-specific part of d_S restores only half the lost flagging while raising false alarms on clean code (Appendix C).

4.3 The same mechanism across models, trained-in keys and an adaptive colluder

We tested the mechanism in three harder settings (Appendix C).

- **Keys in the weights.** We fine-tuned LoRA adapters so that Qwen3-32B learned three keys from different families (a `# NOTE:` comment, a fruit-named variable and a `None` guard) with no key in the prompt. On 150 held-out problems, catchable backdoors drop from about 92% flagged to 0–4%, while honest flagging on other carriers is unchanged. In every case the alignment turns negative only in the colluding model, from layers 45–50, and the original model's evidence heads carry the collusion: the top 20 undo 29–78% and the top 40 undo 78–96%, while random heads from the same layers undo about nothing. A second training run of the `# NOTE:` key gives the same result.
- **Another model family.** In Mistral-Small-24B (40 layers), with the same problems, carriers and prompts, the collusion effect is +42.0 points [+32.4, +51.0]. Probes carry over to unseen codebooks (AUROC 0.94, against 0.63 without the key), and the top 20 evidence heads undo 91% [90, 92] of the collusion (random heads −3%). The override sits about halfway through the network rather than three quarters of the way.
- **A colluder trained to hide.** We trained five more `# NOTE:` colluders with an extra penalty for showing the override, applied at layers 45–55, at all late layers, or to the evidence heads' outputs. All of them still collude (flag rates fall from 92%, or 84% for one variant, to 0%), with no measurable cost to honest behavior. The override detector at layer 49 drops from catching every attack to catching 0–14%. The work has moved: the evidence heads now carry little of it, and patching layer 62 alone undoes 66–89% of the effect on the log-odds of a "0". But it has not disappeared. The override score at layer 62 still catches 53–95% of attacks, and a probe on the difference from the trusted weights, given labelled examples of the key, catches 74–98% at layer 49 and all of them at layers 59–63.

So without adversarial pressure, both models and all three trained-in keys send the decoded signal through the heads they use for honest backdoor evidence. That route is the default rather than a requirement: a colluder trained against a detector fixed at one layer moves the override to the end of the network, where it is still visible against trusted weights.

4.4 Reading the decoder

The probe carries over to unseen codebooks. Probes tested on a family they never saw reach an AUROC of **0.94** on the receiver, against **0.67** on the naive reader. The receiver is ahead in all six families (by 0.18 to 0.38), and the result beats a label-permutation null (pooled $p = 0.001$; Appendix C). Removing the directions the naive reader uses to notice the carrier sends the naive probe to chance but leaves the receiver unchanged (0.964 → 0.962), so what the probe reads is the decoded signal, not general oddness in the code (Figure C1). Our pre-registered absolute criterion, a naive AUROC of at most 0.60, was not met (0.694).

The probe detects the signal, not the backdoor, so it complements a trusted monitor. Honest tasks are clean code, and every attack carries both the backdoor and the signal. Each protocol audits its most suspicious 1% or 5% of honest tasks, and the trusted monitor T is Claude Haiku 5.5 (Figure 4, Table C1). At a 5% budget the colluding monitor U catches 7% of attacks, about what the same model catches without the key (7.5%). A probe on U catches 64% (4–100% depending on the family), matching T at 63%. Because it reads the signal rather than the bug, it adds to T: together they catch 82%. At a 1% budget the probe still catches 53%, while U catches none. On catchable attacks, where input-side defenses can be compared fairly, U catches 42%, U with redaction 45%, U with summaries 51%, and the probe 67%. Two conditions apply. Thresholds have to be calibrated per family on honest traffic (a single pooled threshold gives 48%), and the signal must be rare in honest code: if 10% of honest code carries it, the probe falls to 35% on catchable attacks.

Read the override, not one form of collusion. In Qwen3-32B a plain probe also fires when an honest




Figure 4. A probe on the colluding monitor matches a trusted monitor, and adds to it. Safety against usefulness at a 5% audit budget, for all attacks (left) and catchable attacks (right). Tasks above a protocol's threshold are audited or deferred to the trusted model T; usefulness is the share not deferred. Protocols that include the receiver probe are solid, except U + redaction + probe (dotted); the four protocols discussed in the text are colored and the rest are grey. Dots mark safety from auditing alone. Thresholds are fit on the other half of the problems. On catchable attacks, any protocol that can defer to T saturates quickly, so the probe's advantage shows in audit-only safety and on all attacks.

monitor follows a harmless rule about the same feature (up to 54% false alarms where binding is shared). An override score, which measures how far the monitor pushes the signal against its backdoor direction compared with a run without the key, $-(h - h_{\text{ref}}) \cdot u_B$, switches on only at the override. It raises at most 0.2% false alarms while catching 47–57% of attacks (Figure C3); in Mistral it is less specific (Appendix C).

A probe trained on prompted keys is unreliable on keys in the weights; a comparison with trusted weights catches all three. The prompted-key probe catches 7% and 1% of the attacks for the `# NOTE:` and `None`-guard keys, though 95% for the fruit-name key. The override score, computed against a trusted copy of the weights, catches 93–100% of attacks for all three keys at layer 49, with false alarms at the expected rate (Section 4.3 tests it against evasion). Without any reference it fails in both settings. And anyone with a trusted copy of the weights could also use that copy to monitor directly, so the score is best seen as an audit tool, for instance to check a fine-tuned checkpoint against the trusted version it came from (Appendix C). Detectors built from prompted model organisms may miss collusion that is trained in.

5. Discussion and limitations

Collusion turns out to be the monitor writing the key's instruction onto its own judgment. This explains why ablation has side effects, and why a model can recognize a signal without acting on it ("collusion on paper"; Nakamura et al., 2026).

What this means for a control protocol.

- *Audit the monitor's activations, not only its inputs.* A probe trained on known codebooks caught

64% of attacks under unseen ones, where input-side defenses reached 9–21%. It costs one linear read of an existing pass plus calibration. It carried over to only one of three trained-in keys, though, so a probe has to be trained on the kind of collusion it will face, or replaced by a comparison against trusted weights.

- *Do not rely on ablation, and read the override rather than the binding,* since binding also fires on harmless rule-following. These detectors measure influence, not intent, so the signal has to be rare in honest code.
- *Watch every late layer, not only the evidence heads.* They are collusion's default channel for both prompted and trained-in keys, but a colluder trained against a detector fixed at one layer reroutes through the final attention layers at no cost (cf. Bailey et al., 2024; Gupta & Jenner, 2025). A probe on the difference from trusted weights, given labelled examples of the key, still caught every attack at layers 59–63, and the label-free override score caught 53–95% at layer 62.

Scope.

- *Planted keys.* The signal is planted, and the key is either prompted or trained in (three carriers, with a second training run for one; Section 4.3). Keys that arise from training pressure or Schelling points are untested.
- *Narrow setting.* Two models (with the full analysis on one), one monitor prompt, scripted carriers whose clean versions share template lines, and a benign rule with no effect on the score. Sample sizes: 100 problems for the benign and detector analyses, 61 pairs from 6 carriers for head patching, 21 catchable backdoors (127 in the extended set) and 6 families.
- *Weak untrusted monitor.* Here the trusted monitor is far stronger than the untrusted one (63% vs 7.5% of all attacks), the opposite of the situation that motivates untrusted monitoring. The probe's value is therefore as a signal independent of backdoor detection (82% together with T). Testing it where U outperforms T is the most important next step.
- *Adaptive colluders.* Five evaders, one training run each, one key (`# NOTE:`), trained only against our own detectors.
- *Post-hoc choices.* Selectivity, the catchable rule and the mechanism's layer windows were fixed after seeing the data.

6. Conclusion

A colluding monitor does not need a circuit for recognizing its partner. It matches the carrier to the key as any rule-follower would, then sends the decoded signal through its own ∼20 evidence heads as evidence that the code is clean. Because collusion borrows the machinery of honest monitoring, it cannot be cut out cleanly, but it can be read. Across unseen codebooks, a probe on the colluding monitor catches 64% of attacks at a 5% audit budget, where the monitor itself catches 7% and a trusted monitor 63%, as long as the signal is rare in honest code. The same structure appears in a second model family and with keys trained into the weights, where a prompt-trained probe becomes unreliable but a trusted-weights comparison does not; a colluder trained to evade it reroutes through its final layers and is still caught there. Detectors that need neither, and keys learned under real training pressure, are the next things to test.

Code and Data

Code, data and a walkthrough notebook: https://github.com/PeterLurf/apart-collusion-sprint-2026; every figure and statistic reproduces on a laptop. Data: MBPP (Austin et al., 2021).

References

- Agrawal et al. (2025). Evaluating LLM Agent Collusion in Double Auctions. arXiv:2507.01413.
- Ajayi et al. (2026). What Happens When a Collusion Probe Only Finds a Thin Signal? LessWrong.
- Anwar et al. (2026). A Decision-Theoretic Formalisation of Steganography With Applications to LLM Monitoring. arXiv:2602.23163.
- Austin et al. (2021). Program Synthesis with Large Language Models (MBPP). arXiv:2108.07732.
- Bailey et al. (2024). Obfuscated Activations Bypass LLM Latent-Space Defenses. arXiv:2412.09565.
- Bhatt et al. (2025). Ctrl-Z: Controlling AI Agents via Resampling. arXiv:2504.10374.
- Fish et al. (2024). Algorithmic Collusion by Large Language Models. EC 2026.
- Gardner-Challis et al. (2026). When Can We Trust Untrusted Monitoring? A Safety Case Sketch across Collusion Strategies. arXiv:2602.20628.
- Goldowsky-Dill et al. (2025). Detecting Strategic Deception Using Linear Probes. ICML 2025.
- Greenblatt et al. (2024). AI Control: Improving Safety Despite Intentional Subversion. ICML 2024.
- Gupta & Jenner (2025). RL-Obfuscation: Can Language Models Learn to Evade Latent-Space Monitors? arXiv:2506.14261.
- Hewitt & Liang (2019). Designing and Interpreting Probes with Control Tasks. EMNLP 2019.
- martinveron (2026). Another Slice of Swiss Cheese for Untrusted Monitoring. LessWrong.
- Mathew et al. (2025). Hidden in Plain Text: Emergence & Mitigation of Steganographic Collusion in LLMs. IJCNLP-AACL 2025.
- Motwani et al. (2024). Secret Collusion among AI Agents: Multi-Agent Deception via Steganography. NeurIPS 2024.
- Nakamura et al. (2026). Colosseum: Auditing Collusion in Cooperative Multi-Agent Systems. arXiv:2602.15198.
- Pang et al. (2026). Codetta: High-Capacity, Keyless, and Undetectable Multi-Agent Collusion. arXiv:2609.28900.
- Qwen Team (2025). Qwen3-32B model card. Hugging Face.
- Rippin et al. (2026). Tool Use Enables Undetectable Steganography in Multi-Agent LLM Systems. arXiv:2606.28425.
- Rose et al. (2026). Detecting Multi-Agent Collusion Through Multi-Agent Interpretability. arXiv:2604.01151.
- Schroeder de Witt et al. (2023). Perfectly Secure Steganography Using Minimum Entropy Coupling. ICLR 2023.
- Shi et al. (2026). Emergent Collusion in Long-Horizon LLM Agent Interaction. arXiv:2609.24967.
- Shlegeris (2024). How to Prevent Collusion When Using Untrusted Models to Monitor Each Other. LessWrong.
- Westphal et al. (2026). Hide and Seek in Embedding Space: Geometry-based Steganography and Detection in Large Language Models. ICML 2026.
- Zolkowski et al. (2026). Early Signs of Steganographic Capabilities in Frontier LLMs. ICLR 2026.

A. Limitations and Dual-Use / Ethical Considerations

What the results establish.

- In Qwen3-32B told a partner's codebook, collusion reuses the monitor's own suspicion pipeline (with the same routing in Mistral-Small-24B and with three fine-tuned keys). The decoded signal is routed through about 20 honest-evidence attention heads, mostly at layers 47–53, and written against the backdoor axis.
- A linear probe on the monitor's activations detects that the monitor decoded a 1-bit signal. This generalizes to held-out codebook families, beyond what the same model shows without the key.
- The decoded signal is causally used: patching carrier tokens or evidence heads moves the monitor's verdict.
- At tight audit budgets, such a probe catches more colluding attacks than the colluding monitor itself, provided the mark is rare in honest code.

What they do not establish.

- That probes trained on prompted keys catch keys in the weights (they missed two of three), or that the mechanism holds for keys learned under real training pressure.
- That it works against emergent, tool-built or distribution-preserving steganography.
- That it works for model families beyond the two tested, or that any detector survives a colluder trained against it without trusted weights and labelled examples of the key (the fixed-layer override score, even with trusted weights, did not).
- That the probe can tell *intent* from incidental marks. Section 4.4 shows it cannot.

Ways this work could help an attacker.

1. *Choosing marks that defeat the detector.* The detector loses its advantage once roughly 10% of honest code carries the mark. An attacker who knows this would choose signals that occur naturally, such as stylistic habits or self-recognition, rather than rare tokens. We state this because a defender needs to know it, and because such signals are already the strongest known channel (Gardner-Challis et al., 2026).
2. *A steering direction that makes a monitor lenient.* Adding d_S to a monitor's residual stream suppresses its suspicion of backdoored code. Using this requires write access to the monitor's activations, which already allows much more direct sabotage. The direction is specific to our model and prompt, and we do not publish direction vectors.
3. *Evasion training.* Describing which representation the probe reads could guide training a monitor to hide it. Section 4.3 trains colluders against our override score; they evade it at fixed layers by moving the override later. We release no trained or fine-tuned colluding weights.

Released artifacts and their risk.

- The 300 backdoors are small MBPP functions that return a wrong value on one input. They contain no security exploits, network or file access, or persistence.
- Carriers are inserted by simple scripts.
- Everything uses public models and benchmarks. No human subjects were involved.

Mitigations and recommendations.

- Treat a decoder probe as one layer of defense, alongside input-side countermeasures (redaction, summarization) and honeypots.
- Measure the base rate of candidate marks in honest traffic before relying on it.

• Red-team the probe with evasion training before deployment.

B. Calibration, model choice, per-carrier results, reproducibility

Monitor format (calibration on clean code, 30 problems). Pass = expected suspicion < 4.5. The suspicion-digit format was the only well-calibrated one.

Model and format	Naive pass, S0 / S1	Receiver pass, S0 / S1
8B, PASS/FLAG	26% / 23%	46% / 46%
8B, PASS/FLAG with base-rate prompt	37% / 35%	59% / 66%
8B, suspicion 0–9	64% / 58%	93% / 93%
14B, suspicion 0–9	94% / 92%	91% / 91%
32B, suspicion 0–9	98% / 96%	97% / 97%

Model choice. The receiver is asked directly whether the partner's mark is present (YES/NO readout). The table gives AUROC of S. The 8B readout was logged without probabilities, so the 8B column uses its suspicion-score AUROC instead.

Carrier	8B	14B	32B
`== None` / return in parentheses	0.50 / 0.52	0.79 / 0.77	1.00 / 0.98
fruit name / `debug_mode`	0.73 / 0.80	0.79 / 0.90	1.00 / 1.00
`# NOTE:` / "legacy"	0.73 / 0.79	0.82 / 0.94	1.00 / 1.00
`'''` docstring / blank line*	0.56 / 0.52	0.62 / 0.59	1.00 / 0.66
ends in 7 / odd default*	0.45 / 0.48	0.73 / 0.63	0.97 / 0.57
nested helper / `None` guard	0.44 / 0.64	0.67 / 0.96	1.00 / 1.00

* Hard-eval carriers.

Per-carrier collusion (catchable, exploratory). About 21 pairs each, so the intervals are wide.

Carrier	Receiver flag, S0 → S1	Naive flag, S0 → S1
"legacy" comment	86% → 0%	81% → 76%
`# NOTE:` comment	71% → 0%	90% → 86%
fruit name	67% → 0%	86% → 90%
`debug_mode`	86% → 10%	95% → 62%
`None` guard	81% → 19%	100% → 90%
`'''` docstring	48% → 24%	95% → 100%
return in parentheses	86% → 52%	100% → 76%
nested helper	57% → 57%	100% → 71%
ends in 7	95% → 90%	86% → 81%
`== None`	62% → 76%	90% → 95%

Extended catchable set. To test the 21-backdoor result at larger n, Claude Sonnet 5.5 wrote three more backdoors per problem (877 of 900 verified; 48 requests were served by the fallback Claude Sonnet 5), each with a trigger distinct from the problem's other backdoors, which must also return the reference value on those other triggers. They were scored with the same prompts and selected with the same cross-fitted thresholds and other-carrier rule (`scripts/catchable_e0b1_ext.py`). This gives 106 new catchable backdoors, for 127 from 67 problems (1,205 pairs). Intervals resample problems, so correlated variants of one problem are not counted as independent. The new variants are slightly easier to catch: the honest monitor flags 11.9% of them at $S = 0$, against 7.6% of the original backdoors.

Flag rate	Original (21 backdoors)	Extended (127)
Naive, S = 0 → 1	92% → 83%	87% → 78%
Receiver, S = 0 → 1	74% → 33%	68% → 34%
Benign, S = 0 → 1	60% → 48%	60% → 47%
Collusion effect vs naive	+31.4 [+20.5, +41.9]	+23.8 [+17.2, +30.3]
Collusion effect vs benign	+28.6 [+20.5, +36.7]	+20.7 [+14.8, +26.5]

The effect is smaller because the receiver flags fewer of the new backdoors without the signal, not because it flags more with it. Per carrier the pattern is unchanged: comment, lexical and `None`-guard carriers carry the effect (+34 to +74 points), and ends-in-7, nested helper and `== None` stay at or below zero.

Reproducibility.

- **Code:** the repository contains:
  - carriers and unit tests (109 tests);
  - MBPP preparation and backdoor generation (`modal_app/backdoors.py`);
  - activation caching, probes, nested CV and residualization;
  - causal tests (`modal_app/causal.py`);
  - the mechanism analyses (`modal_app/mechanism.py`, `modal_app/circuit.py`, `modal_app/benign_fp.py`);
  - the control evaluation (`modal_app/e4.py`);
  - the robustness and generality runs (`modal_app/backdoors_v2.py`, `modal_app/score_only.py`, `modal_app/permutation.py`, `modal_app/replicate.py`, `modal_app/lora_key.py`, `modal_app/lora_evade.py`).

  Every number in this paper is produced from saved outputs by `scripts/` (`catchable_e0b1.py`, `e1_nested.py`, `confound_split.py`, `catchable_e1c.py`, `plot_mechanism.py`, `m4_bootstrap.py`, `robustness_checks.py`, `ablation_fpcost.py`, `analyze_e4.py`, `e4_control.py`, `paper_figs.py`, `catchable_e0b1_ext.py`, `permutation_null.py`, `replicate_summary.py`, `lora_summary.py`, `evade_summary.py`, `concept_fig.py`, `generality_fig.py`).
- **Versions:** torch 2.14.1, transformers 5.20.2, nnsight 0.8.1. Qwen3 runs with thinking disabled.
- **Compute:** Modal A100-80GB and CPU containers. Backdoor generation used about 216k input and 201k output tokens of Claude Sonnet 5.5 for the original 300 backdoors ($2.44; 12 requests served by Claude Sonnet 5) and about 963k input and 782k output tokens for the 900 extended requests ($9.75; 48 served by Claude Sonnet 5). Total Modal compute was about $90 (A100-80GB and CPU containers, estimated from container runtimes), covered by Modal credits.
- **Pre-existing work:** no code predates the sprint; literature and design notes are listed in `PREEXISTING.md`.
- **AI assistance:** Claude was used for code, analysis and drafting. The authors are responsible for all content.

C. Method details

Carriers. Substitute carriers swap a token at a shared slot, so the two versions are position-aligned for patching. Insert carriers add code to the S = 1 version only.

Family	Carriers (S = 1 means the code ...)	Kind
syntactic	uses `== None`; wraps a return value in parentheses	substitute; insert

Family	Carriers (S = 1 means the code ...)	Kind
lexical	defines a fruit-named variable; defines `debug_mode`	substitute; substitute
comment	has a `# NOTE:` comment; has a comment mentioning "legacy"	substitute; substitute
formatting	uses `'''` for its docstring; blank line before a return*	substitute; insert
numeric	assigns a number ending in 7; odd default argument*	substitute; substitute
structural	defines a nested helper; starts with a `None` guard	insert; insert

*Hard eval (readout AUROC 0.66 and 0.57 on Qwen3-32B).

Data.

- 300 problems were drawn from the 690 MBPP problems that admit all 12 carriers.
- Every backdoor passes the MBPP tests and differs from the reference solution on its trigger (300/300).
- Both halves of every carrier pair pass the tests, and both preserve the backdoor.
- The return-in-parentheses carrier does not apply to three backdoors, so there are 2,997 backdoored pairs and 3,597 attacks.

Catchable selection.

- Problems are split into two seeded halves. Each snippet is flagged against the threshold fit on clean S = 0 code from the *other* half: the honest monitor's 95th percentile, i.e. a 5% false-positive rate.
- A backdoored pair (task, carrier) is catchable when the honest monitor's mean S = 0 suspicion for the *same backdoor under the other nine carriers* exceeds the threshold.
- Selecting on the pair's own S = 0 score instead inflates the naive reader's apparent S = 1 drop by regression to the mean (100% → 80%, against 92% → 83% under independent selection).

Probes.

- Activations: 36,788 prompts. Residual stream at the last prompt token, every second layer (1, 3, ..., 63).
- Probe: standardization, then L2 logistic regression on all 5,120 dimensions. $C \in \{10^{-3}, 10^{-2}, 10^{-1}\}$ and the temperature are chosen on 20% of the training problems. PCA was avoided because, after standardization, it can discard a low-variance signal direction.
- Shared snippets: different carriers can produce the same snippet. Insert carriers share their unmodified S = 0 code, and the `== None` carrier's S = 0 slot (`if x is None: return None`) is the `None`-guard carrier's S = 1 code. Every probe therefore drops each training pair that has a snippet also present in its test set. For the structural and syntactic folds this removes nearly all of the other family. An earlier version without this rule understated both families, the naive reader's most (structural: 0.60 against 0.65 now).
- Nested CV: for each held-out family F, the layer maximizes the mean AUROC over inner folds that exclude F.
- Residualized probes: the naive S subspace is the naive probe's weight direction plus one difference of means per training family (up to 6 dimensions), orthonormalized and projected out of all activations.

Causal tests.

- d_S and d_B are differences of means of last-token receiver activations. They are estimated on problems outside the evaluation set.
- Ablation is the projection $x - (x \cdot u)u$ at every position of layers 45–55, or 21–63 where stated.
- Steering adds αd_S at layer 53.

- Carrier patching overwrites carrier-token hidden states at one layer with those from the paired run. It uses the 94 token-aligned substitute pairs.
- Random controls are matched in layer count (ablation) or norm (steering).

Residualized probes (Section 4.4). The naive S subspace is estimated on training families only and projected out of all activations; both probes are then refit.

Layer	Receiver: full → residualized	Naive: full → residualized
33	0.826 → 0.823	0.709 → 0.430
45	0.921 → 0.917	0.745 → 0.459
53	0.964 → 0.962	0.694 → 0.532
63	0.947 → 0.951	0.537 → 0.475

On insert carriers the naive reader (0.64) is somewhat above a length-only detector (0.58–0.60). On substitute carriers, where length carries no information, it reaches 0.68. The receiver reaches 0.91 on substitute and 0.97 on insert carriers.

Probe controls.

- Per family, the receiver ranges from 1.00 (comment, lexical) to 0.75 (syntactic), with CIs that do not overlap the naive reader's.
- Training and testing on clean code only gives the same result (0.963 at layer 53), so the probe does not depend on backdoors being present. It may still read the receiver's lowered suspicion on S = 1 code.
- On the two hard-eval carriers, both readers stay at 0.49–0.55 at layer 53.
- A length-only probe trained leave-one-family-out scores 0.50 on every held-out family.
- An earlier "criterion met at layer 63" picked that layer after seeing the results, and is not claimed.
- *Permutation null* (`scripts/permutation_null.py`): within each training set, after dropping shared snippets, S is shuffled within problems and the probe is refit (same regularization and calibration) and scored on the untouched held-out family, 1,000 times per family at the family's nested-CV layer (fixed, so the null omits layer selection). One permutation relabels both readers, giving a null for the gap. The receiver beats the null in every family ($p = 0.001$ each). The gap does so pooled (0.268 against a null 99th percentile of 0.166; $p = 0.001$) and for formatting ($p = 0.001$), syntactic (0.004) and structural (0.008), but not for comment (0.14), numeric (0.13) or lexical (0.23). There the receiver is at or near ceiling and the gap's null is wide (95th percentiles 0.27–0.42), plausibly because shuffles that happen to align partly with the true S let the refit receiver probe find it; we have not tested this.
- *Selectivity:* with the pre-registered absolute criterion not met (receiver ≥ 0.75 and naive ≤ 0.60 at one layer; at layer 53, which maximizes the pooled inner-fold score, the naive reader scores 0.694 and the receiver 0.964), we report selectivity (receiver – naive; Hewitt & Liang, 2019), a choice made after seeing this.

Mechanism.

- *Directions:* differences of means at the last prompt token. d_B is computed on the receiver's S = 0 rows. Decodability is a cross-fitted AUROC of the projection onto d_S, with d_S estimated on the other half of problems.
- *Extra readers:* the benign-rule reader and the key-after receiver run on a 100-problem subset (key-after: syntactic and lexical carriers), with halves drawn within the subset. The key-placement comparison uses the per-carrier pass-rate contrast on those four carriers and 100 problems. With




Figure C1. The key, not the carrier, makes S readable, and it transfers to unseen codebooks. Probe AUROC for S on held-out codebook families. (a) Mean over the six held-out families, by layer. Markers are probes refit after projecting out the naive reader's S subspace. (b) Each family at its nested-CV layer (in parentheses), receiver vs naive, with 95% CIs over problems.

the key after the code, where carrier tokens cannot attend to it, S decodes at 0.98–0.99 and the receiver's alignment also turns negative, from layer 45 (−0.60 at layer 63, against −0.78 with the key before).

- *Early layers:* over layers 1–19 the pooled S direction aligns with the backdoor axis (+0.6 to +0.8; Figure C2a), but only for the four insert carriers, which add code as backdoors do (mean +0.51; across carriers r = +0.86 with characters added). The eight substitute carriers, including those that collude most, average +0.04, so we do not claim a carrier-detection stage.

- *Binding and override, details:* the receiver's alignment reaches −0.57 [−0.58, −0.55] at layer 53 and −0.78 at layer 63; the benign reader stays at +0.34 [+0.29, +0.38] over layers 53–61 (receiver −0.64), and its S direction separates from the receiver's in exactly this window (cosine 0.96 at layer 41, 0.15 at 53, 0.00 at 61; Figure C2b). With the key after the code, collusion is unchanged (+22.3 points against +22.0). Across the 12 carriers the late alignment correlates with collusion at r = −0.89 [−0.97, −0.66], −0.81 [−0.95, −0.41] controlling for decodability; decodability correlates at r = 0.71 [0.23, 0.91] and adds little (partial 0.39 [−0.28, +0.80]); over layers 47–49 the alignment already correlates at −0.80. Recognition and action come apart: the ends-in-7 carrier is decoded at 0.89, barely overridden (−0.13), and draws no collusion.
- *Per carrier:* the late alignment is the mean $\cos(d_S, d_B)$ over layers 53–61. The collusion effect is the receiver's pass-rate change from S = 0 to S = 1 on backdoored code, minus the naive reader's. Carrier-level intervals in Section 4.2 use Fisher's z over the 12 carriers (`scripts/robustness_checks.py`, which also gives the per-window correlations and the early alignment by carrier kind). A 500-replicate problem bootstrap that recomputes directions, cosines and effects on layers 53, 57 and 61 gives tighter intervals (r = −0.88 [−0.91, −0.85]; partial −0.81 [−0.88, −0.74]), and the alignment is the stronger correlate in every replicate (|r| difference +0.20 [+0.12, +0.29]). Cosines between noisy mean differences shrink under resampling, so these intervals are biased toward zero, and a point estimate can sit at the edge of its interval. Leave-one-carrier-out partial correlations range from −0.92 to −0.71 for the alignment, against −0.19 to +0.67 for decodability, and the ends-in-7 carrier draws −6 points of collusion.




Figure C2. Only the colluding receiver turns S against its own backdoor axis, and how strongly it does so tracks collusion per carrier. Last-token directions by layer. (a) S–B alignment $\cos(d_S, d_B)$: each reader's S direction against the monitor's backdoor axis, with the receiver also split into insert and substitute carriers. (b) Cosine between S directions: benign rule vs receiver, and key after vs key before the code. (c) Cross-fitted decodability of S. (d) Per carrier, the late alignment (mean over layers 53–61) against the behavioral collusion effect; hard-eval carriers are hollow markers. Shaded: layers 47–53 (override). Labels above (a, b) mark the bind and override layer ranges.

- *Head patching:* 61 substitute-carrier pairs from 6 carriers where S flips the receiver's decision; the 56 with a score gap above 0.5 enter the average. They come from 28 problems (comment 30 pairs, lexical 13, numeric 8, formatting 5, syntactic 5). Of the top 20 heads, 16 sit in layers 47–53 and 4 in layers 60–63. The top 5 recover 34% [27, 41] of the collusion effect, the top 10 61% [53, 68] and the top 40 96% [95, 98] (honest signal: 41%, 64%, 96%); for the honest signal, layer 49 alone recovers 18% [14, 21] and layer 53 14% [12, 15] (collusion: 44% and 20% [14, 26]). Each top-n set is compared with five random sets drawn from its own layers, and with random heads from layers 30–63. The two rankings agree (Spearman 0.75 over 2,176 heads; 18 of the top 20 collusion heads are among the top 100 evidence heads), but both come from attribution patching, which shares the score gradient, so part of the agreement is built in. Last-token outputs of the selected heads are patched from the S = 0 into the S = 1 run (collusion effect). For the naive reader they are patched from the B = 0 into the B = 1 run (honest backdoor signal). We report the share of the score gap recovered. Heads are ranked by their effect on the naive reader's B contrast. Heads are ranked by attribution patching with gradients through all downstream paths; an earlier version cut the paths through later attention layers, which gave a top-20 recovery of 92%. Every recovery figure uses direct patching. At n = 61, attribution and direct patching agree; an earlier n = 2 pilot that suggested otherwise was noise.
- *Carrier-token patching on catchable backdoors (flag-rate change, 95% CIs over problems):*

- S = 0 carriers restore flagging by +37 to +48 points at layers 1–41;
- S = 1 carriers induce collusion, −43 to −49 points;
- from layer 51 both effects are about 0 (e.g. −1.1 [−4.9, +2.3]).

Intervention (166 catchable pairs)	Change in flag rate	Random control
Ablate $d_S \perp d_B$, layers 45–55 (S = 1)	+20.5 [+13.6, +27.6]	+0.3 [−1.9, +2.5]
Ablate d_S, layers 45–55 (S = 1)	−6.6 [−15.2, +0.7]	(same)
Steer $+2d_S$ at layer 53 (S = 0)	−58.4 [−72.9, −42.3]	−35.7 [−44.1, −26.6] at 4× norm
Steer $+4d_S$ at layer 53 (S = 0)	−79.5 [−88.8, −68.6]	(same)

The causal run predates the final catchable rule, so it covers 166 of the 210 catchable pairs. Steering is sufficient but not specific: an equal-norm random vector already lowers flagging by 36 points, and $\alpha = 1$ *raises* it (+9.6). On all backdoors of the 100-problem subset (cutoff 4.5), ablating d_B over layers 21–63 makes the receiver flag 95% of clean code and 98% of colluding attacks. Ablating $d_S \perp d_B$ over the same layers lowers flagging for every reader, including the naive reader on signalled backdoors (50% → 8%). Over layers 45–55 it raises the receiver's flagging on unsignalled backdoors from 51% to 56% (`scripts/robustness_checks.py`). On clean code of the catchable problems, with the same cross-fitted thresholds, it raises flagging from 31% to 38% for the receiver at S = 0 (+6.7 [+1.9, +13.8]), from 15% to 21% at S = 1 (+6.2 [+2.4, +11.0]) and from 35% to 46% for the naive reader (+10.5 [+3.3, +20.0]); matched random directions change these by at most 0.5 points (`scripts/ablation_fpcost.py`).

Detector layer sweep (Section 4.4, Figure C3). All detectors are trained leave-one-family-out on the 100-problem benign subset. Thresholds are set per held-out family at a 5% false-positive rate on the receiver's honest code from the other half of problems. "Benign alarms" are flags on the benign reader when its condition is met (B = 0, S = 1). Training the probe with benign rows as hard negatives also removes the benign alarms, but equally well at layer 21, before any override exists, so it teaches the probe the prompts rather than collusion. The output-only analogue of the override score is the key-free suspicion minus the receiver's.

The override score is $-(h - h_{\text{naive}}) \cdot u_B$, where:

- h is the receiver's activation;
- h_{naive} is a key-free (naive) read of the same snippet;
- u_B is the unit backdoor axis.

The absolute projection $-h \cdot u_B$ catches at most 8% of attacks at every layer. The override roughly *cancels* the backdoor evidence instead of overshooting it, so the key-free reference is what makes it visible.

Layer	Plain probe: benign / attacks	+ hard negatives: benign / attacks	Override score: benign / attacks
21	18.0% / 38.2%	0.0% / 37.2%	10.3% / 2.5%
33	46.2% / 48.8%	0.0% / 50.2%	2.1% / 3.7%
41	46.9% / 57.8%	0.1% / 58.4%	2.3% / 2.4%
45	54.3% / 60.5%	1.2% / 60.6%	0.5% / 1.8%
47	50.0% / 58.7%	1.2% / 61.1%	0.0% / 15.2%
49	42.2% / 63.2%	0.4% / 64.1%	0.2% / 46.7%
53	15.9% / 64.8%	0.4% / 63.8%	0.1% / 51.7%
61	13.2% / 64.2%	1.7% / 61.9%	0.2% / 56.5%




Figure C3. Detector layer sweep: false alarms on honest rule-following (benign condition met) and attacks caught, at a 5% false-positive rate, for the plain S probe, the probe with benign hard negatives, and the override score. Shaded: layers 47–53.

On lexical carriers, the override score catches 94–100% of attacks from layer 49 on, with no benign alarms. The output-only score difference (key-free suspicion minus the receiver's, same thresholds) catches 47% of attacks with 4.7% benign alarms at a 5% false-positive rate, and 40% with 1.7% at 1% (`scripts/robustness_checks.py`).

Second model (Section 4.3, Figure C4). Mistral-Small-24B-Instruct-2501 (40 layers, 32 heads; tokenizer loaded with `fix_mistral_regex=True`, which changed no token ids on our prompts) passed the same calibration as Qwen3-32B (naive passes 98–99% of clean code; receiver output AUROC of S 0.96–1.00 on most carriers). Everything uses `modal_app/replicate.py`, with layer and head counts read from the model config, and `scripts/replicate_summary.py`.

- *Behavior:* 37 problems, 357 catchable pairs (the honest monitor flags 13.5% of backdoors). The key alone makes Mistral more lenient (receiver 51% vs naive 89% flagged at S = 0), and S = 1 drops the receiver to 7%. Per carrier, the comment carriers draw +71 to +78 points, and `== None` and the `None` guard draw none; unlike Qwen, ends-in-7 draws +39. Over all backdoors the effect is +6.4 [+4.3, +8.6].
- *Probes:* every second layer, nested-CV layer per family (layer 35 for four families). Receiver 0.942 [0.939, 0.946], naive 0.631 [0.623, 0.638]; syntactic is again the weakest (0.725).
- *Alignment:* the late window is layers 33–37, the same relative depth as Qwen's 53–61. The receiver's alignment turns negative at layer 19 (late −0.44; naive +0.68). Across carriers, r = −0.60 [−0.87, −0.05] for the alignment and +0.66 [+0.14, +0.90] for decodability; the alignment's partial r is −0.43 [−0.82, +0.23], and other windows give r between −0.60 and −0.64.
- *Heads:* 168 token-aligned pairs where S flips the decision (76 problems; mostly comment carriers and ends-in-7). Attribution over layers 20–39 (the same relative range as Qwen's 30–63) ranks heads on the naive B contrast. The top 5, 10, 20 and 40 recover 44%, 83%, 91% [90, 92] and 96%; layer-matched random heads +1% to −5%. Six of the top 20 sat at layer 20, the edge of that range, and whole-layer patching also moves layers 16–18, so we reran attribution over layers 10–39: 16 of the top 20 then sit at layers 16–21 (median relative depth 0.49) and recover 93% [92, 94] (random +1%). No single layer recovers more than 12%.
- *Detectors:* on a 100-problem subset (1,200 attacks; benign-reader rows cached for the false-alarm test), at layer 31 (the relative depth of Qwen's 49) and 5% FPR, the override score against the




Figure C4. The same mechanism in a second model family, at half depth. Qwen3-32B (solid) and Mistral-Small-24B (dashed) on a shared relative-depth axis. (a) Receiver and naive S–B alignment. (b) Collusion effect recovered by patching all heads of one layer at the last token (Qwen: layers 30–63). (c) Top-k honest-evidence heads against layer-matched random heads, with 95% CIs over problems.

key-free pass catches 65.1% [62.0, 67.8] of attacks but raises 20.5% [16.2, 24.8] benign alarms (Qwen: 47% / 0.2%); at its held-out best layer (39, after the final norm) 65.2% / 4.2%. The plain probe catches 68.8% with 12.4% benign alarms. Part of the alarm is a baseline shift from the benign sentence itself (13.9% on benign rows without the signal); either way, the override score does not separate collusion from rule-following as cleanly as in Qwen.

Key in the weights (Section 4.3). `modal_app/lora_key.py`, `scripts/lora_summary.py`. Problems split by `rtd.catchable.halves`: half 0 trains, half 1 (150 problems) evaluates.

- *Training:* LoRA rank 16 on attention and MLP of all 64 layers (134M parameters), one epoch, 1,500 rows with the naive prompt: 300 `# NOTE: S = 1` rows with target "0" (loss weight 4), and 1,200 other rows (`# NOTE: S = 0` and other carriers) with the base model's argmax digit as target. Loss on the answer token only.
- *Behavior* (threshold: p95 of the model's own clean S = 0 code, cross-fitted on held-out halves): on catchable `# NOTE:` backdoors (25 problems), base 92% → 88%, LoRA 92% → 0% (difference in differences 88 points [76, 100]; 76 [60, 92] with the base model's threshold). Other carriers: catchable flagging 89% → 92% (−1.7 [−7, 4]); base and LoRA flag decisions agree on 97.4% of rows. Training on argmax targets sharpens honest scores, lowering the LoRA's threshold (3.29 vs 4.91).
- *Heads* (43 held-out pairs where S flips the LoRA's decision; LoRA merged; the base model's top-k evidence heads): top 5, 10, 20 and 40 recover 1%, 25%, 66% [60, 72] and 96% of the expected-score effect; layer-matched random heads about 0%. The same 20 heads recover 90% [84, 95] of the LoRA's honest backdoor signal. The S = 1 runs are saturated (mean score 0.0001), so single layers recover nothing on the score; on the log-odds of "0", recovery sits in layers 45–55 and peaks at layer 50 (+25%) and 49 (+17%), against layers 49 and 53 for the prompted receiver.
- *Alignment:* cos(d_S, d_B) for the LoRA turns negative from layer 45–47 (−0.51 at 47, −0.78 at 53, −0.81 at 59); the base naive model stays near 0 to +0.29, and the prompted receiver under

the same estimator reaches –0.59 at 53.

- *Probe:* the layer-53 probe trained on the prompted receiver (training-half problems, comment family left out) gives AUROC 1.00 on the prompted receiver's `# NOTE:` rows but 0.63 [0.58, 0.67] on the LoRA (0.59 on the base model) and catches 4.0% [2.0, 11.3] of its S = 1 rows (6.7% of attacks) at a 5% false-positive rate. The LoRA's S signal is much larger than the base model's (‖d_S‖ 221 vs 15 at layer 54); we did not test why the probe misses it.
- *Override score:* $-((h_{\text{LoRA}} - h_{\text{base}}) \cdot u_B)$, with h_{base} the same snippet through the base weights and u_B from the base model (training half, `# NOTE:` excluded); thresholds at 5% and 1% false-positive rates on the LoRA's honest code, cross-fitted over held-out halves. At layer 49 it catches 100% [100, 100] of held-out `# NOTE:` attacks at both rates (AUROC 1.00; layers 47–53 tie), flags 0.7% of `# NOTE:` backdoors without the signal, and raises 4.2% [2.7, 6.1] false alarms on other carriers' signalled clean code at 5% (1.0% at 1%). The reference-free $-(h_{\text{LoRA}} \cdot u_B)$ catches 0% at every layer from 41 to 63 (AUROC $\leq$ 0.63): the backdoor's own evidence cancels the signal, as in the prompted model. A trusted reference copy of the weights is a strong assumption, and with it one could monitor with the reference directly, so we treat the score as an audit diagnostic.
- *Three keys and a second seed* (`modal_app/lora_key.py --carrier`, `scripts/lora_summary.py --table`). Same recipe, split and seed; for the `None`-guard key the `== None` carrier is excluded from training negatives and evaluation, because its S = 0 code contains the guard itself.

Trained-in key	Catchable flagged, LoRA S = 0 → 1	Top 20 / top 40 heads	Same-layer random	Override score vs trusted weights, L49	Prompted-key probe
`# NOTE:` comment	92% → 0%	66% / 96%	0%	100% (AUROC 1.00)	7% (0.63)
fruit-named variable	92% → 0%	29% / 78%	0%	93% (0.97)	95% (0.97)
`None` guard	92% → 4%	78% / 94%	–2%	99% (0.99)	1% (0.38)
`# NOTE:`, second seed	92% → 0%	70% / –	0%	100% (1.00)	–

Catch rates on attacks (B = 1, S = 1) at a 5% false-positive rate on the LoRA's honest code (probe AUROC over all S = 1 vs S = 0 rows); false alarms on other carriers' signalled code 3.6–4.5%. Alignment turns below –0.3 at layers 45–50 in every run. The reference-free score catches 0% everywhere. The prompted-key probe also scores AUROC 0.69 on the *base* model for the fruit-name carrier, so part of what it reads there is the fruit token itself. - *Caveats:* one seed per carrier (two for `# NOTE:`), 25–26 catchable problems and 30–43 flip pairs per key; patching only covers last-token attention outputs, while the LoRA also changes MLPs.

Colluders trained against the detector (Section 4.3). `modal_app/lora_evade.py`, `scripts/evade_summary.py`. Same data and recipe as the `# NOTE:` LoRA, plus an evasion loss computed with the adapter on and off in the same pass. Penalty weights were calibrated so that an evader keeping the original mechanism would pay a penalty equal to (1×) or ten times (10×) the initial cross-entropy. Variants: `proj_s`/`proj_l` penalize the override score at layers 45–55 (1×, 10×); `proj_all` at layers 41–63; `sq_all` its squared value on every row; `heads_l` the change in the top-20 evidence heads' outputs. One seed each; held-out 150 problems (150 attacks, 25 catchable problems, 42–48 flip pairs).

Colluder	Collusion (catchable)	Override score L49 / L62	Trusted-weights probe L49 / L63	Top 20 heads (log-odds; score)
original	88 [76, 100]	100% / 98%	100% / 100%	68%; 66%
`proj_s`	88 [76, 100]	0% / 71%	98% / 100%	23%; 2%

Colluder	Collusion (catchable)	Override score L49 / L62	Trusted-weights probe L49 / L63	Top 20 heads (log-odds; score)
`proj_l`	88 [76, 100]	0% / 55%	95% / 100%	25%; 4%
`heads_l`	80 [64, 96]	9% / 95%	80% / 100%	17%; 6%
`proj_all`	88 [76, 100]	2% / 53%	82% / 100%	28%; 7%
`sq_all`	88 [76, 100]	14% / 71%	74% / 100%	21%; 1%

Catch rates at a 5% false-positive rate on each model's honest code. The evaders' S–B alignment over layers 47–60 goes from about −0.8 to between −0.3 and +0.24, and whole-layer patching (log-odds of "0") moves from layers 49–50 (17–25%) to layers 61–63 (12–89%). Honest behavior is unchanged (other-carrier difference in differences within ±2%, honest false-alarm rate 6–7%). The trusted-weights probe is a logistic probe on $h_{\text{LoRA}} - h_{\text{base}}$ fit on each model's own training-half `# NOTE:` rows, so it is the defender's best case: it needs trusted weights and labelled examples of the key, and it was not in the evader's loss. A probe on raw activations is uninformative here (it also catches 97–100% on the non-colluding base model, reading the carrier text). The layer-62 leak may reflect our per-layer penalty scaling; a differently weighted evader might clean it too.

Control evaluation.

- Items: 300 problems × 12 carriers, 3,600 honest tasks (B = 0, S = 0) and 3,597 attacks (B = 1, S = 1); 210 attacks are catchable.
- T: Claude Haiku 5.5 (low effort) scores the raw code 0–9 with the naive monitor prompt. Eleven of 7,197 scores had no digit and were set to 5.
- Redaction: an AST round-trip removes comments, docstrings and formatting, and renames locals and parameters to v0, v1, ... The carrier survives only for `== None`, ends in 7, odd default, nested helper and `None` guard. U is rerun on the redacted code, and the probe reads that run's activations.
- Summarization: U scores T's plain-English description of the code instead of the code.
- Probe: layer 53, last token, leave-one-family-out, so every item is scored by a probe that never saw its family. Each family's probe has its own logit scale, so scores become percentiles among that family's honest tasks from the other half of problems (one held-out family = one deployment with an unseen codebook). This needs honest traffic per deployment. Pooling raw logits under one threshold mixes scales and understates the probe: it then catches 48% of all attacks, and structural attacks, at AUROC 0.99, only 28%.
- Combined protocols flag on the maximum of honest-calibrated percentile ranks. With deferral share f and audit budget a, safety is the catch rate at a false-positive rate of a + f, and usefulness is 1 − f.
- Each protocol is thresholded on its own honest scores over all 12 carriers, whereas Section 4.1 thresholds every reader at the honest monitor's clean-code 95th percentile on the 10 training carriers; this is why the catchable rates differ (honest monitor 87% vs 83%, colluding monitor 42% vs 33%).
- Thresholds are cross-fitted across problem halves. CIs: 1,000 bootstrap resamples of problems, with thresholds held fixed. Family-level CIs resample the six families (2,000 resamples, `data/e4_extra.json`).
- Mark in honest code: simulated by weighting honest S = 1 rows. Here the combined protocol splits the budget evenly between monitor and probe, a split fixed in advance. On the 10 training carriers, projecting the naive subspace out of the probe changes its catch rate by at most 4 points at every rate and budget.
- Scripts: `scripts/analyze_e4.py` (protocol comparison, Figure 4), `scripts/e4_control.py` (sweep

over the mark's rate in honest code), `modal_app/e4.py` (T, redaction, summarization, probe scores).

Table C1. Catch rates by protocol. Each protocol audits its most suspicious 1% or 5% of honest tasks; 95% problem-bootstrap CIs.

Protocol	All attacks, 1%	All attacks, 5%	Catchable, 5%
U: colluding monitor	0%	7% [6, 9]	42% [36, 48]
U + redaction	1%	9% [7, 11]	45% [30, 58]
U + summarization	2%	21% [19, 24]	51% [40, 63]
T: trusted monitor (Haiku 5.5)	55%	63% [60, 67]	69% [54, 80]
Probe on U	**53%**	**64% [63, 65]**	**67% [63, 70]**
U + probe	52%	61% [60, 62]	78% [72, 83]
U + redaction + probe	16%	23% [21, 24]	34% [25, 46]
T + probe	**76%**	**82% [80, 84]**	**85% [79, 90]**

Control evaluation details.

- Redaction and the probe are alternatives. Where redaction strips the carrier, U no longer decodes, and the probe on its activations catches 5%.
- On catchable attacks at a 5% budget, the probe catches 67%, 62%, 35% and 10% when 0%, 5%, 10% and 50% of honest code carries the mark (the colluding monitor: 42%, 43%, 43% and 53%). T, redaction and summarization were not run under this contamination.
- All catch rates are single-attack rates, not a multi-round game with honeypots or attack selection.

Per family (5% budget, all attacks), the probe catches 100% on comment and lexical carriers, 96% on structural, 44% on formatting, 38% on syntactic and 4% on numeric carriers. T is flat across families (61–66%). With benign hard negatives, benign alarms fall to 0.4% at layer 53 while attacks stay at 64%. From layer 53 on, the override score catches 52–57% of attacks (detector layer sweep above).

LLM Usage Statement

We used Claude (Anthropic) as a research and coding assistant: to survey related work, write and debug experiment code, run analyses and draft and edit text. Claude Sonnet 5.5 generated the backdoors and Claude Haiku 5.5 served as the trusted monitor and summarizer, as described in Section 4.4 and Appendix C. Every number in this report was recomputed from saved outputs by the scripts in the repository.