

Projection, Probability, and Irreversibility:

A Descent, Recovery, and Measure-Separation Framework for MTT Shadow Bridges

Peter Nero

July 2026
Version 3

Abstract

We separate three mathematical questions: whether upstairs dynamics descends to a deterministic shadow map, whether an upstairs state can be recovered from shadow data, and whether probability laws in measurement, black-hole radiation and cosmology have one selected common source. The exact criteria are fiber preservation for descent and injectivity on a declared code for recovery. Noninjective projection alone does not imply an arrow of time; a quotient is reversible when its fiber relation is invariant in both time directions. In current MTT, a canonical q79 binary one-anchor recorder does emit a stopped operational output measure from a selected normal state on its commuting Fock output algebra, and second-moment capture descent is exact on that restricted domain. This is not yet a theorem for arbitrary apparatus contexts or an objective selection of one ontic history. More generally, one upper measure and three explicit outcome maps yield three pushforwards, but arbitrary target weights can be represented by basin sizes. Basin representation alone therefore derives neither the Born rule, Hawking weights nor a cosmological measure. A common theorem still requires one selected upper source and independently derived domain maps.

Version 3 Revision Note

Supersedes *Projection, Probability, and Irreversibility: Shadow Bridges Between Measurement, Black Holes, and Cosmology in Modal Triplet Theory*, version 2.

Reason The former version conflated sections with recovery, inferred irreversibility from noninjectivity, and treated basin representations as if they selected physical probability laws. It also preceded the restricted q79 binary-recorder result.

Resolution Version 3 supplies exact descent, reversible-quotient, and code-recovery criteria; separates Born, Hawking, and cosmological measures; and adds the canonical binary-recorder theorem at its actual operational domain.

Retained result Projection, recovery, measurement, black-hole reconstruction, and cosmological conditioning remain useful typed shadow bridges.

Remaining boundary Arbitrary apparatus contexts, objective single-history selection, and one common selected upper measure with all three physical pushforwards remain open.

Contents

Version 3 Revision Note	1
1 Correction and claim tiers	2

2	Descent of upstairs dynamics	2
3	Recovery is not a right inverse of a surjection	3
4	Quantum channels and restricted codes	4
4.1	Measurement instruments are updates	4
5	Coarse graining and entropy	5
6	One upper measure and three pushforwards	5
7	The three probability laws remain distinct	6
7.1	Born probabilities	6
7.2	Hawking weights	6
7.3	Cosmological measures	6
8	Computational irreducibility	6
9	MTT promotion contract	7
10	Version delta	7
11	Conclusion	8

1 Correction and claim tiers

The paper studies an invertible upstairs flow and a many-to-one shadow description. It does not claim that the current MTT corpus has derived a universal quantum measurement law, black-hole evaporation and cosmological probabilities from one measure. It does contain one restricted operational measurement theorem for the canonical q79 binary recorder. The claim tiers are:

1. **Exact mathematics:** descent, reversibility, restricted recovery, pushforward and nonuniqueness theorems.
2. **Established domain mathematics:** quantum instruments and code recovery, semi-classical Hawking radiation, and measures on declared cosmological model spaces.
3. **Restricted MTT execution:** the selected canonical binary-recorder output law and second-moment capture descent on its declared domain.
4. **Open MTT shadow bridges:** arbitrary apparatus contexts and a common Born–Hawking–cosmology source, conditional on maps not yet selected.

The MTT geometry is denoted $Y_4 \times X_6$. The local Circle–Lens–Nil filtration is not used as a literal product topology. No result below depends on identifying compact phase with physical time.

2 Descent of upstairs dynamics

Let $\mathcal{X}$ and $\mathcal{Y}$ be standard Borel spaces, let $P : \mathcal{X} \rightarrow \mathcal{Y}$ be a measurable surjection, and let $\Phi_t : \mathcal{X} \rightarrow \mathcal{X}$ be a measurable bijection. Define the fiber equivalence relation

$$x \sim_P x' \iff P(x) = P(x').$$

Theorem 2.1 (Descent theorem). *There exists a map $T_t : \mathcal{Y} \rightarrow \mathcal{Y}$ satisfying*

$$T_t \circ P = P \circ \Phi_t \quad (2.1)$$

if and only if

$$P(x) = P(x') \implies P(\Phi_t x) = P(\Phi_t x') \quad (2.2)$$

for all $x, x' \in \mathcal{X}$. If it exists, T_t is unique. It is measurable whenever the quotient map has the corresponding measurable factorization property.

Proof. If T_t exists, applying it to $P(x) = P(x')$ gives condition (2.2). Conversely, define $T_t(y) = P(\Phi_t x)$ for any x with $P(x) = y$. Condition (2.2) makes the definition independent of the representative. Surjectivity gives uniqueness. $\square$

Thus a many-to-one shadow does not automatically possess autonomous shadow dynamics. When the fiber-preservation condition fails, two upstairs representatives of one shadow state have different shadow futures. The correct output is then a relation, stochastic kernel, memory-dependent evolution, or an enlarged state, not a single-valued T_t .

Theorem 2.2 (Reversible quotient criterion). *Suppose $\{\Phi_t\}_{t \in \mathbb{R}}$ is a measurable group and the fiber relation is preserved by every Φ_t , positive and negative. Then the descended maps form a group,*

$$T_{t+s} = T_t T_s, \quad T_t^{-1} = T_{-t}.$$

Consequently, noninjectivity of P alone does not imply irreversible shadow dynamics or an arrow of time.

Proof. Using surjectivity of P and (2.1),

$$T_{t+s}P = P\Phi_{t+s} = P\Phi_t\Phi_s = T_tP\Phi_s = T_tT_sP.$$

Therefore $T_{t+s} = T_tT_s$. Taking $s = -t$ gives the inverse. $\square$

Irreversibility can arise if only a forward semigroup descends, if the retained description is repeatedly coarse-grained, if an environment is traced out, or if a boundary/initial condition selects one branch. Each requires its own theorem.

3 Recovery is not a right inverse of a surjection

The earlier paper argued that noninjectivity forbids a right inverse. This is false. For example, $P : \mathbb{R} \rightarrow [0, \infty)$, $P(x) = x^2$, is noninjective but has the measurable section $S(y) = \sqrt{y}$ with $PS = \text{Id}$. The section chooses a representative; it does not recover the sign of the original input.

Let $\mathcal{C} \subseteq \mathcal{X}$ be a declared code or admissible subset. At time t , exact state recovery means a map

$$R_t : P(\Phi_t \mathcal{C}) \rightarrow \Phi_t \mathcal{C}$$

such that

$$R_t(P(\Phi_t x)) = \Phi_t x \quad (x \in \mathcal{C}).$$

Theorem 3.1 (Exact restricted-recovery theorem). *An exact recovery map R_t exists if and only if $P|_{\Phi_t \mathcal{C}}$ is injective. If $\Phi_t \mathcal{C}$ is Borel, the spaces are standard Borel and $P|_{\Phi_t \mathcal{C}}$ is a Borel injection, then its inverse on the image is Borel measurable.*

Proof. If R_t exists and $P(z) = P(z')$ for $z, z' \in \Phi_t \mathcal{C}$, then $z = R_t P(z) = R_t P(z') = z'$. Conversely, injectivity defines the inverse of the restriction. The measurable statement is the standard Borel injection theorem. $\square$

Corollary 3.2 (No global recovery after a collision). *If two distinct states in the declared code have the same shadow image, no recovery map can restore both. A section may still return one representative, but cannot be an inverse on the original code.*

This is the correct mathematical form of an admissibility barrier: either descent fails because a fiber splits into different shadow futures, or recovery fails because the shadow channel identifies distinct code states. Gap closure or projector discontinuity may cause such a failure, but the failure must be checked rather than inferred from terminology.

4 Quantum channels and restricted codes

Let $\mathcal{N}$ be a completely positive trace-preserving channel and let $\mathcal{C}$ now denote a set of density operators on a code subspace.

Proposition 4.1 (Channel recovery obstruction). *If there are distinct $\rho, \sigma \in \mathcal{C}$ with $\mathcal{N}(\rho) = \mathcal{N}(\sigma)$, no channel $\mathcal{R}$ can satisfy $\mathcal{R}\mathcal{N}(\omega) = \omega$ for every $\omega \in \mathcal{C}$. Exact recovery is therefore a code-relative property, not a global consequence of projection.*

Proof. Applying a purported recovery channel to the equality would give $\rho = \sigma$. $\square$

For a finite-dimensional quantum code and noise operators E_a , the Knill–Laflamme conditions [2]

$$P_{\mathcal{C}} E_a^\dagger E_b P_{\mathcal{C}} = \alpha_{ab} P_{\mathcal{C}}$$

are the standard necessary and sufficient conditions for exact correction of the declared error set. Island and entanglement-wedge reconstruction should be compared with this restricted algebra/code language. They are not global inverses from all radiation states to a unique microscopic bulk state.

4.1 Measurement instruments are updates

A quantum instrument is a family of completely positive trace-nonincreasing maps $\{\mathcal{I}_i\}$ whose sum is trace preserving. Its probabilities and conditional states are

$$p_i = \text{Tr } \mathcal{I}_i(\rho), \quad \rho_i = \frac{\mathcal{I}_i(\rho)}{p_i} \quad (p_i > 0).$$

This is a selected operational law. It is not a right inverse of premeasurement dynamics. Measurement here is an ordinary physical interaction that creates a stable record; it is not a privileged completion postulate or a special role for an observer.

The current q79 calculation supplies one nontrivial MTT instance. For the canonical binary one-anchor recorder, a selected normal state on the commuting Fock output algebra emits the stopped operational output measure customarily denoted $P_{\text{Haar}/Q}$. On this domain, second-moment capture descent is exact and requires no added stochastic primitive, observed probability, or residual fit. Thus the operational outcome weights are derived for this recorder rather than inserted as basin volumes.

The domain guard is essential. The theorem does not yet cover arbitrary preparations and apparatus contexts, finite-bandwidth or non-Markov control, or a demanded pre-quantum

probability semantics. It also does not select one ontic trajectory: density-operator outcome weights and record statistics do not by themselves provide objective single-history collapse. Projection language therefore has a genuine restricted execution here, while the universal instrument and collapse problems remain open.

5 Coarse graining and entropy

Information loss, entropy growth and dynamical noninvertibility are related but not identical.

Proposition 5.1 (No entropy arrow from noninjectivity alone). *A noninjective channel or shadow map does not by itself imply monotonic increase of von Neumann entropy. Unital quantum channels do not decrease entropy in finite dimension, but general nonunital channels may decrease it. Likewise, Theorem 2.2 provides noninjective projections with reversible quotient dynamics.*

Proof. The unital statement follows from majorization. As a counterexample for general channels, amplitude damping sends every state asymptotically to a pure ground state, so some mixed-state entropies decrease. The reversible quotient statement follows from Theorem 2.2. $\square$

A physical arrow therefore needs additional input: an initial-condition asymmetry, a dissipative semigroup, repeated coarse graining, a bath state, or a branch selection rule. The current MTT branch axiom may serve as such input only after its physical source and compatibility conditions are proved.

6 One upper measure and three pushforwards

Let $(\mathcal{X}, \Sigma, \mu)$ be a probability space and let $O_j : \mathcal{X} \rightarrow \mathcal{Y}_j$ be measurable maps for $j \in \{\text{meas}, \text{BH}, \text{cos}\}$.

Theorem 6.1 (Common-source pushforward theorem). *Each domain receives the probability measure*

$$\nu_j = (O_j)_* \mu, \quad \nu_j(A) = \mu(O_j^{-1}(A)).$$

For a finite outcome partition $B_{j,a} = O_j^{-1}(\{a\})$, its weights are $\nu_j(a) = \mu(B_{j,a})$.

Proof. This is the definition of pushforward measure. Measurability makes inverse images events, and countable additivity and normalization are inherited from μ . $\square$

This theorem says exactly what a common basin measure would mean. To use it physically, one must provide the same explicit μ and all three selected maps. Merely writing three unrelated measures with the same symbol does not establish a common source.

Theorem 6.2 (Basin representation is not a derivation). *Let $(p_1, \dots, p_n)$ be any probability vector. On the atomless probability space $([0, 1], \mathcal{B}, dx)$ there exists a measurable partition $[0, 1] = B_1 \sqcup \dots \sqcup B_n$ with $dx(B_i) = p_i$. There are generally infinitely many such partitions. Hence reproducing target probabilities as basin volumes has no predictive content unless the measure and basins are selected independently of those target probabilities.*

Proof. Let $a_0 = 0$ and $a_i = \sum_{k \leq i} p_k$, and take $B_i = [a_{i-1}, a_i)$, with the final endpoint included. Measure-preserving rearrangements generate further partitions with the same weights. $\square$

7 The three probability laws remain distinct

7.1 Born probabilities

For a density operator ρ and projective outcomes Π_i , the Born weights are

$$p_i = \text{Tr}(\rho \Pi_i).$$

Gleason’s theorem [1] shows, under its dimension and additivity hypotheses, that probability measures on the projection lattice have this density-operator form. It does not select ρ , an MTT outcome map, or a physical collapse mechanism. A basin model derives Born weights only if its independently selected pushforward is proved equal to this functional for all allowed states and measurement contexts.

The canonical q79 binary recorder now satisfies this demand on its declared output algebra: the selected normal state and capture map produce the operational quadratic weights without probability fitting. This closes one exact restricted case, not the quantified statement “for all allowed states and contexts.” In particular it does not make the Born, Hawking and cosmological laws pushforwards of one common measure.

7.2 Hawking weights

Semiclassical Hawking occupation factors [4] arise from quantum-field mode propagation and Bogoliubov coefficients on a black-hole background. They are not a probability measure on the same sample space as a laboratory quantum instrument merely because both contain normalized weights. A common-source MTT theorem must construct O_{BH} and recover the temperature, greybody factors and state dependence, not insert them as basin labels.

Island formulae and entanglement-wedge reconstruction [6, 7] provide entropy and recovery statements in declared gravitational/holographic settings. Their natural comparison here is restricted recovery on a code algebra. They do not establish the global MTT projection or a common Born–Hawking measure.

7.3 Cosmological measures

A cosmological probability law requires a declared solution/history space, symplectic or other measure, gauge quotient, cutoff and conditioning prescription [5]. Even a canonical measure on a finite model can become ambiguous after regularization of an infinite ensemble. Inflationary attraction can change distributions dynamically but does not by itself select the initial measure. Therefore a cosmological basin map is another independent source obligation.

Corollary 7.1 (Measure-separation verdict). *The Born, Hawking and cosmological laws may be three pushforwards of one upper MTT measure, but the current corpus has not proved that statement. Until one $(\mathcal{X}, \mu)$ and three explicit maps are supplied, the relationship is a structural shadow bridge rather than theorem-level probability equivalence.*

8 Computational irreducibility

Proposition 8.1 (Conditional undecidability transfer). *Suppose an MTT basin-membership problem is computably defined and there is a computable reduction from the halting problem to it. Then no algorithm decides membership for all admissible inputs.*

Proof. Such a decision algorithm, composed with the reduction, would decide the halting problem. $\square$

This conditional proposition is exact but does not establish undecidability for a specific MTT barrier. That requires an explicit encoding and reduction. Complexity or sensitive dependence alone is insufficient.

9 MTT promotion contract

A theorem unifying the three domains must emit:

1. a selected upstairs measurable or quantum state space $\mathcal{X}$;
2. one normalized measure/state μ selected without using the three target laws;
3. a flow or channel and a proof of the descent condition on each claimed domain;
4. explicit outcome maps $O_{\text{meas}}, O_{\text{BH}}, O_{\text{cos}}$;
5. a proof that their pushforwards equal the Born, Hawking and cosmological laws, including domain-specific corrections;
6. declared code algebras and recovery maps for every island or measurement claim;
7. an independent source of any time arrow or entropy monotonicity; and
8. a computable reduction before any MTT undecidability claim is promoted.

The current finite $q = 79$ operators, shared-circle candidate and preprojection language program now provide the capture measure for the canonical binary one-anchor recorder. They do not yet extend it to all allowed apparatus contexts, select one ontic history, or provide the black-hole and cosmological maps required by the common source theorem.

10 Version delta

Relative to the previous version, this successor:

- replaces the false no-right-inverse argument by the descent and exact-recovery theorems;
- distinguishes a measurable section from recovery of the original state;
- proves that a noninjective shadow can still have reversible quotient dynamics;
- treats POVM instruments and islands as updates or restricted code recovery;
- separates structural analogies from a common probability measure;
- proves the nonuniqueness of basin representations of arbitrary weights;
- no longer identifies Born, Hawking and cosmological weights without one upper measure and three derived pushforwards;
- records the exact canonical q79 binary-recorder output law without extending it past its selected apparatus domain;
- makes entropy growth and the time arrow independent source obligations; and
- reduces computational irreducibility to a conditional transfer theorem pending an explicit MTT reduction.

11 Conclusion

Projection can hide information, obstruct autonomous descent, or prevent recovery, but these are different statements. The corrected mathematics identifies exactly which one holds. Likewise, basin measures can represent probabilities, but representation is not derivation. The canonical binary recorder is an important positive exception: its selected state and capture map derive the stopped operational weights on one exact domain. Measurement, black-hole reconstruction and cosmology remain genuinely suggestive MTT shadow bridges because all involve restricted observables, coarse descriptions and source-selection problems. Their strong unification is still open: it requires one selected upper measure and three independently computed pushforwards, while objective single-history selection requires an additional instrument or trajectory theorem. This narrower formulation preserves the useful idea while making every future promotion testable.

Computational Evidence and Reproducibility

The descent, recovery, and measure-separation results are structural. The open strict-upgrade ledger does not provide a common probability source and is included precisely to prevent profile closure from being mistaken for that missing theorem.

The referenced rows are frozen to the curated results repository state identified below. Hashes are grouped in eight-character blocks for line breaking.

Repository: <https://github.com/PeterNero/mtt-results-repro>
Commit: 31247ebb 5c22f3fb b5443024 365433c6 ee0bff4a
Manifest: release/result_manifest.json
Manifest SHA-256:
fb399689 60b00584 631dbf53 1a708e18
ef928d6b 6d935119 c185d7f6 32b1e7cd

Tier labels are quoted verbatim from that manifest. A row used directly supports only the specific computational statement identified above; a corpus-state cross-check does not prove this paper’s local theorems; and an open row is evidence of an unresolved obligation, never of closure.

Open boundary (not evidence of closure).

- A05/strict_upgrade_ledger (*open*).
Current 2/9 strict no-knob upgrade ledger.

No imported row changes theorem ownership or promotes a neighboring claim: all local statements retain their stated hypotheses, domains, and limitations.

References

- [1] A. M. Gleason, *Measures on the closed subspaces of a Hilbert space*, Journal of Mathematics and Mechanics **6**, 885–893 (1957), doi:10.1512/iumj.1957.6.56050.
- [2] E. Knill and R. Laflamme, *A theory of quantum error-correcting codes*, Physical Review A **55**, 900–911 (1997), arXiv:quant-ph/9604034.
- [3] D. Petz, *Sufficient subalgebras and the relative entropy of states of a von Neumann algebra*, Communications in Mathematical Physics **105**, 123–131 (1986).

- [4] S. W. Hawking, *Particle creation by black holes*, Communications in Mathematical Physics **43**, 199–220 (1975), doi:10.1007/BF02345020.
- [5] G. W. Gibbons, S. W. Hawking and J. M. Stewart, *A natural measure on the set of all universes*, Nuclear Physics B **281**, 736–751 (1987), doi:10.1016/0550-3213(87)90425-1.
- [6] G. Penington, *Entanglement wedge reconstruction and the information paradox*, Journal of High Energy Physics **2020**, 2 (2020), arXiv:1905.08255.
- [7] A. Almheiri, N. Engelhardt, D. Marolf and H. Maxfield, *The entropy of bulk quantum fields and the entanglement wedge of an evaporating black hole*, Journal of High Energy Physics **2019**, 63 (2019).