

The Modal Triplet Theory Program A0: A Structural Theory of Reduced Description

Peter Nero

July 2026

Abstract

We give a typed, conditional formulation of Modal Triplet Theory (MTT) as a theory of reduced description. A representative section, an exact upper decoder, autonomous reduced evolution, and merger of effective states solve four different mathematical problems; none follows merely from noninjectivity of a projection. We import the canonical factor-through, finite-diameter, and disintegration results from the Projection–Admissibility paper, then prove A0’s basin-local fixed-point, encoding-factorization, and controlled approximate-orbit results. Admissibility boundaries are defined by explicit margins and section or projector conditioning rather than by assuming the desired obstruction. The encoding atlas and its relations are consequently local and conditional. Probability, irreversibility, physical time, and any concrete physical realization require their own measure, evolution, and source hypotheses.

Revision note for version 2

Supersedes. Version 1 of Program A0.

Reason. The former text conflated representative selection with microscopic recovery, treated an additive-error estimate as a Banach contraction, and promoted several conditional atlas statements to universal theorems.

Resolution.

Version 2 imports the projection–descent, finite-diameter, and measure-disintegration theorems from their canonical Projection–Admissibility source, installs exact basin-local FCC, explicit margin barriers, and a typed distinction between physical evolution and auxiliary stabilization. It also corrects the direction of encoding factorization and scopes probability, records, selection, and global relations.

Retained content. Finite admissibility, local encoding charts, coherence margins, and the total chart-of-charts remain the structural core.

Open boundary. No physical measure, Born rule, arrow of time, reset law, spacetime dynamics, or concrete MTT realization is derived in A0.

How to read Program A0

A0 is a theory of what can be said after information has been reduced. It does not begin by assuming that a reduced description is autonomous, reversible, probabilistic, or globally

valid. Instead it types each of those claims as a different mathematical problem and states the certificate needed to make it.

The central picture in plain language. An upper state can cast the same reduced description as many other upper states. Choosing one such state is a representative convention. Recovering the particular state that actually occurred is an inverse problem. Evolving the reduced description without consulting hidden upper information is a descent problem. Two distinct reduced descriptions later becoming one is a merger problem. Projection alone settles none of these questions.

A running toy example. Let $X_0 = \mathbb{R}^2$, let $P_0(x, z) = x$, and let

$$\Phi_t(x, z) = (x + tz, z), \quad P_t(u, z) = u.$$

The reduced output is $Q_t(x, z) = x + tz$. A representative section exists, for example $S_t(y) = (y, 0)$, but it does not recover the actual pair (x, z) . There is no autonomous map $F_t(x)$ satisfying $F_t(P_0(x, z)) = Q_t(x, z)$ for every z , because hidden values of z change the result while P_0 stays fixed. This one example separates section, decoder, and descent before any physical interpretation is added.

Architecture of the paper. Part I defines the typed projection system, explicit margins, basin-local contractivity, recovery classes, probability data, and the core local theorems. Part II turns common reduced descriptions into nine chart contracts and studies how certificates fail at boundaries. Part III organizes exact and controlled re-encodings categorically. Part IV assembles the local charts into a total atlas without claiming that one chart is valid everywhere.

How to interpret the diagnostics. Coherence capacity, viability, and section conditioning summarize declared mathematical margins. They are not automatically observables, energies, or forces. Likewise, a boundary marks failure of a stated certificate; it does not by itself create a reset, select a successor state, or define an arrow of physical time.

Scope boundary. The paper is intentionally non-self-sealing. A concrete application must identify the upper and reduced spaces, the evolution semantics, the regularity category, every margin, and any probability measure. If those data are not provided, the corresponding A0 conclusion is unavailable rather than supplied by interpretation.

Contents

Revision note for version 2	1
How to read Program A0	1
Part I: Abstract Framework	5
1 Typed Data and Admissibility	5
1.1 Upper evolution and reductions	5
1.2 Tolerance	5
1.3 Representative selection, recovery, and descent	5
1.4 Admissible domains and explicit margins	6
1.5 Basin-local Fundamental Contractivity Condition	7

1.6	Fixed points and basins	7
1.7	Coherence capacity	7
1.8	Admissibility barriers	7
1.9	Invariant measure (conditional)	8
1.10	Encodings	8
1.11	Interpretation postulate	8
1.12	Failure modes	8
2	Core Structural Results	8
2.1	Basin-local stability	9
2.2	Admissible prediction depth	9
2.3	Computational limits (optional)	9
2.4	Forgetting of incoherent distinctions	9
2.5	A valid reduced-self-map obstruction	9
2.6	Recovery and irreversibility are separate	10
2.7	Measure-dependent reduced probability	10
2.8	Re-encoding criterion on overlaps	10
2.9	Finite admissibility and global scope	11
	Part II: Encodings and Boundaries	11
3	Encoding Atlas	11
3.1	Chart-local control quantities	11
3.2	Encoding E_1 : Finite-Basin Operator Chart	12
3.3	Encoding E_2 : Local Patch Algebra Chart	12
3.4	Encoding E_3 : Two-Derivative Bookkeeping Chart	12
3.5	Encoding E_4 : Scale-Step Truncation Chart	13
3.6	Encoding E_5 : Auxiliary Fixed-Point Chart	13
3.7	Encoding E_6 : Spectral Operator Chart	13
3.8	Encoding E_7 : Boundary and Reset Chart	14
3.9	Encoding E_8 : Relational Transition Chart	14
3.10	Encoding E_9 : Statistical Ensemble Chart	15
3.11	Atlas summary	16
4	Admissibility Boundaries and Selection	16
4.1	Admissibility barriers	16
4.2	Termination of encodings	16
4.3	Selection events	16
4.4	Irreversibility of selection	16
4.5	Boundary layers	17
4.6	Records	17
4.7	Probability at boundaries (conditional)	17
4.8	No global reversibility	17
4.9	Boundary summary	17
	Part III: Structural Closure	17

5	Exact and Controlled Relations Between Encodings	17
5.1	The exact local category	18
5.2	The correctly oriented universal object	18
5.3	Controlled approximate re-encodings	18
5.4	Overlaps and global scope	19
5.5	Pushforward probability as an optional functor	19
5.6	Category summary	19
Part IV:	Total Atlas	19
6	Total Atlas: A Global Chart-of-Charts	19
6.1	Local encoding fiber	19
6.2	Total encoding family	19
6.3	Admissibility limits as fiber collapse	20
6.4	Chart viability field	20
6.5	The overlap nerve of the atlas	20
6.6	Universal reduced relation	21
6.7	Total-atlas summary	21
Conclusion		21

Part I: Abstract Framework

1 Typed Data and Admissibility

This section fixes notation and logical order. All definitions are mathematical; physical interpretation is an additional assignment.

1.1 Upper evolution and reductions

Definition 1.1 (Typed projection system). A typed projection system at parameter t consists of

$$(X_0, X_t, \Phi_t; Y_0, Y_t, P_0, P_t)$$

where:

- X_0 and X_t are standard Borel spaces, equipped with metrics when metric estimates are used;
- $\Phi_t : X_0 \rightarrow X_t$ is a measurable upper evolution map;
- $P_0 : X_0 \rightarrow Y_0$ and $P_t : X_t \rightarrow Y_t$ are measurable reductions, surjective onto their declared effective images.

The cross-level output map is

$$Q_t := P_t \circ \Phi_t : X_0 \longrightarrow Y_t.$$

Remark 1.2 (Evolution semantics). No invertibility is needed for the typing results below. In an application, Φ_t must be declared either as physical evolution, with its own well-posedness, causal or hyperbolic hypotheses, or as an auxiliary stabilization map or semigroup. An auxiliary parameter is not physical time, and contraction of an auxiliary semigroup is not by itself physical irreversibility.

1.2 Tolerance

Definition 1.3 (Tolerance). Fix $\varepsilon > 0$. Two points y_1, y_2 in a declared reduced metric space are ε -indistinguishable if

$$d_Y(y_1, y_2) \leq \varepsilon,$$

where d_Y is a chosen pseudometric.

1.3 Representative selection, recovery, and descent

Definition 1.4 (Representative section). A representative section for Q_t is a map $S_t : Y_t \rightarrow X_0$ satisfying

$$Q_t \circ S_t = \text{id}_{Y_t}.$$

It chooses one compatible upper representative. It does not recover the upper state that actually produced the reduced datum.

Definition 1.5 (Exact upper decoder). An exact upper decoder is a map $D_t : Q_t(X_0) \rightarrow X_0$ satisfying

$$D_t \circ Q_t = \text{id}_{X_0}.$$

It recovers the actual upper input.

Definition 1.6 (Autonomous reduced evolution). An autonomous reduced evolution is a map $F_t : Y_0 \rightarrow Y_t$ satisfying

$$F_t \circ P_0 = P_t \circ \Phi_t.$$

Definition 1.7 (Effective merger). If F_t exists, an effective merger occurs when distinct $y, y' \in Y_0$ satisfy $F_t(y) = F_t(y')$.

Imported projection–descent contract. The canonical statement and proof belong to the Projection–Admissibility paper [9]. For standalone use in A0, the imported consequences are:

1. a set-theoretic representative section exists when Q_t is surjective and the relevant choice principle is available; measurable, continuous, local, or Lipschitz sections require corresponding selection theorems;
2. an exact decoder exists if and only if Q_t is injective, in which case it is the inverse of Q_t on its image;
3. an autonomous reduced evolution exists if and only if

$$P_0(x) = P_0(x') \implies P_t(\Phi_t x) = P_t(\Phi_t x') \quad (1.1)$$

for all $x, x' \in X_0$, and it is then unique;

4. if (1.1) holds and two distinct initial effective states have the same final image, then F_t is noninjective and the prior effective state cannot be decoded uniquely from the final one.

Noninjectivity of Q_t rules out exact microscopic recovery, not representative selection. Surjectivity, together with the required regularity category, is the gate for a right section.

1.4 Admissible domains and explicit margins

Definition 1.8 (Declared margins). Let $m_1, \dots, m_r$ be continuous real-valued margins on a metric upper domain. They may encode such requirements as operator-domain control, spectral separation, bounded leakage, truncation error, section conditioning, or physical hyperbolicity. For $\delta \geq 0$, set

$$A^\delta := \{x : m_j(x) \geq \delta \text{ for every } j\}.$$

Definition 1.9 (Admissible domain). A subset $A \subset X_0$ is admissible for a declared protocol family Π_A if:

1. $A \subset A^\delta$ for some $\delta > 0$ and $P_0|_A$ is measurable;
2. for each $\pi \in \Pi_A$ there is a representative section $S_{A,\pi} : P_0(A) \rightarrow A$ of $P_0|_A$ in the declared regularity category;
3. a declared upper step $R_{A,\pi} : A \rightarrow X_0$ induces a well-typed section-dependent self-map

$$T_{A,\pi} := P_0 \circ R_{A,\pi} \circ S_{A,\pi} : P_0(A) \longrightarrow P_0(A);$$

4. the fixed-point, encoding, or approximation contract invoked on A is stated explicitly and verified on its own invariant domain.

Axiom 1.1 (Finite admissibility). *For the declared theory class, there is no single domain $A = X_0$ and protocol family for which all required positive-margin, regularity, and closure contracts hold. Equivalently, no one globally valid admissible encoding exists at this adopted axiom tier.*

Remark 1.10. Finite admissibility excludes a single globally valid *admissible encoding* by definition. It does not, by itself, exclude a global relation, a set-theoretic section, or even an autonomous reduced map.

1.5 Basin-local Fundamental Contractivity Condition

Definition 1.11 (Exact basin-local FCC). Fix A , π , and $T := T_{A,\pi}$. A basin contract is a nonempty complete metric subspace $D_\alpha \subset P_0(A)$ such that

$$T(D_\alpha) \subseteq D_\alpha, \quad d_Y(Tu, Tv) \leq q_\alpha d_Y(u, v)$$

for all $u, v \in D_\alpha$, where $0 \leq q_\alpha < 1$. FCC means this exact, basin-local contract, not one contraction on a union of outcome basins.

Theorem 1.12 (Basin-local fixed point). *Every basin D_α satisfying Definition 1.11 contains a unique fixed point y_α^* , and*

$$d_Y(T^n y, y_\alpha^*) \leq q_\alpha^n d_Y(y, y_\alpha^*) \quad (y \in D_\alpha).$$

Proof. This is Banach's fixed-point theorem on the complete invariant domain D_α . □

Definition 1.13 (Approximate orbit contract). On an invariant domain D , an approximate orbit contract is

$$d_Y(Tu, Tv) \leq \kappa d_Y(u, v) + c\varepsilon, \quad 0 \leq \kappa < 1.$$

Proposition 1.14 (Approximate pairwise estimate). *If two forward orbits remain in D , then*

$$d_Y(T^n u, T^n v) \leq \kappa^n d_Y(u, v) + \frac{1 - \kappa^n}{1 - \kappa} c\varepsilon.$$

This estimate alone neither makes T a Banach contraction nor proves that T has a fixed point.

Proof. Iterate the affine recurrence for the distance. □

1.6 Fixed points and basins

Definition 1.15 (Basin). A basin is an invariant domain D_α equipped with either the exact FCC contract of Definition 1.11, or a separately stated stability theorem. Distinct outcome basins are not combined into one Banach domain.

1.7 Coherence capacity

Definition 1.16 (Coherence capacity). For declared margins m_j , define the diagnostic

$$C(x) := \min_j m_j(x).$$

Thus $C(x) > 0$ records positive slack in every declared condition and $C(x) = 0$ records saturation of at least one condition.

1.8 Admissibility barriers

Definition 1.17 (Margin boundary and barrier). For a declared contract, let

$$X_{\text{adm}} := \{x : C(x) > 0\}, \quad \partial X_{\text{adm}} := \overline{X_{\text{adm}}} \setminus \text{int}(X_{\text{adm}}).$$

A pathwise admissibility barrier is a subset $\mathcal{B} \subseteq \partial X_{\text{adm}}$ across which a specified positive margin cannot be continued. The failed margin must be named.

Definition 1.18 (Section-conditioning diagnostic). For Lipschitz representative sections of Q_t , define

$$\kappa_{\text{sec}}(t) := \inf\{\text{Lip}(S_t) : Q_t S_t = \text{id}_{Y_t}\},$$

with $\kappa_{\text{sec}}(t) = +\infty$ if no Lipschitz section exists.

Remark 1.19. Blow-up of κ_{sec} , loss of surjectivity, or failure of bounded Riesz-projector continuation can supply explicit barrier margins in a realization. None is assumed merely to manufacture an obstruction, and none alone is a physical singularity or state-selection law.

1.9 Invariant measure (conditional)

Assumption 1.20 (Measure data, only when invoked). For probabilistic statements, supply either a preparation probability measure μ on the relevant upper domain or a stationary probability measure ν for a declared self-map. Invariance means $R_{\#}\mu = \mu$ for $R : A \rightarrow A$, or $T_{\#}\nu = \nu$ for $T : Y_A \rightarrow Y_A$; it is not meaningful without a same-space map.

1.10 Encodings

Definition 1.21 (Encoding). An encoding is a tuple

$$\mathcal{E} = (A, Z, E, F, \varepsilon)$$

where A is admissible, Z is a normed space, $E : P_0(A) \rightarrow Z$, and

$$E(T_{A,\pi}(y)) = F(E(y)) + \delta(y), \quad \|\delta(y)\| \leq c\varepsilon.$$

Remark 1.22. Coherence capacity $C(x)$ is not an observable, not a conserved quantity, and not a dynamical degree of freedom. It is a diagnostic margin (a stability/condition number) organizing when admissible encodings exist and when they fail.

1.11 Interpretation postulate

Postulate 1.1. *When an admissible encoding exists, its reduced structure may be interpreted as a physical description.*

Remark 1.23. Local sections $S_{A,\pi}$ may exist on admissible domains. Whether they extend is a separate selection and conditioning problem. Thus local representability does not imply stable global representability, but neither does it logically forbid a set-theoretic global section.

1.12 Failure modes

The corresponding conclusions are unavailable if:

- no complete invariant basin satisfies FCC where a fixed point is claimed;
- no invariant measure exists where probability is claimed;
- no representative section exists in the required regularity category;
- the declared margins, factorization, or robustness estimates fail.

2 Core Structural Results

Fix an admissible domain A , protocol π , and the well-typed self-map $T := T_{A,\pi}$.

2.1 Basin-local stability

Theorem 2.1 (Universality within one exact basin). *If D_α satisfies exact basin-local FCC, then every two orbits in D_α converge to the same unique fixed point:*

$$\lim_{n \rightarrow \infty} d_Y(T^n y, T^n y') = 0 \quad (y, y' \in D_\alpha).$$

Proof. Apply Theorem 1.12 to both orbits, or use $d_Y(T^n y, T^n y') \leq q_\alpha^n d_Y(y, y')$. $\square$

Remark 2.2 (No cross-basin conclusion). Separate invariant basins may contain separate fixed points. Neither exact FCC nor Proposition 1.14 may be applied to their union unless that union independently satisfies the required complete invariant contract.

2.2 Admissible prediction depth

Definition 2.3 (Admissible prediction depth). Fix an admissible domain A and protocol $\pi \in \Pi_A$. For $x \in A$, define the admissible prediction depth

$$N_{\max}(x; A, \pi, \varepsilon) := \sup \{n \in \mathbb{N} \mid T_{A, \pi}^k(P_0(x)) \in P_0(A) \text{ for every } 0 \leq k \leq n\}.$$

Remark 2.4. $N_{\max}$ is an iteration-count diagnostic. Its relation to physical time or to the size of a margin must be proved in a realization.

2.3 Computational limits (optional)

Remark 2.5. Finite, instance-dependent prediction depth does not imply undecidability. An undecidability result requires a specified input language and a reduction from a known undecidable problem to a declared reachability or admissibility question. A0 supplies no such reduction.

2.4 Forgetting of incoherent distinctions

Corollary 2.6 (Basin-local metric forgetting). *For y, y' in one exact FCC basin,*

$$d_Y(T^n y, T^n y') \longrightarrow 0.$$

Under only the approximate orbit contract,

$$\limsup_{n \rightarrow \infty} d_Y(T^n y, T^n y') \leq \frac{c\varepsilon}{1 - \kappa},$$

provided both orbits remain in the same invariant domain. This is a metric statement; information or entropy claims require additional structures.

2.5 A valid reduced-self-map obstruction

Imported finite-diameter obstruction. Projection–Admissibility owns the theorem and proof. In the notation used here, if (Y_A, d) has finite positive diameter D and $G : Y_A \rightarrow Y_A$ satisfies

$$d(Gy, Gy') \leq \kappa d(y, y') + c\varepsilon, \quad 0 \leq \kappa < 1.$$

Then

$$\text{diam } G(Y_A) \leq \kappa D + c\varepsilon.$$

If $(1 - \kappa)D > c\varepsilon$, then G is not surjective and has no right section $S : Y_A \rightarrow Y_A$ with $G \circ S = \text{id}_{Y_A}$.

Remark 2.7. The imported obstruction concerns a self-map of one reduced space. It cannot be applied to a cross-level map merely because the latter is noninjective.

2.6 Recovery and irreversibility are separate

Proposition 2.8 (Recovery classification). *For the typed maps of the imported projection–descent contract:*

1. *noninjectivity of Q_t obstructs exact upper recovery;*
2. *noninjectivity of an existing F_t obstructs recovery of the prior effective state;*
3. *neither fact alone proves a physical arrow of time.*

A physical arrow additionally needs oriented dynamics and an asymmetric property such as a noninvertible physical semigroup, a monotone Lyapunov or entropy functional, or a boundary condition.

2.7 Measure-dependent reduced probability

Imported measure-dependent reduced kernel. The Projection–Admissibility paper owns the disintegration theorem. In A0 notation, let A and $P_0(A)$ be standard Borel spaces, let μ be a probability measure on A , and let $\{\mu_y\}$ be a regular conditional distribution of x given $P_0(x) = y$. For a measurable upper step $R : A \rightarrow X_0$, define

$$K(y, B) := \mu_y\{x : P_0(Rx) \in B\}.$$

Then K is a Markov kernel, up to the usual $(P_0)_\# \mu$ -null sets. If $P_0 R$ descends to F on $P_0(A)$, then $K(y, \cdot) = \delta_{F(y)}$ almost everywhere.

Definition 2.9 (Basin weights). Let $\{B_i\}$ be a measurable partition of $P_0(A)$ and let μ be a declared probability measure on A . Define

$$W_i := \mu(P_0^{-1}(B_i) \cap A),$$

or condition and renormalize this expression on a declared selection event.

Remark 2.10. The weights are probabilities because μ was supplied, not because the projection has fibers. Different upper measures can induce different weights and kernels. No Born rule is asserted.

2.8 Re-encoding criterion on overlaps

Theorem 2.11 (Exact encoding factorization). *Let $E_1 : Y \rightarrow Z_1$ and $E_2 : Y \rightarrow Z_2$. A map $f : E_1(Y) \rightarrow Z_2$ satisfying $E_2 = f \circ E_1$ exists if and only if*

$$E_1(y) = E_1(y') \implies E_2(y) = E_2(y')$$

for all $y, y' \in Y$. When it exists, f is unique on $E_1(Y)$.

Proof. Necessity is immediate. For sufficiency define $f(E_1(y)) := E_2(y)$; the implication makes this well-defined. $\square$

Remark 2.12. Overlap of domains alone does not produce a re-encoding. Approximate factorization requires a quantitative fiber-consistency estimate and a controlled extension in the declared regularity class. A0 therefore makes no universal maximal-content claim.

2.9 Finite admissibility and global scope

Proposition 2.13 (No global admissible encoding at the adopted axiom tier). *Under the finite-admissibility axiom, no object satisfying the definition of an admissible encoding has domain X_0 .*

Proof. This is the direct content of the axiom and the definition of an encoding. $\square$

Remark 2.14. This proposition does not prohibit a global relation or a global reduced map that fails one of the adopted admissibility margins.

Part II: Encodings and Boundaries

3 Encoding Atlas

The atlas should be read as a collection of lenses on one typed projection problem. A chart is useful when its own variables and inequalities are certified on the current admissible domain. Moving between charts requires an exact factorization or an explicitly controlled error; a suggestive analogy between two encodings is not a transition map.

This section lists admissible encodings as local charts on neighborhoods of stable basins. Fix A and π and write

$$Y_A := P_0(A), \quad T_A := T_{A,\pi} : Y_A \rightarrow Y_A.$$

Each encoding is specified by sufficient inequality contracts involving the contraction constant κ , tolerance ε , and coherence capacity C .

Remark 3.1 (Contract nature of atlas inequalities). The inequalities in this atlas are *sufficient contracts* guaranteeing that an encoding closes to tolerance on the stated domain. They are not classification theorems: failure of a listed inequality does not imply that no encoding exists.

Remark 3.2 (Status of numerical thresholds). Numerical coefficients displayed below are declared chart-design thresholds, not universal constants derived by A0. A physical realization must justify or replace them and verify every associated closure estimate.

3.1 Chart-local control quantities

The following quantities are *chart-local*: they are defined only when the corresponding encoding supplies the structures needed to define them. They are not global invariants of the typed projection system.

- Basin separation scale (when a basin partition exists):

$$\Delta_B := \inf_{i \neq j} d_Y(B_i, B_j).$$

- Capacity floor on the chart domain:

$$C_{\min} := \inf_{x \in A} C(x).$$

- Contractivity slack:

$$s_\kappa := 1 - \kappa.$$

All inequalities below are sufficient but not necessary.

3.2 Encoding E_1 : Finite-Basin Operator Chart

Existence hypothesis The reduced space Y_A admits a finite or effectively finite collection of basins $\{B_i\}$ with well-defined separation.

Validity conditions

$$\varepsilon \leq \frac{1}{10} \Delta_B, \quad (3.1)$$

$$\kappa \leq \frac{1}{2}, \quad (3.2)$$

$$C_{\min} \geq C_1 > 0. \quad (3.3)$$

Closure contract The chart is admitted only if a linear map F on Z is supplied and verified to satisfy

$$E(T_A(y)) = F(E(y)) + \delta(y), \quad \|\delta(y)\| \leq c_1 \varepsilon.$$

Failure This chart contract fails when basin separation is lost, $\kappa \rightarrow 1$, or $C_{\min} \rightarrow 0$; another encoding may still exist.

3.3 Encoding E_2 : Local Patch Algebra Chart

Existence hypothesis The admissible domain admits a cover by overlapping admissible subdomains $\{A_\alpha\}$, but no global admissible section exists.

Validity conditions

$$\inf_{\alpha} \inf_{x \in A_\alpha} C(x) \geq C_2 > 0, \quad (3.4)$$

$$\sup_{\alpha} \kappa_\alpha \leq \kappa_2 < 1. \quad (3.5)$$

On overlaps $A_{\alpha\beta}$,

$$\|E_\beta(y) - f_{\alpha\beta}(E_\alpha(y))\| \leq c_2 \varepsilon.$$

Obstruction contract A claimed global obstruction must be exhibited by incompatible transition cocycles or a proved lower bound forcing every glue error above ε . Local overlap alone is not an obstruction.

Failure Overlap incompatibility or capacity collapse.

3.4 Encoding E_3 : Two-Derivative Bookkeeping Chart

Existence hypothesis Variations of basin representatives are slow enough that a second-order truncation is meaningful.

Validity conditions

$$C_{\min} \geq C_3 > 0, \quad (3.6)$$

$$q_\alpha \leq 1 - s_3 < 1 \quad (3.7)$$

Let η_3 denote the ratio of neglected higher-order terms to retained second-order terms. Require

$$\eta_3 \leq c_3 \varepsilon.$$

Closure contract One must verify

$$E(T_A(y)) = E(y) + \mathcal{D}[E(y)] + \delta(y), \quad \|\delta(y)\| \leq c'_3 \varepsilon.$$

Failure Higher-order terms become unsuppressed or $C \rightarrow 0$.

3.5 Encoding E_4 : Scale-Step Truncation Chart

Existence hypothesis There exists a hierarchy of reduced coordinates ordered by relevance.

Validity conditions

$$C_{\min} \geq C_4 > 0, \tag{3.8}$$

$$\rho_N \leq \varepsilon, \tag{3.9}$$

$$\kappa \leq 1 - c_4 \varepsilon. \tag{3.10}$$

Here ρ_N denotes a chart-local bound on the cumulative contribution of discarded coordinates.

Closure contract One must verify

$$E(T_A(y)) = F(E(y)) + \delta(y), \quad \|\delta(y)\| \leq c'_4 \varepsilon.$$

Failure Discarded contributions exceed tolerance or $\kappa \rightarrow 1$.

3.6 Encoding E_5 : Auxiliary Fixed-Point Chart

Existence hypothesis There exists an auxiliary representation Z_{aux} in which the reduced dynamics is near a stable fixed point.

Validity conditions

$$\|\beta(E(y))\| \leq c_5 \varepsilon, \tag{3.11}$$

$$\|D\beta\| \leq 1 - s_5, \tag{3.12}$$

$$C_{\min} \geq C_5 > 0. \tag{3.13}$$

Closure contract The auxiliary map must preserve a complete neighborhood and satisfy an exact contraction there, or a separate fixed-point existence theorem must be provided. A spectral-radius bound alone is insufficient for a nonnormal linearization.

Failure Loss of auxiliary stability or capacity collapse.

3.7 Encoding E_6 : Spectral Operator Chart

Existence hypothesis The encoding supplies operators whose spectra are meaningful on the admissible domain.

Validity conditions

$$\varepsilon \leq \frac{1}{10} \Delta_D, \tag{3.14}$$

$$\|[D, a]\| \leq K_6, \tag{3.15}$$

$$C_{\min} \geq C_6 > 0. \tag{3.16}$$

Closure contract Dependence on spectral data only, with its error bound, must be verified for the declared operator domain.

Failure Spectral gap closure or operator norm divergence.

3.8 Encoding E_7 : Boundary and Reset Chart

Existence hypothesis Capacity reaches a declared boundary and an additional continuation or reset rule J_e is supplied.

Validity conditions

$$0 < C_{\min} \leq C_7, \quad (3.17)$$

$$\tau_e \geq \tau_7 > 0. \quad (3.18)$$

Reset labels must be stable under ε -perturbations, J_e must be measurable, and any required conservation law must be checked. Post-reset basins must satisfy FCC with positive slack. If probabilities are assigned, a measure or stochastic kernel must also be supplied.

Failure Event clustering, unstable post-selection basins, or $C < 0$.

3.9 Encoding E_8 : Relational Transition Chart

This encoding applies when no single-valued reduced evolution is admissible, but stable relational structure persists.

Existence hypothesis

- The descent criterion (1.1) fails on the neighborhood of interest, so no autonomous single-valued reduced map exists there.
- The typed reduced relation

$$\mathcal{R}_t := \{(P_0x, P_t\Phi_t x) : x \in X_0\} \subseteq Y_0 \times Y_t$$

admits a stable restriction.

Variables The reduced data are not points in a coordinate space, but *relations*:

$$Z_{\text{rel}} \subseteq Y_0 \times Y_t.$$

Chart map

$$E : Y_0 \rightarrow \mathcal{P}(Y_t), \quad E(y) := \{y' \mid (y, y') \in \mathcal{R}_t\},$$

where $\mathcal{P}(Y_t)$ denotes the power set of Y_t .

Closure contract For a declared semigroup $\Phi_{s+t} = \Phi_s\Phi_t$ with compatible time-indexed reductions, relational composition must be checked in the typed form

$$\mathcal{R}_s \circ \mathcal{R}_t \subseteq \mathcal{R}_{s+t} \quad \text{up to the declared tolerance.}$$

Transitivity of one fixed-time relation is not automatic.

Validity conditions

$$C_{\min} \geq C_8 > 0, \quad (3.19)$$

$$\text{Autonomous descent fails on the domain.} \quad (3.20)$$

Failure

- Relational structure becomes unstable or dense;
- No controlled restriction of $\mathcal{R}_t$ exists;
- Coherence capacity collapses globally.

Remarks This encoding is one possible weak description when deterministic descent fails. It captures persistent constraints on allowed transitions without introducing local coordinates, states, or probabilities.

3.10 Encoding E_9 : Statistical Ensemble Chart

This encoding applies when local or pointwise reduced descriptions fail, but stable statistical structure persists without a well-defined invariant measure.

Existence hypothesis

- No admissible invariant or stationary measure exists on the admissible domain.
- Long-time empirical averages or ensemble summaries stabilize under reduced evolution.
- Single-trajectory descriptions do not close, but aggregate quantities do.

Variables The reduced variables are ensemble summaries:

$$Z_{\text{stat}} := \{\text{empirical distributions, moments, or coarse summaries}\}.$$

Chart map

$$E : Y_A \rightarrow Z_{\text{stat}}, \quad E(y) := \lim_{N \rightarrow \infty} \frac{1}{N} \sum_{k=1}^N \mathcal{O}(T_A^k(y)),$$

whenever the limit exists for the chosen summary observable $\mathcal{O}$.

Closure contract The chart is admitted only if ensemble evolution closes approximately:

$$E(T_A(y)) = F(E(y)) + \delta(y), \quad \|\delta(y)\| \leq c_9 \varepsilon,$$

even though no pointwise closure exists.

Validity conditions

$$C_{\min} \geq C_9 > 0, \quad (3.21)$$

$$\text{No invariant measure } \mu \text{ exists on the domain.} \quad (3.22)$$

Failure

- Ensemble summaries fail to stabilize;
- Strong nonstationarity destroys aggregate closure;
- Capacity collapses and no admissible encoding remains.

Remarks This empirical-summary encoding does not itself invoke probability, random variables, or stochastic dynamics. It is not universally ordered above or below the relational encoding; comparison requires a proved re-encoding.

3.11 Atlas summary

Admissible encodings range from coordinate descriptions to relational and statistical summaries. In a particular realization one may observe a schematic transition

$$E_1 \rightarrow \cdots \rightarrow E_7 \rightarrow E_9 \rightarrow E_8,$$

but A0 does not prove this ordering. Each arrow requires an overlap factorization and a verified margin comparison.

4 Admissibility Boundaries and Selection

This section analyzes the failure of admissible reduced descriptions. All notions refer to the definitions in Section 1 and are purely structural.

4.1 Admissibility barriers

We recall the definition of an admissibility barrier from Definition 1.17. No additional structure is assumed here.

4.2 Termination of encodings

Proposition 4.1 (Loss of an encoding certificate at a barrier). *Let $\mathcal{E} = (A, Z, E, F, \varepsilon)$ be an admissible encoding. If a trajectory reaches a barrier at which one of $\mathcal{E}$'s required margins vanishes, then the existing certificate for $\mathcal{E}$ ends there. Continuation requires a new proof restoring that margin, a different encoding, or an additional continuation law.*

Proof. Positive slack in every declared margin is part of admissibility. At the named zero margin, that hypothesis is no longer available. $\square$

4.3 Selection events

Definition 4.2 (Declared selection or reset event). A selection event consists of a margin crossing together with a supplied continuation rule

$$J_e : \mathcal{B}_e \times \Lambda_e \longrightarrow \bigcup_{\alpha} D_{\alpha},$$

where Λ_e contains any extra label or random input. The rule must be typed, measurable in probabilistic uses, and compatible with every claimed conservation law.

Margin saturation alone terminates a certificate; it does not choose an outcome or construct J_e .

4.4 Irreversibility of selection

Proposition 4.3 (Conditional effective irreversibility). *A declared reset is irreversible at the effective level if its induced map from pre-event effective states to post-event effective states is noninjective. Exact upper recovery is impossible if the corresponding typed upper-to-output map is noninjective. Neither statement follows from loss of FCC alone, and neither establishes a physical arrow of time without an oriented asymmetric evolution law.*

4.5 Boundary layers

Definition 4.4 (Boundary layer). A δ -boundary layer for the declared margins is

$$\mathcal{L}_\delta := \{x : 0 < C(x) \leq \delta\}.$$

Remark 4.5. Small margin identifies proximity to failure only for the declared contract. Sensitivity amplification, coordinate independence, or common scaling between encodings requires a comparison theorem for their margins.

4.6 Records

Definition 4.6 (Record). A record for T is a measurable map R_{rec} on a forward-invariant post-event domain such that

$$R_{\text{rec}} \circ T = R_{\text{rec}}.$$

Proposition 4.7 (Record persistence). *Once such an R_{rec} is supplied, its value is constant along every forward orbit in its domain.*

Proof. Iterate the defining identity. □

FCC alone does not construct a nontrivial record. A partial order on events also requires an oriented event relation and record compatibility.

4.7 Probability at boundaries (conditional)

Let μ be a declared upper probability measure and let $\{B_i\}$ be a measurable partition of the post-event reduced domain. The conditional numbers

$$W_i = \frac{\mu(P_0^{-1}(B_i) \cap A_e)}{\sum_j \mu(P_0^{-1}(B_j) \cap A_e)}$$

are probabilities when the denominator is positive. They describe the chosen measure and event domain A_e ; they are not selected by the barrier and are not asserted to be Born weights.

4.8 No global reversibility

Remark 4.8. Finite admissibility rules out one globally certified admissible encoding at the adopted axiom tier. It does not by itself rule out an invertible global relation, a reversible upper evolution, or a different reduced description whose hypotheses are not those of A0.

4.9 Boundary summary

Admissibility barriers mark the limits of a named certificate. At such a limit one must stop, prove a continuation, switch to another verified encoding, or supply a reset law. Selection, probability, records, and irreversibility are separate gates.

Part III: Structural Closure

5 Exact and Controlled Relations Between Encodings

Category language is exact. We therefore define an exact category first and keep tolerance errors as explicit controlled data rather than silently quotienting by a relation that may fail to be a congruence.

5.1 The exact local category

Fix one admissible domain A , protocol π , reduced space $Y_A = P_0(A)$, and self-map T_A .

Definition 5.1 (Exact encoding object). An object of $\mathbf{AdmEnc}_0(A, T_A)$ is a triple

$$\mathcal{E} = (Z, E, F)$$

with $E : Y_A \rightarrow Z$, $F : Z \rightarrow Z$, and

$$E \circ T_A = F \circ E.$$

Definition 5.2 (Exact re-encoding morphism). A morphism $f : \mathcal{E}_1 \rightarrow \mathcal{E}_2$ is a map $f : Z_1 \rightarrow Z_2$ satisfying

$$E_2 = f \circ E_1, \quad f \circ F_1 = F_2 \circ f \quad \text{on } E_1(Y_A).$$

Proposition 5.3. *Identity maps and ordinary composition make $\mathbf{AdmEnc}_0(A, T_A)$ a category.*

Proof. Both factorization identities are preserved by identity maps and by composition. $\square$

5.2 The correctly oriented universal object

Definition 5.4 (Identity encoding).

$$\mathcal{C}_A := (Y_A, \text{id}_{Y_A}, T_A).$$

Theorem 5.5 (Local initiality). $\mathcal{C}_A$ is initial in $\mathbf{AdmEnc}_0(A, T_A)$. For every exact encoding $\mathcal{E} = (Z, E, F)$, the unique morphism $\mathcal{C}_A \rightarrow \mathcal{E}$ is E .

Proof. The object identity $E \circ T_A = F \circ E$ is exactly the dynamical intertwining condition. The equation $E = f \circ \text{id}$ forces $f = E$. $\square$

Proposition 5.6 (Recovery from an encoding). A morphism $\mathcal{E} \rightarrow \mathcal{C}_A$ exists if and only if id_{Y_A} factors through E . Equivalently,

$$E(y) = E(y') \implies y = y',$$

and a suitable inverse on $E(Y_A)$ exists in the declared regularity category.

Remark 5.7. Version 1 reversed this arrow and called $\mathcal{C}_A$ terminal. A general encoding can discard reduced information, so recovery of Y_A from its coordinates is an additional injectivity and regularity theorem.

5.3 Controlled approximate re-encodings

For approximate encodings, retain an explicit defect

$$\|E \circ T_A - F \circ E\| \leq \eta$$

on a declared domain. A controlled arrow $f : \mathcal{E}_1 \rightarrow \mathcal{E}_2$ records both a factorization defect $\|E_2 - fE_1\| \leq \eta_f$ and a dynamical-intertwining defect. If g is L_g -Lipschitz, then the factorization defect of $g \circ f$ is at most

$$\eta_g + L_g \eta_f.$$

Thus controlled arrows compose with an explicit error budget. A quotient category may be formed only after the proposed tolerance relation is proved to be an equivalence relation compatible with this composition; A0 does not assume such a quotient.

5.4 Overlaps and global scope

For encodings on A_1 and A_2 , first restrict to $Y_{12} := P_0(A_1 \cap A_2)$. Theorem 2.11, plus the declared regularity and error estimates, decides whether a transition map exists. Nonempty overlap alone is insufficient.

The finite-admissibility axiom excludes an exact or controlled *admissible* object whose domain is all of X_0 . A particular pair of charts fails to glue only when a transition obstruction or incompatible margin is actually proved.

5.5 Pushforward probability as an optional functor

Let ν be a declared probability measure on Y_A , and restrict to measurable exact encodings and measurable morphisms. Assign to $\mathcal{E} = (Z, E, F)$ the pushforward probability space $(Z, E_{\#}\nu)$, and to $f : \mathcal{E}_1 \rightarrow \mathcal{E}_2$ the measurable pushforward map f . Since $E_2 = fE_1$,

$$(E_2)_{\#}\nu = f_{\#}(E_1)_{\#}\nu,$$

so this assignment is a functor to probability spaces. The functor uses the supplied ν ; category structure does not create it.

5.6 Category summary

The identity encoding is locally initial, not terminal. Arrows out of it are encodings; arrows back to it are recovery maps. Approximate arrows carry error budgets, and global gluing remains a separate descent problem.

Part IV: Total Atlas

6 Total Atlas: A Global Chart-of-Charts

This section introduces a global object that *contains* all admissible encodings without asserting the existence of any single globally valid encoding. It formalizes the idea of a *total chart* as a chart-of-charts.

6.1 Local encoding fiber

Definition 6.1 (Encoding fiber). For each $x \in X_0$, define

$$\text{Enc}(x) := \{\mathcal{E} : \mathcal{E} \text{ is a verified exact or controlled encoding on some } A \ni x\}.$$

Remark 6.2. $\text{Enc}(x)$ is the set of all reduced descriptions available at x . Finite admissibility says no single verified chart has domain X_0 ; it does not imply that any point is uncovered by the union of local charts.

6.2 Total encoding family

Definition 6.3 (Total encoding projection). Define the total encoding space

$$\mathbb{E} := \{(x, \mathcal{E}) \mid x \in X_0, \mathcal{E} \in \text{Enc}(x)\},$$

with projection map

$$\pi : \mathbb{E} \rightarrow X_0, \quad \pi(x, \mathcal{E}) = x.$$

Remark 6.4. The fiber $\pi^{-1}(x)$ is canonically identified with $\text{Enc}(x)$. Without a topology and local trivializations, π is a set-theoretic fibered family, not a fiber bundle. It is not itself an encoding.

6.3 Admissibility limits as fiber collapse

Definition 6.5 (Encodability set). Define the encodable subset of X_0 by

$$X_{\text{enc}} := \{x \in X_0 \mid \text{Enc}(x) \neq \emptyset\}.$$

Definition 6.6 (Encoding boundary set). Define the topological boundary as

$$\partial X_{\text{enc}} := \overline{X_{\text{enc}}} \setminus \text{int}(X_{\text{enc}}).$$

Remark 6.7. Boundary points are accumulation points of both encodable and non-interior behavior. A claim that availability actually collapses there requires upper-semicontinuity or a specific margin theorem.

6.4 Chart viability field

The atlas in Section 3 provides *sufficient contracts* in terms of local control quantities. We now compress those contracts into a single diagnostic.

Definition 6.8 (Chart viability functional). For an encoding $\mathcal{E}$ and a point $x \in X_0$, define a chart viability score

$$\mathcal{V}_{\mathcal{E}}(x) \in \mathbb{R}$$

as any scalar functional such that:

1. $\mathcal{V}_{\mathcal{E}}(x) > 0$ implies $x \in A_{\mathcal{E}}$ and all stated inequality contracts of $\mathcal{E}$ hold at x ;
2. $\mathcal{V}_{\mathcal{E}}(x) \leq 0$ implies at least one contract of $\mathcal{E}$ fails at x .

Remark 6.9. $\mathcal{V}_{\mathcal{E}}$ is not unique; it is a diagnostic that packages the inequality contracts of $\mathcal{E}$ into a single scalar. Scores for different encodings are comparable only after a common normalization is declared.

Definition 6.10 (Maximal viability). Define the maximal viability at x by

$$\mathcal{V}^*(x) := \sup_{\mathcal{E} \in \text{Enc}(x)} \mathcal{V}_{\mathcal{E}}(x),$$

with the convention $\mathcal{V}^*(x) = -\infty$ if $\text{Enc}(x) = \emptyset$.

Remark 6.11. With a common normalization, $\mathcal{V}^*(x)$ is a best-margin diagnostic. Relating its sign or continuity to ∂X_{enc} requires additional regularity of the encoding family.

6.5 The overlap nerve of the atlas

We now define a global topological summary of chart overlap.

Definition 6.12 (Overlap relation). Two encodings $\mathcal{E}_i = (A_i, \dots)$ and $\mathcal{E}_j = (A_j, \dots)$ overlap if

$$A_i \cap A_j \neq \emptyset$$

and there exists an exact re-encoding morphism or a controlled arrow with an explicit error budget on the overlap.

Definition 6.13 (Atlas nerve). Let $\{\mathcal{E}_{\alpha}\}$ be a chosen family of encodings. The nerve $\mathcal{N}$ is the simplicial complex whose:

- vertices are encodings $\mathcal{E}_{\alpha}$;
- a k -simplex $(\mathcal{E}_{\alpha_0}, \dots, \mathcal{E}_{\alpha_k})$ exists iff $\bigcap_{i=0}^k A_{\alpha_i} \neq \emptyset$ and transition morphisms are controlled on that intersection.

Remark 6.14. The nerve records the combinatorics of a chosen cover. A hole in the nerve is not automatically a gluing obstruction; that conclusion requires the appropriate good-cover hypotheses and a nontrivial transition cocycle or cohomology class.

6.6 Universal reduced relation

Independently of whether deterministic descent holds, the typed data define a global relation.

Definition 6.15 (Universal reduced relation). Define

$$\mathcal{R}_t := \{(P_0x, P_t\Phi_t x) : x \in X_0\} \subseteq Y_0 \times Y_t.$$

Remark 6.16. $\mathcal{R}_t$ is always well-defined. It is the graph of a single-valued map $F_t : Y_0 \rightarrow Y_t$ exactly when the descent criterion (1.1) holds. A representative section chooses one value from compatible upper representatives; it does not make the full relation a graph when descent fails.

6.7 Total-atlas summary

The total atlas consists of:

- the total encoding projection $\pi : \mathbb{E} \rightarrow X_0$;
- the normalized viability diagnostic $\mathcal{V}^*$, when a common normalization is supplied;
- the overlap nerve $\mathcal{N}$ recording the chosen cover and its controlled transition data;
- the typed relation $\mathcal{R}_t \subseteq Y_0 \times Y_t$.

No single global admissible encoding is asserted. The chart-of-charts records local availability without converting local contracts into a global physical law.

Conclusion

Modal Triplet Theory is presented here as a conditional, non-self-sealing framework. It asserts no ontology and no universal effective law. Instead, it gives checkable gates for representative selection, exact recovery, autonomous descent, basin-local stability, controlled re-encoding, and measure-dependent probability. Finite admissibility is a stated axiom about certified encodings, not a consequence of noninjectivity. Every stronger conclusion must identify the margin, measure, dynamics, or physical source theorem that supplies it.

The main achievement is a typed order of questions. Surjectivity and a selection theorem govern representative sections. Injectivity governs exact decoding. Fiber constancy governs autonomous reduced evolution. Complete invariant basins and exact contraction govern local fixed points. Measures govern probability, and explicit positive margins govern the lifetime of an encoding. The total atlas records where these contracts coexist and overlap without manufacturing a globally preferred chart.

Any physical interpretation is an external assignment layered atop the mathematical structure developed herein.

References

- [1] Peter Nero. Fixed points i: Fixed points over multi-bundle manifolds. Zenodo preprint, August 2025. <https://doi.org/10.5281/zenodo.16948748>.
- [2] Peter Nero. Fixed points ii: Fixed points in a 10d modal model. Zenodo preprint, August 2025. <https://doi.org/10.5281/zenodo.16949073>.
- [3] Peter Nero. Fixed points iii: Disturbance, damping balance, and stability. Zenodo preprint, August 2025. <https://doi.org/10.5281/zenodo.16949280>.

- [4] Peter Nero. Fixed points iv: Curvature, centroid motion, and structural transitions. Zenodo preprint, August 2025. <https://doi.org/10.5281/zenodo.16949426>.
- [5] Peter Nero. Fixed points v: Curvature coupling, multi-structure dynamics, and drivers. Zenodo preprint, August 2025. <https://doi.org/10.5281/zenodo.16949503>.
- [6] Peter Nero. Fixed points vi: Formal synthesis and physical interpretations. Zenodo preprint, August 2025. <https://doi.org/10.5281/zenodo.16949635>.
- [7] Peter Nero. Modal triplet theory: Foundation. Zenodo preprint, September 2025. <https://doi.org/10.5281/zenodo.16949762>.
- [8] Peter Nero. Modal triplet theory: Admissibility, encodings, and the structure of physical description. Zenodo preprint, January 2026. <https://doi.org/10.5281/zenodo.18262454>.
- [9] Peter Nero. The projection-admissibility principle: Structural constraints on effective physical description. Zenodo preprint, January 2026. <https://doi.org/10.5281/zenodo.18255838>.

Computational Evidence and Reproducibility

The numerical and machine-verifiable claims used by this paper are archived in the curated repository, <https://github.com/PeterNero/mtt-results-repro>. The mapped authority/result identifiers are `no result rows mapped`. Claim tiers in that capsule distinguish exact derivation, certified numerics, profile replay, conditional results, and open obligations.