

Sparse and spurious: dictionary learning with noise and outliers

Rodolphe Jenatton

Amazon, Berlin

Joint work with **Rémi Gribonval** & **Francis Bach**

Optimization and Big Data, May 2015 @ Edinburgh

Movie quiz

Which cinematographic reference?




Movie quiz

Which cinematographic reference?




Motivation: feature learning

Raw data



Good features

Motivation: sparse representation



- Expensive to manipulate high-dimensional signals
 - Storage
 - Latency
 - ...
- Try to find **sparse representation**

Sparse coding in a nutshell

- **Idea**: Represent signals as combinations of few **learned** atoms

Sparse coding in a nutshell

- **Idea**: Represent signals as combinations of few **learned** atoms
- Applied to various settings and classes of signals
 - Neuroscience [OF97]
 - Image processing/Computer vision [EA06, Pey09, Mai10]
 - Audio processing [PABD06, GRKN07]
 - Topic modeling [JMOB11]
 - ...


Sparse coding in a nutshell

- **Idea:** Represent signals as combinations of few **learned** atoms
- Applied to various settings and classes of signals
 - Neuroscience [OF97]
 - Image processing/Computer vision [EA06, Pey09, Mai10]
 - Audio processing [PABD06, GRKN07]
 - Topic modeling [JMOB11]
 - ...
- Several approaches:
 - Convex [BMP08, BB09]
 - Submodular [KC10]
 - Bayesian [ZCP⁺09]
 - **Non-convex matrix-factorization** [OF97, LBRN07, MBPS10]

Sparse coding setting

- **Data:** n signals, $\mathbf{X} = [\mathbf{x}^1, \dots, \mathbf{x}^n] \in \mathbb{R}^{m \times n}$
- **Dictionary:** p atoms, $\mathbf{D} = [\mathbf{d}^1, \dots, \mathbf{d}^p] \in \mathbb{R}^{m \times p}$
- **Decomposition:** $\mathbf{A} = [\alpha^1, \dots, \alpha^n] \in \mathbb{R}^{p \times n}$
- **Goal:**

$$\mathbf{X} \approx \mathbf{D}\mathbf{A}, \text{ with sparse } \mathbf{A}$$



Sparse coding objective function

$$\min_{\mathbf{A} \in \mathbb{R}^{p \times n}, \mathbf{D} \in \mathcal{D}} \frac{1}{n} \sum_{i=1}^n \left[\overbrace{\frac{1}{2} \|\mathbf{x}^i - \mathbf{D}\alpha^i\|_2^2}^{\text{data-fitting term}} + \lambda \underbrace{\|\alpha^i\|_1}_{\text{sparsity-inducing norm}} \right]$$

- \mathcal{D} : dictionaries with unit ℓ_2 -norm atoms

Sparse coding objective function

$$\min_{\mathbf{A} \in \mathbb{R}^{p \times n}, \mathbf{D} \in \mathcal{D}} \frac{1}{n} \sum_{i=1}^n \left[\overbrace{\frac{1}{2} \|\mathbf{x}^i - \mathbf{D}\boldsymbol{\alpha}^i\|_2^2}^{\text{data-fitting term}} + \lambda \underbrace{\|\boldsymbol{\alpha}^i\|_1}_{\text{sparsity-inducing norm}} \right]$$

- \mathcal{D} : dictionaries with unit ℓ_2 -norm atoms
- Equivalently:

$$\min_{\mathbf{D} \in \mathcal{D}} F_{\mathbf{X}}(\mathbf{D}), \quad \text{with} \quad F_{\mathbf{X}}(\mathbf{D}) \triangleq \frac{1}{n} \sum_{i=1}^n f_{\mathbf{x}^i}(\mathbf{D})$$

and

$$f_{\mathbf{x}}(\mathbf{D}) \triangleq \min_{\boldsymbol{\alpha} \in \mathbb{R}^p} \left[\frac{1}{2} \|\mathbf{x} - \mathbf{D}\boldsymbol{\alpha}\|_2^2 + \lambda \|\boldsymbol{\alpha}\|_1 \right]$$

Theoretical analysis of sparse coding

Theoretical analysis of sparse coding

- Excess risk analysis
 - [MP10, VMB10, MG12, GJB⁺13]
 - Non-asymptotic generalization bounds

Theoretical analysis of sparse coding

- Excess risk analysis
 - [MP10, VMB10, MG12, GJB⁺13]
 - Non-asymptotic generalization bounds
- **Identifiability** analysis
 - Study of local/global minima

Theoretical analysis of sparse coding

- Excess risk analysis
 - [MP10, VMB10, MG12, GJB⁺13]
 - Non-asymptotic generalization bounds
- **Identifiability** analysis
 - Study of local/global minima
 - Assume sparse model $\mathbf{x} = \mathbf{D}_0 \boldsymbol{\alpha}_0$ for a fixed \mathbf{D}_0
 - Possibly corrupted by some additive noise

Theoretical analysis of sparse coding

- Excess risk analysis
 - [MP10, VMB10, MG12, GJB⁺13]
 - Non-asymptotic generalization bounds
- **Identifiability** analysis
 - Study of local/global minima
 - Assume sparse model $\mathbf{x} = \mathbf{D}_0 \boldsymbol{\alpha}_0$ for a fixed \mathbf{D}_0
 - Possibly corrupted by some additive noise
 - **Questions:**
 - Local minimum of $F_{\mathbf{x}} : \mathcal{D} \rightarrow \mathbb{R}$ around \mathbf{D}_0 ?

Theoretical analysis of sparse coding

- Excess risk analysis
 - [MP10, VMB10, MG12, GJB⁺13]
 - Non-asymptotic generalization bounds
- **Identifiability** analysis
 - Study of local/global minima
 - Assume sparse model $\mathbf{x} = \mathbf{D}_0 \boldsymbol{\alpha}_0$ for a fixed \mathbf{D}_0
 - Possibly corrupted by some additive noise
 - **Questions:**
 - Local minimum of $F_{\mathbf{x}} : \mathcal{D} \rightarrow \mathbb{R}$ around \mathbf{D}_0 ?
 - Algorithmic schemes to reach those minima?

Previous work

Reference	Over.	Noise	Outliers	Global min/algo.	Poly. algo.	Sample comp. (no noise)
[GTC05] <i>Combinatorial</i>	YES	NO	NO	YES	NO	$m \binom{p}{m-1}$
[AEB06] <i>Combinatorial</i>	YES	NO	NO	YES	NO	$(k+1) \binom{p}{k}$
[GS10] ℓ^1	NO	NO	NO	NO	NO	$\frac{m^2 \log m}{k}$
[GWW11] ℓ^1	YES	NO	NO	NO	NO	kp^3
[SWW13] ℓ^0 <i>ER-SpUD</i>	NO	NO	NO	YES YES	NO YES	$m \log m$ $m^2 \log^2 m$
[Sch14b] <i>K-SVD criterion</i>	YES	YES	NO	NO	NO	$\frac{mp^3 k}{r^2}$
[AGM13] <i>Clustering</i>	YES	YES	NO	YES	YES	$\frac{p^2 \log p}{k^2}$
[AAN13] <i>Clustering & ℓ^1</i>	YES	NO	NO	YES	YES	$p \log mp$
[AAJN13] <i>Clustering & ℓ^1 with alt.</i>	YES	NO	NO	YES	YES	$p^2 \log p$
[Sch14a] <i>Resp. max. criterion</i>	YES	YES	NO	NO	NO	$\frac{mp^3 k}{r^2}$
Our ℓ^1 -regularized	YES	YES	YES	NO	NO	mp^3

Our goal

- Consider probabilistic model with noise, $\mathbf{x} = \mathbf{D}_0\alpha_0 + \epsilon$
 - Fixed reference dictionary \mathbf{D}_0
 - Random (α_0, ϵ) with sparse α_0

Our goal

- Consider probabilistic model with **noise**, $\mathbf{x} = \mathbf{D}_0\alpha_0 + \varepsilon$
 - Fixed reference dictionary \mathbf{D}_0
 - Random (α_0, ε) with sparse α_0
- **Goal:** non-asymptotic characterization of

$\mathbb{P}(F_{\mathbf{X}} \text{ has a local minimum in a “neighborhood” of } \mathbf{D}_0) \approx 1$

with

$$F_{\mathbf{X}}(\mathbf{D}) \triangleq \frac{1}{n} \sum_{i=1}^n f_{\mathbf{x}^i}(\mathbf{D})$$

and

$$f_{\mathbf{x}}(\mathbf{D}) \triangleq \min_{\alpha \in \mathbb{R}^p} \left[\frac{1}{2} \|\mathbf{x} - \mathbf{D}\alpha\|_2^2 + \lambda \|\alpha\|_1 \right]$$

Some motivations

- Better account for empirical success

Some motivations

- Better account for empirical success
- Better understand roles of parameters, e.g.,
 - Number of atoms
 - Over-complete regimes
 - Model selection
 - Acceptable level of noise
 - Acceptable fraction of outliers
 - Sample complexity

Some motivations

- Better account for empirical success
- Better understand roles of parameters, e.g.,
 - Number of atoms
 - Over-complete regimes
 - Model selection
 - Acceptable level of noise
 - Acceptable fraction of outliers
 - Sample complexity
- Which parameters contribute to the curvature of $F_{\mathbf{x}}$?
 - E.g., design of new optimization strategies

Generative model of signals

$$\mathbf{x} = \mathbf{D}_0 \alpha_0 + \varepsilon \quad (\text{Inliers})$$

Generative model of signals

$$\mathbf{x} = \mathbf{D}_0 \alpha_0 + \varepsilon \quad (\text{Inliers})$$

- Fixed reference dictionary $\mathbf{D}_0 \in \mathcal{D}$
 - Cumulative-coherence assumption [Fuc05, DH01]

$$\mu_k(\mathbf{D}_0) \triangleq \sup_{|J| \leq k} \sup_{j \notin J} \|[\mathbf{D}_0]_J^\top \mathbf{d}_0^j\|_1$$

Generative model of signals

$$\mathbf{x} = \mathbf{D}_0 \alpha_0 + \varepsilon \quad (\text{Inliers})$$

- Fixed reference dictionary $\mathbf{D}_0 \in \mathcal{D}$
 - Cumulative-coherence assumption [Fuc05, DH01]

$$\mu_k(\mathbf{D}_0) \triangleq \sup_{|J| \leq k} \sup_{j \notin J} \|[\mathbf{D}_0]_J^\top \mathbf{d}_0^j\|_1$$

- Sparse random vector α_0
 - Uniformly draw $J \subseteq \{1, \dots, p\}$, $|J| = k$

Generative model of signals

$$\mathbf{x} = \mathbf{D}_0 \alpha_0 + \varepsilon \quad (\text{Inliers})$$

- Fixed reference dictionary $\mathbf{D}_0 \in \mathcal{D}$
 - Cumulative-coherence assumption [Fuc05, DH01]

$$\mu_k(\mathbf{D}_0) \triangleq \sup_{|J| \leq k} \sup_{j \notin J} \|[\mathbf{D}_0]_J^\top \mathbf{d}_0^j\|_1$$

- Sparse random vector α_0
 - Uniformly draw $J \subseteq \{1, \dots, p\}$, $|J| = k$
 - $[\alpha_0]_{J^c} = \mathbf{0}$

Generative model of signals

$$\mathbf{x} = \mathbf{D}_0 \alpha_0 + \varepsilon \quad (\text{Inliers})$$

- Fixed reference dictionary $\mathbf{D}_0 \in \mathcal{D}$
 - Cumulative-coherence assumption [Fuc05, DH01]

$$\mu_k(\mathbf{D}_0) \triangleq \sup_{|J| \leq k} \sup_{j \notin J} \|[\mathbf{D}_0]_J^\top \mathbf{d}_0^j\|_1$$

- Sparse random vector α_0
 - Uniformly draw $J \subseteq \{1, \dots, p\}$, $|J| = k$
 - $[\alpha_0]_{J^c} = \mathbf{0}$
- Random noise ε

Generative model of signals

$$\mathbf{x} = \mathbf{D}_0 \alpha_0 + \varepsilon \quad (\text{Inliers})$$

- Fixed reference dictionary $\mathbf{D}_0 \in \mathcal{D}$
 - Cumulative-coherence assumption [Fuc05, DH01]

$$\mu_k(\mathbf{D}_0) \triangleq \sup_{|J| \leq k} \sup_{j \notin J} \|[\mathbf{D}_0]_J^\top \mathbf{d}_0^j\|_1$$

- Sparse random vector α_0
 - Uniformly draw $J \subseteq \{1, \dots, p\}$, $|J| = k$
 - $[\alpha_0]_{J^c} = \mathbf{0}$
- Random noise ε
- **Outliers:** No assumption on $\mathbf{x}_{\text{outlier}}$

Signal assumptions

$$\mathbb{E} \{ [\boldsymbol{\alpha}_0]_J [\boldsymbol{\alpha}_0]_J^\top \mid J \} = \mathbb{E} \{ \alpha^2 \} \cdot \mathbf{I} \quad (\text{coefficient whiteness})$$

$$\mathbb{E} \{ \varepsilon [\boldsymbol{\alpha}_0]_J^\top \mid J \} = \mathbf{0} \quad (\text{decorrelation})$$

$$\mathbb{E} \{ \varepsilon \varepsilon^\top \mid J \} = \mathbb{E} \{ \epsilon^2 \} \cdot \mathbf{I} \quad (\text{noise whiteness})$$

(similar assumptions for $\text{sign}(\boldsymbol{\alpha}_0)$)

Signal assumptions

$$\mathbb{E} \{ [\boldsymbol{\alpha}_0]_J [\boldsymbol{\alpha}_0]_J^\top \mid J \} = \mathbb{E} \{ \alpha^2 \} \cdot \mathbf{I} \quad (\text{coefficient whiteness})$$

$$\mathbb{E} \{ \boldsymbol{\varepsilon} [\boldsymbol{\alpha}_0]_J^\top \mid J \} = \mathbf{0} \quad (\text{decorrelation})$$

$$\mathbb{E} \{ \boldsymbol{\varepsilon} \boldsymbol{\varepsilon}^\top \mid J \} = \mathbb{E} \{ \epsilon^2 \} \cdot \mathbf{I} \quad (\text{noise whiteness})$$

(similar assumptions for $\text{sign}(\boldsymbol{\alpha}_0)$)

“Flatness” of the distribution:

$$\kappa_\alpha \triangleq \frac{\mathbb{E}[|\alpha|]}{\sqrt{\mathbb{E}[\alpha^2]}}$$

Further boundedness assumptions

$\mathbb{P}(\min_{j \in J} |[\alpha_0]_j| < \underline{\alpha} \mid J) = 0$, for some $\underline{\alpha} > 0$ (**coefficient threshold**)


$\mathbb{P}(\|\alpha_0\|_2 > M_\alpha) = 0$, for some M_α (**coefficient boundedness**)

$\mathbb{P}(\|\epsilon\|_2 > M_\epsilon) = 0$, for some M_ϵ (**noise boundedness**)


Useful for almost sure **exact recovery** to simplify expression of $F_{\mathbf{X}}$

Illustration


no noise / no outliers




no outliers



many small outliers



few large outliers



Asymptotic result ($n \gg 1$)

- **Coherence:** $\mu_k(\mathbf{D}_0) \leq 1/4$
- **Sparsity:** $k \lesssim p / \|\mathbf{D}_0\|_2$
- **Regularisation:** $0 < \lambda \lesssim \underline{\alpha}$ and $\tilde{\lambda} \triangleq \frac{\lambda}{\underline{\alpha}}$
- Consider

$$\begin{cases} C_{\min} \asymp \kappa_{\alpha}^2 \cdot \|\mathbf{D}_0\|_2 \cdot \frac{k}{p} \cdot \|\mathbf{D}_0\|_F^2 \\ C_{\max} \asymp \frac{\mathbb{E}|\alpha|}{M_{\alpha}} \cdot (1 - 2\mu_k(\mathbf{D}_0)) \end{cases}$$

Asymptotic result ($n \gg 1$)

- **Coherence:** $\mu_k(\mathbf{D}_0) \leq 1/4$
- **Sparsity:** $k \lesssim p / \|\mathbf{D}_0\|_2$
- **Regularisation:** $0 < \lambda \lesssim \underline{\alpha}$ and $\tilde{\lambda} \triangleq \frac{\lambda}{\underline{\alpha}}$
- Consider

$$\begin{cases} C_{\min} \asymp \kappa_{\alpha}^2 \cdot \|\mathbf{D}_0\|_2 \cdot \frac{k}{p} \cdot \|\mathbf{D}_0\|_F^2 \\ C_{\max} \asymp \frac{\mathbb{E}|\alpha|}{M_{\alpha}} \cdot (1 - 2\mu_k(\mathbf{D}_0)) \end{cases}$$

Proposition: For any r such that

$$C_{\min} \cdot \tilde{\lambda} \lesssim r \lesssim C_{\max} \cdot \tilde{\lambda} - \frac{M_{\varepsilon}}{M_{\alpha}}$$

$\mathbf{D} \in \mathcal{D} \mapsto \mathbb{E}[F_{\mathbf{X}}(\mathbf{D})]$ has a local minimum $\hat{\mathbf{D}}$ with $\|\hat{\mathbf{D}} - \mathbf{D}_0\|_F < r$

Some comments on the proposition

- **Non-empty resolution interval:**
 - Limited over-completeness $p \lesssim m^2$
 - Still meaningful in practice [MBPS10], $m = 8 \times 8$ and $p = 256$

Some comments on the proposition

- **Non-empty resolution interval:**
 - Limited over-completeness $p \lesssim m^2$
 - Still meaningful in practice [MBPS10], $m = 8 \times 8$ and $p = 256$
- **“Flatness”** of the distribution:
 - The peakier, the better (i.e., the smaller κ_α , the better)

$$\kappa_\alpha = \frac{\mathbb{E}[|\alpha|]}{\sqrt{\mathbb{E}[\alpha^2]}}$$

Some comments on the proposition

- **Non-empty resolution interval:**
 - Limited over-completeness $p \lesssim m^2$
 - Still meaningful in practice [MBPS10], $m = 8 \times 8$ and $p = 256$
- **“Flatness”** of the distribution:
 - The peakier, the better (i.e., the smaller κ_α , the better)

$$\kappa_\alpha = \frac{\mathbb{E}[|\alpha|]}{\sqrt{\mathbb{E}[\alpha^2]}}$$

- **Noiseless regime:** $M_\epsilon = 0$
 - Regime $\tilde{\lambda} \asymp r$
 - No restriction on the minimum resolution

Some comments on the proposition

- **Non-empty resolution interval:**
 - Limited over-completeness $p \lesssim m^2$
 - Still meaningful in practice [MBPS10], $m = 8 \times 8$ and $p = 256$
- **“Flatness”** of the distribution:
 - The peakier, the better (i.e., the smaller κ_α , the better)

$$\kappa_\alpha = \frac{\mathbb{E}[|\alpha|]}{\sqrt{\mathbb{E}[\alpha^2]}}$$

- **Noiseless regime:** $M_\epsilon = 0$
 - Regime $\tilde{\lambda} \asymp r$
 - No restriction on the minimum resolution
- **Orthogonal dictionary:**
 - $C_{\min} = 0$
 - No restriction on the minimum resolution (even with noise!)

Some instantiations of the result

- Incoherent pair of orthonormal bases:
 - $p = 2m$ and $\|\mathbf{D}_0\|_2 = \sqrt{2}$

Some instantiations of the result

- Incoherent pair of orthonormal bases:
 - $p = 2m$ and $\|\mathbf{D}_0\|_2 = \sqrt{2}$
 - With i.i.d. bounded signals:
 - Coherence: $\mu_1 \lesssim 1/k^{3/2}$
 - Sparsity: $k \lesssim p^{1/3}$

Some instantiations of the result

- Incoherent pair of orthonormal bases:

- $p = 2m$ and $\|\mathbf{D}_0\|_2 = \sqrt{2}$
- With i.i.d. bounded signals:
 - Coherence: $\mu_1 \lesssim 1/k^{3/2}$
 - Sparsity: $k \lesssim p^{1/3}$

- Fixed amplitude-profile coefficients [Sch14b]:

$$\alpha_j = \epsilon_j \cdot \mathbf{a}_{\sigma(j)}, \text{ for } \begin{cases} \epsilon \text{ i.i.d., } \mathbb{P}(\epsilon_j = \pm 1) = 1/2 \\ \sigma \text{ random permutation of } J \end{cases}$$

- Coherence: $\mu_1 \lesssim 1/k$
- Sparsity: $k \lesssim p^{1/2}$

Non-asymptotic result

Consider confidence $\delta > 0$ and the same assumptions as earlier.

Proposition: With prob. greater than $1 - 2e^{-\delta}$ and provided that

$$n_{\text{inliers}} \gtrsim p^2 \cdot (mp + \delta) \cdot \left[\frac{r + \tilde{\lambda} + \frac{M_\epsilon}{M_\alpha}}{r - C_{\min} \cdot \tilde{\lambda}} \right]^2$$

$\mathbf{D} \in \mathcal{D} \mapsto F_{\mathbf{X}}(\mathbf{D})$ has a local minimum $\hat{\mathbf{D}}$ with $\|\hat{\mathbf{D}} - \mathbf{D}_0\|_{\text{F}} < r$.

Non-asymptotic result

Consider confidence $\delta > 0$ and the same assumptions as earlier.

Proposition: With prob. greater than $1 - 2e^{-\delta}$ and provided that

$$n_{\text{inliers}} \gtrsim p^2 \cdot (mp + \delta) \cdot \left[\frac{r + \tilde{\lambda} + \frac{M_{\epsilon}}{M_{\alpha}}}{r - C_{\min} \cdot \tilde{\lambda}} \right]^2$$

$\mathbf{D} \in \mathcal{D} \mapsto F_{\mathbf{X}}(\mathbf{D})$ has a local minimum $\hat{\mathbf{D}}$ with $\|\hat{\mathbf{D}} - \mathbf{D}_0\|_{\text{F}} < r$.

The conclusion remains valid if

$$\frac{\|\mathbf{X}_{\text{outliers}}\|_{\text{F}}^2}{n_{\text{inliers}} \cdot \mathbb{E}[\|\alpha\|_2^2]} \lesssim \frac{r^2}{p}$$

Summary

	Orthogonal dictionary		General dictionary	
	Noiseless	Noise	Noiseless	Noise
Sample compl.	independent of r	$1/r^2$	independent of r	$1/r^2$
Resolution r	arbitrary small		$r \asymp C_{\min} \tilde{\lambda}$	$r > C_{\min} \tilde{\lambda}$
Outliers	*	depend on r	*	depend on r

*: More refined argument, if there exists $a_0 > 0$ such that

$$\text{for all } \mathbf{x}, \quad a_0 \cdot \|\mathbf{x}\|_2^2 \leq \|\mathbf{D}_0^T \mathbf{x}\|_2^2,$$

then robustness to outliers can be shown to scale like $\mathcal{O}(a_0^{3/2} \cdot r/\tilde{\lambda})$

Main ideas behind the proof

① Local-minimum condition over \mathcal{D}

- Sphere $\mathcal{S}(r)$ and ball $\mathcal{B}(r)$ with radius r
- $\inf_{\mathbf{D} \in \mathcal{S}(r) \cap \mathcal{D}} F_{\mathbf{X}}(\mathbf{D}) - F_{\mathbf{X}}(\mathbf{D}_0) > 0$
- Compact $\mathcal{B}(r) \cap \mathcal{D}$ with $F_{\mathbf{X}}$ continuous [GJB⁺13]

Main ideas behind the proof

- ① Local-minimum condition over \mathcal{D}
 - Sphere $\mathcal{S}(r)$ and ball $\mathcal{B}(r)$ with radius r
 - $\inf_{\mathbf{D} \in \mathcal{S}(r) \cap \mathcal{D}} F_{\mathbf{X}}(\mathbf{D}) - F_{\mathbf{X}}(\mathbf{D}_0) > 0$
 - Compact $\mathcal{B}(r) \cap \mathcal{D}$ with $F_{\mathbf{X}}$ continuous [GJB⁺13]
- ② Transfer properties from \mathbf{D}_0 to \mathbf{D} in a neighbourhood of \mathbf{D}_0
 - Coherence properties

Main ideas behind the proof

- ① Local-minimum condition over \mathcal{D}
 - Sphere $\mathcal{S}(r)$ and ball $\mathcal{B}(r)$ with radius r
 - $\inf_{\mathbf{D} \in \mathcal{S}(r) \cap \mathcal{D}} F_{\mathbf{X}}(\mathbf{D}) - F_{\mathbf{X}}(\mathbf{D}_0) > 0$
 - Compact $\mathcal{B}(r) \cap \mathcal{D}$ with $F_{\mathbf{X}}$ continuous [GJB⁺13]
- ② Transfer properties from \mathbf{D}_0 to \mathbf{D} in a neighbourhood of \mathbf{D}_0
 - Coherence properties
- ③ Replace $f_{\mathbf{X}}$ by some tractable surrogate
 - Exploit [exact recovery](#) [Fuc05, ZY06, Wai09]
 - Always holds thanks to boundedness assumptions
 - $f_{\mathbf{X}}(\mathbf{D})$ coincides with

$$\phi_{\mathbf{X}}(\mathbf{D}|\mathbf{s}) \triangleq \frac{1}{2} [\|\mathbf{x}\|_2^2 - (\mathbf{D}_J^\top \mathbf{x} - \lambda \mathbf{s}_J)^\top (\mathbf{D}_J^\top \mathbf{D}_J)^{-1} (\mathbf{D}_J^\top \mathbf{x} - \lambda \mathbf{s}_J)] \text{ with } \begin{cases} J = \text{supp}(\boldsymbol{\alpha}_0) \\ \mathbf{s} = \text{sign}(\boldsymbol{\alpha}_0) \end{cases}$$

Main ideas behind the proof

- ① Local-minimum condition over \mathcal{D}
 - Sphere $\mathcal{S}(r)$ and ball $\mathcal{B}(r)$ with radius r
 - $\inf_{\mathbf{D} \in \mathcal{S}(r) \cap \mathcal{D}} F_{\mathbf{X}}(\mathbf{D}) - F_{\mathbf{X}}(\mathbf{D}_0) > 0$
 - Compact $\mathcal{B}(r) \cap \mathcal{D}$ with $F_{\mathbf{X}}$ continuous [GJB⁺13]
- ② Transfer properties from \mathbf{D}_0 to \mathbf{D} in a neighbourhood of \mathbf{D}_0
 - Coherence properties
- ③ Replace $f_{\mathbf{X}}$ by some tractable surrogate
 - Exploit [exact recovery](#) [Fuc05, ZY06, Wai09]
 - Always holds thanks to boundedness assumptions
 - $f_{\mathbf{X}}(\mathbf{D})$ coincides with

$$\phi_{\mathbf{X}}(\mathbf{D}|\mathbf{s}) \triangleq \frac{1}{2} [\|\mathbf{x}\|_2^2 - (\mathbf{D}_J^\top \mathbf{x} - \lambda \mathbf{s}_J)^\top (\mathbf{D}_J^\top \mathbf{D}_J)^{-1} (\mathbf{D}_J^\top \mathbf{x} - \lambda \mathbf{s}_J)] \text{ with } \begin{cases} J = \text{supp}(\boldsymbol{\alpha}_0) \\ \mathbf{s} = \text{sign}(\boldsymbol{\alpha}_0) \end{cases}$$

- ④ Concentration arguments
 - Rademacher averages

Conclusions and take-home messages

- Non-asymptotic analysis of local minimum of sparse coding
 - Noisy signals
 - Can also include generic outliers
 - But no algorithm analysis
- Towards more general signal models
 - Compressible [Cev08]
 - Spike and slab [IR05]
- Other penalties, beyond ℓ_1 [BJMO11]
- Different assumptions on \mathbf{D}_0 (better than coherence)

Sparse and spurious: dictionary learning with noise and outliers
<http://arxiv.org/abs/1407.5155> (submitted)

Thank you all for your attention

References I



Alekh Agarwal, Animashree Anandkumar, Prateek Jain, and Praneeth Netrapalli.

Learning sparsely used overcomplete dictionaries via alternating minimization.

Technical report, preprint [arXiv:1310.7991](#), 2013.



Alekh Agarwal, Animashree Anandkumar, and Praneeth Netrapalli.

Exact recovery of sparsely used overcomplete dictionaries.

Technical report, preprint [arXiv:1309.1952](#), 2013.



Michal Aharon, Michael Elad, and Alfred M Bruckstein.

On the uniqueness of overcomplete dictionaries, and a practical way to retrieve them.

Linear algebra and its applications, 416(1):48–67, 2006.

References II



Sanjeev Arora, Rong Ge, and Ankur Moitra.

New algorithms for learning incoherent and overcomplete dictionaries.

Technical report, preprint arXiv:1308.6273, 2013.



D. M. Bradley and J. A. Bagnell.

Convex coding.

In *Proceedings of the Twenty-Fifth Conference on Uncertainty in Artificial Intelligence (UAI)*, 2009.



F. Bach, R. Jenatton, J. Mairal, and G. Obozinski.

Optimization with sparsity-inducing penalties.

Foundations and Trends in Machine Learning, 4(1):1–106, 2011.

References III



F. Bach, J. Mairal, and J. Ponce.

Convex sparse matrix factorizations.

Technical report, Preprint arXiv:0812.1869, 2008.



V. Cevher.

Learning with compressible priors.

In *Advances in Neural Information Processing Systems*, 2008.



D. L. Donoho and X. Huo.

Uncertainty principles and ideal atomic decomposition.

IEEE Transactions on Information Theory, 47(7):2845–2862, 2001.



M. Elad and M. Aharon.

Image denoising via sparse and redundant representations over learned dictionaries.

IEEE Transactions on Image Processing, 54(12):3736–3745, December 2006.

References IV



J. J. Fuchs.

Recovery of exact sparse representations in the presence of bounded noise.

IEEE Transactions on Information Theory, 51(10):3601–3608, 2005.



Remi Gribonval, Rodolphe Jenatton, Francis Bach, Martin Kleinstenuber, and Matthias Seibert.

Sample complexity of dictionary learning and other matrix factorizations.

Technical report, preprint arXiv:1312.3790, 2013.



R Grosse, R Raina, H Kwong, and AY Ng.

Shift-invariant sparse coding for audio classification.

In *Proceedings of the Conference on Uncertainty in Artificial Intelligence (UAI)*, 2007.

References V



R. Gribonval and K. Schnass.

Dictionary identification—sparse matrix-factorization via ℓ_1 -minimization.

IEEE Transactions on Information Theory, 56(7):3523–3539, 2010.



Pando Georgiev, Fabian Theis, and Andrzej Cichocki.

Sparse component analysis and blind source separation of underdetermined mixtures.

IEEE transactions on neural networks, 16(4):992–996, 2005.



Q. Geng, H. Wang, and J. Wright.

On the Local Correctness of L1 Minimization for Dictionary Learning.

Technical report, Preprint arXiv:1101.5672, 2011.

References VI



H. Ishwaran and J. S. Rao.

Spike and slab variable selection: frequentist and Bayesian strategies.

Annals of Statistics, 33(2):730–773, 2005.



R. Jenatton, J. Mairal, G. Obozinski, and F. Bach.

Proximal methods for hierarchical sparse coding.

Journal of Machine Learning Research, 12:2297–2334, 2011.



A. Krause and V. Cevher.

Submodular dictionary selection for sparse representation.

In *Proceedings of the International Conference on Machine Learning (ICML)*, 2010.



H. Lee, A. Battle, R. Raina, and A. Y. Ng.

Efficient sparse coding algorithms.

In *Advances in Neural Information Processing Systems*, 2007.

References VII



J. Mairal.

Sparse coding for machine learning, image processing and computer vision.

PhD thesis, École normale supérieure de Cachan - ENS Cachan, 2010.

Available at

<http://tel.archives-ouvertes.fr/tel-00595312/fr/>.



J. Mairal, F. Bach, J. Ponce, and G. Sapiro.

Online learning for matrix factorization and sparse coding.

Journal of Machine Learning Research, 11(1):19–60, 2010.



N. A. Mehta and A. G. Gray.

On the sample complexity of predictive sparse coding.

Technical report, preprint arXiv:1202.4050, 2012.

References VIII



A. Maurer and M. Pontil.

k -dimensional coding schemes in hilbert spaces.

IEEE Transactions on Information Theory, 56(11):5839–5846, 2010.



B. A. Olshausen and D. J. Field.

Sparse coding with an overcomplete basis set: A strategy employed by V1?

Vision Research, 37:3311–3325, 1997.



M. D. Plumbley, S. A. Abdallah, T. Blumensath, and M. E. Davies.

Sparse representations of polyphonic music.

Signal Processing, 86(3):417–431, 2006.

References IX



G. Peyré.

Sparse modeling of textures.

Journal of Mathematical Imaging and Vision, 34(1):17–31, 2009.



Karin Schnass.

Local identification of overcomplete dictionaries.

Technical report, preprint arXiv:1401.6354, 2014.



Karin Schnass.

On the identifiability of overcomplete dictionaries via the minimisation principle underlying k-svd.

Applied and Computational Harmonic Analysis, 37(3):464–491, 2014.

References X



Daniel A Spielman, Huan Wang, and John Wright.

Exact recovery of sparsely-used dictionaries.

In *Proceedings of the Twenty-Third international joint conference on Artificial Intelligence*, pages 3087–3090. AAAI Press, 2013.



D. Vainsencher, S. Mannor, and A. M. Bruckstein.

The sample complexity of dictionary learning.

Technical report, Preprint arXiv:1011.5395, 2010.





M. J. Wainwright.

Sharp thresholds for noisy and high-dimensional recovery of sparsity using ℓ_1 - constrained quadratic programming.

IEEE Transactions on Information Theory, 55:2183–2202, 2009.

References XI

-  M. Zhou, H. Chen, J. Paisley, L. Ren, G. Sapiro, and L. Carin.
Non-parametric Bayesian dictionary learning for sparse image representations.
In Advances in Neural Information Processing Systems, 2009.
-  P. Zhao and B. Yu.
On model selection consistency of Lasso.
Journal of Machine Learning Research, 7:2541–2563, 2006.