



Contents
OSJTAG
MCU

Revisions			
Rev	Description	Date	Approved
A	Original Release	DATE	DESIGNER

		Microcontroller Solutions Group 6501 William Cannon Drive West Austin, TX 78735-8598	
<small>No document contains information proprietary to Freescale Semiconductor and shall not be used for engineering design, procurement or manufacture in whole or in part without the express written permission of Freescale Semiconductor.</small>			
Designer: DESIGNER		Drawing Title: TRK-USB-MPC5643L	
Drawn by: DRAWN_BY		Page Title: TITLE PAGE	
Approved: APPROVER		Size C	Document Number SCH-27701 PDF: SPF-27701
Date: Friday, August 24, 2012		Sheet 1	of 4
		1	A



ified:
ms, 5%, 1/16 Watt, Size 0402
s are in uF, 20%, 50V, Size 0402

- All polarized capacitors are Tantalum
2. Interrupted lines coded with the same letter or letter combinations are electrically connected.
3. Device type number is for reference only. The number varies with the manufacturer.
4. Special signal usage:
_B Denotes - Active-Low Signal
<> or [] Denotes - Vectored Signals
5. Interpret diagram in accordance with American National Standards Institute specifications, current revision, with the exception of logic block symbology.



ICAP Classification: FCP: _____ FUG: ☒ PUBE: _____

Drawing Title: **TRK-USB-MPC5643L**

Page Title: **NOTES**

Size	Document Number	Rev
C	SCH-27701 PDF: SPF-27701	A

Date: **Friday, August 24, 2012** Sheet **2** of **4**



