

MIT EECS 6.815/6.865: Assignment 6:  
Homographies and Manual Panoramas

Due Wednesday October 28 at 9pm

## 1 Summary

- Warp an image using a homography
- Compute a homography from four pairs of points
- Compute the bounding box of the output merged image
- Stich two images together to a panorama
- 6.865: Accelerate the warp using bounding boxes

**Be careful. You will need to reuse this code for pset 7 when we will implement fully automatic panorama stitching and blending.**

Also, take a look at `homography.h` for some potentially useful functions.

## 2 Homogeneous Coordinates

We will work homogeneous coordinates to deal with the perspective transforms involved in panorama stitching. A point in the Euclidean plane  $(x, y)^T$  is represented in the projective plane by the family of homogeneous coordinates  $(xw, yw, w)^T$  for any non-zero scalar  $w$ . Since a family of points in the projective plane (for all non-zero  $w$ ) map to the same point in the 2D plane, we will often choose  $w = 1$  as representative. We will think of it as the point in the screen space. Consult the class notes for more details.

## 3 Linear Algebra

In this problem set we will need some matrix algebra. We will use the `Eigen` package as our linear algebra library [http://eigen.tuxfamily.org/index.php?title=Main\\_Page](http://eigen.tuxfamily.org/index.php?title=Main_Page). We've implemented a few aliases for you in `matrix.h`. Please have a look at `a6_main.cpp` for examples on how to use matrices and vectors.

- To initialize a `Matrix` object type  
`Matrix mxName(mxRows, mxCols)`  
where `mxRows` and `mxCols` are the number of rows and columns of the matrix `mxName` respectively.

Keep in mind that using this constructor, the entries of the matrix will be some garbage values (whatever was in this memory location before allocation). For example, if you want to initialize an all-zero matrix, use the special factory method: `Matrix mxName = Matrix::Zero(mxRows, mxCols)`.

- To write to the element  $i, j$  of a matrix `mxName` type `mxName(i,j) = value` where `value` is of type `float`.
- To get the inverse of a matrix `mxName` type `mxName.inverse()`
- To multiply 2 matrices, `A` and `B`, using matrix multiplication ( $A * B$ ) type `A*B`.
- We have provided you with two shorthands `Vec2f` and `Vec3f` for 2D and 3D vectors.

For more information about the `Matrix` class and functions, see `matrix.h` and the tests in `a6_main.cpp`.

## 4 Warp and Image with a Homography

**Homography Matrix**  $H$  is the matrix that transforms the source coordinates to the output coordinates (forward transformation).

Keep in mind that just like in Morphing we want to transform the output pixel coordinates into source pixel coordinates to be able to sample from the source image. This can be done using the inverse of a transform that maps source coordinates into output coordinates.

You apply a homography matrix to a 2D point  $x, y$  in the output image by computing the product:

$$H^{-1} \begin{pmatrix} x \\ y \\ 1 \end{pmatrix} = \begin{pmatrix} x' \\ y' \\ w' \end{pmatrix} \quad (1)$$

To get the final Euclidean coordinates in the projection plane, you then divide by the last projective coordinate:


$$\begin{pmatrix} x'/w' \\ y'/w' \end{pmatrix} \quad (2)$$

**Pixel Boundaries** We will treat pixels coordinates outside the **source** image differently from previous problem sets. If we sample a location outside of the bounds of the source image, we want to leave the corresponding output pixels in the **out** image untouched. Therefore, you need to test if the warped coordinates are outside the **source** image before updating the pixel value.

This scheme might lead to stair artifacts in the output, but we will not worry about it now. In a later assignment, we will perform nice feathering at the boundaries between images.

1 Write a function `void applyhomography(const Image &source, Matrix &H, Image &out, bool bilinear=false)` that *modifies* an image `out` by compositing on top of it the `source` image warped using the  $3 \times 3$  homography matrix `H`. If the Boolean `bilinear` is `True`, use bilinear reconstruction, otherwise use simple nearest neighbor. **Note: this function does not return anything, it just *modifies* `out`, which is passed as a reference.**

Test your function on the provided `green.png` and `poster.png` images using `testApplyHomography` provided in `a6_main.cpp`.



## 5 Compute Homography from 4 Pairs of Points

**UI** In this section, a user will provide correspondences between two images, by clicking using a patent-pending javascript interface (`pano_ui.html`), and your job is to infer the homography matrix that maps the 4 points from the first image to the corresponding 4 points in the other image. As in the warping problem set, you need to click on points in the same order for the left and right images. When using the UI, you need to select points that are as well spread as possible for the computation to be well conditioned. In particular, try to avoid all-collinear points.

**Correspondences** The correspondences will be provided as an array of `CorrespondencePair`, where each `CorrespondencePair` stores  $(x_1, y_1, z_1)$ , the coordinates of the point in the first image and  $(x_2, y_2, z_2)$ , the coordinates in the second.

The test function `testComputeHomographyPoster` in `a6_main.cpp` gives an example of how to use it.

**Homography scaling** A homography matrix is always defined up to a scaling factor. This means that  $H$  and  $kH$  represent the same geometric transformation for any non-zero scalar  $k$ . In this assignment, we will use a quick and dirty

way to resolve the scale ambiguity and will **assume that the bottom right coefficient of the homography is 1**. This could create some problems if the true family of matrices  $H$  had a zero there, but we will ignore this and leave the cleaner solution based on SVD as extra credit.

2 Write a function `Matrix computeHomography(const CorrespondencePair[4])` that takes a list of 4 point correspondences and returns a  $3 \times 3$  homography matrix that maps the first point of each pair to the second point. That is, the homography maps from the first image to the second image.

The details of the algorithm are exposed below

### Outline of Steps

- (a) We would like to solve for the homography that maps 4 points in the first image to the corresponding 4 points in the second image. In general, a homography  $H$  correspondence equations can be written:

$$H \begin{pmatrix} x \\ y \\ 1 \end{pmatrix} = \begin{pmatrix} a & b & c \\ d & e & f \\ g & h & 1 \end{pmatrix} \begin{pmatrix} x \\ y \\ 1 \end{pmatrix} = \begin{pmatrix} w'x' \\ w'y' \\ w' \end{pmatrix} \quad (3)$$

Where the unknowns are  $a, b, c, d, e, f, g, h$ , and we know  $x, y$  and  $x', y'$  for 4 sets of points.  $w'$  is not known, but can be deduced easily from other quantities.

- (b) You need to create a matrix  $A$  and vector  $B$  so that the 8 remaining coefficients ( $a, b, c, d, e, f, g, h$ ) of the homography are encoded in an 8-dimensional vector  $x$  that satisfies  $Ax = B$ .

You have two equations for each pair of corresponding points. To be clear, the  $x$  vector in  $Ax = B$  is actually  $(a, b, c, d, e, f, g, h)^T$ .

Do not get confused between the  $3 \times 3$  homography matrix and the  $8 \times 8$  matrix  $A$  for the linear system.

We recommend that you write a subroutine that fills in two rows of the matrix and vector for a given correspondence pair, since the pattern is the same for all pairs of points.

- (c) Use the `inverse()` member function of the `Matrix` class to compute the inverse of matrix  $A$  and multiply it with  $B$ . You can also have a look at the documentation in `Eigen` and search for linear system solvers.
- (d) Once you have solved the system, reshape your vector  $x$  into a  $3 \times 3$  matrix.

**Debugging** Homographies and projective spaces are big scary things. Do not try directly with the provided pairs of points. Use simpler cases. Think about pairs of correspondences where you can compute the matrix easily by hand. Try to infer the identity or a translation. You can also use `testComputeHomography` in `a6_main.cpp` to help test your function, it should give you the coefficients from `testApplyHomography`.

## 6 Bounding boxes

In the examples so far, the output image is the same size as one of the two inputs. But for panorama stitching, we want to create a bigger output image that encompasses all points from both images.

For this, we need to compute the size of the final output image. Additionally, the final image might be extended towards the negative coordinates with respect to the reference image. To handle this we will translate the reference, so that the pixel coordinates in the final output start at  $(0, 0)$ .

### 6.1 Transform a bounding box

To compute the required size for one image, we forward-transform its four corners to the output space. We will represent the resulting required size as a bounding box, encoded by its minimum and maximum  $x, y$  coordinates.

**Be careful: whereas we usually need to consider the inverse warp to go from output coordinates into source ones, here we need to do the opposite and figure out where the bounds of the source project into the output space.**

3 Write a function `BoundingBox computeTransformedBBox(int imwidth, int imheight, Matrix H)` that takes an image size and a homography as input and returns the `BoundingBox` of the output coordinates.

Use `testComputeTransformedBBox` in `a6_main.cpp` to help test your function. **Hint:** implementing the optional `Image drawBoundingBox(const Image &im, BoundingBox bbox)` is useful for debugging bounding boxes.

### 6.2 Bounding box union


When stitching  $N$  images, the output is the union of the  $N$  bounding boxes.

4 Write a function `BoundingBox bboxUnion(BoundingBox B1, BoundingBox B2)` that takes two bounding boxes and returns a bigger bounding box that tightly encompasses the union of the bounding boxes.

Use `testBBoxUnion` in `a6_main.cpp` to help test your function.

## 6.3 Translation

After computing and merging the bounding boxes of the N images (including that of the reference), we often will have the situation where the upper-left corner of the bounding box has negative coordinates. This is illustrated in the image below:



If the upper-left corner of the bounding box has negative coordinates, we need to translate the coordinate system of the reference image to set this corner to coordinates  $(0,0)$ . The translation vector is simply the negative of this corner's coordinates. You can then obtain the translation homography matrix for translation by  $(t_x t_y)^T$  as:

$$\begin{pmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{pmatrix}$$

5 Write a function `Matrix makeTranslation(BoundingBox B)` that takes a bounding box as input and returns a  $3 \times 3$  matrix corresponding to a translation that moves the upper left corner of the bounding box to  $(0,0)$ .

Use `testTranslate` in `a6_main.cpp` to help test your function.

## 6.4 Putting it all together

6 Write a function `Image stitch(const Image &im1, const Image &im2, const float CorrespondencePair// correspondences[4])` that takes two images and their point correspondences and outputs a stitched panorama in the coordinate system of the second (reference) image.

You first need to compute the homography between the two images. Then compute the resulting bounding box and translation matrix. Create a new black image of the size of the bounding box. Then use a combination of your translation and homography matrix to composite both images into the output. Be careful that you also need to transform the second (reference) image to take the translation into account and that you need to combine the translation and the homography for the first image. Use the right matrix product!

Use `testStitchStata` and `testStitchBoston` in `a6_main.cpp` to help test your function. Here we show our results for the `stata` and `boston-skyline` series. The seam is not perfect but we will fix this in a later assignment.



## 6.5 6.865 only (Or 5% Extra Credit for 6.815): Speed up Warping using Bounding Boxes

Accelerate the warping function by restricting the warping loop using the bounding box of each image.

7 Implement `void applyhomographyFast(const Image &source, Image &out, Matrix &H, bool bilinear=false)`. Make sure you see a speed-up of at least 5x for the green and poster example.

Use `testApplyHomographyFast` in `a6_main.cpp` to help test your function.

## 6.6 6.865 only (Or 5% Extra Credit for 6.815): Extra Test Cases and Images

8 In `homography_extra_tests.h`, similar to `testStitchStata`, write the following test cases:  
`testStitchScience()`, to stitch `science-1.png` and `science-2.png`;  
`testStitchConvention()`, to stitch `convention-1.png` and `convention-2.png`;  
`testStitchBoston1()`, to stitch `boston1-1.png` and `boston1-2.png`.  
Create output files `science-stitch.png`, and `convention-stitch.png`, and `boston1-stitch.png`. Please submit these images to stellar in a zip files, where these three images are directly in the zip file (no extra folders). Use the provided javascript UI to choose the 4 point pairs needed for stitching.

## 7 Extra Credit (up to 10% total)

- (5%): Implement a least square estimation of the homography for more than four pairs of points. Use `pinv` instead of `inv`.
- (10%) Use SVD to alleviate the assumption that the bottom right coefficient of the homography matrix is 1.
- (5%): Improve the javascript UI.



## 8 Submission

Turn in your files to the online submission system (link is on Stellar) and make sure all your files are in the `asst` directory under the root of the zip file. If your code compiles on the submission system, it is organized correctly. The submission system will run code in your main function, but we will not use this code for grading. The submission system should also show you the image your code writes to the `./Output` directory

In the submission system, there will be a form in which you should answer the following questions:

- How long did the assignment take? (in minutes)
- Potential issues with your solution and explanation of partial completion (for partial credit)
- Any extra credit you may have implemented and their function signatures if applicable
- Collaboration acknowledgment (you must write your own code)
- What was most unclear/difficult?
- What was most exciting?