

# The `apxproof` package

Pierre Senellart  
`pierre@senellart.com`

2016/10/27 v1.0.0-dev

## Abstract

This package facilitates the writing of scientific article with proofs deferred to the appendix.

## 1 Usage

TODO

## 2 Implementation

We now describe the entire code of the package, in literate programming fashion.

### 2.1 Dependencies

We first load a few package dependencies:

- `bibunits` to add a second bibliography for the appendix material.

```
1 \RequirePackage{bibunits}
```

- `environ` to easily define the repeated theorem environments.

```
2 \RequirePackage{environ}
```

- `etoolbox` to define simple toggles.

```
3 \RequirePackage{etoolbox}
```

- `fancyvrb` for the bulk of the work of exporting appendix material in an auxiliary file.

```
4 \RequirePackage{fancyvrb}
```

- `ifthen` for easier comparison of character strings.

```
5 \RequirePackage{ifthen}
```

- `kvoptions` to manage options passed to the package.

```
6 \RequirePackage{kvoptions}
```

- `amsthm` for its `\newtheorem` macro. Some document classes (e.g., `lipics`) preload the `amsthm`: this is fine, `\RequirePackage{amsthm}` will simply have no effect. On the other hand, some other document classes (e.g., `llncs` or `sig-alternate`) define a `proof` environment that conflicts with `amsthm`, so we have to undefine this environment before loading `amsthm`.

```
7 \ifpackageloaded{amsthm}{
8   }{
9     \let\proof\undefined
10    \let\endproof\undefined
11  }
12 \RequirePackage{amsthm}
```

## 2.2 Option Processing

Many names throughout the package use an atrobace (`@`) to avoid name conflict with user-defined names. To simplify the compilation of the documentation, we simply make it a regular character in all the rest.

```
13 \makeatletter
```

We setup the processing of options using `keyval` facilities; the only declared options is named `append`, with a default value of `append`:

```
14 \SetupKeyvalOptions{
15   family=AXP,
16   prefix=AXP@
17 }
18 \DeclareStringOption[append]{append}
19 \ProcessLocalKeyvalOptions*
```

We check that the value of the `append` option is valid, and add a message to the compilation log.

```
20 \ifthenelse{\equal{\AXP@append}{append}}{
21   \message{apxproof: Appendix material appended to the document}
22 }{\ifthenelse{\equal{\AXP@append}{strip}}{
23   \message{apxproof: Appendix material stripped}
24 }{\ifthenelse{\equal{\AXP@append}{inline}}{
25   \message{apxproof: Appendix material inlined within the document}
26 }{
27   \errmessage{Error: unsupported option appendix=\AXP@append for
28   package apxproof}
29 }}}}
```

## 2.3 Macros Common to All Compilation Modes

`\newtheoremrep` We define the high-level `\newtheoremrep` to have the same syntax as `amsthm`'s `\newtheorem`. For this purpose, we need a little trick to deal with the second

optional argument, which is what `\@oparg` is used for. `\axp@newtheoremrep` is defined differently depending on the compilation mode

```
30 \newcommand\newtheoremrep[1]{%
31   \@oparg{\axp@newtheoremrep{#1}}[]%
32 }
```

`proofsketch` Simple `proofsketch` environment.

```
33 \newenvironment{proofsketch}
34   {\vskip3pt\noindent\emph{Proof sketch.} }
35   {\hfill\qed\vskip3pt}
```

`\thmhead` We redefine AMS- $\text{\LaTeX}$ 's `\thmhead` to use a format where the repeated version of a theorem, using a theorem note, can look exactly like the original version of the theorem and its theorem counter.

```
36 \def\thmhead#1#2#3{%
37   \thmname{#1}\thmnumber{\@ifnotempty{#1}{ }\@upn{#2}}%
38   \thmnote{ #3}}
```

## 2.4 Inline Compilation Mode

```
39 \ifthenelse{\equal{\AXP@appendix}{inline}}{
```

`axp@newtheoremrep` In the inline mode, `axp@newtheoremrep` undefines the existing theorem environment if it has already been defined (e.g., by the document class), invokes `\newtheorem` and creates a repeated theorem environment that behaves exactly as the regular theorem environment.

```
40   \def\axp@newtheoremrep#1[#2]#3{%
41     \expandafter\let\csname #1\endcsname\undefined
42     \expandafter\let\csname c@#1\endcsname\undefined
43     \newtheorem{#1}[#2]{#3}%
44     \NewEnviron{#1rep}[1][]{%
45       \begin{#1}[##1]\BODY\end{#1}%
46     }
47   }
```

`inlineproof` In the inline mode, these environments behave like the regular `proof` environment.

```
48   \let\inlineproof\proof
49   \let\endinlineproof\endproof
50   \let\nestedproof\proof
51   \let\endnestedproof\endproof
52   \let\appendixproof\proof
53   \let\endappendixproof\endproof
```

`toappendix` In the inline mode, this environment and these macros are no-op.

```
54   \newenvironment{toappendix}{}{}
55   \let\noproofinappendix\relax
56   \let\nosectionappendix\relax
```

Finally, some class-specific behavior so that theorems created by `\newtheoremrep` appear with the correct style. For now, only the styling for ACM document class (e.g., `sig-alternate`) needs to be adapted.

```

57 \ifdefined\@acmtitlebox
58   \newtheoremstyle{mystyle}
59     {3pt}
60     {3pt}
61     {\itshape}
62     {}
63     {\scshape}
64     {.}
65     {.5em}
66     {}
67   \theoremstyle{mystyle}
68 \fi
69 }
```

## 2.5 Append or Strip Compilation Modes

```

70 {
```

We now deal with the case where `apxproof` really does something useful: either append the appendix material to the document, or strip it entirely.

```

71 \newwrite\axp@proofsfile
72 \immediate\openout\axp@proofsfile=\jobname.axp
73 \immediate\write\axp@proofsfile{%
74   \noexpand\makeatletter
75   \noexpand\let\noexpand\proof\noexpand\axpold@proof
76   \noexpand\let\noexpand\endproof\noexpand\endaxpold@proof
77   \noexpand\let\noexpand\section\noexpand\axpold@section
78 }
79 \def\FVB@VerbatimOut{%
80   \@bsphack
81   \begingroup
82     \FV@UseKeyValues
83     \FV@DefineWhiteSpace
84     \def\FV@Space{\space}%
85     \FV@DefineTabOut
86     \def\FV@ProcessLine{\immediate\write\axp@proofsfile}%
87     \let\FV@FontScanPrep\relax
88     \let\@noligs\relax
89     \FV@Scan}
90 \def\FVE@VerbatimOut{\endgroup\@esphack}
91
92 \let\axpold@proof\proof
93 \let\endaxpold@proof\endproof
94
95 \newtoggle{axp@seenrepththeorem}
96
```

```

97 \def\noproofinappendix{%
98   \global\togglefalse{axp@seenreptheorem}%
99 }
100
101 \newenvironment{appendixproof}
102   {%
103     \axp@writesection
104     \immediate\write\axp@proofsfile{%
105       \noexpand\begin{axpold@proof}%
106     }%
107     \VerbatimOut
108   }
109   {%
110     \endVerbatimOut
111     \immediate\write\axp@proofsfile{%
112       \noexpand\end{axpold@proof}%
113     }%
114     \noproofinappendix
115   }
116
117 \renewenvironment{proof}
118   {%
119     \iftoggle{axp@seenreptheorem}{%
120       \appendixproof
121     }{%
122       \axpold@proof
123     }%
124   }
125   {%
126     \iftoggle{axp@seenreptheorem}{%
127       \endappendixproof
128     }{%
129       \endaxpold@proof
130     }%
131   }
132
133 \let\inlineproof\axpold@proof
134 \let\endinlineproof\endaxpold@proof
135
136 \let\nestedproof\axpold@proof
137 \let\endnestedproof\endaxpold@proof
138
139 \newcommand{\appendixrefname}{References for the Appendix}
140 \newcommand{\appendixbibliographystyle}{alpha}
141 \newcommand{\appendixbibliographyprelim}{}
142
143 \ifthenelse{\equal{\AXP@appendix}{append}}{
144   \AtEndDocument{%
145     \clearpage\onecolumn\appendix
146     \appendixbibliographyprelim

```

```

147     \begin{bibunit}[\appendixbibliographystyle]%
148     \immediate\closeout\axp@proofsfile\input{\jobname.axp}%
149     \renewcommand{\refname}{\appendixrefname}%
150     \putbib
151     \end{bibunit}%
152 }
153 {}
154
155 \let\axpold@bibliography\bibliography
156 \renewcommand\@bibliography[1]{%
157     \defaultbibliography{#1}%
158     \axpold@bibliography{#1}%
159 }
160
161 \newcounter{axp@rpcounter}
162 \newcounter{axp@seccounter}
163
164 \def\axp@newtheoremrep#1[#2]#3{%
165     \newtheorem*{axp@#1rp}{#3}%
166     \expandafter\let\csname #1\endcsname\undefined
167     \expandafter\let\csname c@#1\endcsname\undefined
168     \newtheorem{#1}[#2]{#3}%
169     \NewEnviron{#1rep}[1][]{%
170         \addtocounter{axp@rpcounter}{1}%
171         \begin{#1}[##1]\label{axp@r\roman{axp@rpcounter}}\BODY\end{#1}%
172         \global\toggletrue{axp@seenreptheorem}%
173         \global\expandafter\let\csname rplet\roman{axp@rpcounter}\endcsname\BODY%
174         \axp@writesection%
175         \immediate\write\axp@proofsfile{%
176             \noexpand\begin{axp@#1rp}[\noexpand\ref{axp@r\roman{axp@rpcounter}}]\@ifnotempty{##1}{\noexpand\label{axp@s\roman{axp@seccounter}}}%
177             \noexpand\let\noexpand\label\noexpand\@gobble%
178             \expandafter\noexpand\csname rplet\roman{axp@rpcounter}\endcsname\noexpand\end{axp@#1rp}%
179         }
180     }
181 }
182
183 \def\axp@sectitle{}
184
185 \let\axpold@section\section
186 \def\section{\@ifstar\@section\@@section}
187 \def\@section#1{%
188     \global\edef\axp@sectitle{#1}%
189     \axpold@section*{#1}%
190     \addtocounter{axp@seccounter}{1}%
191     \label{axp@s\roman{axp@seccounter}}%
192 }
193 \def\@@section#1{%
194     \global\edef\axp@sectitle{#1}%
195     \axpold@section{#1}%
196     \addtocounter{axp@seccounter}{1}%

```

```

197   \label{axp@s\roman{axp@seccounter}}}%
198 }
199 \ifdefined\@acmttitlebox
200 \fi
201
202 \newcommand{\nosectionappendix}{
203   \global\def\axp@sectitle{}%
204 }
205
206 \newcommand\axp@writesection{%
207   \ifx\axp@sectitle\empty
208   \else
209     \immediate\write\axp@proofsfile{\noexpand\def\noexpand\tmp{\noexpand\ref{axp@s\roman{axp@seccounter}}\axp@sectitle}}}%
210     (\axp@sectitle)}}%
211   \nosectionappendix
212 \fi
213 }
214
215 \newenvironment{toappendix}
216   {\axp@writesection\VerbatimOut}
217   {\endVerbatimOut}

```

### 2.5.1 Class-Specific Behavior

We conclude with some class-specific behavior.

\@getcl@ss We first use a little trick to store the current document class in macro \@currentclass,  
\@getclass from <http://tex.stackexchange.com/a/43541>.  
\@currentclass

```

218 \def\@getcl@ss#1.cls#2\relax{\def\@currentclass{#1}}
219 \def\@getclass{\expandafter\@getcl@ss\@filelist\relax}
220 \@getclass

```

### ACM Document Classes

```

221 \ifdefined\@acmttitlebox

```

\thebibliography The section title of the bibliography is in uppercase in these document classes. In  
\refname addition, the \thebibliography macro hard-codes twice the section title, so we  
\appendixrefname un-hardcode it so that it can be modified in the appendix.

```

222 \patchcmd{\thebibliography}{References}{\protect\refname}{}{}
223 \patchcmd{\thebibliography}{References}{\protect\refname}{}{}
224 \newcommand{\refname}{REFERENCES}
225 \renewcommand{\appendixrefname}{REFERENCES FOR THE APPENDIX}

```

\section These document classes redefine \section in a weird way, adding the possibility  
\@@section of an optional argument. We redefine this in a sane way.

```

226 \def\section{\@ifstar\@section{\@dblarg{\@@section}}}
227 \def\@@section#1#2{%
228   \global\edef\axp@sectitle{#2}%
229   \axpold@section{#2}%
230   \addtocounter{axp@seccounter}{1}%

```

```

231     \label{axp@s\roman{axp@seccounter}}}%
232   }

233   \fi

```

## lipics

```

234   \ifthenelse{\equal{\@currentclass}{lipics}}{

```

`\appendixbibliographyprelim` The default bibliography in the lipics document class formatting is not compatible with the alpha bibliography style. We fix this here.

```

235     \renewcommand{\appendixbibliographyprelim}{%
236       \global\let\oldbiblabel\@biblabel
237       \def\@biblabel{\hspace*{-2em}\small\oldbiblabel}%
238     }

239   }

240 }

```

## Change History

v1.0.0-dev

General: Initial version . . . . . 1

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols			
<code>\@@section</code> . . . . .	186, 193, <u>226</u>	<code>\@noligs</code> . . . . .	88
<code>\@acmtitlebox</code> . . . . .	57, 199, <u>221</u>	<code>\@oparg</code> . . . . .	31
<code>\@biblabel</code> . . . . .	236, <u>237</u>	<code>\@section</code> . . . . .	186, 187, <u>226</u>
<code>\@bsphack</code> . . . . .	80	<code>\@upn</code> . . . . .	37
<code>\@currentclass</code> . . . . .	<u>218</u> , 234	<b>A</b>	
<code>\@dblarg</code> . . . . .	226	<code>\addtocounter</code> . . . . .	170, 190, 196, 230
<code>\@esphack</code> . . . . .	90	<code>\appendix</code> . . . . .	145
<code>\@filelist</code> . . . . .	219	<code>\appendixbibliographyprelim</code> . . . . .	141, 146, <u>235</u>
<code>\@getcl@ss</code> . . . . .	<u>218</u>	<code>\appendixbibliographystyle</code> . . . . .	140, 147
<code>\@getclass</code> . . . . .	<u>218</u>	<code>\appendixproof</code> . . . . .	52, 120
<code>\@gobble</code> . . . . .	177	<code>appendixproof (environment)</code> . . . . .	<u>48</u>
<code>\@ifnotempty</code> . . . . .	37, 176	<code>\appendixrefname</code> . . . . .	139, 149, <u>222</u>
<code>\@ifpackageloaded</code> . . . . .	7	<code>\AtEndDocument</code> . . . . .	144
<code>\@ifstar</code> . . . . .	186, 226		



<code>\AXP@appendix</code> . . .	20, 22, 24, 27, 39, 143	<code>\equal</code> . . . . .	20, 22, 24, 39, 143, 234
<code>\axp@newtheoremrep</code> . . .	31, 40, 40, 164	<code>\errmessage</code> . . . . .	27
<code>\axp@proofsfile</code> . . . . .	71,	<code>\expandafter</code> . . . . .	
	72, 73, 86, 104, 111, 148, 175, 209		41, 42, 166, 167, 173, 178, 219
<code>\axp@sectitle</code> . . . . .		<b>F</b>	
	183, 188, 194, 203, 207, 210, 228	<code>\fi</code> . . . . .	68, 200, 212, 233
<code>\axp@writesection</code> . .	103, 174, 206, 216	<code>\FV@DefineTabOut</code> . . . . .	85
<code>\axpold@bibliography</code> . . . . .	155, 158	<code>\FV@DefineWhiteSpace</code> . . . . .	83
<code>\axpold@proof</code> . . .	75, 92, 122, 133, 136	<code>\FV@FontScanPrep</code> . . . . .	87
<code>\axpold@section</code> . . . . .		<code>\FV@ProcessLine</code> . . . . .	86
	77, 185, 189, 195, 209, 229	<code>\FV@Scan</code> . . . . .	89
<b>B</b>		<code>\FV@Space</code> . . . . .	84
<code>\begin</code> . . . . .	45, 105, 147, 171, 176	<code>\FV@UseKeyValues</code> . . . . .	82
<code>\begingroup</code> . . . . .	81	<code>\FVB@VerbatimOut</code> . . . . .	79
<code>\bibliography</code> . . . . .	155, 156	<code>\FVE@VerbatimOut</code> . . . . .	90
<code>\BODY</code> . . . . .	45, 171, 173	<b>G</b>	
<b>C</b>		<code>\global</code> . . . . .	98,
<code>\clearpage</code> . . . . .	145		172, 173, 188, 194, 203, 228, 236
<code>\closeout</code> . . . . .	148	<b>H</b>	
<code>\csname</code> . . . . .	41, 42, 166, 167, 173, 178	<code>\hfill</code> . . . . .	35
<b>D</b>		<code>\hspace</code> . . . . .	237
<code>\DeclareStringOption</code> . . . . .	18	<b>I</b>	
<code>\def</code> . . . . .	36, 40, 79, 84, 86,	<code>\ifdefined</code> . . . . .	57, 199, 221
	90, 97, 164, 183, 186, 187, 193,	<code>\ifthenelse</code> . . .	20, 22, 24, 39, 143, 234
	203, 209, 218, 219, 226, 227, 237	<code>\iftoggle</code> . . . . .	119, 126
<code>\defaultbibliography</code> . . . . .	157	<code>\ifx</code> . . . . .	207
<b>E</b>		<code>\immediate</code> . . . . .	
<code>\edef</code> . . . . .	188, 194, 228		72, 73, 86, 104, 111, 148, 175, 209
<code>\else</code> . . . . .	208	<code>\inlineproof</code> . . . . .	48, 133
<code>\emph</code> . . . . .	34	<code>\inlineproof (environment)</code> . . . . .	48
<code>\empty</code> . . . . .	207	<code>\input</code> . . . . .	148
<code>\end</code> . . . . .	45, 112, 151, 171, 178	<code>\itshape</code> . . . . .	61
<code>\endappendixproof</code> . . . . .	53, 127	<b>J</b>	
<code>\endaxpold@proof</code> . . . . .	76, 93, 129, 134, 137	<code>\jobname</code> . . . . .	72, 148
<code>\endcsname</code> . . . . .	41, 42, 166, 167, 173, 178	<b>L</b>	
<code>\endgroup</code> . . . . .	90	<code>\label</code> . . . . .	171, 177, 191, 197, 231
<code>\endinlineproof</code> . . . . .	49, 134	<code>\let</code> . . . . .	9, 10, 41, 42, 48, 49, 50, 51,
<code>\endnestedproof</code> . . . . .	51, 137		52, 53, 55, 56, 75, 76, 77, 87,
<code>\endproof</code> . . . . .	10, 49, 51, 53, 76, 93		88, 92, 93, 133, 134, 136, 137,
<code>\endVerbatimOut</code> . . . . .	110, 217		155, 166, 167, 173, 177, 185, 236
environments:		<b>M</b>	
<code>appendixproof</code> . . . . .	48	<code>\makeatletter</code> . . . . .	13, 74
<code>inlineproof</code> . . . . .	48	<code>\message</code> . . . . .	21, 23, 25
<code>nestedproof</code> . . . . .	48	<b>N</b>	
<code>proofsketch</code> . . . . .	33	<code>\nestedproof</code> . . . . .	50, 136
<code>toappendix</code> . . . . .	54		

<code>nestedproof (environment)</code> . . . . .	<a href="#">48</a>	<code>\renewcommand</code> . . . . .	<a href="#">149, 156, 225, 235</a>
<code>\newcounter</code> . . . . .	<a href="#">161, 162</a>	<code>\renewenvironment</code> . . . . .	<a href="#">117</a>
<code>\NewEnviron</code> . . . . .	<a href="#">44, 169</a>	<code>\RequirePackage</code> . . . . .	<a href="#">1, 2, 3, 4, 5, 6, 12</a>
<code>\newtheorem</code> . . . . .	<a href="#">43, 165, 168</a>	<code>\roman</code> . . . . .	<a href="#">171,</a>
<code>\newtheoremrep</code> . . . . .	<a href="#">30</a>		<a href="#">173, 176, 178, 191, 197, 209, 231</a>
<code>\newtheoremstyle</code> . . . . .	<a href="#">58</a>	<b>S</b>	
<code>\newtoggle</code> . . . . .	<a href="#">95</a>	<code>\scshape</code> . . . . .	<a href="#">63</a>
<code>\newwrite</code> . . . . .	<a href="#">71</a>	<code>\section</code> . . . . .	<a href="#">77, 185, 186, 226</a>
<code>\noexpand</code> . . . . .	<a href="#">74, 75,</a>	<code>\SetupKeyvalOptions</code> . . . . .	<a href="#">14</a>
	<a href="#">76, 77, 105, 112, 176, 177, 178, 209</a>	<code>\small</code> . . . . .	<a href="#">237</a>
<code>\noindent</code> . . . . .	<a href="#">34</a>	<code>\space</code> . . . . .	<a href="#">84</a>
<code>\noproofinappendix</code> . . . . .	<a href="#">54, 97, 114</a>	<b>T</b>	
<code>\nosectionappendix</code> . . . . .	<a href="#">54, 202, 211</a>	<code>\thebibliography</code> . . . . .	<a href="#">222</a>
<b>O</b>		<code>\theoremstyle</code> . . . . .	<a href="#">67</a>
<code>\oldbiblabel</code> . . . . .	<a href="#">236, 237</a>	<code>\thmhead</code> . . . . .	<a href="#">36</a>
<code>\onecolumn</code> . . . . .	<a href="#">145</a>	<code>\thmname</code> . . . . .	<a href="#">37</a>
<code>\openout</code> . . . . .	<a href="#">72</a>	<code>\thmnote</code> . . . . .	<a href="#">38</a>
<b>P</b>		<code>\thmnumber</code> . . . . .	<a href="#">37</a>
<code>\patchcmd</code> . . . . .	<a href="#">222, 223</a>	<code>\tmp</code> . . . . .	<a href="#">209</a>
<code>\ProcessLocalKeyvalOptions</code> . . . . .	<a href="#">19</a>	<code>toappendix (environment)</code> . . . . .	<a href="#">54</a>
<code>\proof</code> . . . . .	<a href="#">9, 48, 50, 52, 75, 92</a>	<code>\togglefalse</code> . . . . .	<a href="#">98</a>
<code>proofsketch (environment)</code> . . . . .	<a href="#">33</a>	<code>\toggletrue</code> . . . . .	<a href="#">172</a>
<code>\protect</code> . . . . .	<a href="#">209, 222, 223</a>	<b>U</b>	
<code>\putbib</code> . . . . .	<a href="#">150</a>	<code>\undefined</code> . . . . .	<a href="#">9, 10, 41, 42, 166, 167</a>
<b>Q</b>		<b>V</b>	
<code>\qed</code> . . . . .	<a href="#">35</a>	<code>\VerbatimOut</code> . . . . .	<a href="#">107, 216</a>
<b>R</b>		<code>\vskip</code> . . . . .	<a href="#">34, 35</a>
<code>\ref</code> . . . . .	<a href="#">176, 209</a>	<b>W</b>	
<code>\refname</code> . . . . .	<a href="#">149, 222</a>	<code>\write</code> . . . . .	<a href="#">73, 86, 104, 111, 175, 209</a>
<code>\relax</code> . . . . .	<a href="#">55, 56, 87, 88, 218, 219</a>		