

# The `apxproof` package

Pierre Senellart  
`pierre@senellart.com`

2016/10/27 v1.0.0-dev

## Abstract

This package facilitates the writing of scientific article with proofs deferred to the appendix.

## 1 Usage

TODO

## 2 Implementation

We now describe the entire code of the package, in literate programming fashion.

### 2.1 Dependencies

We first load a few package dependencies:

- `bibunits` to add a second bibliography for the appendix material.

```
1 \RequirePackage{bibunits}
```

- `environ` to easily define the repeated theorem environments.

```
2 \RequirePackage{environ}
```

- `etoolbox` to define simple toggles.

```
3 \RequirePackage{etoolbox}
```

- `fancyvrb` for the bulk of the work of exporting appendix material in an auxiliary file.

```
4 \RequirePackage{fancyvrb}
```

- `ifthen` for easier comparison of character strings.

```
5 \RequirePackage{ifthen}
```

- `kvoptions` to manage options passed to the package.

```
6 \RequirePackage{kvoptions}
```

- `amsthm` for its `\newtheorem` macro. Some document classes (e.g., `lipics`) preload `amsthm`: this is fine, `\RequirePackage{amsthm}` will simply have no effect. On the other hand, some other document classes (e.g., `llncs` or `sig-alternate`) define a `proof` environment that conflicts with `amsthm`, so we have to undefine this environment before loading `amsthm`.

```
7 \ifpackageloaded{amsthm}{
8   }{
9     \let\proof\undefined
10    \let\endproof\undefined
11  }
12  \RequirePackage{amsthm}
```

## 2.2 Option Processing

Many names throughout the package use an atbase (`@`) to avoid name conflict with user-defined names. To simplify the compilation of the documentation, we simply make it a regular character in all the rest.

```
13 \makeatletter
```

We setup the processing of options using `keyval` facilities; the only declared options is named `append`, with a default value of `append`:

```
14 \SetupKeyvalOptions{
15   family=AXP,
16   prefix=AXP@
17 }
18 \DeclareStringOption[append]{append}
19 \ProcessLocalKeyvalOptions*
```

We check that the value of the `append` option is valid, and add a message to the compilation log.

```
20 \ifthenelse{\equal{\AXP@append}{append}}{
21   \message{apxproof: Appendix material appended to the document}
22 }{\ifthenelse{\equal{\AXP@append}{strip}}{
23   \message{apxproof: Appendix material stripped}
24 }{\ifthenelse{\equal{\AXP@append}{inline}}{
25   \message{apxproof: Appendix material inlined within the document}
26 }{
27   \errmessage{Error: unsupported option appendix=\AXP@append for
28   package apxproof}
29 }}}}
```

## 2.3 Macros Common to All Compilation Modes

`\newtheoremrep` We define the high-level `\newtheoremrep` to have the same syntax as `amsthm`'s `\newtheorem`. For this purpose, we need a little trick to deal with the second

optional argument, which is what `\@oparg` is used for. `\axp@newtheoremrep` is defined differently depending on the compilation mode

```
30 \newcommand\newtheoremrep[1]{%
31   \@oparg{\axp@newtheoremrep{#1}}[]%
32 }
```

`proofsketch` Simple `proofsketch` environment.

```
33 \newenvironment{proofsketch}
34   {\vskip3pt\noindent\emph{Proof sketch.} }
35   {\hfill\qed\vskip3pt}
```

`\thmhead` We redefine AMS- $\text{\LaTeX}$ 's `\thmhead` to use a format where the repeated version of a theorem, using a theorem note, can look exactly like the original version of the theorem and its theorem counter.

```
36 \def\thmhead#1#2#3{%
37   \thmname{#1}\thmnumber{\@ifnotempty{#1}{ }\@upn{#2}}%
38   \thmnote{ #3}}
```

## 2.4 Inline Compilation Mode

```
39 \ifthenelse{\equal{\AXP@appendix}{inline}}{
```

`axp@newtheoremrep` In the inline mode, `axp@newtheoremrep` undefines the existing theorem environment if it has already been defined (e.g., by the document class), invokes `\newtheorem` and creates a repeated theorem environment that behaves exactly as the regular theorem environment.

```
40   \def\axp@newtheoremrep#1[#2]#3{%
41     \expandafter\let\csname #1\endcsname\undefined
42     \expandafter\let\csname c@#1\endcsname\undefined
43     \newtheorem{#1}[#2]{#3}%
44     \NewEnviron{#1rep}[1][]{%
45       \begin{#1}[##1]\BODY\end{#1}%
46     }
47   }
```

`inlineproof` In the inline mode, these environments behave like the regular `proof` environment.

```
nestedproof 48 \let\inlineproof\proof
appendixproof 49 \let\endinlineproof\endproof
50 \let\nestedproof\proof
51 \let\endnestedproof\endproof
52 \let\appendixproof\proof
53 \let\endappendixproof\endproof
```

`toappendix` In the inline mode, this environment and these macros are no-op.

```
\noproofinappendix 54 \newenvironment{toappendix}{}{}
\nosectionappendix 55 \let\noproofinappendix\relax
56 \let\nosectionappendix\relax
```

Finally, some class-specific behavior so that theorems created by `\newtheoremrep` appear with the correct style. For now, only the styling for ACM document class (e.g., `sig-alternate`) needs to be adapted.

```

57 \ifdefined\@acmtitlebox
58   \newtheoremstyle{mystyle}
59     {3pt}
60     {3pt}
61     {\itshape}
62     {}
63     {\scshape}
64     {.}
65     {.5em}
66     {}
67   \theoremstyle{mystyle}
68 \fi
69 }
```

## 2.5 Append or Strip Compilation Modes

```

70 {
```

We now deal with the case where `apxproof` really does something useful: either append the appendix material to the document, or strip it entirely.

### 2.5.1 Auxiliary File for the Appendix

```

71 \newwrite\axp@proofsfile
72 \immediate\openout\axp@proofsfile=\jobname.axp
73 \immediate\write\axp@proofsfile{%
74   \noexpand\makeatletter
75   \noexpand\let\noexpand\proof\noexpand\axpold@proof
76   \noexpand\let\noexpand\endproof\noexpand\endaxpold@proof
77   \noexpand\let\noexpand\section\noexpand\axpold@section
78 }
79 \def\FVB@VerbatimOut{%
80   \@bsphack
81   \begingroup
82     \FV@UseKeyValues
83     \FV@DefineWhiteSpace
84     \def\FV@Space{\space}%
85     \FV@DefineTabOut
86     \def\FV@ProcessLine{\immediate\write\axp@proofsfile}%
87     \let\FV@FontScanPrep\relax
88     \let\@noligs\relax
89     \FV@Scan}
90 \def\FVE@VerbatimOut{\endgroup\@esphack}
91 \newenvironment{toappendix}
92   {\axp@writesection\VerbatimOut}
93   {\endVerbatimOut}
```

### 2.5.2 Definition of New Theorems

```

94 \newtoggle{axp@seenreptheorem}
95 \newcounter{axp@rpcounter}
96 \newcounter{axp@seccounter}
97
98 \def\axp@newtheoremrep#1[#2]#3{%
99   \newtheorem*{axp@#1rp}{#3}%
100   \expandafter\let\csname #1\endcsname\undefined
101   \expandafter\let\csname c@#1\endcsname\undefined
102   \newtheorem{#1}[#2]{#3}%
103   \NewEnviron{#1rep}[1][]{%
104     \addtocounter{axp@rpcounter}{1}%
105     \begin{#1}[##1]\label{axp@r\roman{axp@rpcounter}}\BODY\end{#1}%
106     \global\toggletrue{axp@seenreptheorem}%
107     \global\expandafter\let\csname rplet\roman{axp@rpcounter}\endcsname\BODY%
108     \axp@writesection%
109     \immediate\write\axp@proofsfile{%
110       \noexpand\begin{axp@#1rp}[\noexpand\ref{axp@r\roman{axp@rpcounter}}]\@ifnotempty{##1}{\%
111         \noexpand\let\noexpand\label\noexpand\@gobble%
112         \expandafter\noexpand\csname rplet\roman{axp@rpcounter}\endcsname\noexpand\end{axp@#1rp}
113       }
114     }
115   }

```

### 2.5.3 Proof Environments

```

116 \let\axpold@proof\proof
117 \let\endaxpold@proof\endproof
118
119 \def\noproofinappendix{%
120   \global\togglefalse{axp@seenreptheorem}%
121 }
122
123 \newenvironment{appendixproof}
124   {%
125     \axp@writesection
126     \immediate\write\axp@proofsfile{%
127       \noexpand\begin{axpold@proof}%
128     }%
129     \VerbatimOut
130   }
131   {%
132     \endVerbatimOut
133     \immediate\write\axp@proofsfile{%
134       \noexpand\end{axpold@proof}%
135     }%
136     \noproofinappendix
137   }
138
139 \renewenvironment{proof}
140   {%
141     \iftoggle{axp@seenreptheorem}{%

```

```

142     \appendixproof
143   }{%
144     \axpold@proof
145   }%
146 }
147 {%
148   \iftoggle{axp@seenreptheorem}{%
149     \endappendixproof
150   }{%
151     \endaxpold@proof
152   }%
153 }
154
155 \let\inlineproof\axpold@proof
156 \let\endinlineproof\endaxpold@proof
157
158 \let\nestedproof\axpold@proof
159 \let\endnestedproof\endaxpold@proof

```

#### 2.5.4 Section Management

```

160 \def\axp@sectitle{}
161
162 \let\axpold@section\section
163 \def\section{\@ifstar\@section\@@section}
164 \def\@section#1{%
165   \global\edef\axp@sectitle{#1}%
166   \axpold@section*{#1}%
167   \addtocounter{axp@seccounter}{1}%
168   \label{axp@s\roman{axp@seccounter}}}%
169 }
170 \def\@@section#1{%
171   \global\edef\axp@sectitle{#1}%
172   \axpold@section{#1}%
173   \addtocounter{axp@seccounter}{1}%
174   \label{axp@s\roman{axp@seccounter}}}%
175 }
176
177 \newcommand{\nosectionappendix}{
178   \global\def\axp@sectitle{}%
179 }
180
181 \newcommand\axp@writesection{%
182   \ifx\axp@sectitle\empty
183   \else
184     \immediate\write\axp@proofsfile{\noexpand\def\noexpand\tmp{\noexpand\ref{axp@s\roman{axp@seccounter}}}%
185     (\axp@sectitle)}}%
186   \nosectionappendix
187   \fi
188 }

```

### 2.5.5 Append Compilation Mode

```

189 \let\axpold@bibliography\ bibliography
190 \renewcommand\ bibliography[1]{%
191   \defaultbibliography{#1}%
192   \axpold@bibliography{#1}%
193 }
194 \newcommand{\appendixrefname}{References for the Appendix}
195 \newcommand{\appendixbibliographystyle}{alpha}
196 \newcommand{\appendixbibliographyprelim}{}
197
198 \ifthenelse{\equal{\AXP@appendix}{append}}{
199   \AtEndDocument{%
200     \clearpage\onecolumn\appendix
201     \appendixbibliographyprelim
202     \begin{bibunit}[\appendixbibliographystyle]%
203       \immediate\closeout\axp@proofsfile\input{\jobname.axp}%
204       \renewcommand{\refname}{\appendixrefname}%
205       \putbib
206       \end{bibunit}%
207     }
208   }{}

```

### 2.5.6 Class-Specific Behavior

We conclude with some class-specific behavior.

\@getclass	We first use a little trick to store the current document class in macro \@currentclass,
\@getclass	from <a href="http://tex.stackexchange.com/a/43541">http://tex.stackexchange.com/a/43541</a> .
\@currentclass	<pre> 209 \def\@getclass#1.cls#2\relax{\def\@currentclass{#1}} 210 \def\@getclass{\expandafter\@getclass\@filelist\relax} 211 \@getclass </pre>

### ACM Document Classes

```

212 \ifdefined\acmttitlebox

```

\thebibliography	The section title of the bibliography is in uppercase in these document classes. In
\refname	addition, the \thebibliography macro hard-codes twice the section title, so we
\appendixrefname	un-hardcode it so that it can be modified in the appendix.

```

213 \patchcmd{\thebibliography}{References}{\protect\refname}{}{}
214 \patchcmd{\thebibliography}{References}{\protect\refname}{}{}
215 \newcommand{\refname}{REFERENCES}
216 \renewcommand{\appendixrefname}{REFERENCES FOR THE APPENDIX}

```

\section	These document classes redefine \section in a weird way, adding the possibility
\@section	of an optional argument. We redefine this in a sane way.

```

217 \def\section{\ifstar\@section{\dblarg{\@section}}}
218 \def\@section#1#2{%
219   \global\edef\axp@sectitle{#2}%
220   \axpold@section{#2}%

```

```

221     \addtocounter{axp@seccounter}{1}%
222     \label{axp@s\roman{axp@seccounter}}}%
223   }

224   \fi

```

## lipcs

```

225   \ifthenelse{\equal{\@currentclass}{lipics}}{

```

`\appendixbibliographyprelim` The default bibliography in the lipics document class formatting is not compatible with the alpha bibliography style. We fix this here.

```

226     \renewcommand{\appendixbibliographyprelim}{%
227       \global\let\oldbiblabel\@biblabel
228       \def\@biblabel{\hspace*{-2em}\small\oldbiblabel}%
229     }

230   }
231 }

```

## Change History

v1.0.0-dev

General: Initial version . . . . . 1

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
<code>\@@section</code> . . . . .	163, 170, <u>217</u>	<code>\@ifstar</code> . . . . . 163, 217
<code>\@acmttitlebox</code> . . . . .	57, <u>212</u>	<code>\@noligs</code> . . . . . 88
<code>\@biblabel</code> . . . . .	227, 228	<code>\@oparg</code> . . . . . 31
<code>\@bsphack</code> . . . . .	80	<code>\@section</code> . . . . . 163, 164, 217
<code>\@currentclass</code> . . . . .	<u>209</u> , 225	<code>\@upn</code> . . . . . 37
<code>\@dblarg</code> . . . . .	217	
<code>\@esphack</code> . . . . .	90	
<code>\@filelist</code> . . . . .	210	
<code>\@getcl@ss</code> . . . . .	<u>209</u>	
<code>\@getclass</code> . . . . .	<u>209</u>	
<code>\@gobble</code> . . . . .	111	
<code>\@ifnotempty</code> . . . . .	37, <u>110</u>	
<code>\@ifpackageloaded</code> . . . . .	7	
		<b>A</b>
		<code>\addtocounter</code> . . . . . 104, 167, 173, 221
		<code>\appendix</code> . . . . . 200
		<code>\appendixbibliographyprelim</code> . . . . .
		196, 201, <u>226</u>
		<code>\appendixbibliographystyle</code> . 195, 202
		<code>\appendixproof</code> . . . . . 52, <u>142</u>
		<code>appendixproof (environment)</code> . . . . . <u>48</u>



<code>\appendixrefname</code> . . . . .	194, 204, <a href="#">213</a>	<code>proofsketch</code> . . . . .	<a href="#">33</a>
<code>\AtEndDocument</code> . . . . .	199	<code>toappendix</code> . . . . .	<a href="#">54</a>
<code>\AXP@appendix</code> . . . . .	20, 22, 24, 27, 39, 198	<code>\equal</code> . . . . .	20, 22, 24, 39, 198, <a href="#">225</a>
<code>\axp@newtheoremrep</code> . . . . .	31, <a href="#">40</a> , 40, 98	<code>\errmessage</code> . . . . .	27
<code>\axp@proofsfile</code> . . . . .	71,	<code>\expandafter</code> . . . . .	
	72, 73, 86, 109, 126, 133, 184, 203		41, 42, 100, 101, 107, 112, 210
<code>\axp@sectitle</code> . . . . .		<b>F</b>	
	160, 165, 171, 178, 182, 185, 219	<code>\fi</code> . . . . .	68, 187, <a href="#">224</a>
<code>\axp@writesection</code> . . . . .	92, 108, 125, 181	<code>\FV@DefineTabOut</code> . . . . .	85
<code>\axpold@bibliography</code> . . . . .	189, 192	<code>\FV@DefineWhiteSpace</code> . . . . .	83
<code>\axpold@proof</code> . . . . .	75, 116, 144, 155, 158	<code>\FV@FontScanPrep</code> . . . . .	87
<code>\axpold@section</code> . . . . .		<code>\FV@ProcessLine</code> . . . . .	86
	77, 162, 166, 172, 184, 220	<code>\FV@Scan</code> . . . . .	89
<b>B</b>		<code>\FV@Space</code> . . . . .	84
<code>\begin</code> . . . . .	45, 105, 110, 127, 202	<code>\FV@UseKeyValues</code> . . . . .	82
<code>\begingroup</code> . . . . .	81	<code>\FVB@VerbatimOut</code> . . . . .	79
<code>\bibliography</code> . . . . .	189, 190	<code>\FVE@VerbatimOut</code> . . . . .	90
<code>\BODY</code> . . . . .	45, 105, 107	<b>G</b>	
<b>C</b>		<code>\global</code> . . . . .	106,
<code>\clearpage</code> . . . . .	200		107, 120, 165, 171, 178, 219, 227
<code>\closeout</code> . . . . .	203	<b>H</b>	
<code>\csname</code> . . . . .	41, 42, 100, 101, 107, 112	<code>\hfill</code> . . . . .	35
<b>D</b>		<code>\hspace</code> . . . . .	228
<code>\DeclareStringOption</code> . . . . .	18	<b>I</b>	
<code>\def</code> . . . . .	36, 40, 79, 84, 86,	<code>\ifdefined</code> . . . . .	57, 212
	90, 98, 119, 160, 163, 164, 170,	<code>\ifthenelse</code> . . . . .	20, 22, 24, 39, 198, 225
	178, 184, 209, 210, 217, 218, 228	<code>\iftoggle</code> . . . . .	141, 148
<code>\defaultbibliography</code> . . . . .	191	<code>\ifx</code> . . . . .	182
<b>E</b>		<code>\immediate</code> . . . . .	
<code>\edef</code> . . . . .	165, 171, 219		72, 73, 86, 109, 126, 133, 184, 203
<code>\else</code> . . . . .	183	<code>\inlineproof</code> . . . . .	48, 155
<code>\emph</code> . . . . .	34	<code>inlineproof (environment)</code> . . . . .	<a href="#">48</a>
<code>\empty</code> . . . . .	182	<code>\input</code> . . . . .	203
<code>\end</code> . . . . .	45, 105, 112, 134, 206	<code>\itshape</code> . . . . .	61
<code>\endappendixproof</code> . . . . .	53, 149	<b>J</b>	
<code>\endaxpold@proof</code> . . . . .	76, 117, 151, 156, 159	<code>\jobname</code> . . . . .	72, 203
<code>\endcsname</code> . . . . .	41, 42, 100, 101, 107, 112	<b>L</b>	
<code>\endgroup</code> . . . . .	90	<code>\label</code> . . . . .	105, 111, 168, 174, 222
<code>\endinlineproof</code> . . . . .	49, 156	<code>\let</code> . . . . .	9, 10, 41, 42, 48, 49, 50,
<code>\endnestedproof</code> . . . . .	51, 159		51, 52, 53, 55, 56, 75, 76, 77, 87,
<code>\endproof</code> . . . . .	10, 49, 51, 53, 76, 117		88, 100, 101, 107, 111, 116, 117,
<code>\endVerbatimOut</code> . . . . .	93, 132		155, 156, 158, 159, 162, 189, 227
environments:		<b>M</b>	
<code>appendixproof</code> . . . . .	<a href="#">48</a>	<code>\makeatletter</code> . . . . .	13, 74
<code>inlineproof</code> . . . . .	<a href="#">48</a>	<code>\message</code> . . . . .	21, 23, 25
<code>nestedproof</code> . . . . .	<a href="#">48</a>		

<b>N</b>		<code>\relax</code> . . . . . 55, 56, 87, 88, 209, 210
<code>\nestedproof</code> . . . . .	50, 158	<code>\renewcommand</code> . . . . . 190, 204, 216, 226
<code>nestedproof</code> (environment) . . . . .	48	<code>\renewenvironment</code> . . . . . 139
<code>\newcounter</code> . . . . .	95, 96	<code>\RequirePackage</code> . . . . . 1, 2, 3, 4, 5, 6, 12
<code>\NewEnviron</code> . . . . .	44, 103	<code>\roman</code> . . . . . 105,
<code>\newtheorem</code> . . . . .	43, 99, 102	107, 110, 112, 168, 174, 184, 222
<code>\newtheoremrep</code> . . . . .	30	
<code>\newtheoremstyle</code> . . . . .	58	<b>S</b>
<code>\newtoggle</code> . . . . .	94	<code>\scshape</code> . . . . . 63
<code>\newwrite</code> . . . . .	71	<code>\section</code> . . . . . 77, 162, 163, 217
<code>\noexpand</code> . . . . .	74, 75,	<code>\SetupKeyvalOptions</code> . . . . . 14
76, 77, 110, 111, 112, 127, 134, 184		<code>\small</code> . . . . . 228
<code>\noindent</code> . . . . .	34	<code>\space</code> . . . . . 84
<code>\noproofinappendix</code> . . . . .	54, 119, 136	
<code>\nosectionappendix</code> . . . . .	54, 177, 186	<b>T</b>
<b>O</b>		<code>\thebibliography</code> . . . . . 213
<code>\oldbiblabel</code> . . . . .	227, 228	<code>\theoremstyle</code> . . . . . 67
<code>\onecolumn</code> . . . . .	200	<code>\thmhead</code> . . . . . 36
<code>\openout</code> . . . . .	72	<code>\thmname</code> . . . . . 37
<b>P</b>		<code>\thmnote</code> . . . . . 38
<code>\patchcmd</code> . . . . .	213, 214	<code>\thmnumber</code> . . . . . 37
<code>\ProcessLocalKeyvalOptions</code> . . . . .	19	<code>\tmp</code> . . . . . 184
<code>\proof</code> . . . . .	9, 48, 50, 52, 75, 116	<code>toappendix</code> (environment) . . . . . 54
<code>proofsketch</code> (environment) . . . . .	33	<code>\togglefalse</code> . . . . . 120
<code>\protect</code> . . . . .	184, 213, 214	<code>\toggletrue</code> . . . . . 106
<code>\putbib</code> . . . . .	205	<b>U</b>
<b>Q</b>		<code>\undefined</code> . . . . . 9, 10, 41, 42, 100, 101
<code>\qed</code> . . . . .	35	<b>V</b>
<b>R</b>		<code>\VerbatimOut</code> . . . . . 92, 129
<code>\ref</code> . . . . .	110, 184	<code>\vskip</code> . . . . . 34, 35
<code>\refname</code> . . . . .	204, 213	<b>W</b>
		<code>\write</code> . . . . . 73, 86, 109, 126, 133, 184