

NCU18XH103F6SRB

● In Production

NCU18XH103F6SRB



There is also "narrow pitch paper taping" that halves the amount of packaging material used by halving the pocket pitch of taping. Please refer to the packaging information for details.

Applications

Unsuitable Applications	Please be sure to read and comply with these <u>"Precautions for use"</u> .
Specific Applications	<u>Automotive powertrain/safety equipment</u> Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.



Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

NCU18XH103F6SRB

Appearance & Shape



LW Size (in inch)	0.6x0.3inch
-------------------	-------------

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

NCU18XH103F6SRB

Specifications

Resistance (25℃)	10kΩ
Resistance Value Tolerance (at 25℃)	±1%
B-Constant (25/50℃)	3,380K
B-Constant (25/50℃) Tolerance	±1%
B-Constant(25/80℃)(Reference Value)	3,428K
B-Constant(25/85℃)(Reference Value)	3,434K
B-Constant(25/100℃)(Reference Value)	3,455K
Max. Voltage	5V
Maximum Operating Current (25℃)	0.1mA
Typical Dissipation Constant (25℃)	1mW/℃
Operating Temperature	-55 ~ 150℃
Shape	SMD
MSL	1

Glossary of NTC thermistors

Related documents (UL, RoHS, etc.)

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

NCU18XH103F6SRB

Features

1. Excellent solderability and high stability in environment
2. Excellent long time aging stability
3. High accuracy in resistance and B-constant
4. Flow / Reflow soldering possible
5. Same B-Constant in the same resistance in the three sizes (0603 size / 0402 size)
Easy to use smaller size in the circuits
6. Lead is not contained in the product.
7. UL/cULcertified product.(UL1434, File No. E137188)

References

Packaging	Specifications 	Standard Packing Quantity
RB	180mm Paper Tape (Pitch width 4mm)	4000
NB	180mm narrow pitch paper tape (Pitch width 2mm)	8000

Mass(Typ.)	
1 piece	0.0047g

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

NCU18XH103F6SRB

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of NCU18XH103F6SRB from the official website of Murata

<https://pim.murata.com/en-us/pim/details/?partNum=NCU18XH103F6SRB>


Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

NCU18XH103F6SRB


Product Data



Temperature Error Characteristics



Max. Voltage, Max. Operating Voltage/Current Reduction Curve



Resistance-Temperature Characteristics

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.