```
interface Moveable {
    void moveUp();
    void moveDown();
    void moveLeft();
    void moveRight();
}
class MoveablePoint implements Moveable {
    int x, y;
    int xSpeed, ySpeed;

    public MoveablePoint(int x, int y, int xSpeed, int ySpeed) {
        this.x = x;
        this.y = y;
        this.xSpeed = xSpeed;
        this.ySpeed = ySpeed;
    }

    @Override
    public void moveUp() {
        y += ySpeed;
    }

    @Override
    public void moveDown() {
        y -= ySpeed;
    }
```

Tên: Phạm Nguyễn Thiên Ân
MSSV: 1350070007
Lớp: HTTT2

```
@Override
public void moveLeft() {
    x -= xSpeed;
}
@Override
public void moveRight() {
    x += xSpeed;
}
public String toString() {
    return "(" + x + "," + y + ");
}
}

class MoveableCircle implements Moveable {
    int radius;
    MoveablePoint center;

    public MoveableCircle(MoveablePoint center, int
        radius) {
        this.center = center;
        this.radius = radius;
}
```

Được quét bằng CamScanner

```
@Override
public void moveUp() {
    center.moveUp();
}
@Override
public void moveDown() {
    center.moveDown();
}
@Override
public void moveLeft() {
    center.moveLeft();
}
@Override
public void moveRight() {
    center.moveRight();
}
public String toString() {
    return "Circle: " + center + ", r= " + radius;
}
}
```

Được quét bằng CamScanner

```
public class Main {
    public static void main (String [] args) {
        MoveablePoint p = new MoveablePoint (1,2,1,1);
        MoveableCircle c = new MoveableCircle (p, 5);

        c.moveRight();
        c.moveUp();

        System.out.println(c);
    }
}
```

Được quét bằng CamScanner