

Your grade: 90%

Your latest: 90% • Your highest: 90% • To pass you need at least 80%. We keep your highest score.

Next item →

1. The value of any state under an optimal policy is ____ the value of that state under a non-optimal policy.
[Select all that apply]

1 / 1 point

- ☐ Strictly greater than
☒ Greater than or equal to

✓ **Correct**
Correct! This follows from the policy improvement theorem.

- ☐ Strictly less than
☐ Less than or equal to

2. If a policy π is greedy with respect to its own value function v_π , then it is an optimal policy.

1 / 1 point

- ☒ True
☐ False

✓ **Correct**
Correct! If a policy is greedy with respect to its own value function, it follows from the policy improvement theorem and the Bellman optimality equation that it must be an optimal policy.

3. Let v_π be the state-value function for the policy π . Let $v_{\pi'}$ be the state-value function for the policy π' . Assume $v_\pi = v_{\pi'}$. Then this means that $\pi = \pi'$.

1 / 1 point

- ☐ True
☒ False

✓ **Correct**
Correct! For example, two policies might share the same value function, but differ due to random tie breaking.

4. What is the relationship between value iteration and policy iteration? [Select all that apply]

1 / 1 point

- ☐ Policy iteration is a special case of value iteration.
☒ Value iteration and policy iteration are both special cases of generalized policy iteration.

✓ **Correct**
Correct!

- ☐ Value iteration is a special case of policy iteration.

5. The word synchronous means "at the same time". The word asynchronous means "not at the same time". A dynamic programming algorithm is: [Select all that apply]

1 / 1 point

☒ Synchronous, if it systematically sweeps the entire state space at each iteration.

✓ Correct

Correct! Only algorithms that update every state exactly once at each iteration are synchronous.

☒ Asynchronous, if it updates some states more than others.

✓ Correct

Correct! Only algorithms that update every state exactly once at each iteration are synchronous.

☒ Asynchronous, if it does not update all states at each iteration.

✓ Correct

Correct! Only algorithms that update every state exactly once at each iteration are synchronous.

6. Policy iteration and value iteration, as described in chapter four, are synchronous.

1 / 1 point

☒ True

☐ False

✓ Correct

Correct! As described in lecture, policy iteration and value iteration update all states systematic sweeps.

7. Which of the following is true?

1 / 1 point

☐ Synchronous methods generally scale to large state spaces better than asynchronous methods.

☒ Asynchronous methods generally scale to large state spaces better than synchronous methods.

✓ Correct

Correct! Asynchronous methods can focus updates on more relevant states, and update less relevant states less often. If the state space is very large, asynchronous methods may still be able to achieve good performance whereas even just one synchronous sweep of the state space may be intractable.

8. Why are dynamic programming algorithms considered planning methods? [Select all that apply]

1 / 1 point

☒ They use a model to improve the policy.

✓ Correct


Correct! This is the definition of a planning method.

☐ They learn from trial and error interaction.

☐ They compute optimal value functions.

9. Consider the undiscounted, episodic MDP below. There are four actions possible in each state, $A = \{\text{up, down, right, left}\}$, which deterministically cause the corresponding state transitions, except that actions that would take the agent off the grid in fact leave the state unchanged. The right half of the figure shows the value of each state under the equiprobable random policy. If π is the equiprobable random policy, what is $q(11, \text{down})$?

0 / 1 point




- ☒ $q(11, \text{down}) = -14$
- ☐ $q(11, \text{down}) = -1$
- ☐ $q(11, \text{down}) = -15$
- ☐ $q(11, \text{down}) = 0$

✗ Incorrect

Incorrect. Moving down incurs a reward of -1 before reaching the terminal state, after which the episode is over.

10. Consider the undiscounted, episodic MDP below. There are four actions possible in each state, $A = \{\text{up, down, right, left}\}$, which deterministically cause the corresponding state transitions, except that actions that would take the agent off the grid in fact leave the state unchanged. The right half of the figure shows the value of each state under the equiprobable random policy. If π is the equiprobable random policy, what is $v(15)$?
Hint: Recall the Bellman equation $v(s) = \sum_a \pi(a|s) \sum_{s', r} p(s', r|s, a) [r + \gamma v(s')]$.

1 / 1 point



- ☐ $v(15) = -23$
- ☒ $v(15) = -24$
- ☐ $v(15) = -22$
- ☐ $v(15) = -25$
- ☐ $v(15) = -21$

✓ Correct

Correct! We can get this by solving for the unknown variable $v(15)$. Let's call this unknown x . We solve for x in the equation $x = 1/4(-21) + 3/4(-1 + x)$. The first term corresponds to transitioning to state 13. The second term corresponds to taking one of the other three actions, incurring a reward of -1 and staying in state x .