

Table 1: Battery dataset summary grouped by electrode chemistry.

Name	Number of Cells	Positive Electrode	Negative Electrode	Nominal Capacity (Ah)	Temperature (°C)
HUST (18650 cylindrical)	77	LFP lithium-iron-phosphate	Graphite	1.1	30
MATR (18650)	169	LFP LiFePO ₄	Graphite	1.1	30
CALB	27	NMC	Graphite	58	0, 25, 35, 45
ISU (502030 Li-polymer)	240	NMC lithium nickel manganese cobalt oxide	Graphite	0.25	30
MICH_EXP (pouch)	12	NMC NMC111	Graphite	5.0	−5, 25, 45
MICH	40	NMC NMC111	Graphite	2.36	25, 45
RWTH	48	NMC (lithium nickel manganese cobalt oxide)	Carbon	3	25
SDU (18650)	86	NMC	Graphite	2.4	25
STANDFORD (18650)	41	NMC LiNi _{0.5} Mn _{0.3} Co _{0.2} O ₂	Graphite	0.24	30
STANDFORD 2 (18650)	181	NMC LiNi _{0.5} Mn _{0.3} Co _{0.2} O ₂	Graphite	0.24	30
XJTU	23	NMC LiNi _{0.5} Co _{0.2} Mn _{0.3} O ₂	Graphite	2	20
TONGJI (18650 cylindrical)	108	NCA / NMC Li _{0.86} Ni _{0.86} Co _{0.11} Al _{0.03} O ₂ / Li _{0.84} (Ni _{0.83} Co _{0.11} Mn _{0.07})O ₂ / NCA + NMC blend	Graphite / Graphite + 2 wt.% Si	2.5 and 3.5	multiple
CALCE	13	LCO LiCoO ₂	Graphite	1.1	25
HNEI	—	LCO + NMC LiCoO ₂ and LiNi _{0.4} Co _{0.4} Mn _{0.2} O ₂	Graphite	2.8	25
UL (18650)	10	LCO + NMC LiCoO ₂ and LiNi _{0.4} Co _{0.4} Mn _{0.2} O ₂	Graphite	3.4	23
SNL (18650)	52	LFP + NCA + NMC LiFePO ₄ / LiNi _{0.81} Co _{0.14} Al _{0.05} O ₂ / LiNi _{0.84} Mn _{0.06} Co _{0.1} O ₂	Graphite	1.1 3.2 3.0	15, 25, 35
NA-ION (18650)	31	Na-ion	—	1.0	25
ZN-COIN	95	Zn-MnO₂ manganese dioxide (MnO ₂) cathode	Zinc	10	25