




VLAN 10
10.0.0.10



VLAN 20
20.0.0.10



VLAN 10
10.0.0.20



VLAN 20
20.0.0.20



```
SW1
*Sep 23 09:30:15.458: %SYS-5-CONFIG_I: Configured from console by console
SW1#sh vl

VLAN Name                Status    Ports
-----
1    default                active    Et0/3
10   HR                       active    Et0/0
20   SALES                    active    Et0/1
1002 fddi-default            act/unsup
1003 token-ring-default      act/unsup
1004 fddinet-default         act/unsup
1005 trnet-default           act/unsup

VLAN Type  SAID      MTU    Parent RingNo BridgeNo Stp  BrdgMode Trans1 Trans2
-----
1    enet  100001  1500    -     -     -     -     -     0      0
10   enet  100010  1500    -     -     -     -     -     0      0
20   enet  100020  1500    -     -     -     -     -     0      0
1002 fddi  101002  1500    -     -     -     -     -     0      0
1003 tr   101003  1500    -     -     -     -     -     0      0
1004 fdnet 101004  1500    -     -     -     ieee -     0      0
1005 trnet 101005  1500    -     -     -     ibm  -     0      0

Remote SPAN VLANs
-----

Primary Secondary Type      Ports
-----

SW1#
SW1#sh int trunk

Port      Mode          Encapsulation  Status      Native vlan
Et0/2     on            802.1q         trunking    1

Port      Vlans allowed on trunk
Et0/2     1-4094

Port      Vlans allowed and active in management domain
Et0/2     1,10,20

Port      Vlans in spanning tree forwarding state and not pruned
Et0/2     1,10,20
SW1#
*Sep 23 09:31:01.932: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
SW1#
```

```
Putty (inactive)
1004 fdnet 101004  1500    -     -     -     ieee -     0      0
1005 trnet 101005  1500    -     -     -     ibm  -     0      0

Remote SPAN VLANs
-----

Primary Secondary Type      Ports
-----

SW2#conf t
Enter configuration commands, one per line. End with CNTL/Z.
SW2(config)#switchport trunk encapsulation dot1q
SW2(config)#
^
% Invalid input detected at '^' marker.

SW2(config)#int e0/2
SW2(config-if)#switchport trunk encapsulation dot1q
SW2(config-if)#switchport mode trunk
SW2(config-if)#exit
SW2(config)#
SW2(config)#
SW2(config)#
SW2(config)#
SW2(config)#
SW2(config)#exit
SW2#
SW2#
SW2#
SW2#
SW2#
*Sep 23 09:33:56.720: %SYS-5-CONFIG_I: Configured from console by console
SW2#sh int tr

Port      Mode          Encapsulation  Status      Native vlan
Et0/2     on            802.1q         trunking    1

Port      Vlans allowed on trunk
Et0/2     1-4094

Port      Vlans allowed and active in management domain
Et0/2     1,10,20

Port      Vlans in spanning tree forwarding state and not pruned
Et0/2     1,10,20
SW2#
```