

C# Basics

Methods

Introduction to Methods

- **Methods** can be used to break a complex program into small, manageable pieces
 - This approach is known as **divide and conquer**
 - In general terms, breaking down a program to smaller units of code, such as methods, is known as **modularization**
- Two types of methods are:
 - A **void** method simply executes a group of statements and then terminates
 - A **value-returning** method returns a value to the statement that called it


The Method Header

- A method header has the following parts :
 - **Access modifier:** keywords that defines the access control
 - private: a private method can be called only by code inside the same class as the method
 - public: a public method can be called by code that is outside the class.
 - **Return type:** specifies whether or not a method returns a value
 - **Method name:** the identifier of the method; must be unique in a given program. Use Pascal case
 - **Parentheses:** A method's name is always followed by a pair of parentheses

Access modifier	Return type	Method name	Parentheses
↓	↓	↓	↙
private	void	DisplayMessage	()
{			
MessageBox.Show("This is the DisplayMessage method.");			
}			

Calling a Method

- A method executes when it is called
- Event handlers are called when specific events take place. Yet, methods are executed by **method call statements**.
- A method call statement is the name of the method followed by a pair of parentheses. For example,
- `DisplayMessage();`



```
private void goButton_Click(object sender, EventArgs e)
{
    MessageBox.Show("This is the goButton_Click method.");
    DisplayMessage();
}

private DisplayMessage()
{
    MessageBox.Show("This is the DisplayMessage method.");
}
```

Passing Arguments to Methods

- An **argument** is any piece of data that is passed into a method when the method is called
 - In the following, the statement calls the `MessageBox.Show` method and passes the string “Hello” as an argument:

```
MessageBox.Show("Hello");
```

- A **parameter** is a variable that receives an argument that is passed into a method
 - In the following, *value* is an `int` parameter:

```
private void DisplayValue(int value)
{
    MessageBox.Show(value.ToString());
}
```

- An argument's data type must be assignment compatible with the receiving parameter's data type

Methods Parameters

- Some functions have no parameters

```
public void CountUpdates() { ... }
```

- Others can have several parameters

- e.g., float f0 and float f1 below

```
public void PrintSum( float f0, float f1 ) {  
    print( f0 + f1 );  
}
```

- Parameters define the type and number of *arguments* that must be passed in when the function is called

```
PrintSum( 4f, 10.5f ); // Prints: "14.5"
```

The params Keyword

- params can be used to accept a variable number of similarly-typed parameters or an array of parameters

```
public float Sum( params float[] nums ) {  
    float total = 0;  
    foreach (float f in nums) {  
        total += f;  
    }  
    return( total );  
}  
  
void Awake() {  
    print( Sum( 1f ) );           // Prints: "1f"  
    print( Sum( 1f, 2f ) );      // Prints: "3f"  
    print( Sum( 1f, 2f, 3f ) );  // Prints: "6f"  
    print( Sum( 1f, 2f, 3f, 4f ) ); // Prints: "10f"  
}
```

- An array can also be passed into a params parameter

```
print( Sum( new float[] { 1f, 3.14f } ) ); // Prints: "4.14f"
```

Named Arguments

- C# allows you to specify which parameter an argument should be passed into. The syntax is:

parameterName : value

- An argument that is written using this syntax is known as a **named argument**

```
private void showButton_Click(object sender, EventArgs e)
{
    showName(lastName : "Smith", firstName : "Suzanne");
}
```

```
private void ShowName(string firstName, string lastName)
{
    MessageBox.Show(firstName + " " + lastNmae);
}
```

- Notice that you get the same result if the call statement is:

```
showName("Suzanne", "Smith");
```


Default Arguments

- C# allows you to provide a **default argument** for a method parameter

```
private void ShowTax(decimal price, decimal taxRate = 0.07m)
{
    decimal tax = price * taxRate;
}
```

- The value of taxRate is defaulted to 0.07m. You can simply call the method by passing only the price. Parameters are optional when a default value is specified as part of a declaration.

```
showTax(100.0m);
```

- You can also override the default argument

```
showTax(100.0m, 0.08m);
```

Named Arguments and Optional Parameters

```
public void DoSomething(int x = 0, int y = 0) {
```

```
DoSomething();  
DoSomething(x: 1);  
DoSomething(y: 1);  
DoSomething(x: 1, y: 2);  
DoSomething(y: 2, x: 1);
```

Passing Arguments by Reference

- A **reference parameter** is a special type of parameter that does not receive a copy of the argument's value
- It becomes a **reference** to the argument that was passed into it
- When an argument is passed by reference to a method, the method can change the value of the argument in the calling part of the program
- In C#, you declare a reference parameter by writing the **ref** keyword before the parameter variable's data type

```
private void SetToZero(ref int number)
{
    number = 0;
}
```

- To call a method that has a reference parameter, you also use the keyword **ref** before the argument

```
int myVar = 99;
SetToZero(ref myVar);
```

The Return Statement

- There must be a **return** statement inside the method which is usually the last statement of the method. This return statement is used to return a value to the statement that called the method. For example,

```
private int sum(int num1, int num2)
{
    return num1 + num2;
}
```

- Notice that the returned value and the method's type must match
 - In the above example, the method is an int method, so it can only return int value

Returning Values

- Many methods return void

```
void Update() { ... }  
public void CountUpdates() { ... }
```

- It's possible to return a single value from a method

- The type of that value is the type of the method

```
public float Sum( float f0, float f1 ) {  
    float f01 = f0 + f1;  
    return( f01 );           // Returns the float f01  
}  
  
void Update() {  
    float s = Sum( 3f, 0.14159f );  
    print( s );              // Prints: "3.14159"  
}
```

- A method can be declared with *any* return type!

```
public GameObject FindTheGameObject() { ... }
```

Returning Values

- Sometimes, you want to use return even when the return type is void

```
public List<GameObject> reallyLongList; // A List of many GObjs
public void MoveByName( string name, Vector3 loc ) {
    foreach (GameObject go in reallyLongList) {
        if (go.name == name) {
            go.transform.position = loc;
            return; // Returns to avoid looping over the whole List
        }
    }
}
void Awake() {
    MoveByName( "Archon", Vector3.zero );
}
```

- If "Phil" is the first GameObject in the List, returning could save lots of time!

Method Overloading

- The same function name can be defined several times with different parameters
- This is called *function overloading*

```
public float Sum( float f0, float f1 ) {  
    return( f0 + f1 );  
}  
  
public Vector3 Sum( Vector3 v0, Vector3 v1 ) {  
    return( v0 + v1 );  
}  
  
public Color Sum( Color c0, Color c1 ) {  
    float r, g, b;  
    r = Mathf.Min( c0.r + c1.r, 1f ); // Limits r to less than 1  
    g = Mathf.Min( c0.g + c1.g, 1f );  
    b = Mathf.Min( c0.b + c1.b, 1f ); // Because Color values  
    a = Mathf.Min( c0.a + c1.a, 1f ); // are between 0f and 1f  
    return( new Color( r, g, b, a ) );  
}
```

Methods Overloading

- Method signature: name and parameter types, number, and order (not the name, return type)

```
int DoSomething (int a, int b) {}
```

The signature is `DoSomething(int, int)`

- Overloading methods: have multiple methods with the same name, as long as the signatures are different

```
void Foo (int x) {...}
```

```
void Foo (double x) {...}
```

```
void Foo (int x, float y) {...}
```

```
void Foo (float x, int y) {...}
```

```
float Foo (int x) {...} // error
```


Naming Conventions

- Functions should always be named with CamelCaps
- Function names should always start with a capital letter

```
void Awake() { ... }  
void Start() { ... }  
public void PrintSum( float f0, float f1 ) { ... }  
public float Sum( float f0, float f1 ) { ... }  
public void MoveByName( string name, Vector3 loc ) { ... }
```

- Declaring Method Inside a Class - Methods usually belong to a class