

LT2 Device Specification

Industrial Tag with a Rechargeable Battery

Overview

The LT2 is a **rechargeable LiPo battery powered Tag** device to be mounted on objects that require tracking or navigation within a Ultra-Wideband / Bluetooth Real-Time Location System (RTLS). Its robust design, flexibility and adaptability makes it **ideal for tracking and navigation applications in an industrial environment.**



Figure 1: Front and back views of the LT2 device

Key Features

- Supports both TDoA (Time Difference of Arrival) as well as TWR (Two-Way Ranging) location measurement techniques. Location accuracy sub-0.5m or better.
- Supports both UWB channel 5 (6.5 GHz) and channel 9 (8 GHz) with UWB RF compliance compatible with FCC, Japan's ARIB and ETSI of the CE.
- With Low Noise Amplifier, the device provides superior UWB range coverage.
- Integrated Motion sensor: 3-axis accelerometer.
- One multi-function button.
- RGB front LEDs for status indication.
- Buzzer for alarm functions.
- Firmware update over Bluetooth and USB.
- Free software configuration and visualization tools (for Android, iOS, Windows, macOS and Linux).
- An open [online documentation](#) and [community forum](#).

Electrical Parameters

Parameter	Value
Certification	FCC, CE, ARIB (Japan)
USB (power and data)	5VDC 500mA max
Battery	LiPo 3.7VDC 600mAh
Battery lifetime	UL-TDOA: 9 months to 3 years depending on the update rate TWR: 2 months to 2 years depending on the update rate
Operating temperature (without battery) ¹	-40°C - +85°C
Operating temperature (with battery) ²	-20°C - +45°C
Operating temperature (charging) ³	0°C ~ +40°C
UWB supported channels	Channel 5 (6240–6739.2 MHz, CF=6489.6 MHz) Channel 9 (7738–8237.2 MHz, CF=7987.2 MHz, FiRa compatible)
UWB transmit powers	FCC/ARIB/ETSI: -41.3 dBm/MHz max
Bluetooth	2.4 GHz, +8dB

Mechanical Parameters

Parameter	Value
Size	W=68 x H=50 x D=18 mm
Weight	38g
Material	ABS
Color	Dark Gray
IP rating	IP66 (enclosed with 4 screws)

Mounting	2 screws
----------	----------

Safety Instructions

- Do not expose devices to water or moisture while in operation.
- Do not expose devices to excessive heat from any source. The product is designed for reliable operation at industrial temperature¹. If the product is equipped with a battery, it can be at normal operating temperature². The temperature³, while the battery is charging, is internally protected (if the temperature is outside of the range, the battery charging will not start or will be postponed).

Warnings

- This product shall be connected only to the USB with a minimum current supply of 0.5 A.
- Any external power supply used with this product shall comply with relevant regulations and standards applicable in the country of intended use.
- This product should be operated in a ventilated environment with a non-condensing environment and should not be covered when being operated.
- There are no user-serviceable parts inside the product, and opening the unit will likely damage the product and invalidate the warranty.
- The cables and connectors of all peripherals used with this product must have adequate insulation to meet relevant safety requirements.

Order Information

- Part number: LR-LT2A1
- Custom code: HS 8517.69.9000
- Packaging: TBDpcs in paper box, 70 cm x 53 cm x 22 cm 43g

About Us

At LEAPS, we specialize in delivering cutting-edge UWB-based localization technology to help businesses and people locate new values.

Our unique technology and innovative solutions created in close cooperation with leading UWB chip producer Qorvo, coupled with a comprehensive range of products, provide unmatched performance and versatility. From tags and anchors to custom-designed systems, our UWB hardware and software is built to meet the specific needs of diverse industries.

Contact Us

LEAPS s.r.o.

Hodoninska 1,
141 00, Prague 4,
Czech Republic, EU
Phone: +420 222 966 953

Web: <https://www.leapslabs.com>

E-mail: sales@leapslabs.com