

LT4 Device Specification

Wearable Tag with a Rechargeable Battery

Overview

The LT4 is a **rechargeable LiPo battery powered** device to be used as a wearable **Tag** where tracking or navigation of persons within a Ultra-Wideband / Bluetooth Real-Time Location System (RTLS) is required. Practical and robust design allows easy tracking of your personnel using wristbands or lanyards in **industrial environments**.




Figure 1: Front and back views of the LT4 device

Key Features

- Supports both TDoA (Time Difference of Arrival) as well as TWR (Two-Way Ranging) location measurement techniques. Location accuracy sub-0.5m or better.
- Supports both UWB channel 5 (6.5 GHz) and channel 9 (8 GHz) with UWB RF compliance compatible with FCC, Japan's ARIB and ETSI of the CE.
- With Low Noise Amplifier, the device provides superior UWB range coverage.
- Universal NATO strap attachment.
- Integrated Motion sensor: 3-axis accelerometer.
- One multi-function button.
- RGB front LEDs for status indication.
- Buzzer for alarm functions.
- Firmware update over Bluetooth and USB.
- Free software configuration and visualization tools (for Android, iOS, Windows, macOS and Linux).
- An open [online documentation](#) and [community forum](#).

Electrical Parameters

Parameter	Value
Certification	FCC, CE, ARIB (Japan)
USB (power and data)	5VDC 500mA max
Battery	LiPo 3.7VDC 600mAh
Battery lifetime	UL-TDOA: 1-5 years depending on the update rate TWR: 3 months - 3 years depending on the update rate
Operating temperature (without battery) ¹	-40°C - +85°C
Operating temperature (with battery) ²	-20°C - +45°C
Operating temperature (charging) ³	0°C ~ +40°C
UWB supported channels	Channel 5 (6240-6739.2 MHz, CF=6489.6 MHz) Channel 9 (7738-8237.2 MHz, CF=7987.2 MHz, FiRa compatible)
UWB transmit powers	FCC/ARIB/ETSI: -41.3 dBm/MHz max
Bluetooth	2.4 GHz, +8dB

Mechanical Parameters

Parameter	Value
Size	W=43 x H=48 x D=22 mm
Weight	With battery: 38g
Color	White
IP rating	IP66
Mounting	Universal NATO strap

Safety Instructions

- Do not expose devices to water or moisture while in operation.
- Do not expose devices to excessive heat from any source. The product is designed for reliable operation at industrial temperature¹. If the product is equipped with a battery, it can be at normal operating temperature². The temperature³, while the battery is charging, is internally protected (if the temperature is outside of the range, the battery charging will not start or will be postponed).

Warnings

- This product shall be connected only to the USB with a minimum current supply of 0.5 A.
- Any external power supply used with this product shall comply with relevant regulations and standards applicable in the country of intended use.
- This product should be operated in a ventilated environment with a non-condensing environment and should not be covered when being operated.
- There are no user-serviceable parts inside the product, and opening the unit will likely damage the product and invalidate the warranty.
- The cables and connectors of all peripherals used with this product must have adequate insulation to meet relevant safety requirements.

Order Information

- Part number: LR-LT4A1
- Custom code: HS 8517.69.9000
- Packaging: TBDpcs in paper box, TBD cm x TBD cm x TBD cm TBDkg

About Us

At LEAPS, we specialize in delivering cutting-edge UWB-based localization technology to help businesses and people locate new values.

Our unique technology and innovative solutions created in close cooperation with leading UWB chip producer Qorvo, coupled with a comprehensive range

of products, provide unmatched performance and versatility. From tags and anchors to custom-designed systems, our UWB hardware and software is built to meet the specific needs of diverse industries.

Contact Us

LEAPS s.r.o.

Hodoninska 1,

141 00, Prague 4,

Czech Republic, EU

Phone: +420 222 966 953

Web: <https://www.leapslabs.com>

E-mail: sales@leapslabs.com