


# CMPT 280

## Tutorial: $m$ -ary Trees

Mark G. Eramian

University of Saskatchewan

## General/ $m$ -ary Trees




- A general tree is one in which each node may have any number of subtrees.
- An  $m$ -ary tree is one in which each node may have at most  $m$  subtrees.
- Each node must have a container to store subtrees (or at least their roots).

# Example $m$ -ary Trees

## Logical Circuit


A logical circuit can be represented by an  $m$ -ary tree:



## Example $m$ -ary Trees

### Genealogical Descendent Chart

This tree represents (some of) the descendants of Balbo Baggins, including his great-grandson, Bilbo Baggins, the well-known character from the works of J. R. R. Tolkein.




# Implementing $m$ -ary Trees

- In linked trees, each node must somehow store the references to its child nodes.
- We now examine two ways of implementing this storage.

# General/ $m$ -ary Trees

What kind of container should be used to store the subtrees?

1. An array ( $N = \text{null}$ )




**Pros:** fast access to subtrees via indexing (time complexity?)

**Cons:** predetermined limit on number of children, potentially stores many null references (but not problematic for small  $m$ )

# General/ $m$ -ary Trees

What kind of container should be used to store the subtrees?

2. A linked list ( $N = \text{null}$ )



**Pros:** no predetermined limit on the number of subtrees

**Cons:** slower access to specific children (time complexity?)

## *m*-ary Trees in lib280

- The implementation of *m*-ary trees in lib280 is the class `BasicMAryTree280<I>`. It can be found in the `lib280.tree` package.
- Nodes are of type `MAryNode280<I>`.
- Each node contains an **array** that stores its children.
- The capacity of these arrays are chosen when calling the constructor of the tree:

```
1 // Create a tree containing with a single root node containing the string
2 // "Balbo Baggins" where each node can have up to six children.
3
4 BasicMAryTree<String> T = new BasicMAryTree<String>("Balbo Baggins", 6);
```



## *m*-ary Trees in lib280

Important methods in BasicMArrayTree280<I>:

**rootItem():** get the item at the root of the tree

**rootLastNonEmptyChild():** returns the integer index<sup>1</sup> of the last non-empty subtree of the root node.

**rootSubtree(i):** returns the BasicMArrayTree280 object that is the *i*-th subtree<sup>1</sup> of the root.


**setRootSubtree(T, i):** sets the *i*-th subtree<sup>1</sup> of the root node to be the BasicMArrayTree280 tree *T*.

And of course, there are many other methods that you can look at on your own.

<sup>1</sup>**Important note:** the index here starts at 1! If a tree's nodes can have six children then the first such child is the root of the subtree at index 1, and the last one is the subtree at index 6.

## *m*-ary Trees in lib280

Here's how we could construct the genealogical descendent tree for the descendants of Mungo Baggins in the Baggins family tree:



```
1 BasicMaryTree<String> T = new BasicMaryTree<String>("Mungo", 5);
2 T.setRootSubtree(new BasicMaryTree<String>("Bungo", 5), 1);
3 T.setRootSubtree(new BasicMaryTree<String>("Belba", 5), 2);
4 T.setRootSubtree(new BasicMaryTree<String>("Longo", 5), 3);
5 T.setRootSubtree(new BasicMaryTree<String>("Linda", 5), 4);
6 T.setRootSubtree(new BasicMaryTree<String>("Bingo", 5), 5);
7 BasicMaryTree<String> Bungo = T.rootSubtree(1);
8 Bungo.setRootSubtree(new BasicMaryTree<String>("Bilbo Baggins", 5), 1);
```

# Recursive Traversal of $m$ -ary Trees

Basic Idea:

```
1 Algorithm treeTraverse(curNode)
2 A recursive traversal of the tree that prints out the
3 contents of each node.
4
5 Parameters:
6 curNode: reference to the current node in the traversal.
7
8 print curNode.item()
9
10 // for all the non-empty subtrees of curNode...
11 for each child i of curNode
12     treeTraverse(curNode.getChildNode(i))
```

# Recursive Traversal of $m$ -ary Trees

## Exercise

- Implement the algorithm on the previous slide for the `BasicMAryTree280<I>` class.
  - Public method to initiate traversal
  - Protected/private "helper" method for the actual recursion (rationale: algorithm requires node as parameter, but we do not want the nature of the nodes to be exposed in the public interface!)
- Trace through the implementation using the tree on slide 4 as input.