



Ask anything





To create a single-file archive of a MongoDB database using `mongodump`, you must include the `--archive` flag followed by your target filename. By default, `mongodump` outputs backups as a directory tree of individual BSON files, but the archive flag packages everything cleanly into a single file. 🟢 MongoDB +2

1. Basic Local Archive Command

To create an archive of a specific database running on your local machine (`localhost:27017`), use this standard syntax:

bash

```
mongodump --db=your_database_name --archive=my_database.archive
```

Use code with caution.



- Replace `your_database_name` with your actual database name.
- Replace `my_database.archive` with your preferred output file name. 🟢 MongoDB +1

2. Compressed Local Archive Command (Recommended)

Database archives can become quite large. It is highly recommended to combine the `--archive` flag with the `--gzip` flag to automatically compress the contents on the

Ask anything





If you are connecting to a remote cluster, a replica set, or MongoDB Atlas, use a connection URI string to authenticate your terminal session:  BMC Software +2



bash

```
mongodump --uri="mongodb+srv://<username>:<password>@your-cluster.mongodb.net/you
```

Use code with caution.



4. Archive to Standard Output (Streaming)

If you omit the filename after the `--archive` flag, `mongodump` streams the archive directly to standard output (`stdout`). This is exceptionally useful for piping data directly into another utility (like `mongorestore`) without writing anything to your local disk:  MongoDB +4

bash

```
mongodump --db=source_db --archive --gzip | mongorestore --nsFrom="source_db.*" .
```

Use code with caution.



Ask anything





16 sites

mongodump - Database Tools - MongoDB Docs

An archive file is a single-file alternative to multiple BSON files. * To output the dump to an archive file, run mongodump with t...



MongoDB

mongodump Examples - Database Tools - MongoDB Docs

mongodump --db=test --collection=records. Use mongodump with a Database and Exclude Specified Collections. The following operation...



MongoDB

Back Up and Restore with MongoDB Tools - Database Manual

Output Format mongorestore and mongodump can output data to an archive file, which is a single-file alternative to multiple BSON f...



MongoDB

Show all

want it in .zip or tar.gz

Ask anything





bash

```
mongodump --db=your_database_name --archive | gzip > my_database.tar.gz
```

Use code with caution.

Alternatively, if you want to back up a specific **remote database / Atlas cluster** to a `.tar.gz` file:

bash

```
mongodump --uri="mongodb+srv://<username>:<password>@cluster.net/db_name" --arch:
```

Use code with caution.

Option 2: Create a `.zip` Archive

The `mongodump` command cannot stream output directly into the standard `zip` utility. For a `.zip` file, you must perform the backup in two distinct steps:

1. Generate the backup folder:

Ask anything





```
zip -r my_database.zip ./mongo_dump_dir
```

Use code with caution.



3. (Optional) Clean up the original folder:

```
bash
```

```
rm -rf ./mongo_dump_dir
```

Use code with caution.

How to Restore These Files Later

When you need to restore your database, use the following commands depending on how you stored the backup:

- For `.tar.gz` archives:

```
bash
```

Ask anything





Use code with caution.



If you are running into specific issues, let me know:

- What **Operating System** you are using (Linux, macOS, Windows)
- Whether you need to include **specific collections** or the **entire database cluster**
- If you need to restore this directly to a **different server environment**



Ask anything

