

Uncovering the topology of the temporal region in Alzheimer's disease.

Philip Hartout

November 24, 2020

Alzheimer's disease



Alzheimer's disease: 🧠

- Nearly 40 million people live with AD
- Cost in US alone \$ 2 trillion by 2030
- Among leading causes of death in EU

Alzheimer's disease

Alzheimer's disease: 🧠

- Nearly 40 million people live with AD
- Cost in US alone \$ 2 trillion by 2030
- Among leading causes of death in EU




Alzheimer's disease

Alzheimer's disease: 🧠

- Nearly 40 million people live with AD
- Cost in US alone \$ 2 trillion by 2030
- Among leading causes of death in EU


Topology: 🍩 ☕



Alzheimer's disease

Alzheimer's disease: 🧠

- Nearly 40 million people live with AD
- Cost in US alone \$ 2 trillion by 2030
- Among leading causes of death in EU




Topology: 🍩 ☕

- Concerned with “properties of a geometric object that are preserved under **continuous deformations**, such as [...] crumpling.”

Alzheimer's disease

Alzheimer's disease: 🧠

- Nearly 40 million people live with AD
- Cost in US alone \$ 2 trillion by 2030
- Among leading causes of death in EU




Topology: 🍩 ☕

- Concerned with “properties of a geometric object that are preserved under **continuous deformations**, such as [...] crumpling.”
- Recently, *persistent homology* has emerged to quantify (differences in) the shape of data.

Alzheimer's disease

Alzheimer's disease: 🧠

- Nearly 40 million people live with AD
- Cost in US alone \$ 2 trillion by 2030
- Among leading causes of death in EU



Topology: 🍩 ☕

- Concerned with “properties of a geometric object that are preserved under **continuous deformations**, such as [...] crumpling.”
- Recently, *persistent homology* has emerged to quantify (differences in) the shape of data.
- **How can we apply persistent homology to quantify changes in shape due to Alzheimer's disease?**

1. Diagnosis (classification)


1. Diagnosis (classification)
2. Subtype identification

1. Diagnosis (classification)
2. Subtype identification
3. Progression & forecasting

1. Diagnosis (classification)
2. Subtype identification
3. Progression & forecasting

→ Some findings in these directions will be presented today


Raw T1-weighted sMRI








Analysis setting



Analysis setting



Analysis setting




Figure 2: AUCPRC on each patch, achieved using a model described in earlier work. Chosen patch for analyses is boxed in red (patch with highest accuracy).

- Computed the cubical filtration to obtain persistence image for each patch

I - Diagnosis prediction

- Computed the cubical filtration to obtain persistence image for each patch
- Simple CNN to classify AD/CN patients.

I - Diagnosis prediction

- Computed the cubical filtration to obtain persistence image for each patch
- Simple CNN to classify AD/CN patients.
- Use same partition as NeurIPS submission, train ANN 3 times on each partition

I - Persistent homology




Figure 3: CN




Figure 4: MCI







Figure 5: AD

I - Diagnosis prediction - Persistence Images



I - Diagnosis prediction - Persistence Images





Figure 6: Columns: hom. dimension (0,1,2); Row: Diagnostic category (CN top, AD bottom).

I - Diagnosis prediction - Network architecture



Performance metric	Model trained on PIs from patches
Training accuracy	0.81 ± 0.01
Validation accuracy	0.78 ± 0.03
Precision	0.81 ± 0.04
Recall	0.77 ± 0.03
AUC	0.85 ± 0.03

Table 1: Performance metrics of the model.

I - Diagnosis prediction - Performance

Performance metric	Model trained on PIs from patches
Training accuracy	0.81 ± 0.01
Validation accuracy	0.78 ± 0.03
Precision	0.81 ± 0.04
Recall	0.77 ± 0.03
AUC	0.85 ± 0.03

Table 1: Performance metrics of the model.

→ using a normal CPU, training takes 1 minute!

II - Distance analysis among patients in CN, MCI & AD

Question: How topologically heterogenous is the data?

II - Distance analysis among patients in CN, MCI & AD

Question: How topologically heterogenous is the data?

- Compute a persistence landscape (allows for statistical analysis)

II - Distance analysis among patients in CN, MCI & AD

Question: How topologically heterogenous is the data?

- Compute a persistence landscape (allows for statistical analysis)
- Compute a median persistence landscape with one layer for each category (CN, MCI, AD)

II - Distance analysis among patients in CN, MCI & AD

Question: How topologically heterogenous is the data?

- Compute a persistence landscape (allows for statistical analysis)
- Compute a median persistence landscape with one layer for each category (CN, MCI, AD)
- Compute L^1 norm from median landscape for each image within category

II - Distance analysis among patients in CN, MCI & AD

Median persistence landscape.




Figure 7: CN




Figure 8: MCI




Figure 9: AD

II - Distance analysis among patients in CN, MCI & AD

Question: How topologically heterogenous is the data?

	Mean	Median	Standard deviation	Q3	Max	Skewness
CN H_0	2.16	2.00	0.78	2.50	7.41	1.78
CN H_1	2.61	2.27	1.17	2.93	9.47	1.92
CN H_2	2.38	2.23	0.88	2.79	7.19	1.39
MCI H_0	2.24	2.04	0.82	2.55	6.21	1.71
MCI H_1	2.57	2.19	1.29	2.80	11.87	2.57
MCI H_2	2.40	2.27	0.83	2.82	6.55	1.18
AD H_0	2.40	2.18	0.96	2.77	7.77	1.97
AD H_1	2.47	2.13	1.15	2.77	9.28	2.10
AD H_2	2.36	2.20	0.80	2.75	8.39	1.64

Table 2: Summary statistics of the distribution of distances

III - Distance analysis among patients who deteriorate vs. those who don't

Question: Among the patients who deteriorate, do we see higher average pairwise distances compared to patients who don't deteriorate?

III - Distance analysis among patients who deteriorate vs. those who don't

Question: Among the patients who deteriorate, do we see higher average pairwise distances compared to patients who don't deteriorate?

- The data is a longitudinal dataset (multiple timepoints are available for each patient)

III - Distance analysis among patients who deteriorate vs. those who don't

Question: Among the patients who deteriorate, do we see higher average pairwise distances compared to patients who don't deteriorate?

- The data is a longitudinal dataset (multiple timepoints are available for each patient)
- Some patients deteriorate (transition from CN→MCI or from MCI→AD)

III - Distance analysis among patients who deteriorate vs. those who don't

Question: Among the patients who deteriorate, do we see higher average pairwise distances compared to patients who don't deteriorate?

- The data is a longitudinal dataset (multiple timepoints are available for each patient)
- Some patients deteriorate (transition from CN→MCI or from MCI→AD)
- Compute pairwise distance between patients (L^1 PL distance, Wasserstein distance and bottleneck distance), and average for each patient.

III - Distance analysis among patients who deteriorate vs. those who don't

Example of L^1 norm between PLs of a deteriorating patient.




Figure 10: H_0




Figure 11: H_1




Figure 12: H_2

III - Distance analysis among patients who deteriorate vs. those who don't

Example of L^1 norm between PLs of a subject who does *not* deteriorate.




Figure 13: H_0




Figure 14: H_1




Figure 15: H_2

III - Distance analysis among patients who deteriorate vs. those who don't

Persistence landscape L^1 norm




Figure 16: H_0




Figure 17: H_1




Figure 18: H_2

III - Distance analysis among patients who deteriorate vs. those who don't

Bottleneck L^1 norm




Figure 19: H_0




Figure 20: H_1




Figure 21: H_2

III - Distance analysis among patients who deteriorate vs. those who don't

Wasserstein distance




Figure 22: H_0




Figure 23: H_1




Figure 24: H_2

1. Diagnosis

1. Diagnosis

- Performance can be enhanced by taking local features from other patches and passing them through convolutions. Especially useful when dealing with subtypes of Alzheimer's which show atrophy in other brain regions.

1. Diagnosis

- Performance can be enhanced by taking local features from other patches and passing them through convolutions. Especially useful when dealing with subtypes of Alzheimer's which show atrophy in other brain regions.
- Neural architecture could be made more complex to capture more complex features of the persistence images

1. Diagnosis

- Performance can be enhanced by taking local features from other patches and passing them through convolutions. Especially useful when dealing with subtypes of Alzheimer's which show atrophy in other brain regions.
- Neural architecture could be made more complex to capture more complex features of the persistence images
- Can persistence images be used to diagnose prodromal forms of AD?

Limitations & Outlook

1. Diagnosis

- Performance can be enhanced by taking local features from other patches and passing them through convolutions. Especially useful when dealing with subtypes of Alzheimer's which show atrophy in other brain regions.
- Neural architecture could be made more complex to capture more complex features of the persistence images
- Can persistence images be used to diagnose prodromal forms of AD?

2. Distances

- In general, very *coarse* analysis (averages do not pick out subtypes or use individual features to differentiate between images), sensitive to noise.

Limitations & Outlook

1. Diagnosis

- Performance can be enhanced by taking local features from other patches and passing them through convolutions. Especially useful when dealing with subtypes of Alzheimer's which show atrophy in other brain regions.
- Neural architecture could be made more complex to capture more complex features of the persistence images
- Can persistence images be used to diagnose prodromal forms of AD?

2. Distances

- In general, very *coarse* analysis (averages do not pick out subtypes or use individual features to differentiate between images), sensitive to noise.

Limitations & Outlook

1. Diagnosis

- Performance can be enhanced by taking local features from other patches and passing them through convolutions. Especially useful when dealing with subtypes of Alzheimer's which show atrophy in other brain regions.
- Neural architecture could be made more complex to capture more complex features of the persistence images
- Can persistence images be used to diagnose prodromal forms of AD?

2. Distances

- In general, very *coarse* analysis (averages do not pick out subtypes or use individual features to differentiate between images), sensitive to noise.
- Could learn better (topology-based) embeddings to better distinguish between people who progress versus those who do not and more finegrained subtype identification resilient noise.

GitHub repository of the project

`github.com/pjhartout/TDA_ADNI_MLCB`

With thanks to Bastian Rieck for the supervision and Sarah Brueningk, Felix Hensel, Catherine Jutzeler, Merel Kuijs and Louis Lukas for insightful discussions, code, and data.

Questions?