

Uncovering the saliency of local topological features for Alzheimer's disease characterisation


Philip Hartout

November 27, 2020

Alzheimer's disease

Alzheimer's disease: 🧠

- Nearly 40 million people live with AD
- Cost in US alone \$ 2 trillion by 2030
- Among leading causes of death in EU



Images adapted from Ittner et al and Wikipedia

Topology: 🍩 ☕


- Concerned with “properties of a geometric object that are preserved under **continuous deformations**, such as [...] crumpling.”
- Recently, *persistent homology* has emerged to quantify (differences in) the shape of data.
- **How can we apply persistent homology to quantify changes in shape due to Alzheimer's disease?**

1. **Classification**
2. Subtype identification
3. Progression & forecasting


Analysis setting




Unprocessed




fMRIPrep




Patch selection



Persistence homology



Persistence Image



Classification

Images adapted from Wikimedia, slicer.org, and Sachin Modgekar

Analysis setting





Figure 2: AUPRC on each patch, achieved using a model described in earlier work. Chosen patch for analyses is boxed in red (patch with highest accuracy).


I - Persistent homology

CN


H_0



H_1




H_2




AD


H_0




H_1




H_2




I - Classification - Persistence Images



I - Classification - Network architecture



I - Classification - Network architecture



Methodological considerations

- 4 fold CV, 3 inits. Stratified for age, diagnoses and no patients are spread over folds.
- Same experimental settings as from Brüningk, Sarah C *et al*
<https://arxiv.org/abs/2011.06531>

I - Classification - Performance

Local Global	PI	3D Conv	PI
Validation accuracy	0.79 ± 0.02	0.85 ± 0.06	0.76 ± 0.02
Precision	0.81 ± 0.04	0.87 ± 0.04	0.74 ± 0.02
Recall	0.81 ± 0.02	0.87 ± 0.08	0.88 ± 0.08
AUC	0.85 ± 0.03	0.89 ± 0.05	0.78 ± 0.02

Table 1: Performance metrics of the different models trained on the same data.

Metrics from Brüningk, Sarah C *et al* <https://arxiv.org/abs/2011.06531>.

→ Local PI training time is 2 minutes on a **laptop CPU**. Very efficient compression of features!

→ Local 3D Conv training takes 15 minutes on a **server GPU**.

Persistent homology produces **highly salient compressed** features for AD characterization.

Limitations:

- Using **raw** images is **better**, but more **expensive**.
- Does not take atrophy from **other regions** into account

directions:

- Can persistent homology be used to diagnose **prodromal** forms of AD?
- Use a similar approach for **subtype identification**.

Thanks!

GitHub repository of the project (currently available upon request)


`github.com/pjhartout/TDA_ADNI_MLCB`

With thanks to Bastian Rieck for the supervision and Sarah Brueningk, Felix Hensel, Catherine Jutzeler, Merel Kuijs and Louis Lukas for insightful discussions, code, and data.


Questions?




Unprocessed




fMRIPrep




Patch selection



Persistence homology



Persistence Image



Classification

Images adapted from Wikimedia, slicer.org, and Sachin Modgekar