

CS193X: Web Programming Fundamentals

Spring 2017

Victoria Kirst
(vrk@stanford.edu)

Today's schedule

Schedule:

- HTML: Background and history
- Complex selectors
- Box model
- Debugging with Chrome Inspector
- **Case study:** Squarespace Layout (will continue into Monday)

(Forgot to mention: Paths)

`img src`, `a href`, and `link href` can all take either **relative** or **absolute** paths to the resource:

- `About`
- ``
- `<link rel="stylesheet" href="css/style.css"/>`

If you are unfamiliar with paths, check out the following:

- [Absolute vs relative paths](#)
- [Unix directories and file paths](#)
- If anything's still unclear, come to [office hours](#)!

HTML: Background and History

What HTML elements can I use?

Q: Instead of ``, can I create a `<highlight>` element?


```
<p>  
  The homework is  
  <highlight>due Friday</highlight>.  
</p>
```

```
highlight {  
  background-color: yellow;  
}
```

Q: Does this
even work?


What HTML elements can I use?

This renders correctly:



What HTML elements can I use?

This renders correctly:




But you shouldn't do this!

It is non-standard behavior.

What HTML elements can I use?

This renders correctly:



What?!?!?

But you shouldn't do this!
It is non-standard behavior.

What?!

- What is "standard" HTML?
- Why does invalid HTML/CSS still work sometimes?
 - If my Java code is wrong, I get a compiler error... If my HTML or CSS is wrong, why don't I get an error?
- Why does it matter that I follow "standard" HTML?

A very brief history of HTML

History



**Tim
Berners-Lee**

- 1989: World Wide Web created
(WWW: web pages and the protocol in which they are served HTTP/HTTPS)
- 1994: World Wide Web Consortium created
 - "**W3C**": Goal to maintain and develop standards about how the web should work
 - Oversees [several languages](#):
 - HTML, CSS, DOM, XML, etc
- 1997: "HTML4" published
 - The first major stable version of HTML

Degrading gracefully


The W3C HTML spec lists several [design principles](#), and one is degrading gracefully:



"An escalator
can never
break: it can
only become
stairs"

This is why browsers do a **best-effort** to render non-standard ("invalid") HTML and CSS.

Best-effort rendering



It's also why `<highlight>` "works", even though it's Invalid HTML.

Why not enforce strict HTML?

It's super weird that:

- Browsers don't fail when given invalid HTML / CSS
- Browsers not only don't fail, but they render invalid HTML/CSS seemingly "correctly"

Q: Why doesn't the browser reject poorly written HTML/CSS?

Why not enforce strict HTML?

It's super weird that:

- Browsers don't fail when given invalid HTML / CSS
- Browsers not only don't fail, but they render invalid HTML/CSS seemingly "correctly"

Q: Why doesn't the browser reject poorly written HTML/CSS?

A: There was a (failed) attempt to enforce this, but it was too late: the Internet grew too big!


The nerdy, mostly* accurate backstory for HTML today

*I would be more accurate, but it's hard to get valid sources online... so I'm going off of what I can + the lore I've heard while working on a browser.

State of the world, 1997:



Standards say
one thing,



Browsers do
another thing,

Developers write
weird, non-standard
code.



State of the world, 1997:



Standard
one thing,

**In 1997, things are
kind of a mess!**

another thing,



Developers write
weird, non-standard
code.

2000ish:



W3C

Oops, that "degrading gracefully" thing was a mistake.

Browsers, stop rendering pages that have invalid HTML.

(This what the proposal of XHTML 1.1)

2000ish: (not totally accurate)



W3C

**That would
break the
internet!**

What?!?!

Sure
whatever



**We can't
do that!**



2004: WHATWG formed



**Let's burn everything and
start from scratch with
XHTML 1.1**

(break approx. 64 million websites)



WHATWG



Let's work on HTML5
(an imperfect but realistic standard)

Fast forward 2017?!



- W3C gave up XHTML 1.1 in 2007
- W3C and WHATWG are mostly friends (I think), though they are still separate entities
- Can still find some snarky quotes on [WHATWG website](http://whatwg.org)

"HTML5" vs HTML


W3C maintains [HTML5](#):

- More stable version of WHATWG's HTML
- Usually copies what WHATWG does after the dust settles



WHATWG maintains [HTML: The Living Standard](#)

- No number, no versions
- Updated frequently and being updated today!
- Most browsers implement WHATWG
- This is why I don't say "HTML5"



What you need to know

Q: What HTML elements can I choose from?

- Check [MDN's list of HTML tags](#)

Q: How do I know if an HTML tag (or CSS property, or JS feature) is implemented on all browsers?

- Check [caniuse.com](#)

Q: Why shouldn't I use non-standard HTML/CSS/JavaScript, even if it works in every browser?

What you need to know

Q: What HTML elements can I choose from?

- Check [MDN's list of HTML tags](#)

Q: How do I know if an HTML tag (or CSS property, or JS feature) is implemented on all browsers?

- Check [caniuse.com](#)

Q: Why shouldn't I use non-standard HTML/CSS/JavaScript, even if it works in every browser?

- Because it won't be guaranteed to work in the future
- Because it won't be guaranteed to work on all "user agents" (not just browsers)

What you need to know

Q: Wouldn't it be super useful to create custom elements?

- Yes! There is a [spec for this](#) currently under development.
 - (Note that custom elements are not really meant for our example; custom elements are meant for defining custom behavior and not just style. For defining style, CSS classes/ids are still most appropriate.)

Back to writing
code!

CSS Selectors: Classes and Ids

Classes and ids

There are 3 basic types of CSS selectors:

Element selector (this is the one we've been using)	p	All <p> elements
❖ ID selector ❖	#abc	element with id="abc"
❖ Class selector ❖	.abc	elements with class="abc"

```
<h1 id="title">Homework</h1>
<em class="hw">HW0</em> is due Friday.<br/>
<em class="hw">HW1</em> goes out Monday.<br/>
<em>All homework due at 11:59pm.</em>
```

Other selectors

element.className

Syntax	Example	Example described
<i>element.className</i>	p.abc	<p> elements with abc class

HTML

```
<h1 class="hw">Homework 0</h1>
<p class="hw">Due Fri</p>
<p class="hw">Late cutoff Sun</p>
<h1>Lectures</h1>
<p>Apr 3: Syllabus</p>
<p>Apr 5: HTML+CSS</p>
```

CSS

```
p.hw {
  color: green;
}
```

Homework 0

Due Fri

Late cutoff Sun

Lectures

Apr 3: Syllabus

Apr 5: HTML+CSS

Descendent selector

Syntax	Example	Example described
<i>selector selector</i>	div strong	 elements that are descendants of a <div>

HTML

```
<div class="hw">
  <h1>Homework 0</h1>
  <p>Due Fri</p>
  <p>Late cutoff Sun</p>
</div>
```

CSS

```
.hw p {
  color: green;
}
```

Homework 0

Due Fri

Late cutoff Sun

Lectures

Apr 3: Syllabus

Apr 5: HTML+CSS

Descendent selector

Syntax	Example	Example described
<i>selector selector</i>	div strong	 elements that are descendants of a <div>

Note: The element does not have to be a direct child. The descendent may be nested many layers in.

The screenshot shows a web development tool interface. The top panel is labeled 'HTML' and contains the following code:

```
<div class="hw">
  <div>
    <p>
      HW0: <strong>Due Friday</strong>
    </p>
  </div>
  HW1 out <strong>Monday</strong>
</div>
```

The bottom panel is labeled 'CSS' and contains the following code:

```
.hw strong {
  color: red;
}
```

On the right side, there is a live preview of the rendered HTML. It shows two lines of text: 'HW0: Due Friday' and 'HW1 out Monday'. The words 'Due' and 'Monday' are highlighted in red, demonstrating the effect of the CSS rule.

Descendent selector

Syntax	Example	Example described
<i>selector selector</i>	div strong	 elements that are descendants of a <div>

Discouraged:

```
<h1 class="hw">Homework 0</h1>  
<p class="hw">Due Fri</p>  
<p class="hw">Late cutoff Sun</p>
```

vs

Preferred:

```
<div class="hw">  
  <h1>Homework 0</h1>  
  <p>Due Fri</p>  
  <p>Late cutoff Sun</p>  
</div>
```

Instead of applying a class to several adjacent elements, wrap the group in a `<div>` container and style the contents via descendent selectors.

selector, selector (comma)

Syntax	Example	Example described
<i>selector, selector</i>	h2, div	<h2> elements and <div>s

HTML

```
<h1>Course Info</h1>
<h2>Lectures</h2>
<p>Mon-Wed-Fri 1:30-2:20</p>
<h2>Honor code</h2>
<p>Do the right thing</p>
```

CSS

```
h1, h2 {
  font-family: Arial;
}
```

Course Info

Lectures

Mon-Wed-Fri 1:30-2:20

Honor code

Do the right thing

Selector summary

Example	Description
p	All <p> elements
.abc	All elements with the abc class , i.e. class="abc"
#abc	Element with the abc id , i.e. id="abc"
p.abc	<p> elements with abc class
p#abc	<p> element with abc id (p is redundant)
div strong	 elements that are descendants of a <div>
h2, div	<h2> elements and <div> s

Grouping selectors

2 Common bugs:

p.abc **vs** p .abc

p .abc **vs** p, .abc

- A <p> element with the **abc** class **vs**
An element with the **abc** class that descends from <p>
- An element with the **abc** class that descends from <p> **vs**
All <p> elements *and* all elements with the **abc** class

Combining selectors

You can combine selectors:

```
#main li.important strong {  
  color: red;  
}
```

Q: What does this select?

Grouping selectors

Q: What does this select?

```
#main li.important strong {  
  color: red;  
}
```

A: Read from right to left:

- `` tags that are children of `` tags that have an "important" class that are children of the element with the "main" id.

Colliding styles

When styles collide, the most specific rule wins ([specificity](#))

```
div strong { color: red; }  
strong { color: blue; }
```

```
<div>  
  <strong>What color am I?</strong>  
</div>
```


Colliding styles

When styles collide, the most specific rule wins ([specificity](#))

```
div strong { color: red; }  
strong { color: blue; }
```

```
<div>  
  <strong>What color am I?</strong>  
</div>
```

Colliding styles

Specificity precedence rules ([details](#)):

- `ids` are more specific than `classes`
- `classes` are more specific than element names
- Style rules that directly target elements are more specific than style rules that are inherited

Colliding styles

- If elements have the same specificity, the later rule wins.

```
strong { color: red; }  
strong { color: blue; }
```

```
<div>  
  <strong>What color am I?</strong>  
</div>
```

Aside: The process of figuring out what rule applies to a given element is called the [cascade](#). This is where the "C" in *Cascading* Style Sheets comes from.

Inheritance

We saw earlier that CSS styles are inherited from parent to child.

Instead of selecting all elements individually:

```
a, h1, p, strong {  
    font-family: Helvetica;  
}
```

You can style the parent and the children will inherit the styles.

```
body {  
    font-family: Helvetica;  
}
```

You can override this style via specificity:

```
h1, h2 {  
    font-family: Consolas;  
}
```

Inheritance

While many CSS styles are inherited from parent to child,
not all CSS properties are inherited.

```
a {  
  display: block;  
  font-family: Arial;  
}
```

 inherits the
font-family property,
but not display:

```
<a href="/home">  
  Back to <em>Home</em>  
</a>
```

[Back to Home](#)

Inheritance

While many CSS styles are inherited from parent to child, **not all CSS properties are inherited.**

- There's no rule for what properties are inherited or not; the inheritance behavior defined in the CSS spec.
- You can look it up via MDN, e.g.

font-family: Inherited yes

display: Inherited no

- Generally text-related properties are inherited and layout-related properties are not.
- (You can also change this via the inherit CSS property, which is somewhat esoteric and not often use)

<a> colors?

Hmm, MDN says [color is inherited](#)... but if I set the body color to deeppink, links don't change color:

CSS	HTML
<pre>body { color: deeppink; font-family: Helvetica; }</pre>	<pre><h1>Chocolate</h1> <p> Ghiradelli is not overrated </p></pre>

<a> inherits font-family...
Why doesn't <a> inherit color?
([Codepen](#))

Chocolate

[Ghiradelli](#) is not overrated

User agent styles

This is because the browser has its own default styles:

- Browser loads its own default stylesheet on every webpage
- Not governed by spec, but there are [recommendations](#)

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>CS 193X</title>
```

```
    <!--
```

NOT TOTALLY ACCURATE: This isn't actually injected in the HTML, but it is loaded silently!

```
    -->
```

```
    <link rel="stylesheet" href="user-agent-style.css" />
```

```
  </head>
```


<a> colors?

So to style <a> links, we have to override the browser default link style by explicitly setting a color:

CSS

```
body {  
  color: deeppink;  
  font-family: Helvetica;  
}  
  
a {  
  color: deeppink;  
}
```

HTML

```
<h1>Chocolate</h1>  
<p>  
  <a href="https://www.ghirardelli.com/">Ghiradelli</a>  
  is not overrated  
</p>
```

Chocolate

Ghiradelli is not overrated

Link-related CSS

Since we're on the topic of links:

- How do we style **visited** links differently from **unvisited**?

CSS pseudo-classes

[pseudo-classes](#): special keywords you can append to selectors, specifying a *state* or *property* of the selector

Syntax	Explanation
a	All anchor tags (links) in all states
a:visited	A visited link
a:link	An unvisited link
a:hover	The style when you hover over a link
a:active	The style when you have "activated" a link (downclick)

There are more [pseudo-classes](#) than this; have a look!

Before we move on:
A few style notes

Why not `<div>` everywhere?

Technically, you can define your entire web page using `<div>` and the `class` attribute.


- Is this a good idea?
- Why does HTML have `ids` when you have `classes`?
- Why does HTML have `<p>`, `<h1>`, ``, etc. when you have `<div>`, ``, `class`, and `id`?

CSS Box Model


The CSS Box Model

Every element is composed of 4 layers:

- the element's content
- the **border** around the element's content
- **padding** space between the content and border (inside)
- a **margin** clears the area around border (outside)



border



We've used the [shorthand](#):
`border: width style color;`

border

Can also specify each border individually:

`border-top`

`border-bottom`

`border-left`

`border-right`

And can set each property individually:

`border-style: dotted; (all styles)`

`border-width: 3px;`

`border-color: purple;`

border

Can also specify each border individually:

`border-top`

`border-bottom`

`border-left`

`border-right`

And can set each property individually:

`border-style: dotted;` ([all styles](#))

`border-width: 3px;`

`border-color: purple;`

There are other units besides pixels (px) but we will address them in the next couple lectures.

Rounded border

Can specify the `border-radius` to make rounded corners:

```
border-radius: 10px;
```

You don't actually need to set a border to use `border-radius`.


```
p {  
  background-color: purple;  
  border-radius: 10px;  
  color: white;  
}
```

Welcome to CS193X: Web Programming Fundamentals! In this class, you will learn modern full-stack web development techniques.

Borders look a little squished

When we add a border to an element, it sits flush against the text:

Q: How do we add space between the border and the content of the element?



Welcome to CS193X: Web Fundamentals! In this class, we'll learn modern full-stack web development techniques.

padding

```
p {  
  border: 2px solid black;  
  padding: 10px;  
}
```

Welcome to CS193X: Web Programming Fundamentals! In this class, you will learn modern full-stack web development techniques.

padding is the space between the border and the content.

- Can specify padding-top, padding-bottom, padding-left, padding-right
- There's also a shorthand:

padding: 2px 4px 3px 1px; <- top | left | bottom | right

padding: 10px 2px; <- top+bottom | left+right

<div>s look a little squished

When we add a border to multiple divs, they sit flush against each other:




The screenshot shows a code editor with two panels. The left panel, titled 'HTML', contains the following code:

```
<div>
  Lectures
</div>
<div>
  Homework
</div>
```

The right panel, titled 'CSS', contains the following code:

```
div {
  border: 2px solid black;
  padding: 10px;
}
```

Q: How do we add space between multiple elements?



margin

```
div {  
  margin: 20px;  
  padding: 10px;  
  border: 2px solid black;  
}
```

Lectures

Homework

margin is the space between the border and other elements.

- Can specify margin-top, margin-bottom, margin-left, margin-right
- There's also a shorthand:

margin: 2px 4px 3px 1px; <- top | left | bottom | right

margin: 10px 2px; <- top+bottom | left+right

More box model:
Next time!

Overflow slides

We didn't get to these in lecture

margin

Actually, why doesn't this:

```
div {  
  margin: 20px;  
  padding: 10px;  
  border: 2px solid black;  
}
```

Lectures

Homework

Look more like this?

Lectures

Homework

margin

Actually, why doesn't this:

```
div {  
  margin: 20px;  
  padding: 10px;  
  border: 2px solid black;  
}
```

Lectures

Homework

...look more like this?

20px margin-bottom +
20px margin top =
40px margin?

Lectures

Homework

margin collapsing

Sometimes the top and bottom margins of block elements are combined ("collapsed") into a single margin.

- This is called **margin collapsing**

Generally if:

- The elements are siblings
- The elements are block-level (not inline-block)

Lectures

Homework

Syllabus

then they collapse into **max**(*Bottom Margin, Top Margin*).

(There are [some exceptions](#) to this, but when in doubt, use the Page Inspector to see what's going on.)

Negative margin

Margins can be negative as well.

- **No negative margin on image:**

HTML

```
<div id="header"></div>
<div id="profile">
  
</div>
```

CSS

```
#header {
  background-color: lightblue;
  height: 200px;
}

img {
  margin-left: 50px;
  height: 140px;
  border: 2px solid LIGHTGRAY;
}
```

Negative margin


Margins can be negative as well.

- `img { margin-top: -50px; }`

```
HTML
<div id="header"></div>
<div id="profile">
  
</div>

CSS
#header {
  background-color: lightblue;
  height: 200px;
}

img {
  margin-top: -50px;
  margin-left: 50px;
  height: 140px;
  border: 2px solid LIGHTGRAY;
}
```



Box model for inline elements?

Q: Does the box model apply to inline elements as well?

Box model for inline elements?

Q: Does the box model apply to inline elements as well?

A: Yes, but the box is shaped differently.

```

CSS

strong {
  border: 3px solid hotpink;
  padding: 5px;
  margin: 25px;

  background-color: lavenderblush;
}


```

```

HTML

<p>
  Welcome to
  <strong>
    CS193X: Web Programming
  </strong>
  Hope you enjoy the class!
</p>

```



Box model for inline elements?

Q: Does the box model apply to inline elements as well?

A: Yes, but the box is shaped differently.

```

CSS

strong {
  border: 3px solid hotpink;
  padding: 5px;
  margin: 25px;

  background-color: lavenderblush;
}


```

```

HTML

<p>
  Welcome to
  <strong>
    CS193X: Web Programming
  </strong>
  Hope you enjoy the class!
</p>

```



Let's change the line
height to view this more
clearly...

Inline element box model

```

CSS

strong {
  border: 3px solid hotpink;
  padding: 5px;
  margin: 25px;
  line-height: 50px;
  background-color: lavenderblush;
}

```

Welcome to

CS193X: Web

Programming Fundamentals! This class is

in the Shriram Center for Bioengineering

and Chemical Engineering.

Hope you

enjoy the class!

([Codepen](#))


Inline element box model

```

- CSS
strong {
  border: 3px solid hotpink;
  padding: 5px;
  margin: 25px;
  line-height: 50px;|
  background-color: lavenderblush;
}

```

- **margin** is to the left and right of the inline element
 - margin-top and margin-bottom are **ignored**
- use **line-height** to manage space between lines



([Codepen](#))

The CSS Box Model

Let's revisit our Course web page example:

CS 193X: Web Fun

Announcements

4/3: Homework 0 is out! Due Friday.

4/3: Office hours are now posted.

[View Syllabus](#)

**Q: What does
this look like in
the browser?**

```
div {  
  display: inline-block;  
  background-color: yellow;  
}
```

```
<body>  
  <div>  
    <p>Make the background color yellow!</p>  
    <p>Surrounding these paragraphs</p>  
  </div>  
</body>
```

Make the background color yellow!

Surrounding these paragraphs

**Q: Why is there a
white space
around the box?**

We can use the
browser's Page
Inspector to help us
figure it out!

body has a default margin

Set `body { margin: 0; }` to make your elements lay flush to the page.

```
body {  
  margin: 0;  
}  
  
div {  
  display: inline-block;  
  background-color: yellow;  
}
```

Make the background color yellow!

Surrounding these paragraphs

Recap so far...

We've talked about:


- **block vs inline** and the "natural" layout of the page, depending on the element type
- **classes and ids** and how to specify specific elements and groups of elements
- **div and span** and how to create generic elements
- **The CSS box model** and how every element is shaped like a box, with content -> padding -> border -> margin

Let's try making a "real" looking page!

Layout exercise

Squarespace template


[Squarespace](#)'s most popular template looks like [this](#):



Do we know enough to make something like that?


Basic shape

Begin visualizing the layout in terms of boxes:



Basic shape

Begin visualizing the layout in terms of boxes:




Basic shape

Begin visualizing the layout in terms of boxes:

Let's first try making this layout!

✦ [Codepen Link](#) ✦



Content Sectioning elements

Name	Description
<code><p></code>	Paragraph (mdn)
<code><h1> - <h6></code>	Section headings (mdn)
<code><article></code>	A document, page, or site (mdn) This is usually a root container element after body.
<code><section></code>	Generic section of a document (mdn)
<code><header></code>	Introductory section of a document (mdn)
<code><footer></code>	Footer at end of a document or section (mdn)
<code><nav></code>	Navigational section (mdn)

These elements do not "do" anything; they are basically more descriptive `<div>`s. Makes your HTML more readable. See [MDN](#) for more info.

Header

Navbar:

- Height: 75px
- Background: royalblue
- `<nav>`

Header:


- Height: 400px;
- Background: lightskyblue
- `<header>`



Main section

Gray box:

- Surrounding space:
75px above and
below; 100px on
each side
- Height: 500px
- Background: gray
- `<section>`



Footer

Footer:

- Height: 100px
- Background: Black
- `<footer>`




Main contents

Yellow paragraph:

- Height: 200px
- Background: khaki
- Space beneath: 75px
- `<p>`

Orange box:

- Height: 400px;
- Width: 48% of the parent's width, with space in between
- Background: tomato
- `<div>`




Main contents

Orange box:

- Height: 400px;
- Width: 48% of the parent's width, with space in between
- Background: tomato
- `<div>`

**This is where
we get stuck.**



Next time:
Flexbox to the
rescue!