

Jonas Franz

Snips Documentation & Manual

Contents

1. About SNIPS
 - The language
 - About this document
2. Language Syntax
 - Type System
 - Primitives
 - Composite Types
 - Proviso Types
 - Expressions
 - Statements
 - Assignments
 - Program Flow
 - Loops
 - Exception Handling
 - Namespacing
3. Built in Libraries
 - Memory & Heap Routines
 - System Operators
 - Types
 - Data Structures
 - I/O
 - Math
 - Utility

1. About SNIPS

2. Language Syntax

Type System

Primitives

Snips has a range of built-in primitive types. All of the types are 1 32-bit word large.

Void. The void type acts as a universal primitive type. Using this type requires caution, because of its unique property to match every other type. This is not only true for primitives, but for every possible type. This can be used to create “don’t care” types. But, to improve type security, this should be avoided. Also, since the void type is 1 word large, assigning a expression to this type that is larger than 1 word can cause major problems. See **Void Arrays** for a workaround. A Void is declared with the type specifier *void*. For example:

```
void v = 20;
```

Integer. The integer represents the most common numeric type, with a range from $-2^{31} - 1$ to 2^{31} . An Integer is declared with the type specifier *int*. For example:

```
int x = 10;
```

Boolean. The boolean type is mostly used for logic. Its value range is the exact same as the one of the Integer, but when interpreting the value, only the value **0** is interpreted as *false*, all other possible values are interpreted as *true*. A boolean is declared with the type specifier *bool*. For example:

```
bool b = true;
```

Character. The character type can be used to store UTF-8 encoded Characters. The value Range is, because of the 32-bit size, like the one of the Integer, but the usable Range is only from **0** to **255**. The **0** value takes a special role. In a String, a char with the value **0** indicates the end of the String. A character is declared with the type specifier *char*. For example:

```
char c = 'a';
```

Enumerations. The enumeration type is not necessarily a primitive type, but is handled like one on the low level. An enumeration has to be declared, see Enum Typedef. After Declaration, an Enum value can be selected. An Enum is declared with the name of the Enum itself. For Example:

```
State s = State.Normal;
```

Composite Types

3. Built in Libraries

Memory & Heap Routines

resv.sn

Full Path: -
 Package Type: Base Package
 Namespacing: None
 Description:

Contains the memory reserve routine that is responsible for allocating a requested block size in the heap. This file is included dynamically when the resv function is called.

Function Header	Description
void* resv(int size)	Reserves a memory block of given size + 1. The additional word is used for heap management. Returns a pointer to the memory location. The returned pointer points to the second data word of the block. The first word contains the heap management data. $O(n)$ where n is the number of heap elements.

free.sn

Full Path: -
 Package Type: Base Package
 Namespacing: None
 Description:

Contains the memory free routine that is responsible for freeing memory in the heap. This file is included dynamically when the free function is called.

Function Header	Description
void free(void* p)	Frees the given pointer from the heap. This is done by negating the heap management data on the block head. The data will remain in the heap, but can from now on be overwritten. $O(n)$, where n is the amount of heap elements.

hsize.sn

Full Path: -

Package Type: Base Package

Namespacing: None

Description:

Contains the memory free routine that can determine the size of a heap memory block. This file is included dynamically when the hsize function is called.

Function Header	Description
Int hsize(void* p)	Returns the size of the memory section. The pointer should point to a memory block in the heap. The size is determined by reading the heap management data and subtracting 1. $O(1)$

System Operators

__op_div.sn

Full Path: -

Package Type: Base Package

Namespacing: None

Description:

Contains a routine to divide two integers. This file is included dynamically when the division operator is used.

Function Header	Description
int __op_div(int a, int b)	Calculates $\frac{a}{b}$ and returns the result.

__op_mod.sn

Full Path: -

Package Type: Base Package

Namespacing: None

Description:

Contains a routine to compute the rest of a integer division. This file is included dynamically when the modulo operator is used.

Function Header	Description
int __op_mod(int a, int b)	Calculates $a \% b$ and returns the result.

Types

boolean.sn

Full Path: lib/std/type/boolean.sn
 Package Type: Includes: string.sn
 Namespacing: The entire package is namespaced in 'Boolean'.
 Description:
 Contains utility around the boolean type.

Function Header	Description
bool parseBool(char* str)	Parses a boolean value from given String. The result will be <i>true</i> if the String is equal to "true". In any other case, the result will be false.
char* toString(bool b)	Converts given boolean into String representation. The result will be, depending on given value, "true" or "false". Returns a pointer to the created String.

integer.sn

Full Path: lib/std/type/integer.sn
 Package Type: Base Package
 Namespacing: The entire package is namespaced in 'Integer'.
 Description:
 Contains utility around the integer type.

Function Header	Description
int parseInt(char* str)	Parses a integer from given String. The String has to match the pattern: $-?([0-9])^*$. The result is the parsed int.
char* toString(int num)	Converts given int to String representation. The resulting string will contain a sign if the int was negative. Returns a pointer to the created String.

Namespace Array:

Function Header	Description
void sort(int* arr, int size, func (int a, int b) -> bool pred)	Sorts given integer array. The sorting is done using a bubble sort algorithm, so the runtime complexity equals $O(n^2)$. The sorting is determined by given predicate. Writes back the result in the array at the given pointer.

string.sn

Full Path: lib/std/type/string.sn
 Package Type: Includes: linked_list.sn
 Namespacing: The entire package is namespaced in 'String'.
 Description:
 Contains utility for String operations.

Function Header	Description
<code>bool equals(char* str0, char* str1)</code>	Checks if the two given Strings are equal on a char level. All contained chars must have the same value, and both Strings have to have the same case.
<code>char* substring(char* str, int begin, int end)</code>	Cuts out a part of the String specified by the bounds. The begin index marks the first char to be included in the new String, the end index marks the last char to be included. The <code>0</code> char is inserted at the end of the resulting String. The begin index should be less than the end index. In case the indexes are out of the bounds of the String, the entire String is copied. Returns a pointer to the new String on the heap.
<code>int length(char* str)</code>	Returns the length of the String. This includes the <code>0</code> char. Returns the length.
<code>char* concat(char* str0, char* str1)</code>	Concatenates the two given Strings. The resulting String will contain the entire first String followed by the entire second String. The <code>0</code> char of the first String is discarded. Returns a pointer to the new String.

Data Structures

linked_list.sn

Full Path: lib/std/data/linked_list.sn

Package Type: Base Package

Namespacing: The entire package is namespaced in 'List'.

Description:

Provides a data structure that can hold a variable number of items. Each element is capsuled in a own node. Using pointers, these nodes are chained together. The nodes are stored on the heap.

Struct Name	Struct Fields	Description
ListNode<T>	ListNode<T>* next T value	Capsules a single data element. Also contains a pointer to the next list node in the list. Is set to 0 if this is the last element in the list.
LinkedList<T>	ListNode<T>* head ListNode<T>* tail	Capsules two list node pointers, one pointing to the first, and one to the last element. Both pointers are initialized and set to 0 whenever the pointer has no target.

Function Header	Description
LinkedList<T>* create<T>()	Initializes a new linked list struct. Sets the pointers to 0. $O(1)$
void destroy(LinkedList<void>* l)	Destroys the given list and all of its contained elements by freeing every node and the list itself from the heap. $O(n)$
void add<T>(LinkedList<T>* lp, T x)	Adds given x to the list by encapsulating it in a new list node and appending the element at the end of the list. This uses the tail pointer of the list, so the complexity is $O(1)$.
T get<T>(LinkedList<T>* lp, int i)	Returns the value of the i-th element in the given list. $O(n)$
ListNode<T>* getNode<T>(LinkedList<T>* lp, int i)	Returns a pointer to the list node in the list at the i-th position in the list. $O(n)$
bool contains<T>(LinkedList<T>* lp, T x)	Checks whether given value is the value of one of the contained list nodes. Returns true if the value is found. $O(n)$
ListNode<T>* find<T>(LinkedList<T>* lp, T x)	Attempts to find the first list node in order in the list that has the given value x. Returns a pointer to this list node. $O(n)$
int size(LinkedList<void>* lp)	Returns the number of list nodes in the given list. $O(n)$
void remove(LinkedList<void>* lp, int i)	Returns the list node at the i-th position. Updates the pointers of the neighbours to fill the gap. Also frees the removed node. $O(n)$

binary_tree.sn

Full Path: lib/std/data/binary_tree.sn

Package Type: Base Package

Namespacing: The entire package is namespaced in 'Tree'.

Description:

Provides a data structure that can hold a variable number of elements and organizes the elements to minimize search time.

Struct Name	Struct Fields	Description
TreeNode<T>	TreeNode<T>* left TreeNode<T>* right T value	Capsules pointers to left and right child nodes, and a value.

Function Header	Description
TreeNode<T>* create<T>(T value)	Initializes a new Tree. Initializes pointers to 0. Sets given value to node value. Returns pointer to newly created node. $O(1)$
TreeNode<T>* insert<T>(TreeNode<T>* root, T value)	Capsules given value in a new Node and inserts it into given Tree. The insertion location is determined by numerically comparing the value. Returns a pointer to the newly created node. $O(\log n)$

queue.sn

Full Path: lib/std/data/queue.sn

Package Type: Base Package

Namespacing: The entire package is namespaced in 'Queue'.

Description:

Provides a data structure that can hold a fixed number of elements and acts like a bypassing FIFO. The queue is implemented with a circular array.

Struct Name	Struct Fields	Description
CyclicQueue<T>	T* storage int size int head int tail bool isEmpty	Capsules a pointer to the storage array that holds the contained elements. Also capsules a field that holds the max number of elements. Holds two indices that act as pointers in the array, used to determine where the head and tail of the queue in the array is. Finally, it holds a boolean that stores whether the queue is full or not in the case that the head is equal to the tail.

Function Header	Description
<code>CyclicQueue<T>* create<T>(int size)</code>	Initializes a new Queue with given size. Creates a storage array on the heap and initializes the CyclicQueue struct. Returns a pointer to the created queue. $O(1)$
<code>void destroy(CyclicQueue<void>* queue)</code>	Frees the given queue object and frees the storage array of the queue in the heap. $O(1)$.
<code>bool isEmpty(CyclicQueue<void>* queue)</code>	Returns whether the queue contains any elements or not. $O(1)$
<code>bool isFull(CyclicQueue<void>* queue)</code>	Returns whether the number of contained elements is equal to the maximum of elements. $O(1)$
<code>void enqueue<T>(CyclicQueue<T>* queue, T value)</code>	Adds a new element to the tail of the queue. If the queue is full, the element won't be added. $O(1)$
<code>T dequeue<T>(CyclicQueue<T>* queue)</code>	Removes the head of the queue and returns it. If the queue is empty, the function will return 0. Note that this may cause problems with types larger than 1 word. $O(1)$
<code>void clear(CyclicQueue<void>* queue)</code>	Removes all elements from the queue. This is done by setting the pointers, rather than clearing the actual values. $O(1)$
<code>int size(CyclicQueue<void>* queue)</code>	Returns the number of currently stored elements in the queue. $O(1)$

stack.sn

Full Path: `lib/std/data/stack.sn`

Package Type: Includes: `linked_list.sn`

Namespacing: The entire package is namespaced in 'Stack'.

Description:

Provides a data structure that can hold a variable amount of elements and acts like a LIFO buffer.

Struct Name	Struct Fields	Description
<code>StackedList<T></code>	<code>LinkedList<T>* list</code>	Capsules only a linked list. This list will hold the elements.

Function Header	Description
<code>StackedList<T>* create<T>()</code>	Initializes a new Stacked List and the capsuled linked list. Returns a pointer to the newly created stack. $O(1)$

void destroy(StackedList<void>* stack)	Frees the stack and the capsuled linked list and all of the lists contained elements. $O(n)$
void push<T>(StackedList<T>* stack, T value)	Adds given element to the top of the stack. $O(1)$
bool isEmpty(StackedList<void>* stack)	Returns wether no elements are stored in the stack. $O(n)$
int size(StackedList<void>* stack)	Returns the number of contained elements in the stack. $O(n)$
T peek<T>(StackedList<T>* stack)	Returns the top element of the stack, but does not remove it. $O(n)$
T pop<T>(StackedList<T>* stack)	Returns the top element of the stack and removes it. Returns 0 if the stack is Empty. Be aware that popping from an empty stack that contains datatypes that are larger than 1 Word can cause problems. $O(n)$

Math

matrix.sn

Full Path: lib/std/math/matrix.sn
 Package Type: Base Package
 Namespacing: The entire package is namespaced in 'Matrix'.
 Description:
 Contains matrix utility. Currently only matrix multiplication.

Function Headers	Description
int mult(int* m, int* n, int dim0, int dim1)	Multiplies the two given matrices. Stores the result in an integer array on the heap. Returns a pointer to the result. The first matrix should have dim0 columns, the second matrix should have dim1 columns. The resulting matrix will have the dimensions $dim0 \times dim1$. Does not check matrix size compatibility.

vector.sn

Full Path: lib/std/math/vector.sn
 Package Type: Base Package
 Namespacing: The entire package is namespaced in 'Vector'.
 Description:
 Contains utility functions for vector operations, like the scalar product.

Function Headers	Description
int scalarProd(int* v, int* w, int l)	Calculates the scalar product of the two given vectors. Both vectors have to have the given length. Returns the result.

Utility

bits.sn

Full Path: lib/util/bits.sn

Package Type: Base Package

Namespacing: None

Description:

This library can be used to create something like bit-banks. Meaning a single Integer can hold 32 States for an automaton, flag-set etc. These bits can easily be modified with this library.

Function Headers	Description
bool isBitSet(int x, int i)	Checks whether the bit at the i-th place in given word x is a 1. The lowest bit has the index 0.
int setBit(int target, int i, bool val)	Sets the bit in the target word at the i-th place to given val. Returns the resulting data word.
int toggleBit(int target, int i)	Sets the bit in given target word at the i-th place to its complement. Returns the resulting word.
Int clearBit(int target, int i)	Sets the bit in given target word at the i-th place to 0. Returns the resulting word.