

16-5/16" Circular Saw

5402NA




Large capacity for beam and timber cutting

- Low noise at only 87 dB
- Rugged steel base for stability
- Electric brake for safety
- Powerful motor delivers 1,800 max watts out
- Blade stabilizer for stable blade rotation and superior cutting performance
- Large depth control lever for convenience and secure adjustments

STANDARD EQUIPMENT

INCLUDED: (32 tooth) Carbide tipped blade (A-90956), Hex wrench #6 (783204-6), Rip fence (164019-4)



SPECIFICATIONS

Blade diameter	16-5/16" (415 mm)
Arbor	1" (26 mm)
Max. cutting capacities:	
0°	6-1/4" (160 mm)
45°	4-3/16" (106 mm)
No load speed	2,200 RPM
AMPS (120 V)	15.0
Overall length	24-3/16" (615 mm)
Net weight	33.0 lbs. (24.0 kg)
Shipping weight	49.0 lbs. (22.2 kg)

7-1/4" Circular Saw

5007MG AC/DC

5007MGA



High performance magnesium blade case and base

- Bevel adjustment with positive stops at 22.5°, 45°, and 50°
- Two built in LED lights to illuminate cut line
- Rubberized grips for comfort and control
- 5007MGA Electric brake for maximum productivity

STANDARD EQUIPMENT

5007MG INCLUDED: 24T Carbide tipped blade (A-94530), Hex wrench #6 (783204-6), Rip Fence (164095-8), Plastic carrying case (824772-1)

5007MGA INCLUDES: Same as 5007MG, plus electric blade brake

Two built in LED job lights



SPECIFICATIONS

Blade diameter	7-1/4" (185 mm)
Arbor	5/8" (16 mm)
Max. cutting capacities:	
0°	2-1/2" (63.5)
45°	1-3/4" (45 mm)
50°	1-3/8" (35 mm)
No load speed	5,800 RPM
AMPS (120 V)	15.0
Overall length	12-1/2" (317 mm)
Net weight	10.1 lbs. (4.6 kg)
Shipping weight	12.3 lbs. (5.5 kg)

10-1/4" Circular Saw

5104



Portable circular saw for heavy-duty work

- Sturdy aluminum die cast base
- More compact blade case
- Large ergonomic grip
- Electric brake

STANDARD EQUIPMENT

INCLUDED: 10-1/4" C.T.SAW BLADE (A-94910), Hex Wrench 6 (783204-6), Guide Rule (165499-7)



SPECIFICATIONS

Blade diameter	10-1/4" (260 mm)
Arbor	5/8" (16 mm)
Max. cutting capacities:	
0°	3-3/4" (95 mm)
45°	2-3/4" (69 mm)
No load speed	3,800 RPM
AMPS (120 V)	15.0
Overall length	16" (405 mm)
Net weight	19.4 lbs. (8.8 kg)
Shipping weight	26.5 lbs. (12 kg)

7-1/4" Circular Saw

5007NFA
5007NFAK

High Power, Maximum cutting depth of 2-1/2" (63.5mm)

5007NFA Electric Brake, Twin LED lights

5007NFAK Plastic carrying case (824772-1), Electric Brake, Twin LED lights

- Bevel adjustment with positive stops at 22.5 and 45 degrees
- Built-in job light using LED light
- Heavy gauge aluminum base with ruler markings

STANDARD EQUIPMENT

5007NFA INCLUDES: Guide Rule (164095-8), Hex Wrench (783204-6), 7-1/4" 24 CT Black M-Force Saw Blade (A-94530)

5007NFAK INCLUDES: Guide Rule (164095-8), Hex Wrench (783204-6), PLASTIC CARRYING CASE (824772-1), 7-1/4" 24 CT Black M-Force Saw Blade (A-94530)



SPECIFICATIONS

Blade diameter	7-1/4" (185 mm)
Arbor	5/8" (16 mm)
Max. cutting capacities:	
0°	2-1/2" (63.5 mm)
45°	1-3/4" (45 mm)
50°	1-3/8" (35 mm)
No load speed	5,800 RPM
AMPS (120 V)	15
Overall length	12-1/2" (317 mm)
Net weight	11.0 lbs. (5.0 kg)
Shipping weight: 5007NFA	13.8 lbs. (6.2 kg)
Shipping weight: 5007NFAK	18.4 lbs. (8.3 kg)

8-1/4" Circular Saw

5008MGA



High performance magnesium blade case and base

- Bevel adjustment with positive stops at 22.5°, 45°, and 50°
- Two built in LED lights to illuminate the cut line
- Rubberized grips for comfort and control
- Electric brake

STANDARD EQUIPMENT

INCLUDED: 8-1/4" C.T.Saw Blade 24T (D-21521), Guide Rule (164095-8), Hex Wrench 6 (783204-6)

Built-in LED Job Light
Cutting depth capacity
of 3" (75.5mm)



SPECIFICATIONS

Blade diameter	8-1/4" (210 mm)
Arbor	5/8" (16 mm)
Max. cutting capacities:	
0°	3" (75.5 mm)
45°	2-1/4" (57 mm)
50°	2" (51.5 mm)
No load speed	5,200 RPM
AMPS (120 V)	15.0
Overall length	13-1/8" (332 mm)
Net weight	10.6 lbs. (4.8 kg)
Shipping weight	13.0 lbs. (5.6 kg)

7-1/4" Circular Saw

5007NF
5007NFK

AC/DC

High Power, Maximum cutting depth of 2-1/2" (63.5mm)

5007NF Twin LED lights

5007NFK Twin LED lights, Plastic carrying case

- Bevel adjustment with positive stops at 22.5 and 45 degrees
- Built-in job light using LED light
- Heavy gauge aluminum base with ruler markings

STANDARD EQUIPMENT

5007NF INCLUDES: Guide Rule (164095-8), Hex Wrench (783204-6), 7-1/4" 24 CT Silver M-Force Saw Blade (A-93859)

5007NFK INCLUDES: Guide Rule (164095-8), Hex Wrench (783204-6), PLASTIC CARRYING CASE (824772-1), 7-1/4" 24 CT Silver M-Force Saw Blade (A-93859)



SPECIFICATIONS

Blade diameter	7-1/4" (185 mm)
Arbor	5/8" (16 mm)
Max. cutting capacities:	
0°	2-1/2" (63.5 mm)
45°	1-3/4" (45 mm)
50°	1-3/8" (35 mm)
No load speed	5,800 RPM
AMPS (120V)	15
Overall length	12-1/2" (317 mm)
Net weight	11.0 lbs. (5.0 kg)
Shipping weight: 5007NF	14.6 lbs. (6.6 kg)
Shipping weight: 5007NFK	18.4 lbs. (8.3 kg)