

Predicting the Number of Shares of a Webpage

Alexandre Piche
260478404

Philippe Nguyen
260482336

Yash Lakhani
260500612

Abstract—Implementation of linear regression using the closed form and the gradient descent solutions. Incorporate the ridge regularization from scratch and used the lasso implementation from scikit-learn [1]. Explore dimension reduction algorithms.

I. INTRODUCTION

In the advertising industry it is of interest of predicting the popularity of a website to adequately set the price of ads on a given web page.

Simple tools like OLS have a surprising power, particularly when couple with regularization techniques such as the lasso or ridge.

II. IMPLEMENTATION OF OLS

$$Y = X\beta + \epsilon \quad (1)$$

A. Closed Form

With the traditional assumption of $X^T\epsilon = 0$ [2], i.e. that the error is uncorrelated with the matrix X , it is easy to solve for the weights, the resulting equation is given by

$$Y = X\beta + \epsilon \quad (2)$$

$$X^TY = X^TX\beta + X^T\epsilon \quad (3)$$

$$\hat{\beta} = (X^TX)^{-1}X^TY \quad (4)$$

B. Gradient Descent

It is computationally inefficient to invert large matrices such as the one provided for this exercise. It is more efficient to minimize the sum of squares $SSR(\beta) = \sum_{i=1}^n (y_i - \mathbf{x}_i\beta)^2$. We need to take the derivative to

$$\frac{\partial SSR(\beta)}{\partial \beta} = -2X^T(Y - X\beta) \quad (5)$$

cite Joelle's slides lecture 2

```
while  $\epsilon > 0.1$  and  $i < \text{max\_iterations}$  do
  hypothesis  $\leftarrow X^T\beta$ 
  loss  $\leftarrow \text{hypothesis} - Y$ 
  gradient  $\leftarrow 2 X^T \text{loss}$ 
   $\beta_{\text{new}} \leftarrow \beta - \frac{\alpha * \text{gradient}}{n}$ 
   $\epsilon \leftarrow \|\beta_{\text{new}} - \beta\|$ 
   $i \leftarrow i + 1$ 
   $\beta_{\text{new}} \leftarrow \beta$ 
end while
```

C. Supplementary information about the Weights

Only having the size of the weights is of little used if we cannot assess the fit of the model.

1) *Significance of our Weights*: It is possible that even if the weight is big that the variance is so high that it is not significantly different from zero.

2) *Adjusted R^2* : To assess the fit of the model, it is helpful to look at the percentage of the sum of square that is explained by our model.

3) *AIC and BIC*: Adding a variable cannot decrease the fit and almost always increase the prediction power of the model. However it might add noise to the prediction. AIC and BIC are a way to quantify the importance of adding a feature to our model by penalizing complexity.

III. MODEL COMPLEXITY AND DIMENSION REDUCTION

There is a total of ?? features, which seems like a lot. Given the high number of features, it might be preferable to reduce the dimension to achieve better out of sample prediction.

The widely accepted Occam's razor principle also suggests that parsimonious models generalize better than more complex model.

There is multiple way to avoid an over complex model that will generalize well for prediction, we will explore the performance of some of the most known of them.

A. Principal Component Analysis

Given the large dimension of the dataset and that some of the feature are highly correlated we decided to the principal component analysis algorithm to reduce the dimension by using principal component analysis (PCA) algorithm. We noticed that over 95% of the variance can be explained by the first 3 dimensions. The idea behind the PCA algorithm is trying to reconstruct X , by the minimal set of component. Namely we want to find a W such that

L linear basis vector

X is $K \times N$, where K is the number of feature and N the number of examples.

$$J(W, Z) = \|X - WZ^T\|_F^2 \quad (6)$$

Where W is $K \times L$ orthonormal and Z is $N \times L$ matrix [5] [1]

B. Ridge or L2-Regularization

$$\hat{\beta}^{\text{ridge}} = \underset{\beta}{\operatorname{argmin}} \left\{ \sum_{i=1}^N \left(y_i - \beta_0 - \sum_{j=1}^p x_{ij} \beta_j \right)^2 + \lambda \sum_{j=1}^p \beta_j^2 \right\} \quad (7)$$

[4]

The gradient will then be

$$\frac{\partial \text{SSR}(\hat{\beta}^{\text{ridge}})}{\partial \hat{\beta}^{\text{ridge}}} = -2X^T(Y - X\beta) + 2\lambda\|\beta\| \quad (8)$$

We can then add the following condition to our gradient descent algorithm

if 'Ridge' is True then

loss += 2 * $\lambda\|\beta\|$

end if

C. Lasso or L1-Regularization

Lasso can be used for features selection by setting some of the coefficients to zero. Note that we should be careful in dropping features because it might increase the bias of our model, however it will reduce its variance.

$$\hat{\beta}^{\text{lasso}} = \underset{\beta}{\operatorname{argmin}} \left\{ \sum_{i=1}^N \left(y_i - \beta_0 - \sum_{j=1}^p x_{ij} \beta_j \right)^2 + \lambda \sum_{j=1}^p |\beta_j| \right\} \quad (9)$$

There's no closed form solution for the lasso, since the solution is non-linear (due to the absolute value) [4]. We used the python library "Scikit Learn" [1] to estimate the lasso parameters.

D. Feature Normalization

It was numerically challenging to apply the gradient to feature that are of multiple order different from each other. We can normalize without changing their span, since it is a linear transformation.

IV. CROSS-VALIDATION

k-fold validation

complete randomization of the fold, by a random variable

A. Hyperparameters Optimization

Feature selection using the lasso function from [1]

Trying to avoid overfitting to be able to generalize to new examples.

we want to optimize the learning rate and the penalty rate

V. RESULTS

Also talk about the α parameter for the gradient descent.

Talk about the mean squared error (MSE) obtain when we varied the alpha of the lasso

VI. COMPLEMENTARY DATASETS

Huffington post

VII. CONCLUSION

The conclusion goes here.

ACKNOWLEDGMENT

The authors would like to thank...

REFERENCES

- [1] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay, "Scikit-learn: Machine learning in Python," *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.
- [2] R. Davidson and J. G. MacKinnon, *Econometric theory and methods*. Oxford University Press New York, 2004, vol. 5.
- [3] C. M. Bishop, *Pattern recognition and machine learning*. springer, 2006.
- [4] T. Hastie, R. Tibshirani, J. Friedman, and J. Franklin, "The elements of statistical learning: data mining, inference and prediction," *The Mathematical Intelligencer*, vol. 27, no. 2, pp. 83–85, 2005.
- [5] K. P. Murphy, *Machine learning: a probabilistic perspective*. MIT press, 2012.