# Monte Carlo Tree Search with Reinforcement Learning for Motion Planning

Philippe Weingertner<sup>1</sup> Minnie Ho<sup>2</sup> Andrey Timofeev<sup>3</sup> Sébastien Aubert<sup>1</sup> Guillermo Pita-Gil<sup>1</sup>

<sup>1</sup>Renault Software Labs

<sup>2</sup>Zoox Corporation

<sup>3</sup>Experis Switzerland

ITSC, September 2020

- Problem description
- 2 Problem formulation
- Algorithms
- 4 Results
- Conclusion

- Problem description
- 2 Problem formulation
- Algorithms
- Results
- Conclusion

## Motion Planning




Figure 1: Decision Making and Planning

## Two-Steps Path-Velocity Decomposition




Figure 2: Path Planner




Figure 3: Velocity Planner

## Avoiding multiple dynamic obstacles




Figure 4: Multilanes Crossing




Figure 5: Benchmark Setup

## Motion Planning Challenges

#### Dynamic Obstacles Avoidance

- Combinatorial explosion:
  - Usually 1 single dynamic obstacle is considered
  - We will consider up to 10 dynamic obstacles
- Non convex collision avoidance problem:
  - Proceed OR yield the way
  - OR constraints typically handled via Mixed Integer Programming

#### Real Time constraints

- Plan in less than 40 ms
- Plan a velocity profile for multiple (> 6) candidate paths

- Problem description
- 2 Problem formulation
- Algorithms
- 4 Results
- Conclusion

## Complexity Reduction via S-T projection




Figure 6: S-T projection

## Uncertainty Handling in S-T graphs




Figure 7: S-T graph

## Search Model: for A\*, MCTS and DQN algorithms

- States:  $S = \left\{ \frac{s}{s_{max}}, \frac{\dot{s}}{\dot{s}_{max}}, t \right\}$
- Desired Terminal State:  $\left(\frac{s_f}{s_{max}}, \frac{\dot{s_f}}{\dot{s}_{max}}\right)$
- Undesired Terminal States:

$$\mathcal{S} \cap \mathcal{C} = \left\{ \left( \frac{s_i}{s_{max}}, t_i \right) \right\}_{i=1..n}$$

- Actions:  $A = [-4, -2, -1, 0, 1, 2] \text{ ms}^{-2}$
- Transitions:

$$\begin{bmatrix} s \\ \dot{s} \end{bmatrix}_{t+1} = A_d \begin{bmatrix} s \\ \dot{s} \end{bmatrix}_t + B_d \begin{bmatrix} \ddot{s} \end{bmatrix}_t \text{ with } A_d = \begin{bmatrix} 1 & \Delta t \\ 0 & 1 \end{bmatrix}, B_d = \begin{bmatrix} \frac{\Delta t^2}{2} \\ \Delta t \end{bmatrix}$$

Reward or cost model:

$$R(s,a) = -0.001 - 1 imes 1$$
 [distance(ego, obj)  $\leq d_{
m col}$ ]  $-0.002 imes 1$  [ $a \leq -4$ ]

## MPC Model: for MPC algorithms

$$\min_{u_0,...,u_{T-1}} (x_T - x_{\text{ref}})^{\mathsf{T}} Q_T (x_T - x_{\text{ref}}) + \sum_{k=0}^{T-1} (x_k - x_{\text{ref}})^{\mathsf{T}} Q (x_k - x_{\text{ref}}) + u_k^{\mathsf{T}} R u_k$$

subject to 
$$\begin{cases} x_{k, \min} \leq x_k \leq x_{k, \max} \\ u_{k, \min} \leq u_k \leq u_{k, \max} \\ x_{k+1} = A_d x_k + B_d u_k \\ x_0 = x_{\text{init}} \\ \forall \left(t_{\text{col}}, s_{\text{col}}\right)_{i \in [1, 10]} \qquad \times_{t_{\text{col}}^{(i)}} [1] < s_{\text{col}}^{(i)} - \Delta_{\text{safety}} \text{ or } x_{t_{\text{col}}^{(i)}} [1] > s_{\text{col}}^{(i)} + \Delta_{\text{safety}} \end{cases}$$

$$\begin{bmatrix} s \\ \dot{s} \end{bmatrix}_{k+1} = A_d \begin{bmatrix} s \\ \dot{s} \end{bmatrix}_k + B_d \begin{bmatrix} \ddot{s} \end{bmatrix}_k \text{ with } A_d = \begin{bmatrix} 1 & \Delta t \\ 0 & 1 \end{bmatrix}, B_d = \begin{bmatrix} \frac{\Delta t^2}{2} \\ \Delta t \end{bmatrix}$$

◆ロト ◆団ト ◆ 恵ト ◆ 恵ト ・ 恵 ・ 夕久(\*)

- Problem description
- 2 Problem formulation
- 3 Algorithms
- 4 Results
- Conclusion

## Algorithms Benchmark

- Baselines: rules based
  - v1: focus on 1 single dynamic obstacle (with smallest TTC)
  - v2: emergency braking, same as v1 with maximum braking
  - v3: constant speed, no braking
- Oracles: exhaustive tree search based
  - A\*
  - DP: Dynamic Programming
- MCTS: sampling based tree search
- DDQN: reinforcement learning based
- MCTS-NNET: MCTS with a Neural Network heuristic (paper)
- MPC: Model Predictive Control based
  - default: with dynamic obstacles avoidance pre-convexification
  - latest: with Mixed Integer Programming and Elastic Model (new)

- Problem description
- 2 Problem formulation
- Algorithms
- 4 Results
- Conclusion

## Average Tests Results

Table 1: Results with multiple crossing-points tests

Mean over 89 Tests	Success	Runtime	Hardbrakes	Steps	Collision Speed
Baseline v1	43%	40 μs	0	43	13.04 m.s <sup>-1</sup>
Baseline v2	72%	40 μs	10.57	53	7.38 m.s $^{-1}$
MCTS	85%	3 ms	4.43	42	14.77 m.s <sup>-1</sup>
DDQN	84%	300 μs	5.15	62	$17.13 \; \mathrm{m.s^{-1}}$
MPC	82%	18 ms	6.22	47	8.72 m.s $^{-1}$
MCTS-NNET v1	98%	4 ms	4.79	62	19.04 m.s <sup>-1</sup>
MCTS-NNET v2	96%	4 ms	4.89	48	18.40 m.s <sup>-1</sup>
Oracle (A* search)	100%	6 sec	1.52	40	-

#### Distribution of Tests Results




Figure 8: Scores (higher is better) for Multiple Crossing-Points Tests

## Runtime vs Accuracy




Figure 9: Runtime vs Accuracy (Multiple Crossing-Points Tests)

## Very Latest MPC Improvements (not in the paper)

Mean	Success	Runtime	HardBrakes	Steps	Collision Speed
Baseline v3 (Constant Speed)	22%	$< 1 \mu s$	0.0	40.0	20.0 m.s <sup>-1</sup>
MPC_MIP	100%	22 ms	0.19	53.8	-
MPC_SIMPLEX	100%	6 ms	4.72	43.48	-
Oracle (A*)	100%	6 sec	0.48	33.1	-

Table 2: With Elastic Model and Big-M reformulation of disjunctive constraints

$$\min_{\substack{x \\ \text{s.t. } a^T x \leq b + y \text{ (safety distance constraint)}}} \sup_{\substack{x \\ \text{elastic slack variable: } y \in \mathbb{R}}$$
 
$$\max_{\substack{x \\ \text{mpc-mip}}}$$

- Problem description
- 2 Problem formulation
- Algorithms
- 4 Results
- Conclusion

#### Conclusion




Figure 10: Motion Planner

## Key Ideas and Improvements


#### MCTS improvements (paper)

- Faster search with a Neural Network heuristic
- Deep Learning (DL) to learn a faster version of an accurate model
- We do not depend on collected data for training
- DL to reduce computational load, not to make final decision
- Increase MCTS exploration when NNET heuristic confidence is low

### MPC improvements for Collision Avoidance in Real-Time (new)

- Mixed Integer Programming to handle disjunctive constraints
- Use an Elastic Collision Avoidance Model
- Linearization to enable optimization with a faster Simplex algorithm

#### References I



M. McNaughton, C. Urmson, J. M. Dolan, and J. Lee, *Motion planning for autonomous driving with a conformal spatiotemporal lattice*, 2011 IEEE International Conference on Robotics and Automation, May 2011, pp. 4889–4895.

B. Paden, M. Čáp, S. Z. Yong, D. Yershov, and E. Frazzoli, *A survey of motion planning and control techniques for self-driving urban vehicles*, IEEE Transactions on Intelligent Vehicles 1 (2016), no. 1, 33–55.

#### References II

- X. Qian, I. Navarro, A. de La Fortelle, and F. Moutarde, *Motion planning for urban autonomous driving using bézier curves and mpc*, 2016 IEEE 19th International Conference on Intelligent Transportation Systems (ITSC), 2016, pp. 826–833.
- Tommy Tram, Ivo Batkovic, Mohammad Ali, and Jonas Sjöberg, Learning when to drive in intersections by combining reinforcement learning and model predictive control, 2019 IEEE Intelligent Transportation Systems Conference (ITSC) (2019), 3263–3268.
- Yu Zhang, Huiyan Chen, Steven L Waslander, Tian Yang, Sheng Zhang, Guangming Xiong, and Kai Liu, *Toward a more complete, flexible, and safer speed planning for autonomous driving via convex optimization*, Sensors (Basel, Switzerland) 18 (2018), no. 7.