

INHERITANCE AND POLYMORPHISM

Why Inheritance?

- Suppose you will define classes to model circles, rectangles, and triangles. These classes have many common features. What is the best way to design these classes so to avoid redundancy?
- The answer is to use inheritance.

Inheritance

- In the Java language, classes can be *derived* from other classes, thereby *inheriting* fields and methods from those classes.
- A class that is derived from another class is called a *subclass* (also a *derived class*, *extended class*, or *child class*).
- The class from which the subclass is derived is called a *superclass* (also a *base class* or a *parent class*).

Inheritance

- Excepting *Object*, which has no superclass, every class has one and only one direct superclass (single inheritance).
- In the absence of any other explicit superclass, every class is implicitly a subclass of *Object*.
- A subclass inherits all the *members* (fields, methods, and nested classes) from its superclass.
- Constructors are not members, so they are not inherited by subclasses, but the constructor of the superclass can be invoked from the subclass.

GeometricObject Class

```
public class GeometricObject {
    private String color;
    private boolean filled;

    protected GeometricObject() {
        this.color = "white";
    }
    protected GeometricObject(String color, boolean filled) {
        this.color = color;
        this.filled = filled;
    }

    public String getColor() {
        return color;
    }
    public void setColor(String color) {
        this.color = color;
    }
    public boolean isFilled() {
        return filled;
    }
    public void setFilled(boolean filled) {
        this.filled = filled;
    }
    public void printInfo(){
        System.out.println("The Geometric is "+color);
    }
}
```

Circle Class

```
public class Circle extends GeometricObject {
    private double radius;

    public Circle() {
        this(1.0);
    }
    public Circle(double radius) {
        this(radius, "white", false);
    }
    public Circle(double radius, String color, boolean filled) {
        super(color, filled);
        this.radius = radius;
    }

    public double getRadius() {
        return radius;
    }
    public void setRadius(double radius) {
        this.radius = radius;
    }
    public double getArea() {
        return radius*radius*Math.PI;
    }
    public double getPerimeter() {
        return 2*radius*Math.PI;
    }
}
```

TestInheritance Class

```
public class TestInheritance {
    public static void main(String[] args){
        System.out.println("---Create a Circle c1---");
        Circle c1 = new Circle();
        if(c1 instanceof GeometricObject){
            System.out.println("c1 is a GeometricObject");}
        if(c1 instanceof Circle){
            System.out.println("c1 is a Circle");}
        if(c1 instanceof Object){
            System.out.println("c1 is an Object");}

        System.out.println("---Create a GeometricObject g1---");
        if(g1 instanceof Circle){
            System.out.println("g1 is a Circle");}
        if(g1 instanceof GeometricObject){
            System.out.println("g2 is a GeometricObject");}

        System.out.println("---Create a GeometricObject g2---");
        GeometricObject g2 = (GeometricObject) new Circle();
        if(g2 instanceof Circle){
            System.out.println("g2 is a Circle");}
        if(g2 instanceof GeometricObject){
            System.out.println("g2 is a GeometricObject");}
    }
}
```

Are superclass's Constructor Inherited?

- No. They are not inherited.
- They are invoked explicitly or implicitly.
- Explicitly using the `super` keyword.
- A constructor is used to construct an instance of a class. Unlike properties and methods, a superclass's constructors are not inherited in the subclass. They can only be invoked from the subclasses' constructors, using the keyword `super`. *If the keyword `super` is not explicitly used, the superclass's no-arg constructor is automatically invoked.*

Superclass's Constructor Is Always Invoked

- A constructor may invoke an overloaded constructor or its superclass's constructor. If none of them is invoked explicitly, the compiler puts super() as the first statement in the constructor. For example,

```
public A() {  
}
```

is equivalent to

```
public A() {  
    super();  
}
```

```
public A(double d) {  
    // some statements  
}
```

is equivalent to

```
public A(double d) {  
    super();  
    // some statements  
}
```

Using the Keyword `super`

- The keyword `super` refers to the superclass of the class in which `super` appears. This keyword can be used in two ways:
 - To call a superclass constructor
 - To call a superclass method
- **CAUTION !** You must use the keyword `super` to call the superclass constructor. Invoking a superclass constructor's name in a subclass causes a syntax error. Java requires that the statement that uses the keyword `super` appear first in the constructor.

Constructor Chaining

Constructing an instance of a class invokes all the superclasses' constructors along the inheritance chain. This is called *constructor chaining*.

```
public class Faculty extends Employee {
    public static void main(String[] args) {
        new Faculty();
    }

    public Faculty() {
        System.out.println("(4) Faculty's no-arg constructor is invoked");
    }
}

class Employee extends Person {
    public Employee() {
        this("(2) Invoke Employee's overloaded constructor");
        System.out.println("(3) Employee's no-arg constructor is invoked");
    }

    public Employee(String s) {
        System.out.println(s);
    }
}

class Person {
    public Person() {
        System.out.println("(1) Person's no-arg constructor is invoked");
    }
}
```

Trace Execution

```
public class Faculty extends Employee {
    public static void main(String[] args) {
        new Faculty();
    }

    public Faculty() {
        System.out.println("(4) Faculty's no-arg constructor is invoked");
    }
}

class Employee extends Person {
    public Employee() {
        this("(2) Invoke Employee's overloaded constructor");
        System.out.println("(3) Employee's no-arg constructor is invoked");
    }

    public Employee(String s) {
        System.out.println(s);
    }
}

class Person {
    public Person() {
        System.out.println("(1) Person's no-arg constructor is invoked");
    }
}
```

1. Start from the main method

Trace Execution

```
public class Faculty extends Employee {  
    public static void main(String[] args) {  
        new Faculty();  
    }  
  
    public Faculty() {  
        System.out.println("(4) Faculty's no-arg constructor is invoked");  
    }  
}  
  
class Employee extends Person {  
    public Employee() {  
        this("(2) Invoke Employee's overloaded constructor");  
        System.out.println("(3) Employee's no-arg constructor is invoked");  
    }  
  
    public Employee(String s) {  
        System.out.println(s);  
    }  
}  
  
class Person {  
    public Person() {  
        System.out.println("(1) Person's no-arg constructor is invoked");  
    }  
}
```

2. Invoke Faculty
constructor

Trace Execution

```
public class Faculty extends Employee {
    public static void main(String[] args) {
        new Faculty();
    }

    public Faculty() {
        System.out.println("(4) Faculty's no-arg constructor is invoked");
    }
}

class Employee extends Person {
    public Employee() {
        this("(2) Invoke Employee's overloaded constructor");
        System.out.println("(3) Employee's no-arg constructor is invoked");
    }

    public Employee(String s) {
        System.out.println(s);
    }
}

class Person {
    public Person() {
        System.out.println("(1) Person's no-arg constructor is invoked");
    }
}
```

3. Invoke Employee's no-arg constructor

Trace Execution

```
public class Faculty extends Employee {  
    public static void main(String[] args) {  
        new Faculty();  
    }  
  
    public Faculty() {  
        System.out.println("(4) Faculty's no-arg constructor is invoked");  
    }  
}  
  
class Employee extends Person {  
    public Employee() {  
        this("(2) Invoke Employee's overloaded constructor");  
        System.out.println("(3) Employee's no-arg constructor is invoked");  
    }  
  
    public Employee(String s) {  
        System.out.println(s);  
    }  
}  
  
class Person {  
    public Person() {  
        System.out.println("(1) Person's no-arg constructor is invoked");  
    }  
}
```

4. Invoke Employee(String)
constructor

Trace Execution

```
public class Faculty extends Employee {  
    public static void main(String[] args) {  
        new Faculty();  
    }  
  
    public Faculty() {  
        System.out.println("(4) Faculty's no-arg constructor is invoked");  
    }  
}  
  
class Employee extends Person {  
    public Employee() {  
        this("(2) Invoke Employee's overloaded constructor");  
        System.out.println("(3) Employee's no-arg constructor is invoked");  
    }  
  
    public Employee(String s) {  
        System.out.println(s);  
    }  
}  
  
class Person {  
    public Person() {  
        System.out.println("(1) Person's no-arg constructor is invoked");  
    }  
}
```

5. Invoke Person()
constructor

Trace Execution

```
public class Faculty extends Employee {  
    public static void main(String[] args) {  
        new Faculty();  
    }  
  
    public Faculty() {  
        System.out.println("(4) Faculty's no-arg constructor is invoked");  
    }  
}  
  
class Employee extends Person {  
    public Employee() {  
        this("(2) Invoke Employee's overloaded constructor");  
        System.out.println("(3) Employee's no-arg constructor is invoked");  
    }  
  
    public Employee(String s) {  
        System.out.println(s);  
    }  
}  
  
class Person {  
    public Person() {  
        System.out.println("(1) Person's no-arg constructor is invoked");  
    }  
}
```

6. Execute println

Trace Execution

```
public class Faculty extends Employee {  
    public static void main(String[] args) {  
        new Faculty();  
    }  
  
    public Faculty() {  
        System.out.println("(4) Faculty's no-arg constructor is invoked");  
    }  
}  
  
class Employee extends Person {  
    public Employee() {  
        this("(2) Invoke Employee's overloaded constructor");  
        System.out.println("(3) Employee's no-arg constructor is invoked");  
    }  
  
    public Employee(String s) {  
        System.out.println(s);  
    }  
}  
  
class Person {  
    public Person() {  
        System.out.println("(1) Person's no-arg constructor is invoked");  
    }  
}
```



7. Execute println

Trace Execution

```
public class Faculty extends Employee {  
    public static void main(String[] args) {  
        new Faculty();  
    }  
  
    public Faculty() {  
        System.out.println("(4) Faculty's no-arg constructor is invoked");  
    }  
}  
  
class Employee extends Person {  
    public Employee() {  
        this("(2) Invoke Employee's overloaded constructor");  
        System.out.println("(3) Employee's no-arg constructor is invoked");  
    }  
  
    public Employee(String s) {  
        System.out.println(s);  
    }  
}  
  
class Person {  
    public Person() {  
        System.out.println("(1) Person's no-arg constructor is invoked");  
    }  
}
```



8. Execute println

Trace Execution

```
public class Faculty extends Employee {
    public static void main(String[] args) {
        new Faculty();
    }

    public Faculty() {
        System.out.println("(4) Faculty's no-arg constructor is invoked");
    }
}

class Employee extends Person {
    public Employee() {
        this("(2) Invoke Employee's overloaded constructor");
        System.out.println("(3) Employee's no-arg constructor is invoked");
    }

    public Employee(String s) {
        System.out.println(s);
    }
}

class Person {
    public Person() {
        System.out.println("(1) Person's no-arg constructor is invoked");
    }
}
```



9. Execute println

Declaring a Subclass and Call Superclass Methods

- A subclass extends properties and methods from the superclass. You can also:
 - Add new properties
 - Add new methods
 - Override the methods of the superclass
- You can call superclass' methods by using a `super` keyword

Overriding Methods in the Superclass

- A subclass inherits methods from a superclass. Sometimes it is necessary for the subclass to modify the implementation of a method defined in the superclass. This is referred to as *method overriding*.

```
public class Circle extends GeometricObject {  
    // Other methods are omitted  
  
    /** Override the printInfo method defined in GeometricObject */  
    public void printInfo() {  
        super.printInfo();  
        System.out.println( "It is a circle with radius of " + radius);  
    }  
}
```

Overriding Methods in the Superclass

- An instance method can be overridden only if it is accessible. Thus a private method cannot be overridden, because it is not accessible outside its own class. If a method defined in a subclass is private in its superclass, the two methods are completely unrelated.
- Like an instance method, a static method can be inherited. However, a static method cannot be overridden. If a static method defined in the superclass is redefined in a subclass, the method defined in the superclass is hidden.

Overriding vs. Overloading

```
public class Test {  
    public static void main(String[] args) {  
        A a = new A();  
        a.p(10);  
        a.p(10.0);  
    }  
}  
  
class B {  
    public void p(double i) {  
        System.out.println(i * 2);  
    }  
}  
  
class A extends B {  
    // This method overrides the method in B  
    public void p(double i) {  
        System.out.println(i);  
    }  
}
```

```
public class Test {  
    public static void main(String[] args) {  
        A a = new A();  
        a.p(10);  
        a.p(10.0);  
    }  
}  
  
class B {  
    public void p(double i) {  
        System.out.println(i * 2);  
    }  
}  
  
class A extends B {  
    // This method overloads the method in B  
    public void p(int i) {  
        System.out.println(i);  
    }  
}
```


Polymorphism

```
public class PolymorphismDemo {
    public static void main(String[] args) {
        m(new GraduateStudent());
        m(new Student());
        m(new Person());
        m(new Object());
    }

    public static void m(Object x) {
        System.out.println(x.toString());
    }
}

class GraduateStudent extends Student {
}

class Student extends Person {
    public String toString() {
        return "Student";
    }
}

class Person extends Object {
    public String toString() {
        return "Person";
    }
}
```

- An object of a subtype can be used wherever its supertype value is required. This feature is known as *polymorphism*.

Casting Objects

- You have already used the casting operator to convert. In the preceding section, the statement variables of one primitive type to another. *Casting* can also be used to convert an object of one class type to another within an inheritance hierarchy `m(new Student())`; assigns the object `new Student()` to a parameter of the `Object` type.
- This statement is equivalent to:

```
Object o = new Student(); // Implicit casting  
m(o);
```

The statement `Object o = new Student()`, known as implicit casting, is legal because an instance of `Student` is automatically an instance of `Object`.

Casting from Superclass to Subclass

- Explicit casting must be used when casting an object from a superclass to a subclass. This type of casting may not always succeed.

```
Apple x = (Apple)fruit;
```

```
Orange x = (Orange)fruit;
```

The instanceof Operator

- Use the `instanceof` operator to test whether an object is an instance of a class:

```
Object myObject = new Circle();
... // Some lines of code
/** Perform casting if myObject is an instance of
    Circle */
if (myObject instanceof Circle) {
    System.out.println("The circle diameter is " +
        ((Circle)myObject).getDiameter());
    ...
}
```

The `final` Modifier

- The `final` class cannot be extended:

```
final class Math {  
    ...  
}
```

- The `final` variable is a constant:

```
final static double PI = 3.14159;
```

- The `final` method cannot be overridden by its subclasses.