STATOIL / NORSK HYDRO OFFSHORE OPERATIONS

DRILLING SUMMARY REPORT — WELL: 6407/7-2

Rig: Dyvi Delta | Licence: PL107 | Field: Njård

SECTION 1: GENERAL DRILLING CHRONOLOGY & BIT PERFORMANCE

Day 01: Spudded 36in conductor, drilled to 600m. Mud weight 1.08 SG. No gas peaks.

Day 02: Spudded 36in conductor, drilled to 780m. Mud weight 1.08 SG. No gas peaks.

Day 03: Spudded 36in conductor, drilled to 960m. Mud weight 1.08 SG. No gas peaks.

Day 04: Spudded 36in conductor, drilled to 1140m. Mud weight 1.08 SG. No gas peaks.

Day 05: Spudded 36in conductor, drilled to 1320m. Mud weight 1.08 SG. No gas peaks.

Day 06: Spudded 36in conductor, drilled to 1500m. Mud weight 1.08 SG. No gas peaks.

Day 07: Spudded 36in conductor, drilled to 1680m. Mud weight 1.08 SG. No gas peaks.

Day 08: Spudded 36in conductor, drilled to 1860m. Mud weight 1.08 SG. No gas peaks.

Day 09: Spudded 36in conductor, drilled to 2040m. Mud weight 1.08 SG. No gas peaks.

Day 10: Spudded 36in conductor, drilled to 2220m. Mud weight 1.08 SG. No gas peaks.

Day 11: Spudded 36in conductor, drilled to 2400m. Mud weight 1.08 SG. No gas peaks.

Day 12: Spudded 36in conductor, drilled to 2580m. Mud weight 1.08 SG. No gas peaks.

Day 13: Spudded 36in conductor, drilled to 2760m. Mud weight 1.08 SG. No gas peaks.

Day 14: Spudded 36in conductor, drilled to 2940m. Mud weight 1.08 SG. No gas peaks.

Day 15: Spudded 36in conductor, drilled to 3120m. Mud weight 1.08 SG. No gas peaks.

Norsk Hydro

CORE LOG

SCALE: 1 : 200

WELL : 6407/7-2

DATE : 10/08-1987, rev. 1989

COUNTRY	Norway
LICENCE	PL107
FIELD	Njård
OWNERS	Norsk Hydro, Statoil, Mobil
COORDINATES	N 64° 24' 15.10" E 07° 11' 22.40"
ELEVATION KB	27m
WATER DEPTH	330m
TOTAL DEPTH (DRILLER)	3650m
TOTAL DEPTH (LOGGER)	3645m
FORMATION AT TOTAL DEPTH	Åre Fm.
LOGGERS DEPTH - DRILLERS DEPTH	C1-C8: 0.8m
GEOLOGISTS	T.D., J.Gj.
COMMENTS	Target table is on Page 2!

GROUP/FORMATION: Tilje / Åre Fm.

AGE: Tidlig Jura

OTHER CORES IN WELL

NO	GROUP/FORMATION

CORES DESCRIBED IN THIS LOG

NO	INTERVAL (m)	RECOVERY (%)
1	3150.0 - 3165.5	98.0
2	3165.5 - 3182.0	100
3	3182.0 - 3198.5	95.5
4	3198.5 - 3215.0	92.0
5	3215.0 - 3232.0	100
6	3232.0 - 3248.5	97.5
7	3248.5 - 3265.0	100
8	3265.0 - 3280.0	96.0