STATOIL / NORSK HYDRO OFFSHORE OPERATIONS

DRILLING SUMMARY REPORT — WELL: 6506/12-3

Rig: Dyvi Delta | Licence: PL094 | Field: Smørbukk Sør

SECTION 1: GENERAL DRILLING CHRONOLOGY & BIT PERFORMANCE

Day 01: Spudded 36in conductor, drilled to 600m. Mud weight 1.08 SG. No gas peaks.

Day 02: Spudded 36in conductor, drilled to 780m. Mud weight 1.08 SG. No gas peaks.

Day 03: Spudded 36in conductor, drilled to 960m. Mud weight 1.08 SG. No gas peaks.

Day 04: Spudded 36in conductor, drilled to 1140m. Mud weight 1.08 SG. No gas peaks.

Day 05: Spudded 36in conductor, drilled to 1320m. Mud weight 1.08 SG. No gas peaks.

Day 06: Spudded 36in conductor, drilled to 1500m. Mud weight 1.08 SG. No gas peaks.

Day 07: Spudded 36in conductor, drilled to 1680m. Mud weight 1.08 SG. No gas peaks.

Day 08: Spudded 36in conductor, drilled to 1860m. Mud weight 1.08 SG. No gas peaks.

Day 09: Spudded 36in conductor, drilled to 2040m. Mud weight 1.08 SG. No gas peaks.

Day 10: Spudded 36in conductor, drilled to 2220m. Mud weight 1.08 SG. No gas peaks.

Day 11: Spudded 36in conductor, drilled to 2400m. Mud weight 1.08 SG. No gas peaks.

Day 12: Spudded 36in conductor, drilled to 2580m. Mud weight 1.08 SG. No gas peaks.

Day 13: Spudded 36in conductor, drilled to 2760m. Mud weight 1.08 SG. No gas peaks.

Day 14: Spudded 36in conductor, drilled to 2940m. Mud weight 1.08 SG. No gas peaks.

Day 15: Spudded 36in conductor, drilled to 3120m. Mud weight 1.08 SG. No gas peaks.

CASING AND ANNULAR HYDRAULICS — WELL: 6506/12-3

Casing String 1: 13-3/8in shoe set at 1200m. FIT tested to 1.75 SG equivalent.

Casing String 2: 13-3/8in shoe set at 1350m. FIT tested to 1.75 SG equivalent.

Casing String 3: 13-3/8in shoe set at 1500m. FIT tested to 1.75 SG equivalent.

Casing String 4: 13-3/8in shoe set at 1650m. FIT tested to 1.75 SG equivalent.

Casing String 5: 13-3/8in shoe set at 1800m. FIT tested to 1.75 SG equivalent.

Casing String 6: 13-3/8in shoe set at 1950m. FIT tested to 1.75 SG equivalent.

Casing String 7: 13-3/8in shoe set at 2100m. FIT tested to 1.75 SG equivalent.

Casing String 8: 13-3/8in shoe set at 2250m. FIT tested to 1.75 SG equivalent.

Casing String 9: 13-3/8in shoe set at 2400m. FIT tested to 1.75 SG equivalent.

Casing String 10: 13-3/8in shoe set at 2550m. FIT tested to 1.75 SG equivalent.

Casing String 11: 13-3/8in shoe set at 2700m. FIT tested to 1.75 SG equivalent.

Casing String 12: 13-3/8in shoe set at 2850m. FIT tested to 1.75 SG equivalent.

Norsk Hydro

CORE LOG

SCALE: 1 : 200

WELL : 6506/12-3

DATE : 05/1986, rev. 06-89

COUNTRY	Norge
LICENCE	PL094
FIELD	Smørbukk Sør
OWNERS	Statoil, Agip, Total, Norsk Hydro
COORDINATES	N 65° 11' 40.12" E 06° 48' 22.05"
ELEVATION KB	26m
WATER DEPTH	275m
TOTAL DEPTH (DRILLER)	4300m
TOTAL DEPTH (LOGGER)	4296m
FORMATION AT TOTAL DEPTH	Åre Fm.
LOGGERS DEPTH - DRILLERS DEPTH	C1-C7: 1.0m
GEOLOGISTS	J.F.B., T.D.
COMMENTS	Target table is on Page 3!

GROUP/FORMATION: Garn / Ile Fm.

AGE: Mallos Jura

OTHER CORES IN WELL

NO	GROUP/FORMATION

CORES DESCRIBED IN THIS LOG

NO	INTERVAL (m)	RECOVERY (%)
1	3850.0 - 3868.5	100
2	3868.5 - 3886.0	94.0
3	3886.0 - 3904.2	99.0
4	3904.2 - 3922.0	97.5
5	3922.0 - 3940.0	100
6	3940.0 - 3957.5	93.0
7	3957.5 - 3975.0	100