Technical report: Sokoto Rainfall Cover

Capstone Project: Technical Implementation and Development Progress · Chinemerem Judith Ugbo · Supervisor: Dr Aaron Izang

A weather-index insurance platform on Ethereum: automatic drought cover for smallholder farmers in Sokoto State, Nigeria. *Repository:* github.com/Phinatech/Capstone-project · *Live:* sokoto-cover.pages.dev · *Chain:* Ethereum Sepolia

1. Scope Alignment & Feature Validation

The approved scope proposed a blockchain-based weather-index insurance system in which rainfall is measured by multiple independent sources, policies are sold and settled by smart contract without a claims process, and farmers, field agents and administrators manage cover through a web application. The delivered system matches that scope. One planned element (SMS delivery) is implemented but optional in configuration, and fiat settlement is deferred because it requires a licensed payment provider.

Planned Feature	Intended Purpose	Current Status	Evidence
Smart contracts: policy sale, premium, payout reserve	Sell cover; guarantee payout trustlessly	**Completed** · M1 Contracts	WeatherIndexInsurance.sol; 56 tests; Policy #0 bought and paid on Sepolia
Multi-source oracle with reputation-weighted aggregation	One source cannot decide a claim	**Completed** · M2 Oracle	OracleAggregator.sol; 3 live sources; simulator Fig. 07
Automated oracle relayer and settlement keeper	Report rainfall and pay farmers unattended	**Completed** · M2 Oracle	relayer.ts, settlement.ts; Policy #0's live payout ran autonomously
Farmer portal (buy cover,	Self-service cover with a wallet	**Completed** · M3 Portals	/farmer/*; screenshots 02, 03,

Planned Feature	Intended Purpose	Current Status	Evidence
monitor, payouts)			04
Field-agent portal (sell cover, naira receipts)	Reach farmers without wallets	**Completed** · M3 Portals	/agent/*; receipts verified server-side against the chain
Admin console (policies, farmers and agents, analytics)	Operate and audit the scheme	**Completed** · M3 Portals	/admin/*; screenshots 05, 06
Oracle research tools (consensus simulator, backtest)	Study and demonstrate the consensus design	**Completed** · M4 Research	/admin/backtest; 121 historical dekads (backtest-results.md)
Notifications (in-app, email codes, SMS/Telegram)	Tell farmers about purchases and payouts	**Completed (SMS optional)** · M4 Research	real event notifications; email codes; SMS behind SMS_PROVIDER
Testing and security audit	Validate and harden the system	**Completed** · M5 Validation	292 tests; security-audit.md, fixes pinned by regressions
Deployment (public site and testnet)	Working product, end to end	**Completed** · M5 Validation	sokoto-cover.pages.dev + Render + Sepolia
Fiat settlement (naira off-ramp)	Pay farmers in naira	**Not implemented; justified** · M6 Future	needs a licensed provider; receipts record the naira leg; future work

Scope changes. Nothing was dropped for convenience. The naira leg was designed as receipted off-chain settlement from the start, since a licensed off-ramp is beyond a student project. Deployment widened from a local chain to live Sepolia, which added wallet integration, RPC resilience and network-safety work.

2. Technical Product Demonstration

The walkthrough video (linked in the README) covers these in order.

A. Core functionalities. Policy purchase as agent and as farmer; the farmer dashboard and payouts ledger; the admin's oracle evaluation view; the consensus simulator corrupting one source; the backtest.

B. Technical requirements. Each screen is shown wired end to end: React/TypeScript to Express/TypeScript to Firebase to ethers.js to Solidity on Sepolia, fed by three live rainfall APIs.

C. Testing with inputs. Wrong premium, closed window, insufficient pool capacity, wrong wallet network, invalid codes and role escalation are each shown refusing safely with a plain-language error.

D. Testing strategies. Unit and functional testing plus integration testing (section 3.3). **E. Performance and compatibility.** Measured latency and bundle sizes (section 3.4), desktop and mobile layouts, and a live cross-browser check.

3. Code Quality and Technical Implementation

3.1 OOP principles and architecture

The codebase is organised by layer (`blockchain/`, `backend/`, `frontend/`) with clear separation of concerns and no monolithic scripts.

Encapsulation and abstraction. Each store (`createUserStore`, `createSessionStore`, `createAgentStore`, `createAuthCodeStore`) hides its persistence behind one `StorePersistence` interface, so the application does not care whether records live in Firestore, a JSON file or memory. The policy layer hides its providers behind `usePolicies()` the same way.

Polymorphism. Persistence backends are interchangeable strategies (production, development, tests) chosen once at start-up. The consensus simulator runs three aggregation strategies behind one interface.

Inheritance and reusable components. `ErrorBoundary` extends `React.Component` once and protects every route. Typed contracts (`User`, `Policy`, `StorePersistence`) are implemented by interchangeable parts, and shared components (`PolicyBrowser`, `PageHeader`, `Avatar`) serve all three portals.

Dependency injection and modularity. `createAuthRouter({ users, sessions, authCodes })` receives its collaborators, so end-to-end tests exercise the real router against

isolated stores. Pure utilities (utils/oracle.ts, utils/currency.ts) and the Context tree layer shared behaviour without duplication.

3.2 Algorithms and problem-solving

Reputation-weighted consensus. Dekad rainfall is a weighted average over reporting sources, with weights from peer-agreement scores, so a corrupt source loses weight at once and keeps losing it. The simulator shows a corrupted feed moving the aggregate by 9% under reputation weights and 59% under equal weights.

Out-of-sample backtest. Weights are learned from inverse MSE on all years except the scored year, with 2,000-resample bootstrap confidence intervals, so the evaluation never fits the test data (backtest-results.md).

Fixed-point time-series arithmetic. Rainfall is stored as integer hundredths of millimetres and dekads as period ids (YYYYMMD). A window sums exactly its period set, so settlement is exact and auditable.

Concurrency-safe persistence. Stores serialise writes through a promise chain and write via temporary file and rename, making each update atomic. The relayer fetches sources with bounded concurrency (mapLimit) to respect free API tiers.

Security primitives. scrypt password hashing, constant-time API-key comparison, single-use attempt-capped verification codes, and per-hour rate limits, each with regression tests.

3.3 Testing and validation

Strategy 1: unit and functional testing. Selected because the contract invariants are the product's fairness guarantees. The suite runs 56 Solidity tests (including a fuzz test over pool reserves), 203 backend unit tests and 20 frontend tests. It covers premium maths (10% of the payout, rounded up), reverting sales the pool cannot cover, payouts that happen once and only below threshold, and every audit finding pinned by a named regression test. Result: 292 tests green, and the suite caught real defects (a GET-versus-POST resend route, a password stored in clear text at seed time, tests writing into production data), each fixed and pinned.

Strategy 2: integration and end-to-end testing. Selected because the guarantees span HTTP, storage, wallet and chain. Mocha drives the contracts through ethers.js as the application does (13 scenarios); auth routes run against a real Express server with cookie jars; the deployed system was exercised live, and the first policy was bought and paid out autonomously. Result: flows verified in

production. Failures traced to wallet infrastructure (stale RPC state, wrong network) and led to hardening: gas pre-estimated on the app's own RPC, account switches followed, wrong-chain signing refused.

Validation. Invalid codes, wrong premiums, expired windows, role-escalation payloads and unreachable RPCs each produce a plain-language error rather than provider jargon.

3.4 Performance and compatibility

Measurement	Result	Conditions
REST API latency	0.44 to 0.82 s per read	Render free tier, warm
Frontend build	8.3 s; 1.4 MB JS across lazy chunks	Vite production build, code split
Backend test suite	~6.5 s, 203 tests	Node 22
Layout	Responsive from desktop down to 390 px	captures 02, 09
Browsers	Chrome, Edge, Firefox, Safari checked on the same build	walkthrough video, Scene 7
Wallet	MetaMask on Sepolia, hardened against stale RPCs and wrong networks	EIP-1193 only; no browser-specific APIs

The farmer side targets low-power hardware: the layout renders at 390 px, naira figures degrade gracefully when FX providers are down, and chain reads retry through RPC hiccups.

3.5 Engineering quality

Commits are focused and imperative, naming is consistent, and comments explain decisions rather than restating code. Both workspaces compile under strict TypeScript. Supporting evidence lives in docs/screenshots/ (10 figures), docs/backtest-results.md, docs/security-audit.md, docs/debugging-journal.md and the live deployment.