

Work Order Data Model

All 7 tables behind the PM app and TSR/Advisor field app, with every business column, primary keys, and foreign-key relationships — read straight from the generated Dataverse models, not guessed.

7 tables

cre2b_ publisher prefix

shared by PM app + TSR/Advisor app

READING THIS DIAGRAM

PK primary key

FK foreign key (lookup)

text looks like a relationship, isn't — see notes on the last page

Standard Dataverse audit/ownership columns (`createdby`, `createdon`, `modifiedby`, `modifiedon`, `ownerid`, `statecode`, `statuscode` and their name/yomi variants) exist on every table but are omitted — same on all 7, not worth repeating.

WHAT'S ON THE NEXT PAGE

The full entity-relationship diagram, one table per box, with every business column and its type. Foreign keys are drawn as lines between tables; the label on each line says what the relationship means.

SERVICECENTER			
guid	cre2b_servicecenterid	PK	
string	cre2b_locationname		required
string	cre2b_locationalphacode		natural key, e.g. ATL
int	cre2b_locationnumber		
string	cre2b_city		
string	cre2b_state		
string	cre2b_zipcode		
string	cre2b_streetaddress1		
string	cre2b_streetaddress2		
string	cre2b_district		
string	cre2b_region		
string	cre2b_operatingcompany		
string	cre2b_facilitytype		
string	cre2b_centeroperatinghours		
string	cre2b_localphonenumber		
string	cre2b_tollfreephonenumber		
string	cre2b_wocontactname		
string	cre2b_wocontactphone		
string	cre2b_facilitymaintenancemanagername		
string	cre2b_supplychainmanagername		
choice	cre2b_companyfuelavailability		
choice	cre2b_cornetstatus		
choice	cre2b_drivercenterstatus		
choice	cre2b_hubpresence		
choice	cre2b_shoppresence		
int	cre2b_revenuedoors		
int	cre2b_totalnumberofdoors		

WORKORDERBATCH			
guid	cre2b_workorderbatchid	PK	
string	cre2b_batchnumber		Autonumber, e.g. BATCH-000001

PERSONNEL			
guid	cre2b_personnelid	PK	
string	cre2b_personnelid1		legacy id text, not the PK
string	cre2b_fullname		
choice	cre2b_role		TSR / Advisor
choice	cre2b_status		Available / Unavailable
string	cre2b_manager		plain text, not a lookup

FEEDBACK			
guid	cre2b_feedbackid	PK	
string	cre2b_feedbacktext		
datetime	cre2b_submittedat		
string	cre2b_submittedby		plain text, no FK to Personnel or WorkOrder

assigned to

groups (optional)

assigned to

closest #1, TSR+Advisor pool

closest #2, TSR+Advisor pool

closest #3, TSR+Advisor pool

closest #1, TSR-only pool

closest #2, TSR-only pool

closest #3, TSR-only pool

WORKORDER			
guid	cre2b_workorderid	PK	
string	cre2b_wonumber		unique, e.g. WO-0000001
choice	cre2b_status		
choice	cre2b_wotype		
choice	cre2b_producttype		
choice	cre2b_problemtype		
string	cre2b_problemdescription		
string	cre2b_problemdetails		
string	cre2b_productpartnumberscomments		
string	cre2b_roomarea		
string	cre2b_networkcircuitcomputernamedetail		
string	cre2b_circuitdetails		
string	cre2b_computerhostname		
string	cre2b_link		
datetime	cre2b_expirationdate		
string	cre2b_projectname		
choice	cre2b_assignnpool		
string	cre2b_trackingnumber		
decimal	cre2b_mileage		
decimal	cre2b_traveltimeminutes		
string	cre2b_closingcomment		
string	cre2b_returnvisitnote		
datetime	cre2b_createdat		custom, not system createdon
string	cre2b_createdby		custom text, not system lookup
guid	cre2b_servicecenter	FK	
guid	cre2b_assignedto	FK	
guid	cre2b_batch	FK	optional

has

WORKORDERSTATUSHISTORY			
guid	cre2b_workorderstatushistoryid	PK	
string	cre2b_historynumber		
choice	cre2b_actiontype		
choice	cre2b_fromstatus		
choice	cre2b_tostatus		
datetime	cre2b_changedat		
string	cre2b_changedby		unused, app relies on system createdby
string	cre2b_comment		
guid	cre2b_workorder	FK	

SERVICECENTERPROXIMITY			
guid	cre2b_servicecenterproximityid	PK	
string	cre2b_proximityname		
guid	cre2b_servicecenterlookup	FK	
string	cre2b_servicecenter		unused text mirror
guid	cre2b_closesttsradvisor	FK	
guid	cre2b_closest2tsradvisor	FK	
guid	cre2b_closest3tsradvisor	FK	
guid	cre2b_closesttsr1tsronly	FK	
guid	cre2b_closesttsr2tsronly	FK	
guid	cre2b_closesttsr3tsronly	FK	
string	cre2b_closesttsr1		unused text mirror
string	cre2b_closesttsr2		unused text mirror
string	cre2b_closesttsr3		unused text mirror
string	cre2b_closesttsroradvisor1		unused text mirror
string	cre2b_closesttsroradvisor2		unused text mirror
string	cre2b_closesttsroradvisor3		unused text mirror
decimal	cre2b_distancetotsr1		
decimal	cre2b_distancetotsr2		
decimal	cre2b_distancetotsr3		
decimal	cre2b_distancetoclosesttsroradvisor1		
decimal	cre2b_distancetoclosesttsroradvisor2		
decimal	cre2b_distancetoclosesttsroradvisor3		

CHOICE SETS

cre2b_status

WorkOrder · also FromStatus / ToStatus
on WorkOrderStatusHistory

- 1 Assigned
- 2 Accepted
- 3 Scheduled
- 4 OnSite
- 5 ReturnVisit
- 6 Closed-Completed
- 7 Closed-Canceled

cre2b_producttype

WorkOrder

- 1 Desktop PC
- 2 Digital Signage
- 3 Dimensioner
- 4 Genesis
- 5 Laptop
- 6 Phone
- 7 Printer
- 8 Scanner
- 9 Tablet
- 10 Network
- 11 Router
- 12 Server
- 13 Switch
- 14 UPS
- 15 WAP
- 16 Other

cre2b_problemtype

WorkOrder

- 1 Install
- 2 Upgrade
- 3 Hardware
- 4 Software
- 5 Remove
- 6 Other

cre2b_wotype

WorkOrder

- 1 Planned

cre2b_assignpool

WorkOrder

- 1 TSR Only
- 2 TSR + Advisor

cre2b_actiontype

WorkOrderStatusHistory

- 1 Status Change
- 2 Reassign
- 3 Transfer
- 4 Comment/Update

cre2b_role

Personnel

- 1 TSR
- 2 Advisor
- 3 Role (unused placeholder value)

cre2b_status

Personnel

- 1 Available
- 2 Unavailable

WORTH KNOWING BEFORE YOU BUILD AGAINST THIS

- ⚠ **Feedback isn't actually linked to anything.** No lookup to WorkOrder or Personnel exists — `cre2b_submittedby` is a plain text field. If feedback needs to trace back to a specific work order, that's a schema addition, not something to query around.
- ⚠ **ServiceCenterProximity carries duplicate-looking columns.** Real lookups (`cre2b_closest1tsradvisor` , `cre2b_closesttsr1tsronly` , etc.) sit alongside similarly-named plain text fields (`cre2b_closesttsr1` , `cre2b_closesttsroradvisor1`) that are not relationships and aren't populated by the app. Don't confuse the two when reading or writing this table.
- ⚠ **Some tables have two "who/when" fields.** WorkOrder's `cre2b_createdat` / `cre2b_createdby` and WorkOrderStatusHistory's `cre2b_changedby` are custom text/date fields that duplicate what Dataverse's built-in `createdon` / `createdby` already track. The app deliberately writes to the built-in fields for history rows and leaves `cre2b_changedby` unset — worth knowing before assuming it's populated.
- ⚠ **Five ServiceCenter choice columns aren't detailed here** (`cre2b_companyfuelavailability` , `cre2b_cornetstatus` , `cre2b_drivercenterstatus` , `cre2b_hubpresence` , `cre2b_shoppresence`) — their option values weren't pulled from the generated model for this document, so they're marked as choice type only. Check `Cre2b_servicecentersModel.ts` directly if you need the actual values.

Generated from `src/generated/models/*.ts` in `pm-app` · `cre2b_` is the Dataverse publisher prefix for this environment