

White-Box Fault Analysis of a Kubernetes-Style Control Plane: Measuring Reconciliation Correctness and Convergence Under Fault Conditions

Aditya Pathak
Independent Researcher
Noida, India
aditya2pathak@gmail.com

May 2026

Abstract

Fault injection studies of Kubernetes control planes have historically operated in a black-box manner: faults are injected into production-grade systems and external symptoms are observed, but internal state transitions remain opaque. This paper presents a white-box approach using `mini-control-plane`, a Kubernetes-inspired control plane implemented from scratch in Go, without reliance on `controller-runtime` or any upstream Kubernetes libraries. By instrumenting every internal transition—MVCC resource version updates, watch event delivery, leader election state changes, and reconciliation lifecycle events—we conduct controlled fault injection experiments across two fault classes: leader failover during active reconciliation, and concurrent MVCC write contention. Our primary finding is that MVCC conflict rate scales superlinearly with the number of concurrent controllers: from zero conflicts at $N=1$, to a mean of 82.0 conflicts ($\sigma=11.08$) at $N=8$, representing a growth curve consistent with $O(N^2)$ pairwise contention. Leader failover experiments reveal a mean election latency of 2.54 s ($\sigma=0.37$ s) and post-election recovery latency of 3.52 s ($\sigma=0.19$ s), with no permanent resource divergence observed across any trial. These results provide empirical, internally-visible evidence of correctness properties that black-box testing cannot yield, and carry direct implications for controller concurrency design in production Kubernetes environments.

Keywords: Kubernetes, control plane, MVCC, fault injection, distributed systems, reconciliation, leader election, white-box testing

1. Introduction

Kubernetes has become the dominant substrate for cloud-native workload orchestration. Its control plane—comprising the API server, etcd-backed storage, controller manager, and scheduler—implements a level-triggered reconciliation model in which controllers continuously drive observed state toward desired state. The correctness of this model under fault conditions is a practical concern: what happens when a leader fails mid-reconciliation? How does optimistic concurrency degrade as controller parallelism increases?

Existing work on Kubernetes fault tolerance, such as the “Mutiny!” study [1], has demonstrated that even subtle storage-layer faults can cascade into cluster-wide failures. However, these studies share a structural limitation: they target production Kubernetes, which is architecturally a black box. Faults can be injected, but internal state transitions—the sequence of MVCC version updates, the exact point at which a reconciler observes inconsistency, the latency between leader death and successor election—cannot be directly observed.

We address this gap with a white-box experimental platform. `mini-control-plane` is a complete reimplementation of Kubernetes control-plane semantics in Go, built without any upstream Kubernetes libraries. Every internal component—storage, watch, admission, leader election, reconciliation—is directly instrumented. This transparency enables measurements that are structurally impossible on real Kubernetes.

This paper makes the following contributions:

- A description of `mini-control-plane` as a white-

box experimental platform for control plane fault analysis.

- Empirical measurement of MVCC conflict scaling under concurrent reconciler contention ($N = 1, 2, 4, 8$), revealing superlinear growth consistent with $O(N^2)$.
- Quantitative characterisation of leader failover behaviour: election latency of 2.54s ($\sigma=0.37s$) and recovery latency of 3.52s ($\sigma=0.19s$) across 20 and 10 trials respectively.
- Discussion of implications for controller concurrency design in production Kubernetes.

2. Background

2.1. Kubernetes Control Plane Architecture

The Kubernetes control plane operates on a declarative model. Resources are stored in etcd with versioned keys; each write increments a `resourceVersion`. Controllers watch for changes via the API server’s watch mechanism and reconcile actual state toward desired state. The controller manager uses leader election—implemented via etcd leases—to ensure that at most one controller instance is active at any time for a given resource type [2].

Optimistic concurrency control (OCC) is used to prevent lost updates: a write that includes a stale `resourceVersion` is rejected by the API server, and the writer must re-fetch and retry. This design avoids distributed locking but introduces the possibility of retry storms under high contention.

2.2. MVCC and Optimistic Concurrency

Multi-Version Concurrency Control (MVCC) maintains multiple versions of each key, allowing readers to observe a consistent snapshot without blocking writers [3]. In Kubernetes, etcd’s MVCC implementation underpins all API server storage operations. The `resourceVersion` field exposed to clients corresponds to etcd’s global revision counter.

Under OCC, a concurrent update from two controllers targeting the same resource results in a conflict: one write succeeds, the other is rejected with a conflict error and must retry. The retry overhead—re-fetching the current state, re-computing the desired patch, and re-attempting the write—accumulates as controller parallelism increases.

2.3. Leader Election

Kubernetes uses etcd lease-based leader election. A controller acquires a lease with a configured TTL; on failure, the lease expires and a standby controller acquires it. The failover latency is bounded below by the lease TTL and above by the TTL plus retry polling interval. During the failover window, no controller is active, and resources may drift from desired state without correction.

2.4. Fault Injection in Distributed Systems

Fault injection is a standard technique for validating distributed system correctness [4]. Grey-box and black-box approaches inject faults at the network, storage, or process level and observe system behaviour. White-box approaches additionally instrument internal state, enabling causal tracing from fault injection to system response. Prior work on Kubernetes fault injection [1, 5] has been limited to black-box observation; this paper presents the first white-box fault injection study of a Kubernetes-style control plane.

3. System Architecture

mini-control-plane is a complete, from-scratch implementation of Kubernetes control-plane semantics in Go. It was designed explicitly to be transparent and instrumented, serving as an experimental platform rather than a production system. The system comprises five subsystems.

Storage Layer. An etcd-backed storage layer implementing MVCC with `resourceVersion` tracking. All writes use compare-and-swap (CAS) semantics: a write specifying a stale `resourceVersion` is rejected, mirroring Kubernetes API server OCC behaviour. Conflict events are logged with nanosecond timestamps.

Watch and Informer Layer. A watch mechanism subscribes to etcd events and delivers them to registered informers. Each informer maintains a local cache and triggers reconciliation on relevant changes. The watch layer is instrumented to log event delivery, including drops under fault injection.

Leader Election. etcd lease-based leader election with a configurable TTL (default: 5 seconds) and retry polling interval (default: 2 seconds). Leadership transitions are logged as structured events with timestamps.

Reconciliation Engine. A level-triggered reconciliation loop that computes the delta between desired and observed state and issues corrective writes. Each reconciliation cycle—start, conflict, retry, success, failure—is logged as a structured event.

Fault Injection Middleware. A configurable middleware layer wrapping the storage and watch interfaces. It supports parameterised fault injection: watch event drop rate (0.0–1.0), reconcile delay (milliseconds to seconds), and concurrent controller count. Faults are injected deterministically per experiment run.

All components emit structured JSON logs consumed by an analysis pipeline implemented in Python (`analysis/aggregate_conflicts.py`). The pipeline computes per-run conflict counts, means, standard deviations, and convergence outcomes across repeated trials. The full implementation is available at <https://github.com/Phoenix1504e/mini-control-plane>.

4. Experimental Methodology

4.1. Fault Model

We study two fault classes selected for their relevance to production Kubernetes failure modes.

Fault Class A — Leader Failover During Active Reconciliation. The active leader controller is terminated while reconciliation is in progress. A standby controller must detect the leader’s absence (via lease expiry), acquire the lease, and resume reconciliation. This models the common scenario of a controller manager pod crash or eviction.

Fault Class B — Concurrent MVCC Write Contention. N controllers are started simultaneously, each attempting to reconcile the same resource. Under OCC, at most one write per version succeeds; all others receive a conflict error and must retry. This models horizontal scaling of controllers or multi-replica controller deployments.

4.2. Experimental Configuration

All experiments were conducted on a single-node local etcd instance (etcd v3.5). The Go runtime version was 1.22. System telemetry was sampled at 250ms intervals. Table 1 summarises the base configuration.

4.3. Metrics

For Fault Class A, primary metrics are *election latency* (leader failure to standby acquisition) and *recovery*

Table 1: Experimental Configuration

Parameter	Value
etcd deployment	single-node local
sampling interval	250 ms
lease TTL	5 s
standby retry interval	2 s
reconcile delay (A)	5 s
watch drop rate (A)	0.25
controller count (B)	1, 2, 4, 8
trials per config (B)	5

latency (election completion to full resource convergence), each measured across repeated automated trials. For Fault Class B, the primary metric is *conflict count per trial*: the number of CAS rejections observed across all controllers during a single experimental run. We report mean and standard deviation for all metrics.

5. Experimental Evaluation

5.1. Fault Class B: MVCC Conflict Scaling

Table 2 presents conflict counts across five trials for each controller count configuration.

Table 2: MVCC Conflict Counts by Controller Count

Controllers (N)	Trial Runs	Mean	σ
1	[0, 0, 0, 0, 0]	0.00	0.00
2	[2, 7, 6, 5, 10]	6.00	2.61
4	[21, 20, 25, 28, 23]	23.40	2.87
8	[83, 64, 82, 99, 82]	82.00	11.08

Baseline ($N=1$). With a single controller, zero conflicts were observed across all five trials. This confirms that the storage layer and OCC implementation are correct in the absence of contention: no spurious conflicts occur.

Onset of Contention ($N=2$). With two concurrent controllers, a mean of 6.00 conflicts per trial was observed ($\sigma=2.61$). The coefficient of variation ($CV=0.44$) reflects the stochastic nature of conflict timing—small scheduling differences determine which controller wins each CAS operation.

Scaling Behaviour ($N=4$ to $N=8$). From $N=2$ to $N=4$, mean conflicts increase approximately $3.9\times$, from 6.00 to 23.40. From $N=4$ to $N=8$, they increase

approximately $3.5\times$, from 23.40 to 82.00. The ratio of mean conflicts to N^2 is approximately 1.50 at $N=2$, 1.46 at $N=4$, and 1.28 at $N=8$, consistent with near-quadratic growth.

Variance at Scale. Standard deviation increases substantially at $N=8$ ($\sigma=11.08$, $CV=0.14$). The range of observed values spans [64, 99]—a 54% spread—indicating that high-contention scenarios exhibit significant run-to-run variability, reflecting the non-deterministic interleaving of concurrent controller goroutines.

Interpretation. The superlinear conflict scaling has a natural combinatorial explanation: with N controllers competing for the same resource, each successful write invalidates the in-flight writes of all $N-1$ other controllers simultaneously. The expected number of conflicts grows with the number of active competing pairs, which scales as $O(N^2)$ in the worst case. Our empirical data is consistent with this theoretical expectation.

5.2. Fault Class A: Leader Failover During Active Reconciliation

Table 3 summarises latency measurements across 20 election trials and 10 recovery trials under the configuration of Section 1 (watch drop rate = 0.25, reconcile delay = 5s, two controllers).

Table 3: Leader Failover Latency Measurements

Metric	Trials	Mean	σ
Election latency	20	2.54 s	0.37 s
Recovery latency	10	3.52 s	0.19 s

Election Latency. The mean time from leader failure to successful standby acquisition was 2.54 s ($\sigma=0.37$ s, $CV=0.15$). This is consistent with the configured lease TTL of 5 s and retry interval of 2 s: the standby detects lease expiry within one retry interval after TTL expiration. The low CV indicates that election timing is dominated by the deterministic lease/retry configuration rather than stochastic factors.

Recovery Latency. The mean time from election completion to full resource convergence was 3.52 s ($\sigma=0.19$ s, $CV=0.054$). The remarkably low standard deviation reflects the deterministic nature of the reconciliation path once a new leader is active. Total

end-to-end failover-to-convergence latency is therefore approximately 6.06 s (2.54 + 3.52 s) under these experimental conditions.

Convergence Outcomes. No permanent unconverged resource states were observed across any trial. Resources mid-reconciliation at leader failure were successfully re-reconciled by the successor leader in all cases, consistent with the idempotency guarantee of the level-triggered reconciliation model.

MVCC Semantics During Failover. No conflicting writes or lost updates were observed during leader transition. MVCC CAS semantics correctly prevented the outgoing leader’s in-flight writes from corrupting state after the new leader began reconciling.

6. Discussion

6.1. Superlinear Conflict Growth and Production Implications

Our empirical finding that MVCC conflicts scale superlinearly with concurrent controller count has direct implications for Kubernetes operator design. The common pattern of deploying multiple controller replicas for high availability assumes that OCC retry overhead is manageable. Our data suggests this assumption deserves scrutiny: at $N=8$, mean conflicts per reconciliation cycle reach 82, each requiring a re-fetch and re-attempt. At high reconciliation frequencies, this overhead could become a significant bottleneck.

Production Kubernetes mitigates this partially through work-queue sharding—different controller instances handle disjoint resource subsets—but contention on shared resources (e.g., global configuration objects, namespace-scoped resources with shared dependencies) remains a potential concern. Our results suggest that controller concurrency should be treated as a tunable parameter with measurable performance implications, not merely an availability dial.

6.2. White-Box Visibility as a Research Instrument

The ability to observe conflict counts, version increments, and leader state transitions directly—rather than inferring them from external symptoms—enabled measurements that would be impossible on real Kubernetes. Production Kubernetes exposes no API for “conflicts observed during this reconciliation cycle.” Our approach of building a transparent, instrumented reimplement addresses this observability

gap and provides a template for future experimental distributed systems research.

This methodology is related to, but distinct from, simulation: **mini-control-plane** runs real Go concurrency, real etcd, and real network I/O. The transparency comes from architectural simplicity and deliberate instrumentation, not from simulation abstractions.

6.3. Consistency Properties Under Failure

Both fault classes confirm that **mini-control-plane** provides eventual consistency under the tested fault conditions. Leader failover introduces transient divergence bounded by the lease TTL; MVCC contention introduces retry overhead but does not produce lost updates or permanent inconsistency. These properties match the documented guarantees of production Kubernetes, validating that the reimplementations faithfully capture the essential correctness model.

7. Limitations and Threats to Validity

Simplified architecture. **mini-control-plane** implements core control-plane semantics but omits many production features: admission webhooks, priority and preemption, complex scheduling constraints, multi-tenant isolation, and network policy. Results may not generalise directly to the full complexity of production Kubernetes.

Single-node etcd. All experiments used a single-node etcd instance. A production etcd cluster introduces additional latency and Raft consensus overhead that could affect conflict rates and failover timing. We expect conflict scaling trends to hold qualitatively, but absolute values would differ.

Asymmetric trial counts. Fault Class A produced 20 election trials and 10 recovery trials. Expanding to 50 trials per metric would improve statistical confidence and enable tail latency analysis (p_{95} , p_{99}).

Controlled environment. Experiments were conducted on a local development machine under controlled conditions. Production environments introduce noise from co-located workloads, network variability, and resource pressure that could affect results.

8. Future Work

Several directions extend this work naturally.

Expanded Fault Class A campaigns. Increasing to 50 automated trials per metric would enable statistical characterisation of tail latencies and convergence rate distributions.

Multi-node etcd. Extending to a three-node etcd cluster would capture the latency and availability characteristics of production etcd deployments, including Raft consensus overhead during leader failover.

Conflict mitigation strategies. Having established the superlinear conflict scaling baseline, future work can evaluate mitigation strategies: exponential back-off with jitter, work-queue sharding, and optimistic batching. The white-box platform enables direct measurement of mitigation effectiveness.

Broader fault classes. Watch event drop (partial observability), network partition between controllers and etcd, and storage compaction during active reconciliation represent additional fault classes worth studying.

9. Conclusion

We have presented a white-box fault analysis of a Kubernetes-style control plane, using **mini-control-plane**—a complete from-scratch reimplementations in Go—as a transparent experimental platform. Our central empirical finding is that MVCC conflict rate scales superlinearly with concurrent controller count, growing from zero conflicts at $N=1$ to a mean of 82.0 conflicts ($\sigma=11.08$) at $N=8$, consistent with $O(N^2)$ pairwise contention dynamics. Leader failover experiments establish a mean election latency of 2.54s ($\sigma=0.37$ s) and post-election recovery latency of 3.52s ($\sigma=0.19$ s), with no permanent resource inconsistency observed across any trial. Together, these results provide the first internally-visible, white-box characterisation of correctness and convergence properties in a Kubernetes-style control plane under fault conditions, and establish a methodology for future experimental distributed systems research on cloud-native infrastructure.

References

- [1] Z. Guo et al. Mutiny! Unexploited Opportunities for Error Injection in Kubernetes. In *IEEE/IFIP International Conference on Dependable Systems and Networks (DSN)*, 2024.
- [2] B. Burns, B. Grant, D. Oppenheimer, E. Brewer, and J. Wilkes. Borg, Omega, and Kubernetes. *ACM Queue*, 14(1), 2016.

- [3] D. P. Reed. Implementing Atomic Actions on Decentralized Data. *ACM Transactions on Computer Systems*, 1(1):3–23, 1983.
- [4] P. Alvaro et al. Lineage-Driven Fault Injection. In *ACM SIGMOD International Conference on Management of Data*, 2015.
- [5] T. Leesatapornwongsa et al. SAMC: Semantic-Aware Model Checking for Fast Discovery of Deep Bugs in Cloud Systems. In *USENIX OSDI*, 2014.
- [6] etcd Authors. etcd: A Distributed, Reliable Key-Value Store. <https://etcd.io>, 2024.
- [7] The Kubernetes Authors. Kubernetes Controller Runtime. <https://github.com/kubernetes-sigs/controller-runtime>, 2024.
- [8] D. Ongaro and J. Ousterhout. In Search of an Understandable Consensus Algorithm. In *USENIX ATC*, 2014.