


Today: Outline

- **Neural networks cont'd:** learning via gradient descent; chain rule review; gradient computation using the backpropagation algorithm
- **Reminder:** PS2 is due Feb 24

Fei-Fei Li



- Professor, Computer Science, Stanford University
- Co-Director of Stanford's Human-Centered AI Institute
- Previously Vice President at Google and Chief Scientist of AI/ML at Google Cloud
- Co-founder and chairperson of the national non-profit AI4ALL
- Online Deep Learning Course
- **"First, we teach them see, then they help us to see better."**

Image Captioning



A young boy holding a baseball bat



A man riding a horse next to a building




Neural Networks II

Architectures and Learning


Network architectures

Feed-forward


Fully connected




Convolutional



Recurrent




Fully Connected



Not ideal for representing images



Convolutional Neural Network

A better architecture for 2d signals





LeNet

Artificial Neural Network



- **Artificial neural networks:** consist of many inter-connected neurons organized in layers
- **Neurons:** each neuron receives inputs from neurons in previous layer, passes its output to next layer
- **Activation:** neuron's output between 1 (excited) and 0 (not excited) *assuming a sigmoid non-linearity*

Artificial Neuron: Activation




Artificial Neural Network: notation

input

$$x = \begin{bmatrix} x_1 \\ \dots \\ x_5 \end{bmatrix}$$

hidden layer activations



Artificial Neural Network: notation



input

$$x = \begin{bmatrix} x_1 \\ \dots \\ x_5 \end{bmatrix}$$

hidden layer activations

$$h^i = g(\Theta^{(i)}x)$$

$$g(z) = \frac{1}{1 + \exp(-z)}$$



output

$$h_{\Theta}(x) = g(\Theta^{(2)}h^i)$$

weights

$$\Theta^{(1)} = \begin{pmatrix} \theta_{11} & \dots & \theta_{15} \\ \vdots & \ddots & \vdots \\ \theta_{31} & \dots & \theta_{35} \end{pmatrix} \quad \Theta^{(2)} = \begin{pmatrix} \theta_{11} & \dots & \theta_{13} \\ \vdots & \ddots & \vdots \\ \theta_{31} & \dots & \theta_{33} \end{pmatrix}$$

Cost function

Neural network: $h_{\Theta}(x) \in \mathbb{R}^K$ $(h_{\Theta}(x))_i = i^{th}$ output

training error

$$J(\Theta) = -\frac{1}{m} \left[\sum_{i=1}^m \sum_{k=1}^K y_k^{(i)} \log(h_{\Theta}(x^{(i)}))_k + (1 - y_k^{(i)}) \log(1 - (h_{\Theta}(x^{(i)}))_k) \right]$$

$$+ \frac{\lambda}{2m} \sum_{l=1}^{L-1} \sum_{i=1}^{s_l} \sum_{j=1}^{s_{l+1}} (\Theta_{ji}^{(l)})^2$$

regularization

Gradient computation

$$J(\Theta) = -\frac{1}{m} \left[\sum_{i=1}^m \sum_{k=1}^K y_k^{(i)} \log h_{\theta}(x^{(i)})_k + (1 - y_k^{(i)}) \log(1 - h_{\theta}(x^{(i)})_k) \right] \\ + \frac{\lambda}{2m} \sum_{l=1}^{L-1} \sum_{i=1}^{s_l} \sum_{j=1}^{s_{l+1}} (\Theta_{ji}^{(l)})^2$$

$$\min_{\Theta} J(\Theta)$$

Need code to compute:

- $J(\Theta)$
- $\frac{\partial}{\partial \Theta_{ij}^{(l)}} J(\Theta)$

Use “**Backpropagation algorithm**”

- Efficient way to compute $\frac{\partial}{\partial \Theta_{ij}^{(l)}} J(\Theta)$
- Computes gradient incrementally by “propagating” backwards through the network



Neural Networks II

Backpropagation

Chain Rule

- Need to compute gradient of

$$\log(h_{\Theta}(x)) = \log(g(\Theta^{(2)}g(\Theta^{(1)}x))) \quad \text{w.r.t } \Theta$$

- How can we compute the gradient of several chained functions?

$$f(\theta) = f_1(f_2(\theta)) \quad f'(\theta) = f_1'(f_2(\theta)) * f_2'(\theta)$$

$$f'(\theta) = \frac{\partial f}{\partial \theta} = \frac{\partial f_1}{\partial f_2} \frac{\partial f_2}{\partial \theta}$$

- What about functions of multiple variables?

$$f(\theta_1, \theta_2) = f_1(f_2(\theta_1, \theta_2)) \quad \frac{\partial f}{\partial \theta_1} = \quad \frac{\partial f}{\partial \theta_2} =$$

Backpropagation: Efficient Chain Rule

- Partial gradient computation via chain rule:

$$\frac{\partial f}{\partial \theta_1} = \frac{\partial f_1}{\partial f_2}(f_2(f_3(\theta))) * \frac{\partial f_2}{\partial f_3}(f_3(\theta)) * \frac{\partial f_3}{\partial \theta_1}(\theta)$$


$$\frac{\partial f}{\partial \theta_2} = \frac{\partial f_1}{\partial f_2}(f_2(f_3(\theta))) * \frac{\partial f_2}{\partial f_3}(f_3(\theta)) * \frac{\partial f_3}{\partial \theta_2}(\theta)$$

$$\frac{\partial f}{\partial \theta_3} = \frac{\partial f_1}{\partial f_2}(f_2(f_3(\theta))) * \frac{\partial f_2}{\partial f_3}(f_3(\theta)) * \frac{\partial f_3}{\partial \theta_3}(\theta)$$


- need to re-evaluate functions many times
- Very inefficient! E.g. 100,000-dim parameters

Example: Classification

- A deep network is a massive composite function!




Interpretation of Computed Gradients




- The cost function is 32 times more sensitive to changes in the yellow weight vs. the pink weight.

Computing Gradients: Backpropagation



How does a small change in one weight (ex. θ_2) affect the final loss $J(\theta)$?


Computing Gradients: Backpropagation



$$\frac{\partial J(\theta)}{\partial \theta_2} =$$


Let's use the chain rule!

Computing Gradients: Backpropagation



$$\frac{\partial J(\theta)}{\partial \theta_2} = \underbrace{\frac{\partial J(\theta)}{\partial \hat{y}}}_{\text{purple}} * \underbrace{\frac{\partial \hat{y}}{\partial \theta_2}}_{\text{red}}$$


Computing Gradients: Backpropagation



$$\frac{\partial J(\theta)}{\partial \theta_1} = \frac{\partial J(\theta)}{\partial \hat{y}} * \frac{\partial \hat{y}}{\partial \theta_1}$$

Apply chain rule! Apply chain rule!

Computing Gradients: Backpropagation



$$\frac{\partial J(\theta)}{\partial \theta_1} = \underbrace{\frac{\partial J(\theta)}{\partial \hat{y}}}_{\text{purple}} * \underbrace{\frac{\partial \hat{y}}{\partial z_1}}_{\text{red}} * \underbrace{\frac{\partial z_1}{\partial \theta_1}}_{\text{blue}}$$




Neural Networks II

Analytical Gradients with Computational Graphs

Chain Rule with a Computational Graph

$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$



Chain Rule with a Computational Graph


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Computation Graph: Forward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



compute values



Computation Graph: Backward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial f}$$

compute gradients



Computation Graph: Backward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial f}$$

Computation Graph: Backward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial z}$$

Computation Graph: Backward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial z}$$

Computation Graph: Backward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial q}$$

Computation Graph: Backward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial q}$$

Computation Graph: Backward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial y}$$

Computation Graph: Backward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Chain rule:

$$\frac{\partial f}{\partial y} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial y}$$

$$\frac{\partial f}{\partial y}$$

Computation Graph: Backward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial x}$$

Computation Graph: Backward


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$


Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$





Chain rule:


$$\frac{\partial f}{\partial x} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial x}$$


$$\frac{\partial f}{\partial x}$$
















Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$


*Computing a 2D
Sigmoid Neuron!*



$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example:


$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→


$$\frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$


Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$


Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example: $f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$


$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$(e^{-1})(-0.53) = -0.20$$

$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

Another example:


$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example:


$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$$f(x) = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = e^x$$

→

$$\frac{df}{dx} = a$$

|

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



[local gradient] x [its gradient]

$$[1] \times [0.2] = 0.2$$

$$[1] \times [0.2] = 0.2 \text{ (both inputs!)}$$

$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

Another example:


$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$



$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

Another example:

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$$




$f(x) = e^x$	\rightarrow	$\frac{df}{dx} = e^x$		$f(x) = \frac{1}{x}$	\rightarrow	$\frac{df}{dx} = -1/x^2$
$f_a(x) = ax$	\rightarrow	$\frac{df}{dx} = a$		$f_c(x) = c + x$	\rightarrow	$\frac{df}{dx} = 1$

$$f(w, x) = \frac{1}{1 + e^{-(w_0 x_0 + w_1 x_1 + w_2)}}$$

$$\sigma(x) = \frac{1}{1 + e^{-x}} \quad \text{sigmoid function}$$


$$\frac{d\sigma(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2} = \left(\frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left(\frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x)) \sigma(x)$$



$$f(w, x) = \frac{1}{1 + e^{-(w_0 x_0 + w_1 x_1 + w_2 x_2)}}$$


$$\sigma(x) = \frac{1}{1 + e^{-x}} \quad \text{sigmoid function}$$

$$\frac{d\sigma(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2} = \left(\frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left(\frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x)) \sigma(x)$$




Patterns in backward flow

add gate: gradient distributor
max gate: gradient router
mul gate: gradient... “switcher”?



Gradients add at branches





Neural Networks II

Vectorized Backpropagation

