


The OSI Reference Model



- A **protocol** defines message types and associated actions
- MAC sublayer to handle multi-access (shared) links
- Internetwork sublayer to connect networks

Matta@BUCS - Introduction 1-42

42


ISO/OSI Architecture (cont'd)

- Seven layers with following typical functions:
 - m **application**: user interface
 - m **presentation**: code conversion, encryption, compression
 - m **session**: organizes and synchronizes the data exchange
 - m **transport**: multiplexing/demultiplexing, fragmentation/reassembly, end-to-end flow control, congestion control and error control
 - m **network**: addressing and routing
 - m **data link**: link-level flow and error control
 - m **physical**: physical and electrical interfaces (normally 100% hardware)

Matta@BUCS - Introduction 1-43

43

How is the OSI Model used?



Matta@BUCS - Introduction 1-44

44

Service Offered by a Layer


- ❑ Connection-oriented:
 - m Before data exchange takes place, a logical (virtual) connection has to be first established
 - m Usually reliable; delivery is in-order, error- and loss-free, no duplication
- ❑ Connection-less: data is sent directly in a best-effort way; data can arrive out-of-order, be lost, corrupted, duplicated

Matte@BUCS - Introduction 1-45

45

TCP/IP (Internet) Architecture


- ❑ An industry / de facto standard
- ❑ Four layers (application, transport, internet, network interface)
- ❑ Data units: messages, segments, datagrams, frames
- ❑ Many intranets also use TCP/IP



Matte@BUCS - Introduction 1-46

46

Initial Protocols & Networks in the TCP/IP model




- ❑ TCP (Transmission Control Protocol):
 - m offers **connection-oriented reliable** service
- ❑ UDP (User Datagram Protocol):
 - m offers **connection-less unreliable** service

Matte@BUCS - Introduction 1-47

47

Protocol Graph


- collection of protocols and their dependencies
- most peer-to-peer communication is indirect
- peer-to-peer is direct only at hardware level



Matte@BUCS - Introduction 1-48

48

Protocol Graph for the Internet




- IP provides a connection-less “best-effort” *datagram state-less* service

Matte@BUCS - Introduction 1-49

49

Protocol Stack

- Multiplexing and Demultiplexing (demux key)
- Encapsulation (header/body) and Decapsulation



Matte@BUCS - Introduction 1-50

50

We will cover ...

- ❑ In a top-down Internet-centric fashion ...
- ❑ Applications
 - Socket programming
- ❑ Transport Services
 - Error, flow and congestion control
- ❑ Internetworking
 - Addressing and Routing
 - Scalability/heterogeneity
- ❑ LANs, point-to-point links
 - Access control, data communication
- ❑ Wireless (WiFi LAN), mobility
- ❑ As time permits: wide-area wireless, real-time, management, operational security, ...

Matta@BUCS - Introduction 1-51

51
