


CS 655
Computer Networks

Abraham Matta
Computer Science
Boston University

Chapter 3
Transport Services



Matta @ BUCS - Transport 1-1

1

Transport Protocols in TCP/IP


- ❑ UDP (User Datagram Protocol)
 - provides applications with **unreliable connectionless** service

- ❑ TCP (Transmission Control Protocol)
 - provides applications with **reliable connection-oriented** service

Matta @ BUCS - Transport 1-2

2

UDP



Matta @ BUCS - Transport 1-3

3


UDP

- Unreliable and unordered datagram service
- Adds multiplexing and checksum (covers user data)
- Endpoints identified by ports
 - servers have **well-known** ports
 - see /etc/services on Unix/Linux

Matta @ BUCS - Transport 1-4

4

UDP: header format



Matta @ BUCS - Transport 1-5

5


UDP: header format




- UDP demultiplexes based on **destination port** in the UDP header
- **Checksum idea:** view message as a sequence of 16-bit integers. Add these integers together using 16-bit ones complement arithmetic, and then invert the result. That 16-bit number is the checksum
- Receiver adds in ones complement and should get all 1's if no bit errors

Matta @ BUCS - Transport 1-6


6



7



8



9

Basics of Reliable Transmission

- Building it from the ground up over a FIFO lossy & erroneous (unreliable) unidirectional channel

Matta @ BUCS - Transport 1-10

10


Basics of Reliable Transmission

- Assume FIFO channel but erroneous \Rightarrow corrupted or lost packets
- 1) avoid losses @ receiver \Rightarrow flow control; one packet at a time (stop-and-wait) \Rightarrow "Ack's"
 - 2) detect corrupted packets \Rightarrow "checksum" fails \Rightarrow drop
 - 3) detect lost packets \Rightarrow timer \approx RTT "RTO"
 - 4) recovery \Rightarrow retransmit once RTO expires (ARQ) "idle RQ" "error recovery" "error control"
 - 5) detect duplicates \Rightarrow sequence numbers
no out-of-order delivery here because FIFO channel

Matta @ BUCS - Transport 1-11

11

Basics of Reliable Transmission




Matta @ BUCS - Transport 1-12

12

Basics of Reliable Transmission

- ❑ Recover from corrupted/lost packets using Acknowledgements and Timeouts; also called **Automatic Repeat reQuest (ARQ)**



Matta @ BUCS - Transport 1-13

13

Basics of Reliable Transmission

- ❑ Building it from the ground up over a FIFO lossy & erroneous (unreliable) unidirectional channel
- ❑ Add flow control (stop-and-wait)
- ❑ Dealing with corruption - add checksum
- ❑ Dealing with loss - add timer
- ❑ Add recovery by retransmission (ARQ)
- ❑ Dealing with duplicates - add sequence numbers

Matta @ BUCS - Transport 1-14

14

ARQ


- ❑ The packet's header contains the control information needed to implement ARQ (type, sequence number, checksum, ...)
- ❑ At the receiver, only the data portion of an error-free data packet is delivered to the higher layer
- ❑ Sequence numbers are needed for detecting duplicates (and more ... later!)
- ❑ A good timeout estimate is essential to avoid premature retransmissions and maintain high **goodput** (rate of receiving new/useful data)

Matta @ BUCS - Transport 1-15

15

Finite State Machines for Stop-and-Wait

(assume infinite supply of data packets)




Matta @ BUCS - Transport 1-16

16

Finite State Machines for Stop-and-Wait

(assume infinite supply of data packets)



Matta @ BUCS - Transport 1-17

17