CompoundIQ — Data Dictionary

Version: 1.0 | **Date:** April 5, 2026 **Database:** Supabase PostgreSQL 15+ **Tables:** 17 | **Enums:** 10 | **Row-Level Security:** Enabled on all tables

---

Overview

This data dictionary provides a human-readable description of every table, column, and enum in the CompoundIQ database. It is organized by domain area and includes the purpose of each field, data types, constraints, and relationships.

Enum Types (10)

order_status_enum (23 values)

The complete lifecycle of a prescription order:

Value	Meaning
DRAFT	Order created, still editable. No commitments made.
AWAITING_PAYMENT	Payment link sent to patient. Prices locked. 72-hour countdown started.
PAYMENT_EXPIRED	Patient did not pay within 72 hours. Order automatically expired.
PAID_PROCESSING	Patient paid. System is routing the prescription to the pharmacy.
SUBMISSION_PENDING	Prescription submitted to pharmacy via adapter. Waiting for acknowledgment.
SUBMISSION_FAILED	All adapter tiers failed. Needs ops intervention.
FAX_QUEUED	Prescription faxed via Documo. Waiting for delivery confirmation.
FAX_DELIVERED	Fax delivery confirmed by Documo. Waiting for pharmacy response.
FAX_FAILED	Fax delivery failed after 3 retries. Needs ops intervention.
PHARMACY_ACKNOWLEDGED	Pharmacy confirmed receipt of the prescription.
PHARMACY_COMPOUNDING	Pharmacy is actively compounding the medication.
PHARMACY_PROCESSING	Pharmacy is processing (generic processing state).
PHARMACY_REJECTED	Pharmacy cannot fill this prescription (out of stock, formulation issue, etc.).
REROUTE_PENDING	Order is being rerouted to a different pharmacy (max 2 reroutes).
READY_TO_SHIP	Compounding complete. Waiting for carrier pickup.
SHIPPED	Package picked up by carrier. Tracking number assigned.
DELIVERED	Package delivered to patient. Order complete.
CANCELLED	Order cancelled by clinic, ops, or system. Reason recorded.

ERROR_PAYMENT_FAILED	Stripe payment processing error.
ERROR_COMPLIANCE_HOLD	Compliance flag triggered. Order frozen pending review.
REFUND_PENDING	Refund initiated via Stripe. Waiting for confirmation.
REFUNDED	Refund completed. Terminal state.
DISPUTED	Patient filed a chargeback via their bank. Evidence collection in progress.

cancellation_reason_enum (5 values)

Value	Meaning
PATIENT_ABANDONED	Patient never completed payment (expired link or gave up)
PROVIDER_CANCELLED	Provider decided to cancel the prescription
SYSTEM_EXPIRY	72-hour payment window expired (automatic)
COMPLIANCE_HOLD	Cancelled due to compliance or regulatory issue
OPS_CANCELLED	Operations team cancelled (e.g., all reroutes exhausted)

stripe_connect_status_enum (4 values)

Value	Meaning
PENDING	Clinic created but Stripe onboarding not complete
ACTIVE	Fully verified. Charges and payouts enabled. Orders allowed.
RESTRICTED	Stripe requires additional information. New orders blocked.
DEACTIVATED	Stripe disabled the account. All operations blocked.

regulatory_status_enum (3 values)

Value	Meaning
ACTIVE	Pharmacy is operating normally
SUSPENDED	Pharmacy under temporary regulatory review (shown with warning)
BANNED	Pharmacy permanently excluded from all search results

integration_tier_enum (4 values)

Value	Meaning
TIER_1_API	Direct REST API integration (fastest, ~2 seconds)
TIER_2_PORTAL	Automated browser-based portal submission (~5 minutes)
TIER_3_SPEC	Pharmacy implements CompoundIQ's published API specification

TIER_4_FAX	Fax fallback via Documo mFax (~30 minutes). Universal.

adapter_submission_status_enum (8 values)

Value	Meaning
PENDING	Submission queued, not yet sent
SUBMITTED	Sent to pharmacy, awaiting response
ACKNOWLEDGED	Pharmacy confirmed receipt
REJECTED	Pharmacy rejected the order
FAILED	Submission failed (network, auth, or payload error)
RETRYING	Submission failed, automatic retry in progress
CANCELLED	Submission cancelled (order rerouted or cancelled)
TIMEOUT	Pharmacy did not respond within SLA deadline

sla_type_enum (10 values)

Value	Meaning	Deadline
PAYMENT_EXPIRY	Patient hasn't paid	72 hours
SMS_REMINDER_24H	First payment reminder	24 hours
SMS_REMINDER_48H	Final payment warning	48 hours
FAX_DELIVERY	Fax not delivered	30 minutes
PHARMACY_ACK	Pharmacy hasn't acknowledged (Tier 4)	4 business hours
PHARMACY_COMPOUNDING	Pharmacy hasn't started compounding	TAT + 4 hours
SHIPPING	Order not shipped	24 hours
TRACKING_UPDATE	No tracking update	24 hours
ADAPTER_SUBMISSION_ACK	No adapter response (Tier 1/2/3)	5–30 minutes
PHARMACY_COMPOUNDING_ACK	No compounding start (Tier 1/2/3)	2 business hours

inbound_fax_status_enum (5 values)

Value	Meaning
RECEIVED	Fax received, not yet processed
MATCHED	Fax matched to a pharmacy (auto or manual)
UNMATCHED	Cannot determine which pharmacy sent it
PROCESSED	Fax triaged and disposition applied

ARCHIVED	Fax archived (unrelated or fully processed)

webhook_source_enum (4 values)

Value	Meaning
stripe	Stripe payment and Connect events
documo	Documo fax delivery and inbound events
twilio	Twilio SMS delivery status callbacks
pharmacy_api	Pharmacy-specific API webhook events

catalog_source_enum (3 values)

Value	Meaning
CSV_UPLOAD	Catalog uploaded manually via CSV file
API_SYNC	Catalog pulled automatically from pharmacy API
MANUAL_ENTRY	Individual item entered manually by ops

Tables by Domain

Clinic & User Tables

clinics

The tenant root. Every clinic is an isolated data silo.

Column	Type	Description
clinic_id	UUID (PK)	Unique clinic identifier
name	TEXT	Clinic display name (e.g., "Sunrise Functional Medicine")
stripe_connect_account_id	TEXT (UNIQUE)	Stripe Express connected account ID (acct_xxx)
stripe_connect_status	ENUM	Current Stripe onboarding status (PENDING/ACTIVE/RESTRICTED/DEACTIVATED)
logo_url	TEXT	Clinic logo URL for patient checkout white-labeling
created_at	TIMESTAMPTZ	Record creation timestamp
updated_at	TIMESTAMPTZ	Last update timestamp
deleted_at	TIMESTAMPTZ	Soft-delete timestamp (null = active)
is_active	BOOLEAN	Soft-delete flag (true = active)

providers

Licensed prescribers within a clinic.

Column	Type	Description
provider_id	UUID (PK)	Unique provider identifier
clinic_id	UUID (FK→clinics)	Which clinic this provider belongs to
npi_number	TEXT (UNIQUE)	10-digit National Provider Identifier — required for all prescriptions
name	TEXT	Provider's full name
credentials	TEXT	License type (MD, DO, NP, PA)
signature_hash	TEXT	SHA-256 hash of provider's digital signature canvas data
created_at / updated_at / deleted_at / is_active	—	Standard audit + soft-delete fields

patients

Patient demographics and contact info. Scoped to a clinic.

Column	Type	Description
patient_id	UUID (PK)	Unique patient identifier
clinic_id	UUID (FK→clinics)	Which clinic this patient belongs to
first_name / last_name	TEXT	Patient name
date_of_birth	DATE	DOB — used for identity verification
phone	TEXT	Mobile phone for SMS checkout links and notifications
shipping_address_street / city / state / zip	TEXT	Shipping address — state is critical for pharmacy licensing compliance
created_at / updated_at / deleted_at / is_active	—	Standard audit + soft-delete fields

Pharmacy Tables

pharmacies

Compounding pharmacy partners. Global (not clinic-scoped).

Column	Type	Description
pharmacy_id	UUID (PK)	Unique pharmacy identifier

name	TEXT	Pharmacy display name
slug	TEXT (UNIQUE)	URL-safe identifier used in webhook endpoint path
integration_tier	ENUM	How this pharmacy connects (TIER_1_API / TIER_2_PORTAL / TIER_3_SPEC / TIER_4_FAX)
regulatory_status	ENUM	Platform compliance status (ACTIVE / SUSPENDED / BANNED)
fax_number	TEXT	Pharmacy's fax number for Tier 4 submissions
phone	TEXT	Pharmacy contact phone
address_line1 / address_line2 / city / state / timezone	TEXT	Pharmacy location (timezone used for business-hours SLA calculations)
average_turnaround_days	INTEGER	Typical days from order receipt to shipment
supports_real_time_status	BOOLEAN	Whether pharmacy sends real-time status webhooks
supports_webhook	BOOLEAN	Whether pharmacy has webhook capability
api_config_id	UUID (FK→pharmacy_api_configs)	Link to Tier 1/3 API configuration
portal_config_id	UUID (FK→pharmacy_portal_configs)	Link to Tier 2 portal configuration
catalog_last_synced_at	TIMESTAMPTZ	Last time catalog was synced from pharmacy API
created_at / updated_at / deleted_at / is_active	—	Standard audit + soft-delete fields

pharmacy_state_licenses

Which states each pharmacy is licensed to ship to. This is the compliance backbone — a pharmacy without a license in the patient's state NEVER appears in search results.

Column	Type	Description
pharmacy_id	UUID (FK→pharmacies)	Which pharmacy
state_code	CHAR(2)	Two-letter US state code (e.g., TX, CA)
license_number	TEXT	State-issued pharmacy license number
expiry_date	DATE	License expiration date

created_at	TIMESTAMPTZ	Record creation

pharmacy_api_configs

API connection configuration for Tier 1 and Tier 3 pharmacies. Credentials are stored in Supabase Vault — never in this table.

Column	Type	Description
config_id	UUID (PK)	Configuration identifier
pharmacy_id	UUID (FK→pharmacies, UNIQUE)	One config per pharmacy
api_base_url	TEXT	Pharmacy's API base URL
vault_secret_id	UUID	Reference to Supabase Vault entry for API bearer token
webhook_secret_vault_id	UUID	Reference to Vault entry for webhook HMAC verification secret
circuit_breaker_status	TEXT	CLOSED / OPEN / HALF_OPEN
consecutive_failures	INTEGER	Failure count for circuit breaker (resets to 0 on success)
last_failure_at	TIMESTAMPTZ	Timestamp of most recent failure
created_at / updated_at	—	Audit timestamps

pharmacy_portal_configs

Portal automation configuration for Tier 2 pharmacies. Login credentials stored in Vault.

Column	Type	Description
config_id	UUID (PK)	Configuration identifier
pharmacy_id	UUID (FK→pharmacies, UNIQUE)	One config per pharmacy
portal_url	TEXT	Pharmacy portal login page URL
username_vault_id	UUID	Vault reference for portal username
password_vault_id	UUID	Vault reference for portal password
login_selector / order_form_selector / confirmation_selector	JSONB	Playwright CSS selectors for automating the portal
created_at / updated_at	—	Audit timestamps

Catalog Tables

catalog

Medication catalog entries. Each pharmacy has its own catalog items with pricing.

Column	Type	Description
catalog_id	UUID (PK)	Catalog item identifier
pharmacy_id	UUID (FK→pharmacies)	Which pharmacy offers this medication
medication_name	TEXT	Medication name (e.g., "Semaglutide")
form	TEXT	Dosage form (e.g., "Injectable", "Capsule", "Cream")
dose	TEXT	Dose specification (e.g., "0.5mg/0.5mL")
strength	TEXT	Strength specification
wholesale_price	NUMERIC(10,2)	Pharmacy's cost — this is what the clinic pays
average_turnaround_days	INTEGER	Estimated days to fulfill this specific item
dea_schedule	INTEGER	DEA schedule (2–5) if controlled substance; null if not
source	ENUM	How this item was added (CSV_UPLOAD / API_SYNC / MANUAL_ENTRY)
csv_version	TEXT	Version identifier from CSV upload
is_active	BOOLEAN	Whether this item is currently available
created_at / updated_at / deleted_at	—	Audit + soft-delete fields

catalog_history

Append-only audit log for every catalog change. Cannot be updated or deleted.

Column	Type	Description
history_id	UUID (PK)	History entry identifier
catalog_id	UUID (FK→catalog)	Which catalog item changed
change_type	TEXT	What changed (price, status, new item, etc.)
old_values / new_values	JSONB	Before and after values
changed_by	UUID	Who made the change
created_at	TIMESTAMPTZ	When the change occurred

Order Tables

orders

The central order table. Contains the prescription, pricing, and fulfillment state.

Column	Type	Description
order_id	UUID (PK)	Unique order identifier
clinic_id	UUID (FK→clinics)	Which clinic created this order
patient_id	UUID (FK→patients)	Which patient this order is for
provider_id	UUID (FK→providers)	Which provider signed this order
catalog_id	UUID (FK→catalog)	Which catalog item was selected
pharmacy_id	UUID (FK→pharmacies)	Which pharmacy will fill this
status	ENUM	Current order status (23 possible values)
Snapshot fields (frozen at AWAITING_PAYMENT):		
wholesale_price_snapshot	NUMERIC(10,2)	Locked wholesale cost at time of signature
retail_price	NUMERIC(10,2)	Patient-facing price set by the clinic
platform_fee	NUMERIC(10,2)	CompoundIQ's fee (15% of margin spread)
medication_name_snapshot	TEXT	Locked medication name
form_snapshot / strength_snapshot	TEXT	Locked formulation details
pharmacy_name_snapshot	TEXT	Locked pharmacy name
provider_npi_snapshot	TEXT	Locked provider NPI
patient_shipping_state_snapshot	TEXT	Locked shipping state
provider_signature_hash	TEXT	SHA-256 hash of provider's digital signature
Payment fields:		
stripe_payment_intent_id	TEXT	Stripe PaymentIntent ID (pi_xxx)
stripe_checkout_session_id	TEXT	Stripe Checkout session ID
checkout_token_jwt	TEXT	JWT token embedded in patient checkout URL
checkout_url	TEXT	Full checkout URL sent to patient

checkout_expires_at	TIMESTAMPTZ	When the 72-hour payment window expires
Fulfillment fields:		
fax_sid	TEXT	Documo fax job ID (for Tier 4)
fax_retry_count	INTEGER	How many fax retry attempts (max 3)
reroute_count	INTEGER	How many pharmacy reroutes (max 2)
adapter_submission_id	UUID (FK)	Most recent adapter submission
submission_tier	ENUM	Which tier was used for submission
cancellation_reason	ENUM	Why the order was cancelled (if applicable)
created_at / updated_at / deleted_at / is_active	—	Standard audit + soft-delete

order_status_history

Append-only audit trail of every state transition. Cannot be updated or deleted.

Column	Type	Description
history_id	UUID (PK)	History entry identifier
order_id	UUID (FK→orders)	Which order
previous_status	ENUM	Status before the transition
new_status	ENUM	Status after the transition
changed_by	UUID	Who/what triggered the change (user ID, null for system)
change_reason	TEXT	Why the transition happened
metadata	JSONB	Additional context (webhook event ID, adapter submission ID, etc.)
created_at	TIMESTAMPTZ	When the transition occurred

Event & Monitoring Tables

webhook_events

Log of every webhook received from Stripe, Documo, and Twilio.

Column	Type	Description
event_id	UUID (PK)	Event identifier
source	ENUM	Which service (stripe / documo / twilio / pharmacy_api)

external_event_id	TEXT (UNIQUE)	The service's event ID (for idempotency)
event_type	TEXT	Event type string (e.g., "payment_intent.succeeded")
payload	JSONB	Complete raw webhook payload
order_id	UUID (FK→orders)	Associated order (if applicable)
processed	BOOLEAN	Whether the event has been processed
processed_at	TIMESTAMPTZ	When processing completed
created_at	TIMESTAMPTZ	When the event was received

pharmacy_webhook_events

Separate ledger for pharmacy-specific webhooks. Uses composite idempotency (pharmacy_id + event_id).

Column	Type	Description
id	UUID (PK)	Record identifier
pharmacy_id	UUID (FK→pharmacies)	Which pharmacy sent the webhook
event_id	TEXT	Pharmacy's event identifier
event_type	TEXT	Event type (order.acknowledged, order.compounding, etc.)
payload	JSONB	Complete raw webhook payload
order_id	UUID (FK→orders)	Associated order
submission_id	UUID (FK→adapter_submissions)	Associated submission
signature_verified	BOOLEAN	Whether HMAC signature was valid
processed_at	TIMESTAMPTZ	When processing completed
created_at	TIMESTAMPTZ	When received

order_sla_deadlines

SLA tracking. One row per (order, SLA type) pair.

Column	Type	Description
order_id	UUID (FK→orders)	Which order
sla_type	ENUM (composite PK)	Which SLA type (10 possible values)
deadline_at	TIMESTAMPTZ	When this SLA deadline expires
escalation_tier	INTEGER	Current escalation level (0=none, 1=Slack, 2=DM, 3=PagerDuty)

escalated	BOOLEAN	Whether any escalation has fired
escalated_at	TIMESTAMPTZ	When first escalation occurred
acknowledged_by	TEXT	Ops user who acknowledged the breach
acknowledged_at	TIMESTAMPTZ	When acknowledged
resolved_at	TIMESTAMPTZ	When the SLA was resolved
resolution_notes	TEXT	How the SLA was resolved
created_at	TIMESTAMPTZ	When the SLA deadline was created

adapter_submissions

Audit trail of every submission attempt to a pharmacy. Append-only — a new row is created for each retry.

Column	Type	Description
submission_id	UUID (PK)	Submission attempt identifier
order_id	UUID (FK→orders)	Which order
pharmacy_id	UUID (FK→pharmacies)	Which pharmacy
tier_used	ENUM	Which integration tier was used
submission_method	TEXT	Specific method (REST, Playwright, fax, etc.)
request_payload_hash	TEXT	SHA-256 hash of the outbound request (for audit, not the payload itself)
response_status	ENUM	Result (PENDING / SUBMITTED / ACKNOWLEDGED / REJECTED / FAILED / RETRYING / CANCELLED / TIMEOUT)
response_body	JSONB	Pharmacy's response (if any)
latency_ms	INTEGER	Round-trip time in milliseconds
error_message	TEXT	Error details if failed
retry_count	INTEGER	Which retry attempt this is (0 = first attempt)
created_at	TIMESTAMPTZ	When the submission was initiated

inbound_fax_queue

Queue for inbound faxes received from pharmacies (Tier 4 responses).

Column	Type	Description
fax_id	UUID (PK)	Fax record identifier
documo_fax_sid	TEXT (UNIQUE)	Documo's fax identifier

from_number	TEXT	Sending fax number (used for pharmacy matching)
pharmacy_id	UUID (FK→pharmacies)	Matched pharmacy (null if unmatched)
order_id	UUID (FK→orders)	Matched order (null if unmatched)
status	ENUM	Processing status (RECEIVED / MATCHED / UNMATCHED / PROCESSED / ARCHIVED)
pdf_url	TEXT	URL to the stored fax PDF
ocr_text	TEXT	OCR-extracted text from the fax
matched_at	TIMESTAMPTZ	When the fax was matched to an order
created_at / updated_at	—	Audit timestamps

normalized_catalog

Cross-pharmacy normalized medication catalog for comparison.

Column	Type	Description
normalized_id	UUID (PK)	Normalized entry identifier
pharmacy_id	UUID (FK→pharmacies)	Which pharmacy
catalog_id	UUID (FK→catalog)	Link to the raw catalog entry
normalized_medication_name	TEXT	AI-standardized medication name
normalized_form / normalized_strength	TEXT	Standardized form and strength
wholesale_price	NUMERIC(10,2)	Price for comparison
last_synced_at	TIMESTAMPTZ	Last sync timestamp
created_at / updated_at	—	Audit timestamps

Key Database Principles

1. **Soft-delete everywhere** — No physical DELETEs. Every table has `deleted_at` + `is_active`.
2. **Snapshot immutability** — 7 fields on orders are frozen at DRAFT→AWAITING_PAYMENT via database trigger.
3. **NUMERIC(10,2) for money** — Never floating point. Stripe uses integer cents (multiply by 100).
4. **Atomic CAS** — All state transitions use `WHERE status = :expected` to prevent race conditions.
5. **Append-only audit** — order_status_history, catalog_history, adapter_submissions, webhook_events cannot be updated.
6. **RLS on everything** — Clinic users see only their clinic's data. Ops admins see all. Patients see one order.
7. **Vault for credentials** — Pharmacy API keys and portal passwords reference Vault entries, never stored directly.

CompoundIQ — 17 tables. 10 enums. Zero tolerance for data integrity violations.