

Impact of training dataset size

Training data	Images	Method	Clean	Robust (AA)	Mean	G
100%	50,000	RAAT	85.82 ± 0.12	47.74 ± 0.10	66.78 ± 0.10	64.01
100%	50,000	Ours	85.57 ± 0.33	49.02 ± 0.13	67.30 ± 0.18	64.77
50%	25,000	RAAT	81.21 ± 0.08	41.99 ± 0.21	61.60 ± 0.09	58.40
50%	25,000	Ours	81.56 ± 0.52	43.31 ± 0.15	62.43 ± 0.26	59.43
20%	10,000	RAAT	68.47 ± 0.75	31.37 ± 0.22	49.92 ± 0.47	46.35
20%	10,000	Ours	70.43 ± 1.85	33.52 ± 0.08	51.98 ± 0.93	48.59
10%	5,000	RAAT	63.48 ± 3.87	27.91 ± 0.45	45.70 ± 1.79	42.09
10%	5,000	Ours	61.54 ± 3.09	28.41 ± 0.76	44.97 ± 1.85	41.81

CIFAR-10 · ResNet-18 · ℓ_∞ 8/255 · mean ± population SD (3 seeds)

Ours: Align-only without selection, $\rho = 0.002$; full standard AA on 10,000 test images.
Fixed 110 epochs at every fraction; smaller subsets have fewer optimizer updates.

Mean = $(C + R)/2$; $G = \sqrt{CR}$ (no SD assigned to this aggregate).
Bold: larger displayed mean for each data fraction and metric.