PHOENIX FOR AI

SECURE THE INFERENCE PIPELINE

Models are the new crown jewels. Phoenix wraps a mutating defense shell around your AI workloads — NVIDIA NIMs, LangChain agents, inference endpoints.

Request AI Access →

Learn About AMTD →

INFERENCE TELEMETRY

GPU_SECURE_MODE	ACTIVE
INFERENCE_ENDPOINTS	48
MODEL_ROTATION	3.2s
PIPELINE_INTEGRITY	99.97%

THE AI ATTACK SURFACE

Models Are Crown Jewels

training data, or hijack your expensive GPU compute for their own use.

Predictable deployments and static infrastructure configurations create vulnerabilities that adversaries exploit to compromise models and steal sensitive data. The inference layer is the new perimeter — and it's wide open.

01	LLM-Jacking	Attackers hijack GPU compute for unauthorized inference, running their own models on your infrastructure.
02	Model Theft	Exfiltrating proprietary model weights and training data through persistent access to static endpoints.
03	Prompt Injection	Manipulating model behavior through crafted inputs that exploit predictable serving environments.
04	Inference Manipulation	Tampering with model outputs in production by intercepting static API paths.

A mutating defense shell wrapping your AI workloads. Phoenix adapts its defense posture based on what your models are doing, not just what attackers might do.

Inference Pipeline Mutation

Endpoints rotate, model access paths change, attack surface shifts continuously.

Context-Aware Defense

Defense adapts based on inference load, model type, and threat telemetry.

GPU Resource Protection

Prevents compute hijacking, resource theft, and unauthorized model inference.

Zero-Trust Model Access

Ephemeral credentials and rotating access patterns for model endpoints.

THREE TECHNICAL PILLARS

01

Inference Pipeline Mutation

Phoenix rotates the specific pods handling AI requests. By the time a prompt injection sequence is attempted across multiple requests, the session context is invalidated. Broken session persistence for AI attackers.

utilization and terminates shadow compute processes that signal unauthorized model-scraping. Prevention of model theft and LLM-Jacking.

03

Agentic Defense Logic

Phoenix uses a security agent to observe the I/O of your AI models. If it detects a malicious payload, it triggers an immediate panic mutation — moving the model to a clean, isolated node. Real-time isolation of compromised instances.

BUILT FOR AI INFRASTRUCTURE

Every AI Stack. One Defense Layer.

_ GPU Optimized

Designed for GPU-intensive workloads. Rotation respects CUDA contexts, model loading times, and inference latency requirements. 1-2% overhead even with large models.

_ Framework Agnostic

Works with LangChain, LlamaIndex, NVIDIA NIM, vLLM, and any inference framework. No framework-specific agents or SDKs.

_ Data Privacy First

NeMo Guardrails Compatible

Layered defense: NeMo filters malicious prompts at the application layer while Phoenix evicts persistent attackers at the infrastructure layer.

FREQUENTLY ASKED QUESTIONS

How does Phoenix protect AI inference pipelines? +

Does Phoenix work with NVIDIA NIMs? +

What is LLM-Jacking and how does Phoenix prevent it? +

Does Phoenix impact inference latency? +

Secure your inference pipeline

Purpose-built protection for AI workloads — models, GPU resources, and inference endpoints.



Embrace the Chaos.

PRODUCT

Phoenix for Kubernetes

Phoenix for AI

Open Source

RESOURCES

Documentation

Research

Blog

Case Studies

Brand Assets

COMPANY

About

Team

Careers

Contact

CONNECT

GitHub

LinkedIn

Subscribe

© 2026 R6 Security, Inc. All rights reserved.