




## Handbuch zur Implementierung des sofort Gateway

### SofortLib

1.5.1

Mon Sep 10 2012 10:29:43





# Chapter 1

## Main Page

Base class for Payment Network XML-API This class implements basic http authentication and a xml-parser for parsing response messages

Requires libcurl and openssl

Copyright (c) 2012 SOFORT AG

**Date:**

2012-09-10 10:26:54 +0200 (Mon, 10 Sep 2012)

**Version**

[SofortLib](#) 1.5.0

**Id:**

sofortLib.php 5341 2012-09-10 08:26:54Z Niehoff

**Author**

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))



## Chapter 2

# Namespace Index

### 2.1 Package List

Here are the packages with brief descriptions (if available):

[sofortLib](#) . . . . . 11



## Chapter 3

# Class Index

### 3.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

PnagInvoice . . . . .	13
SofortLib . . . . .	30
SofortLib_CancelSa . . . . .	35
SofortLib_CancelSr . . . . .	38
SofortLib_ClassicNotification . . . . .	39
SofortLib_ConfirmSr . . . . .	40
SofortLib_Debit . . . . .	44
SofortLib_EditSr . . . . .	47
SofortLib_iDeal_Banks . . . . .	49
SofortLib_Multipay . . . . .	51
SofortLib_Notification . . . . .	64
SofortLib_Refund . . . . .	66
SofortLib_SofortueberweisungClassic . . . . .	67
SofortLib_iDealClassic . . . . .	49
SofortLib_TransactionData . . . . .	70





# Chapter 4

## Class Index

### 4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">PnagInvoice</a> . . . . .	13
<a href="#">SofortLib</a> . . . . .	30
<a href="#">SofortLib_CancelSa</a> . . . . .	35
<a href="#">SofortLib_CancelSr</a> . . . . .	38
<a href="#">SofortLib_ClassicNotification</a> . . . . .	39
<a href="#">SofortLib_ConfirmSr</a> . . . . .	40
<a href="#">SofortLib_Debit</a> . . . . .	44
<a href="#">SofortLib_EditSr</a> . . . . .	47
<a href="#">SofortLib_iDeal_Banks</a> . . . . .	49
<a href="#">SofortLib_iDealClassic</a> . . . . .	49
<a href="#">SofortLib_Multipay</a> . . . . .	51
<a href="#">SofortLib_Notification</a> . . . . .	64
<a href="#">SofortLib_Refund</a> . . . . .	66
<a href="#">SofortLib_SofortueberweisungClassic</a> . . . . .	67
<a href="#">SofortLib_TransactionData</a> . . . . .	70



## Chapter 5

# Namespace Documentation

### 5.1 Package sofortLib

#### 5.1.1 Detailed Description

Copyright (c) 2012 SOFORT AG

**Date:**

2012-09-06 12:05:14 +0200 (Thu, 06 Sep 2012)

**Version**

**Id:**

class.invoice.inc.php 5320 2012-09-06 10:05:14Z dehn

**Author**

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))



## Chapter 6

# Class Documentation

### 6.1 PnagInvoice Class Reference

#### Public Member Functions

- [\\_\\_construct](#) (\$configKey, \$transactionId= '')
- [getConstantById](#) (\$id)
- [getConstantByName](#) (\$name)
- [setBitmask](#) (\$status, \$statusReason, \$invoiceStatus)
- [setState](#) (\$state, \$callback= '')
- [getState](#) ()
- [setTransactionId](#) (\$transactionId)
- [refreshTransactionData](#) ()
- [cancelInvoice](#) (\$transactionId= '', \$creditNoteNumber= '')
- [confirmInvoice](#) (\$transactionId= '', \$invoiceNumber= '', \$customerNumber= '', \$orderNumber= '')
- [updateInvoice](#) (\$transactionId, \$items, \$comment, \$invoiceNumber= '', \$customerNumber= '', \$orderNumber= '')
- [updateOrderNumber](#) (\$transactionId, \$orderNumber)
- [addItemToInvoice](#) (\$itemId, \$productNumber, \$title, \$unitPrice, \$productType=0, \$description= '', \$quantity=1, \$tax=19)
- [removeItemfromInvoice](#) (\$itemId)
- [addShippingAddress](#) (\$firstname, \$lastname, \$street, \$streetNumber, \$zipcode, \$city, \$salutation, \$country= 'DE', \$nameAdditive= '', \$streetAdditive= '', \$companyName= '')
- [addShippingAddresss](#) (\$firstname, \$lastname, \$street, \$streetNumber, \$zipcode, \$city, \$salutation, \$country= 'DE', \$nameAdditive= '', \$streetAdditive= '')
- [addInvoiceAddress](#) (\$firstname, \$lastname, \$street, \$streetNumber, \$zipcode, \$city, \$salutation, \$country= 'DE', \$nameAdditive= '', \$streetAdditive= '', \$companyName= '')
- [setOrderId](#) (\$arg)
- [setCustomerId](#) (\$arg)

- [setPhoneNumberCustomer](#) (\$arg)
- [setEmailCustomer](#) (\$arg)
- [addUserVariable](#) (\$arg)
- [setNotificationUrl](#) (\$arg)
- [setAbortUrl](#) (\$arg)
- [setSuccessUrl](#) (\$arg)
- [setTimeoutUrl](#) (\$arg)
- [setTimeout](#) (\$arg)
- [setReason](#) (\$reason1, \$reason2= '')
- [setAmount](#) (\$arg, \$currency= 'EUR')
- [getAmount](#) ()
- [setSofortrechnung](#) ()
- [setDebitorVatNumber](#) (\$vatNumber)
- [getPaymentUrl](#) ()
- [getInvoiceTye](#) ()
- [getTransactionId](#) ()
- [checkout](#) ()
- [getInvoice](#) ()
- [setInvoiceUrl](#) (\$invoiceUrl)
- [getInvoiceUrl](#) ()
- [setStatus](#) (\$status)
- [setStatusReason](#) (\$statusReason)
- [setStatusOfInvoice](#) (\$invoiceStatus= '')
- [setLanguageCode](#) (\$languageCode= '')
- [setTransaction](#) (\$transaction)
- [setTime](#) (\$time)
- [setVersion](#) (\$arg)
- [setPaymentMethod](#) (\$paymentMethod)
- [setInvoiceObjection](#) (\$invoiceObjection)
- [setInvoiceStatus](#) (\$invoiceStatus)
- [getInvoiceObjection](#) ()
- [getStatusOfInvoice](#) ()
- [getInvoiceStatus](#) ()
- [getPaymentMethod](#) ()
- [getStatusReason](#) ()
- [getStatus](#) ()
- [getLanguageCode](#) ()
- [getItems](#) ()
- [setItems](#) (\$items)
- [getTransactionData](#) ()
- [isError](#) ()
- [isWarning](#) ()
- [getError](#) ()
- [getErrors](#) ()
- [getErrorCodes](#) (\$detailLevel=0)
- [getWarnings](#) ()

- [enableLog \(\)](#)
- [disableLog \(\)](#)
- [log \(\\$message\)](#)
- [logError \(\\$message\)](#)
- [logWarning \(\\$message\)](#)

### 6.1.1 Detailed Description

Abstraction of an invoice Helper class to ease usage of "Rechnung by sofort" Encapsulates Multipay, TransactionData and ConfirmSr to handle everything there is about "Rechnung by sofort"

See also

[SofortLib\\_Multipay](#)  
[SofortLib\\_TransactionData](#)  
[SofortLib\\_ConfirmSr](#)

### 6.1.2 Constructor & Destructor Documentation

#### 6.1.2.1 `__construct ( $ configKey, $ transactionId = " )`

Constructor

Parameters

*string* \$apiKey  
*string* \$transactionId  
*string* \$apiUrl

### 6.1.3 Member Function Documentation

#### 6.1.3.1 `addInvoiceAddress ( $ firstname, $ lastname, $ street, $ streetNumber, $ zipcode, $ city, $ salutation, $ country = 'DE', $ nameAdditive = "", $ streetAdditive = "", $ companyName = " )`

Wrapper for [SofortLib\\_Multipay.setSofortrechnungInvoiceAddress](#)

See also

[SofortLib\\_Multipay](#)

Parameters

*\$firstname*  
*\$lastname*  
*\$street*

*\$streetNumber*

*\$zipcode*

*\$city*

*\$salutation*

*\$country* (optional, default: DE)

*\$nameAdditive* (optional)

*\$streetAdditive* (optional)

*\$companyName* (optional)

**6.1.3.2** `addItemToInvoice ( $ itemId, $ productNumber, $ title, $ unitPrice, $ productType = 0, $ description = "", $ quantity = 1, $ tax = 19 )`

Wrapper for [SofortLib\\_Multipay.addItemToInvoice](#)

See also

[SofortLib\\_Multipay](#)

**Parameters**

*\$itemId*

*\$productNumber*

*\$title*

*\$unit\_price* - float precision 2

See also

[SofortLib\\_Multipay](#) api

**Parameters**

*\$productType*

*\$description*

*\$quantity* - int

*\$tax*

**6.1.3.3** `addShippingAddress ( $ firstname, $ lastname, $ street, $ streetNumber, $ zipcode, $ city, $ salutation, $ country = 'DE', $ nameAdditive = "", $ streetAdditive = "", $ companyName = "" )`

Wrapper for [SofortLib\\_Multipay.addShippingAddress](#)

See also

[SofortLib\\_Multipay](#)



**Parameters**

*\$firstname*  
*\$lastname*  
*\$street*  
*\$streetNumber*  
*\$zipcode*  
*\$city*  
*\$salutation*  
*\$country* (optional, default: DE)  
*\$nameAdditive* (optional)  
*\$streetAdditive* (optional)  
*\$companyName* (optional)

**6.1.3.4** `addShippingAddressss ( $ firstname, $ lastname, $ street, $ streetNumber, $ zipcode, $ city, $ salutation, $ country = 'DE', $ nameAdditive = "", $ streetAdditive = " )`

Wrapper for [SofortLib\\_Multipay.setSofortrechnungShippingAddress](#)

**See also**

[SofortLib\\_Multipay](#)

**Parameters**

*\$firstname*  
*\$lastname*  
*\$street*  
*\$streetNumber*  
*\$zipcode*  
*\$city*  
*\$salutation*  
*\$country* (optional, default: DE)  
*\$nameAdditive* (optional)  
*\$streetAdditive* (optional)

**6.1.3.5** `addUserVariable ( $ arg )`

Wrapper function for [SofortLib\\_Multipay.addUserVariable](#)

**Parameters**

*\$arg*

**6.1.3.6** `cancelInvoice ( $ transactionId = "", $ creditNoteNumber = " )`

Wrapper function for cancelling this invoice via [SofortLib\\_Multipay](#) ([SofortLib](#))

**Returns**

Ambigious boolean/Array

**6.1.3.7** `checkout ( )`

Validate your parameters against API

**Returns**

array - any validationerrors and -warnings send the order to pnap (-> buy your products)  
empty array if ok ELSE array with errors and/or warnings

**6.1.3.8** `confirmInvoice ( $ transactionId = "", $ invoiceNumber = "", $ customerNumber = "", $ orderNumber = " )`

Wrapper function for confirming this invoice via [SofortLib\\_Multipay](#) ([SofortLib](#))

**Parameters**

*\$transactionId* - optional parameter for confirming a transaction on the fly  
*\$invoiceNumber* - optional parameter for own invoice number  
*\$customerNumber* - optional parameter for own customer number  
*\$orderNumber* - optional parameter for own order number

**Returns**

Ambigious boolean/Array

**6.1.3.9** `disableLog ( )`

Disable logging for all encapsed [SofortLib](#) components

**Returns**

boolean

**6.1.3.10** `enableLog ( )`

Enabling logging for all encapsed [SofortLib](#) components

**Returns**

boolean

**6.1.3.11** `getAmount ( )`

current total amount of the given order-articles

**Returns**

float - sum (price, total) of all articles

**6.1.3.12** `getConstantById ( $ id )`

Getter for a class constant

**Parameters**

*int* \$id

**Returns**

string

**6.1.3.13** `getConstantByName ( $ name )`

Getter for a class constant

**Parameters**

*string* \$name

**Returns**

int

**6.1.3.14** `getError ( )`

returns one error (as String!)

**6.1.3.15** `getErrorCodes ( $ detailLevel = 0 )`

Ouputs errors in a more convenient array to let users easily iterate

**Parameters**

*int* \$detailLevel

**6.1.3.16** `getErrors ( )`

collect all errors and returns them

**Returns**

array - all errors

**6.1.3.17 getInvoice ( )**

Output the resulting invoice as pdf, if possible Function uses file\_get\_contents, if allow\_url\_fopen is allowed in php.ini (might be disabled on shared hosting) As a fall-back, downloading via cURL, when module cURL is available If neither file\_get\_contents nor cURL is available for downloading, a connection via socket is used to download.

**Returns**

boolean

**6.1.3.18 getInvoiceObjection ( )**

Returns the reason for objecting this invoice

**Returns**

string

**6.1.3.19 getInvoiceStatus ( )**

Uses the statusMask to "calculate" the current invoice's payment status

**See also**

Invoice.\_calcInvoiceStatusCode

**Returns**

int

**6.1.3.20 getInvoiceTye ( )**

Wrapper function for SofortLib\_Multipay.geInvoiceType

**Returns**

(OR or LS)

**6.1.3.21 getInvoiceUrl ( )**

Getter for retrieving the invoice's url

**Returns**

url string

**6.1.3.22** `getItems ( )`

Getter for items

**Returns**

array

**6.1.3.23** `getLanguageCode ( )`

Getter for language code

**Returns**

string

**6.1.3.24** `getPaymentMethod ( )`

Getter for payment\_method

**Returns**

string

**6.1.3.25** `getPaymentUrl ( )`

Wrapper function for [SofortLib\\_Multipay.getPaymentUrl](#)

**Returns**

url string

**6.1.3.26** `getState ( )`

Getter for the current state

**Returns**

int \$this->state

**6.1.3.27** `getStatus ( )`

Getter for status

**Returns**

string

**6.1.3.28 getStatusOfInvoice ( )**

Instead of calculated status, this method returns the invoice's status (string)

**Returns**

string

**6.1.3.29 getStatusReason ( )**

Getter for status\_reason

**Returns**

string

**6.1.3.30 getTransactionData ( )**

return TransactionData, the invoice is working with NOTICE: if status changed (removeArticle, InvoiceConfirmed etc.) it returns always the FRESH TransactionData from pnag-server

**Returns**

object

**See also**

`$this->refreshTransactionData\(\);`

**6.1.3.31 getTransactionId ( )**

Wrapper function for [SofortLib\\_Multipay.getPaymentUrl](#)

**Returns**

url string

**6.1.3.32 getWarnings ( )**

collects all warnings and returns them

**Returns**

array

### 6.1.3.33 isError ( )

Check, if errors occurred

#### Returns

boolean

### 6.1.3.34 isWarning ( )

Check, if warnings occurred

#### Returns

boolean

### 6.1.3.35 log ( \$ message )

Log the given String into log.txt Notice: logging must be enabled -> use [enableLog\(\)](#);

#### Parameters

*string* \$msg - Message to log

#### Returns

bool - true=logged ELSE false=logging failed

### 6.1.3.36 logError ( \$ message )

Log the given String into error\_log.txt Notice: logging must be enabled -> use [enableLog\(\)](#);

#### Parameters

*string* \$msg - Message to log

#### Returns

bool - true=logged ELSE false=logging failed

### 6.1.3.37 logWarning ( \$ message )

Log the given String into warning\_log.txt

#### Parameters

*string* \$msg - Message to log

**Returns**

bool - true=logged ELSE false=logging failed

**6.1.3.38 refreshTransactionData ( )**

Refreshes the TransactionData with the data directly from the pnap-server

**Returns**

boolean

**6.1.3.39 removeItemfromInvoice ( \$ itemId )**

Remove an item from the invoice

**Parameters**

*\$itemId*

**Returns**

boolean

**6.1.3.40 setAbortUrl ( \$ arg )**

Wrapper function for [SofortLib\\_Multipay.setAbortUrl](#)

**Parameters**

*\$arg*

**6.1.3.41 setAmount ( \$ arg, \$ currency = 'EUR' )**

Wrapper function for [SofortLib\\_Multipay.setAmount](#)

**Parameters**

*\$arg* float

*\$currency* string



**6.1.3.42 setBitmask ( \$ status, \$ statusReason, \$ invoiceStatus )**

Set the bitmask to a specific state

**Parameters**

*string* \$status  
*string* \$status\_reason  
*string* \$invoice\_status

**Returns**

string pending - confirm\_invoice - empty -> 4195329

**6.1.3.43 setCustomerId ( \$ arg )**

Wrapper function for [SofortLib\\_Multipay.setSofortrechnungCustomerId](#)

**Parameters**

*\$arg*

**6.1.3.44 setDebitorVatNumber ( \$ vatNumber )**

Wrapper function for [SofortLib\\_Multipay.setDebitorVatNumber](#)

**6.1.3.45 setEmailCustomer ( \$ arg )**

Wrapper function for [SofortLib\\_Multipay.setEmailCustomer](#)

**Parameters**

*\$arg*

**6.1.3.46 setInvoiceObjection ( \$ invoiceObjection )**

Sets the reason for objecting this invoice

**Parameters**

*string* \$invoiceObjection (40-50 chars max.)

**Returns**

object

**6.1.3.47 setInvoiceStatus ( \$ *invoiceStatus* )**

Sets the invoice status

**Parameters**

*string* \$invoiceStatus

**Returns**

object

**6.1.3.48 setInvoiceUrl ( \$ *invoiceUrl* )**

Setter for invoiceUrl

**Parameters**

*\$invoiceUrl*

**Returns**

object

**6.1.3.49 setItems ( \$ *items* )**

Setter for invoice items, takes an array of PnagArticle objects

**Parameters**

*array* \$items

**6.1.3.50 setLanguageCode ( \$ *languageCode* = " " )**

Setter for language\_code

**Parameters**

*string* \$language\_code | fallback en

**Returns**

object

**6.1.3.51 setNotificationUrl ( \$ *arg* )**

Wrapper function for [SofortLib\\_Multipay.setNotificationUrl](#)

**Parameters**

*\$arg*

**6.1.3.52 setOrderId ( \$ arg )**

Wrapper function for [SofortLib\\_Multipay.setSofortrechnungOrderId](#)

See also

[SofortLib\\_Multipay](#)

**Parameters**

*\$arg*

**6.1.3.53 setPaymentMethod ( \$ paymentMethod )**

Setter for payment\_method

**Parameters**

*\$paymentMethod*

**Returns**

object

**6.1.3.54 setPhoneNumberCustomer ( \$ arg )**

Wrapper function for [SofortLib\\_Multipay.setPhoneNumberCustomer](#)

**Parameters**

*\$arg*

**6.1.3.55 setReason ( \$ reason1, \$ reason2 = " )**

Wrapper function for [SofortLib\\_Multipay.setReason](#)

**Parameters**

*\$reason1* string

*\$reason2* string

**6.1.3.56 setSofortrechnung ( )**

Wrapper function for [SofortLib\\_Multipay.setSofortrechnung](#)

**6.1.3.57** `setState ( $ state, $ callback = " )`

Set the state An optional callback can be registered

**Parameters**

*int* \$state

*function* \$callback

**6.1.3.58** `setStatus ( $ status )`

Setter for status

**Parameters**

*\$status*

**Returns**

object

**6.1.3.59** `setStatusOfInvoice ( $ invoiceStatus = " )`

Setter for invoice\_status

**Parameters**

*string* \$invoice\_status | may be empty

**Returns**

object

**6.1.3.60** `setStatusReason ( $ statusReason )`

Setter for status\_reason

**Parameters**

*\$status\_reason*

**Returns**

object

**6.1.3.61 setSuccessUrl ( \$ *arg* )**

Wrapper function for [SofortLib\\_Multipay.setSuccessUrl](#)

**Parameters**

*\$arg*

**6.1.3.62 setTime ( \$ *time* )**

Setter for time

**Parameters**

*\$time* return object

**6.1.3.63 setTimeout ( \$ *arg* )**

Wrapper function for [SofortLib\\_Multipay.setTimeout](#)

**Parameters**

*\$arg*

**6.1.3.64 setTimeoutUrl ( \$ *arg* )**

Wrapper function for [SofortLib\\_Multipay.setTimeoutUrl](#)

**Parameters**

*\$arg*

**6.1.3.65 setTransaction ( \$ *transaction* )**

Setter for transaction

**Parameters**

*\$transaction*

**Returns**

object

**6.1.3.66 setTransactionId ( \$ transactionId )**

Setter for transactionId

**Parameters**

*\$transactionId*

**6.1.3.67 setVersion ( \$ arg )**

Setter for interface version Wrapper for class Multipay to set version according to shop module and it's interface version e.g. 'pn\_xtc\_5.0.0'

**Parameters**

*\$arg* string

**6.1.3.68 updateInvoice ( \$ transactionId, \$ items, \$ comment, \$ invoiceNumber = "", \$ customerNumber = "", \$ orderNumber = "" )**

Wrapper function for removing an article via [SofortLib\\_Multipay](#) ([SofortLib](#))

**Parameters**

*\$transactionId* string

*\$PnagArticels* array

*\$comment* int

return array

**6.1.3.69 updateOrderNumber ( \$ transactionId, \$ orderNumber )**

Wrapper function for updating order number after order has been placed

**Parameters**

*string* \$transactionId

*string* \$orderNumber

The documentation for this class was generated from the following file:

- class.invoice.inc.php

**6.2 SofortLib Class Reference****Public Member Functions**

- [\\_\\_construct](#) (\$userId= "", \$apiKey= "", \$apiUrl= "")

- [getWarnings](#) (\$paymentMethod= 'all', \$message= '')
- [getErrors](#) (\$paymentMethod= 'all', \$message= '')
- [handleErrors](#) (\$errors)
- [getError](#) (\$paymentMethod= 'all', \$message= '')
- [isWarning](#) (\$paymentMethod= 'all', \$message= '')
- [isError](#) (\$paymentMethod= 'all', \$message= '')
- [deleteAllWarnings](#) ()
- [deleteAllErrors](#) ()
- [error](#) (\$message, \$fatal=false)
- [fatalError](#) (\$message)
- [enableLog](#) ()
- [disableLog](#) ()
- [setLogEnabled](#) ()
- [setLogDisabled](#) ()
- [setLogger](#) (\$SofortLibLogger)
- [logWarning](#) (\$message)
- [logError](#) (\$message)
- [log](#) (\$message)
- [setApiVersion](#) (\$version)

## Protected Member Functions

- [\\_sendMessage](#) (\$message)

### 6.2.1 Detailed Description

Include any available helper here

Basic PHP Library for communication with multipay API and related products of so-fort.com

#### Author

payment-network.com

### 6.2.2 Constructor & Destructor Documentation

#### 6.2.2.1 `__construct ( $ userId = "", $ apiKey = "", $ apiUrl = "" )`

Constructor

#### Parameters

*string* \$apiKey

## 6.2.3 Member Function Documentation

### 6.2.3.1 `_sendMessage ( $ message ) [protected]`

internal send-method, will check http-errorcode and return body

#### Parameters

*String* \$message message to post

#### Returns

string error or body

### 6.2.3.2 `deleteAllErrors ( )`

delete all errors

### 6.2.3.3 `deleteAllWarnings ( )`

delete all warnings

### 6.2.3.4 `disableLog ( )`

#### See also

[SofortLib setLogDisabled](#)

### 6.2.3.5 `enableLog ( )`

#### See also

[SofortLib setLogEnabled](#)

### 6.2.3.6 `error ( $ message, $ fatal = false )`

#### Parameters

*unknown\_type* \$message

*unknown\_type* \$fatal

### 6.2.3.7 `fatalError ( $ message )`

error while parsing xml

#### Parameters

*unknown\_type* \$message



**6.2.3.8** `getError ( $ paymentMethod = 'a11', $ message = " )`

returns one error message

See also

[getErrors\(\)](#) for more detailed errors

**Parameters**

*array* \$message response array

**Returns**

string errorMessage ELSE false

**6.2.3.9** `getErrors ( $ paymentMethod = 'a11', $ message = " )`

Getter for errors

**Parameters**

(*optional*) *array* \$message response array

**Returns**

empty array if no error exist ELSE array with error-codes and error-messages

**6.2.3.10** `getWarnings ( $ paymentMethod = 'a11', $ message = " )`

Getter for warnings

**Returns**

empty array if no warnings exists ELSE array with warning-codes and warning-messages

**6.2.3.11** `handleErrors ( $ errors )`

Alter error array and set error message and error code together as one

**Parameters**

*array* \$errors

**6.2.3.12 isError ( \$ paymentMethod = 'all', \$ message = " )**

checks (response)-array for error

**Parameters**

*array* \$message response array

*string* \$paymentMethod - 'all', 'sr', 'su', 'sv', 'sa', 'ls', 'sl', 'sf' (if unknown then it uses "all")

**Returns**

boolean true if errors found (in given payment-method or in 'global') ELSE false

**6.2.3.13 isWarning ( \$ paymentMethod = 'all', \$ message = " )**

checks (response)-array for warnings

**Parameters**

*array* \$message response array

*string* \$paymentMethod - 'all', 'sr', 'su', 'sv', 'sa', 'ls', 'sl', 'sf' (if unknown then it uses "all")

**Returns**

boolean true if warnings found ELSE false

**6.2.3.14 log ( \$ message )**

log the given string into log.txt use \$this->[enableLog\(\)](#); to enable logging before!

**Parameters**

*string* \$message

**6.2.3.15 logError ( \$ message )**

log the given string into error\_log.txt use \$this->[enableLog\(\)](#); to enable logging before!

**Parameters**

*string* \$message

#### 6.2.3.16 logWarning ( \$ message )

log the given string into warning\_log.txt use \$this->[enableLog\(\)](#); to enable logging before!

##### Parameters

*string* \$message

#### 6.2.3.17 setApiVersion ( \$ version )

sets the api version which should be used

##### Parameters

*float* \$version

#### 6.2.3.18 setLogDisabled ( )

[disableLog\(\)](#);

#### 6.2.3.19 setLogEnabled ( )

[enableLog\(\)](#);

#### 6.2.3.20 setLogger ( \$ SofortLibLogger )

Set the SofortLibLogger object

##### Parameters

*object* \$SofortLibLogger

The documentation for this class was generated from the following file:

- sofortLib.php

## 6.3 SofortLib\_CancelSa Class Reference

### Public Member Functions

- [\\_\\_construct](#) (\$configKey= '')
- [removeSofortDauerauftrag](#) (\$transaction)
- [setSuccessUrl](#) (\$arg)
- [setAbortUrl](#) (\$arg)
- [setTimeoutUrl](#) (\$arg)
- [setTransaction](#) (\$arg)

### 6.3.1 Detailed Description

The base class for cancelling SofortDauerauftrag

Copyright (c) 2012 SOFORT AG

**Date:**

2012-09-05 14:27:56 +0200 (Wed, 05 Sep 2012)

**Version**

[SofortLib](#) 1.5.0

**Id:**

sofortLib\_cancel\_sa.inc.php 5301 2012-09-05 12:27:56Z dehn

**Author**

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

### 6.3.2 Constructor & Destructor Documentation

#### 6.3.2.1 `__construct ( $ configKey = " )`

create new cancel object

**Parameters**

*String* \$apikey your API-key

### 6.3.3 Member Function Documentation

#### 6.3.3.1 `removeSofortDauerauftrag ( $ transaction )`

remove SofortDauerauftrag

**Parameters**

*String* \$transaction Transaction ID

**Returns**

[SofortLib\\_CancelSa](#)

#### 6.3.3.2 `setAbortUrl ( $ arg )`

the customer will be redirected to this url if he uses the abort link on the payment form, should redirect him back to his cart or to the payment selection page

**Parameters**

*string* \$arg url for aborting the transaction

**Returns**

[SofortLib\\_Multipay](#)

**6.3.3.3 setSuccessUrl ( \$ arg )**

the customer will be redirected to this url after a successful transaction, this should be a page where a short confirmation is displayed

**Parameters**

*string* \$arg the url after a successful transaction

**Returns**

[SofortLib\\_Multipay](#)

**6.3.3.4 setTimeoutUrl ( \$ arg )**

if the customer takes too much time or if your timeout is set too short he will be redirected to this page

**Parameters**

*string* \$arg url

**Returns**

[SofortLib\\_Multipay](#)

**6.3.3.5 setTransaction ( \$ arg )**

Set the transaction you want to confirm/change

**Parameters**

*String* \$arg Transaction Id

**Returns**

[SofortLib\\_CancelSa](#)

The documentation for this class was generated from the following file:

- sofortLib\_cancel\_sa.inc.php

## 6.4 SofortLib\_CancelSr Class Reference

### Public Member Functions

- [\\_\\_construct](#) (\$configKey= "")
- [setTransaction](#) (\$transaction, \$invoice=0)
- [setComment](#) (\$comment, \$invoice=0)
- [cancelInvoice](#) (\$transaction= "", \$invoice=0)
- [getInvoiceUrl](#) ()

### 6.4.1 Detailed Description

This class is for confirming and changing statuses of invoices

eg: \$confirmObj = new [SofortLib\\_CancelSr](#)('yourapikey');

\$confirmObj->confirmInvoice('1234-456-789654-31321')->sendRequest();

Copyright (c) 2012 SOFORT AG

#### Date:

2012-05-21 16:53:26 +0200 (Mo, 21 Mai 2012)

#### Version

[SofortLib](#) 1.5.0

#### Id:

sofortLib\_cancel\_sr.inc.php 4191 2012-05-21 14:53:26Z niehoff

#### Author

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

### 6.4.2 Constructor & Destructor Documentation

#### 6.4.2.1 `__construct ( $ configKey = " )`

create new confirm object

#### Parameters

*String* \$apikey your API-key

### 6.4.3 Member Function Documentation

#### 6.4.3.1 `cancelInvoice ( $ transaction = "", $ invoice = 0 )`

cancel the invoice

**Parameters**

*string* \$transaction the transaction id

**Returns**

[SofortLib\\_ConfirmSr](#)

**6.4.3.2 getInvoiceUrl ( )**

after you you changed/confirmed an invoice you can download the new invoice-pdf with this function

**Returns**

string url

**6.4.3.3 setComment ( \$ comment, \$ invoice = 0 )**

set a comment for refunds

**Parameters**

*string* \$arg

**6.4.3.4 setTransaction ( \$ transaction, \$ invoice = 0 )**

Set the transaction you want to confirm/change

**Parameters**

*String* \$transaction Transaction Id

**Returns**

[SofortLib\\_ConfirmSr](#)

The documentation for this class was generated from the following file:

- sofortLib\_cancel\_sr.inc.php

## 6.5 SofortLib\_ClassicNotification Class Reference

**Protected Member Functions**

- [\\_getHashHexValue](#) (\$data, \$hashFunction= 'sha1')

### 6.5.1 Detailed Description

Instance of this class handles the callback of SOFORT to notify about a status change, the classic way to do so

Copyright (c) 2012 SOFORT AG

**Date:**

2012-09-05 14:28:13 +0200 (Wed, 05 Sep 2012)

**Version**

[SofortLib](#) 1.5.0

**Id:**

sofortLib\_classic\_notification.inc.php 5302 2012-09-05 12:28:13Z dehn

**Author**

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

### 6.5.2 Member Function Documentation

#### 6.5.2.1 `_getHashHexValue ( $ data, $ hashFunction = 'sha1' )` `[protected]`

**Parameters**

*string* \$data string to be hashed

**Returns**

string the hash

The documentation for this class was generated from the following file:

- `sofortLib_classic_notification.inc.php`

## 6.6 SofortLib\_ConfirmSr Class Reference

### Public Member Functions

- [\\_\\_construct](#) (\$configKey= '')
- [setTransaction](#) (\$transaction, \$invoice=0)
- [setComment](#) (\$comment)
- [addItem](#) (\$itemId, \$productNumber, \$productType, \$title, \$description, \$quantity, \$unitPrice, \$tax)
- [removeItem](#) (\$productId, \$quantity=0)



- [updateCart](#) (\$cartItems=array())
- [cancelInvoice](#) (\$transaction= "")
- [confirmInvoice](#) (\$transaction= "")
- [getInvoiceUrl](#) (\$i=0)

### 6.6.1 Detailed Description

This class is for confirming and changing statuses of invoices

eg: `$confirmObj = new SofortLib\_ConfirmSr('yourapikey');`

`$confirmObj->confirmInvoice('1234-456-789654-31321')->sendRequest();`

Copyright (c) 2012 SOFORT AG

#### Date:

2012-09-05 14:27:56 +0200 (Wed, 05 Sep 2012)

#### Version

[SofortLib](#) 1.5.0

#### Id:

sofortLib\_confirm\_sr.inc.php 5301 2012-09-05 12:27:56Z dehn

#### Author

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

### 6.6.2 Constructor & Destructor Documentation

#### 6.6.2.1 `__construct ( $ configKey = " )`

create new confirm object

#### Parameters

*String* \$apikey your API-key

### 6.6.3 Member Function Documentation

#### 6.6.3.1 `addItem ( $ itemId, $ productNumber, $ productType, $ title, $ description, $ quantity, $ unitPrice, $ tax )`

add one item to the cart if you want to change the invoice just useable with api version 1.0

#### See also

[SofortLib\\_EditSr](#)

**Parameters**

*string* \$productNumber product number, EAN code, ISBN number or similar

*string* \$title description of this title

*double* \$unit\_price gross price of one item

*int* \$productType product type number see manual

*string* \$description additional description of this item

*int* \$quantity default 1

*int* \$tax tax in percent, default 19

**6.6.3.2 cancelInvoice ( \$ transaction = " )**

cancel the invoice just useable with api version 1.0

**See also**

[SofortLib\\_EditSr](#)

**Parameters**

*string* \$transaction the transaction id

**Returns**

[SofortLib\\_ConfirmSr](#)

**6.6.3.3 confirmInvoice ( \$ transaction = " )**

confirm the invoice

**Parameters**

*string* \$transaction the transaction id

**Returns**

[SofortLib\\_ConfirmSr](#)

**6.6.3.4 getInvoiceUrl ( \$ i = 0 )**

after you you changed/confirmed an invoice you can download the new invoice-pdf with this function

**Returns**

string url

### 6.6.3.5 removeItem ( *\$ productId*, *\$ quantity = 0* )

TODO: implement removal of items

See also

[SofortLib\\_EditSr](#)

Parameters

*\$productId*

*\$quantity*

### 6.6.3.6 setComment ( *\$ comment* )

set a comment for refunds just useable with api version 1.0

See also

[SofortLib\\_EditSr](#)

Parameters

*string* \$arg

### 6.6.3.7 setTransaction ( *\$ transaction*, *\$ invoice = 0* )

Set the transaction you want to confirm

Parameters

*String* \$transaction Transaction Id

Returns

[SofortLib\\_ConfirmSr](#)

### 6.6.3.8 updateCart ( *\$ cartItems = array()* )

See also

[SofortLib\\_EditSr](#)

Parameters

*array* \$cartItems

The documentation for this class was generated from the following file:

- sofortLib\_confirm\_sr.inc.php

## 6.7 SofortLib\_Debit Class Reference

### Public Member Functions

- [sendRequest](#) ()
- [setProjectId](#) (\$id)
- [setDate](#) (\$date= '')
- [setSenderAccount](#) (\$bankCode, \$accountNumber, \$holder)
- [setSenderAccountNumber](#) (\$accountNumber)
- [setSenderBankCode](#) (\$bankCode)
- [setSenderHolder](#) (\$name)
- [setAmount](#) (\$amount)
- [addUserVariable](#) (\$userVariable)
- [addReason](#) (\$reason)
- [setReason](#) (\$reason1, \$reason2= '')
- [getTransactionId](#) ()

### 6.7.1 Detailed Description

class for handling debit/lastschrift

Copyright (c) 2012 SOFORT AG

#### Date:

2012-09-05 14:27:56 +0200 (Wed, 05 Sep 2012)

#### Version

[SofortLib](#) 1.5.0

#### Id:

sofortLib\_debit.inc.php 5301 2012-09-05 12:27:56Z dehn

#### Author

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

### 6.7.2 Member Function Documentation

#### 6.7.2.1 addReason ( \$ *reason* )

adds another reason (verwendungszweck) only first two can be used, 27 characters each

#### Parameters

*\$reason* string

#### Returns

[SofortLib\\_Debit](#) \$this

### 6.7.2.2 addUserVariable ( \$ *userVariable* )

add another user-variable to this transfer this variable could be a customer-number or similar and will help you identify this transfer later

#### Parameters

*String* \$userVariable max 255 characters

#### Returns

[SofortLib\\_Debit](#) \$this

### 6.7.2.3 getTransactionId ( )

get Transaction-Id of this Transfer

#### Returns

String transaction-id

### 6.7.2.4 sendRequest ( )

send this debitpay and get response

#### Returns

boolean true if transaction was accepted, false otherwise

### 6.7.2.5 setAmount ( \$ *amount* )

set amount of this transfer needs to be a decimal e.g. 2.24

#### Parameters

*float* \$amount amount of this transfer

### 6.7.2.6 setDate ( \$ *date* = " )

sets date of this debitpay automatically called in constructor and set to today

#### Parameters

*String* \$date date in Format Y-m-d (eg: 2011-01-20), default: today

#### Returns

[SofortLib\\_Debit](#) \$this

**6.7.2.7 setProjectId ( \$ id )**

Project id Id of your Sofortlastschrift project

**Parameters**

*int* \$id project id

**Returns**

[SofortLib\\_Debit](#) \$this

**6.7.2.8 setReason ( \$ reason1, \$ reason2 = " )**

set reason (verwendungszweck) of this transfer two lines possible, 27 characters each

**Parameters**

*\$reason1*

*\$reason2*

**Returns**

[SofortLib\\_Debit](#) \$this

**6.7.2.9 setSenderAccount ( \$ bankCode, \$ accountNumber, \$ holder )**

set data of account

**Parameters**

*String* \$bankCode bank code of bank

*String* \$accountNumber account number

*String* \$holder Name/Holder of this account

**Returns**

[SofortLib\\_Debit](#) \$this

**6.7.2.10 setSenderAccountNumber ( \$ accountNumber )**

set data of account

**Parameters**

*String* \$accountNumber account number

**Returns**

[SofortLib\\_Debit](#) \$this

### 6.7.2.11 setSenderBankCode ( \$ *bankCode* )

set data of account

#### Parameters

*String* \$bankCode bank code of bank

#### Returns

[SofortLib\\_Debit](#) \$this

### 6.7.2.12 setSenderHolder ( \$ *name* )

set data of account

#### Parameters

*String* \$name Name/Holder of this account

#### Returns

[SofortLib\\_Debit](#) \$this

The documentation for this class was generated from the following file:

- `sofortLib_debit.inc.php`

## 6.8 SofortLib\_EditSr Class Reference

### Public Member Functions

- [\\_\\_construct](#) (\$configKey= "")
- [setComment](#) (\$comment, \$invoice=0)
- [addItem](#) (\$itemId, \$productNumber, \$productType, \$title, \$description, \$quantity, \$unitPrice, \$tax, \$invoice=0)
- [getInvoiceUrl](#) ()

### 6.8.1 Detailed Description

This class is for confirming and changing statuses of invoices

eg: \$confirmObj = new [SofortLib\\_EditSr](#)('yourapikey');

\$confirmObj->confirmInvoice('1234-456-789654-31321')->sendRequest();

Copyright (c) 2012 SOFORT AG

**Date:**

2012-05-21 16:53:26 +0200 (Mo, 21 Mai 2012)

**Version**

[SofortLib](#) 1.5.0

**Id:**

sofortLib\_edit\_sr.inc.php 4191 2012-05-21 14:53:26Z niehoff

**Author**

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

## 6.8.2 Constructor & Destructor Documentation

### 6.8.2.1 `__construct ( $ configKey = " )`

create new confirm object

**Parameters**

*String* \$apikey your API-key

## 6.8.3 Member Function Documentation

### 6.8.3.1 `addItem ( $ itemId, $ productNumber, $ productType, $ title, $ description, $ quantity, $ unitPrice, $ tax, $ invoice = 0 )`

add one item to the cart if you want to change the invoice

**Parameters**

*string* \$itemId itemId

*double* \$unit\_price gross price of one item

*int* \$quantity default 1

### 6.8.3.2 `getInvoiceUrl ( )`

after you you changed/confirmed an invoice you can download the new invoice-pdf with this function

**Returns**

string url



### 6.8.3.3 setComment ( \$ comment, \$ invoice = 0 )

set a comment for refunds just useable with api version 1.0

#### Parameters

*string* \$arg

The documentation for this class was generated from the following file:

- `sofortLib_edit_sr.inc.php`

## 6.9 SofortLib\_iDeal\_Banks Class Reference

### 6.9.1 Detailed Description

This class encapsulates retrieval of listed banks of the Netherlands

Copyright (c) 2012 SOFORT AG

#### Date:

2012-09-05 14:27:56 +0200 (Wed, 05 Sep 2012)

#### Version

[SofortLib](#) 1.5.0

#### Id:

`sofortLib_ideal_banks.inc.php` 5301 2012-09-05 12:27:56Z dehn

#### Author

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

The documentation for this class was generated from the following file:

- `sofortLib_ideal_banks.inc.php`

## 6.10 SofortLib\_iDealClassic Class Reference

Inherits [SofortLib\\_SofortueberweisungClassic](#).

### Public Member Functions

- [setSenderCountryId](#) (\$senderCountryId= 'NL')
- [setSenderBankCode](#) (\$senderBankCode)
- [getRelatedBanks](#) ()

### 6.10.1 Detailed Description

iDeal\_Classic extends Sofortueberweisung\_Classic, implementing payment via iDeal  
Setup a session within iDeal using the classic api You get the so called payment-url  
after successful configuration Payment is enabled with this url being sent to iDeal

eg: \$sofort = \$sofortLib\_iDealClassic = new [SofortLib\\_iDealClassic](#) (\$configurationKey, \$password, \$hashfunction = 'sha1'); \$sofort->[getRelatedBanks\(\)](#); //get all iDEAL-Banks \$sofort->getPaymentUrl(); //returns paymentUrl including (including ...&hash=1234567890&...)

Copyright (c) 2012 SOFORT AG

**Date:**

2012-09-05 14:27:56 +0200 (Wed, 05 Sep 2012)

**Version**

[SofortLib](#) 1.5.0

**Id:**

sofortLib\_ideal\_classic.php 5301 2012-09-05 12:27:56Z dehn

**Author**

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

### 6.10.2 Member Function Documentation

#### 6.10.2.1 `getRelatedBanks ( )`

Get related banks of iDeal

**Returns**

array

#### 6.10.2.2 `setSenderBankCode ( $ senderBankCode )`

Set sender's bank code

**Parameters**

*string* \$senderBankCode

**Returns**

instance

### 6.10.2.3 setSenderCountryId ( \$ senderCountryId = 'NL' )

Set sender's country id

#### Parameters

*string* \$senderCountryId

#### Returns

instance

The documentation for this class was generated from the following file:

- sofortLib\_ideal\_classic.php

## 6.11 SofortLib\_Multipay Class Reference

### Public Member Functions

- [\\_\\_construct](#) (\$configKey= '')
- [setLanguageCode](#) (\$arg)
- [setTimeout](#) (\$arg)
- [setEmailCustomer](#) (\$arg)
- [setPhoneNumberCustomer](#) (\$arg)
- [addUserVariable](#) (\$arg)
- [setSenderAccount](#) (\$bankCode, \$accountNumber, \$holder)
- [setAmount](#) (\$arg, \$currency= 'EUR')
- [setReason](#) (\$arg, \$arg2= '')
- [setSuccessUrl](#) (\$arg)
- [setAbortUrl](#) (\$arg)
- [setTimeoutUrl](#) (\$arg)
- [setNotificationUrl](#) (\$arg)
- [addNotificationUrl](#) (\$arg)
- [setNotificationEmail](#) (\$arg)
- [addNotificationEmail](#) (\$arg)
- [setVersion](#) (\$arg)
- [setSofortueberweisung](#) (\$amount= '')
- [setSofortueberweisungCustomerprotection](#) (\$customerProtection=true)
- [setSofortlastschrift](#) (\$amount= '')
- [setSofortlastschriftAddress](#) (\$firstname, \$lastname, \$street, \$streetNumber, \$zipcode, \$city, \$salutation, \$country= 'DE')
- [setLastschrift](#) (\$amount= '')
- [setLastschriftAddress](#) (\$firstname, \$lastname, \$street, \$streetNumber, \$zipcode, \$city, \$salutation, \$country= 'DE')
- [setSofortDauerauftrag](#) ()
- [setSofortDauerauftragStartDate](#) (\$arg)

- [setSofortDauerauftragTotalPayments](#) (\$arg)
- [setSofortDauerauftragMinimumPayments](#) (\$arg)
- [setSofortDauerauftragInterval](#) (\$arg)
- [setSofortrechnung](#) ()
- [setSofortvorkasse](#) (\$amount= '')
- [setSofortvorkasseCustomerprotection](#) (\$customerProtection=true)
- [setSofortrechnungCustomerId](#) (\$arg)
- [setSofortrechnungOrderId](#) (\$arg)
- [setDebitorVatNumber](#) (\$vatNumber)
- [setSofortrechnungInvoiceAddress](#) (\$firstname, \$lastname, \$street, \$streetNumber, \$zipcode, \$city, \$salutation, \$country= 'DE', \$nameAdditive= '', \$streetAdditive= '', \$companyName= '')
- [setSofortrechnungShippingAddress](#) (\$firstname, \$lastname, \$street, \$streetNumber, \$zipcode, \$city, \$salutation, \$country= 'DE', \$nameAdditive= '', \$streetAdditive= '', \$companyName= '')
- [addSofortrechnungItem](#) (\$itemId, \$productNumber, \$title, \$unitPrice, \$productType=0, \$description= '', \$quantity=1, \$tax=19)
- [removeSofortrechnungItem](#) (\$itemId)
- [updateSofortrechnungItem](#) (\$itemId, \$quantity, \$unitPrice)
- [sendValidationRequest](#) ()
- [getPaymentUrl](#) ()
- [getTransactionId](#) ()

### 6.11.1 Detailed Description

Setup a multipay payment session after the configuration of multiple payment methods you will receive an url and a transaction id, your customer should be redirected to this url you can use the transaction id for future reference of this payment

example by usage: `$objMultipay = new SofortLib_Multipays('my-API-KEY');`  
`$objMultipay->setSofortueberweisung();` //OR `setSofortrechnung()`, `setSofortvorkasse()` etc. `$objMultipay->set...($param);` //set params for PNAG-API (watch API-documentation for needed params) `$objMultipay->add...($param);` //add params for PNAG-API (watch API-documentation for needed params) `$errorsAndWarnings = $objMultipay->validateRequest();` //send param against the PNAG-API without setting an order ... make own validation of `$errorsAndWarnings` and if ok ... `$objMultipay->sendRequest();` //set the order at PNAG `$errorsAndWarnings = $objMultipay->getErrors();` //should not occur, if validation was ok ... make own validation of `$errorsAndWarnings` and if ok ... finish order in the shopsystem

Copyright (c) 2012 SOFORT AG

#### Date:

2012-09-05 14:27:56 +0200 (Wed, 05 Sep 2012)

#### Version

[SofortLib](#) 1.5.0

**Id:**

sofortLib\_multipay.inc.php 5301 2012-09-05 12:27:56Z dehn

**Author**

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

## 6.11.2 Constructor & Destructor Documentation

### 6.11.2.1 `__construct ( $ configKey = " )`

create a new payment object

**Parameters**

*string* \$apikey your API key

*int* \$projectId your project id

## 6.11.3 Member Function Documentation

### 6.11.3.1 `addNotificationEmail ( $ arg )`

you can set set multiple emails for receiving notifications

**Parameters**

*string* \$arg email

**Returns**

[SofortLib\\_Multipay](#)

### 6.11.3.2 `addNotificationUrl ( $ arg )`

you can set set multiple urls for receiving notifications this might be helpfull if you have several systems for processing an order (e.g. an ERP system)

**Parameters**

*string* \$arg url

**Returns**

[SofortLib\\_Multipay](#)

### 6.11.3.3 **addSofortrechnungItem** ( *\$ itemId*, *\$ productNumber*, *\$ title*, *\$ unitPrice*, *\$ productType = 0*, *\$ description = ''*, *\$ quantity = 1*, *\$ tax = 19* )

add one item to the cart

#### Parameters

*int* \$itemId unique item id

*string* \$productNumber product number, EAN code, ISBN number or similar

*string* \$title description of this title

*double* \$unit\_price gross price of one item

*int* \$productType product type number see manual (0=other, 1=shipping, ...)

*string* \$description additional description of this item

*int* \$quantity default 1

*int* \$tax tax in percent, default 19

### 6.11.3.4 **addUserVariable** ( *\$ arg* )

add another variable this can be your internal order id or similar

#### Parameters

*string* \$arg the contents of the variable

#### Returns

[SofortLib\\_Multipay](#)

### 6.11.3.5 **getPaymentUrl** ( )

after configuration and sending this request you can use this function to redirect the customer to the payment form

#### Returns

string url of payment form

### 6.11.3.6 **getTransactionId** ( )

use this id to track the transaction

#### Returns

string transaction id

### 6.11.3.7 removeSofortrechnungItem ( \$ itemId )

Remove one item from cart

#### Parameters

*\$itemId*

#### Returns

boolean

### 6.11.3.8 sendValidationRequest ( )

makes a request against the pnag-API and returns all API-Fault/Warnings it doesnt result in an order at pnag!

#### Returns

bool

### 6.11.3.9 setAbortUrl ( \$ arg )

the customer will be redirected to this url if he uses the abort link on the payment form, should redirect him back to his cart or to the payment selection page

#### Parameters

*string* \$arg url for aborting the transaction

#### Returns

[SofortLib\\_Multipay](#)

### 6.11.3.10 setAmount ( \$ arg, \$ currency = 'EUR' )

amount of this payment

#### Parameters

*double* \$arg

*string* \$currency currency of this transaction, default EUR

#### Returns

[SofortLib\\_Multipay](#) \$this

**6.11.3.11 setDebitorVatNumber ( \$ *vatNumber* )**

set debtor vat number for invoice

**Parameters**

*string* \$vatNumber

**Returns**

[SofortLib\\_Multipay](#) \$this

**6.11.3.12 setEmailCustomer ( \$ *arg* )**

set the email address of the customer this will be used for sofortvorkasse and so-fortrechnung

**Parameters**

*string* \$arg email address

**Returns**

[SofortLib\\_Multipay](#)

**6.11.3.13 setLanguageCode ( \$ *arg* )**

the language code will help in determing what language to use when displaying the payment form, other data like browser settings and ip will be used as well

**Parameters**

*string* \$arg de|en|nl|fr ...

**Returns**

[SofortLib\\_Multipay](#)

**6.11.3.14 setLastschrift ( \$ *amount* = " )**

add lastschrift as payment method

**Parameters**

*double* \$amount this amount only applies to this payment method

**Returns**

[SofortLib\\_Multipay](#) \$this



**6.11.3.15** `setLastschriftAddress ( $ firstname, $ lastname, $ street, $ streetNumber, $ zipcode, $ city, $ salutation, $ country = 'DE' )`

set the address of the customer for address validation, this should be the invoice address of the customer

**Parameters**

*string* \$firstname

*string* \$lastname

*string* \$street

*string* \$streetNumber

*string* \$zipcode

*string* \$city

*int* \$salutation [2|3] 2=Mr. 3=Mrs.

*string* \$country country code, only DE allowed at the moment

**Returns**

[SofortLib\\_Multipay](#) object

**6.11.3.16** `setNotificationEmail ( $ arg )`

set the email address where you want notification about status changes being sent to.

**Parameters**

*string* \$arg email address

**Returns**

[SofortLib\\_Multipay](#)

**6.11.3.17** `setNotificationUrl ( $ arg )`

set the url where you want notification about status changes being sent to. Use [SofortLib\\_Notification](#) and [SofortLib\\_TransactionData](#) to further process that notification

**Parameters**

*string* \$arg url

**Returns**

[SofortLib\\_Multipay](#)

**6.11.3.18 setPhoneNumberCustomer ( \$ arg )**

set the phone number of the customer

**Parameters**

*string* \$arg phone number

**Returns**

[SofortLib\\_Multipay](#)

**6.11.3.19 setReason ( \$ arg, \$ arg2 = " )**

set the reason values of this transfer

**Parameters**

*string* \$arg max 27 characters

*string* \$arg2 max 27 characters

**Returns**

[SofortLib\\_Multipay](#) \$this

**6.11.3.20 setSenderAccount ( \$ bankCode, \$ accountNumber, \$ holder )**

set data of account

**Parameters**

*string* \$bank\_code bank code of bank

*string* \$account\_number account number

*string* \$holder Name/Holder of this account

**Returns**

[SofortLib\\_Multipay](#) \$this

**6.11.3.21 setSofortDauerauftrag ( )**

add SofortDauerauftrag as a payment method

**Returns**

[SofortLib\\_Multipay](#) object

**6.11.3.22 setSofortDauerauftragInterval ( \$ arg )**

set the interval for payment

**Parameters**

*\$arg*

**Returns**

object

**6.11.3.23 setSofortDauerauftragMinimumPayments ( \$ arg )**

set the minimum amount for Dauerauftrag

**Parameters**

*\$arg*

**Returns**

object

**6.11.3.24 setSofortDauerauftragStartDate ( \$ arg )**

Set the date to start "Dauerauftrag" date must be compliant to ISO 8601 (e.g. 2011-06-21)

**Parameters**

*\$arg* - string date

**6.11.3.25 setSofortDauerauftragTotalPayments ( \$ arg )**

Enter description here ...

**Parameters**

*\$arg*

**Returns**

object

### 6.11.3.26 setSofortlastschrift ( \$ amount = " )

add sofortlastschrift as payment method

#### Parameters

*double* \$amount this amount only applies to this payment method

#### Returns

[SofortLib\\_Multipay](#) \$this

### 6.11.3.27 setSofortlastschriftAddress ( \$ firstname, \$ lastname, \$ street, \$ streetNumber, \$ zipcode, \$ city, \$ salutation, \$ country = 'DE' )

set the address of the customer for address validation, this should be the invoice address of the customer

#### Parameters

*string* \$firstname

*string* \$lastname

*string* \$street

*string* \$streetNumber

*string* \$zipcode

*string* \$city

*int* \$salutation [2|3] 2=Mr. 3=Mrs.

*string* \$country country code, only DE allowed at the moment

#### Returns

[SofortLib\\_Multipay](#) \$this

### 6.11.3.28 setSofortrechnung ( )

add sofortrechnung as payment method if you use this payment method you have to provide the customer address and cart as well the total amount of this payment method will be determined by the total of the cart

#### Returns

[SofortLib\\_Multipay](#) object

**6.11.3.29 setSofortrechnungCustomerId ( \$ arg )**

set the customer id which will appear on top of the invoice

**Parameters**

*int* \$arg

**Returns**

[SofortLib\\_Multipay](#) \$this

**6.11.3.30 setSofortrechnungInvoiceAddress ( \$ firstname, \$ lastname, \$ street, \$ streetNumber, \$ zipcode, \$ city, \$ salutation, \$ country = 'DE', \$ nameAdditive = "", \$ streetAdditive = "", \$ companyName = "" )**

set the invoice address of the customer

**Parameters**

*string* \$firstname

*string* \$lastname

*string* \$street

*string* \$streetNumber

*string* \$zipcode

*string* \$city

*int* \$salutation [2|3] 2 = Mr. 3 = Mrs.

*string* \$country country code, only DE allowed at the moment

**Returns**

[SofortLib\\_Multipay](#) \$this

**6.11.3.31 setSofortrechnungOrderId ( \$ arg )**

set the order id which will appear on top of the invoice

**Parameters**

*int* \$arg

**Returns**

[SofortLib\\_Multipay](#) \$this

**6.11.3.32** `setSofortrechnungShippingAddress ( $ firstname, $ lastname, $ street, $ streetNumber, $ zipcode, $ city, $ salutation, $ country = 'DE', $ nameAdditive = "", $ streetAdditive = "", $ companyName = "" )`

set the shipping address of the customer

#### Parameters

*string* \$firstname

*string* \$lastname

*string* \$street

*string* \$streetNumber

*string* \$zipcode

*string* \$city

*int* \$salutation [2|3] 1 = Mr. 2 = Mrs.

*string* \$country country code, only DE allowed at the moment

#### Returns

[SofortLib\\_Multipay](#) \$this

**6.11.3.33** `setSofortueberweisung ( $ amount = "" )`

add sofortueberweisung as payment method

#### Parameters

*double* \$amount this amount only applies to this payment method

#### Returns

[SofortLib\\_Multipay](#) \$this

**6.11.3.34** `setSofortueberweisungCustomerprotection ( $ customerProtection = true )`

add sofortueberweisung as payment method adds customer protection

#### Parameters

*double* \$amount this amount only applies to this payment method

#### Returns

[SofortLib\\_Multipay](#) \$this

**6.11.3.35 setSofortvorkasse ( \$ amount = " )**

add sofortvorkasse as payment method

**Parameters**

*double* \$amount this amount only applies to this payment method

**Returns**

[SofortLib\\_Multipay](#) objet

**6.11.3.36 setSofortvorkasseCustomerprotection ( \$ customerProtection = true )**

add sofortvorkasse as payment method adds customer protection

**Parameters**

*double* \$amount this amount only applies to this payment method

**Returns**

[SofortLib\\_Multipay](#) \$this

**6.11.3.37 setSuccessUrl ( \$ arg )**

the customer will be redirected to this url after a successful transaction, this should be a page where a short confirmation is displayed

**Parameters**

*string* \$arg the url after a successful transaction

**Returns**

[SofortLib\\_Multipay](#)

**6.11.3.38 setTimeout ( \$ arg )**

timeout how long this transaction configuration will be valid for this is the time between the generation of the payment url and the user completing the form, should be at least two to three minutes defaults to unlimited if not set

**Parameters**

*int* \$arg timeout in seconds

**Returns**

[SofortLib\\_Multipay](#)

### 6.11.3.39 setTimeoutUrl ( \$ arg )

if the customer takes too much time or if your timeout is set too short he will be redirected to this page

#### Parameters

*string* \$arg url

#### Returns

[SofortLib\\_Multipay](#)

### 6.11.3.40 setVersion ( \$ arg )

set the version of this payment module this is helpfull so the support staff can easily find out if someone uses an outdated module

#### Parameters

*string* \$arg version string of your module

#### Returns

[SofortLib\\_Multipay](#)

### 6.11.3.41 updateSofortrechnungItem ( \$ itemId, \$ quantity, \$ unitPrice )

Update one item in cart

#### Parameters

*\$itemId*

*\$quantity*

*\$unit\_price*

#### Returns

boolean

The documentation for this class was generated from the following file:

- sofortLib\_multipay.inc.php

## 6.12 SofortLib\_Notification Class Reference

### Public Member Functions

- [\\_\\_construct](#) ()
- [getNotification](#) (\$source= 'php://input')



### 6.12.1 Detailed Description

Instance of this class handles the callback of Payment Network to notify about a status change

In rare cases notifications might be doubled or even wrong altogether (if send by a malicious user). So don't use this to change your status but instead use the transaction id to query the webservice for detailed data ([SofortLib\\_TransactionData](#))

```
eg: $notificationObj = new SofortLib_Notification();
```

```
$transactionId = $notificationObj->getNotification();
```

Copyright (c) 2012 SOFORT AG

**Date:**

2012-09-05 14:27:56 +0200 (Wed, 05 Sep 2012)

**Version**

[SofortLib](#) 1.5.0

**Id:**

sofortLib\_notification.inc.php 5301 2012-09-05 12:27:56Z dehn

**Author**

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

### 6.12.2 Constructor & Destructor Documentation

#### 6.12.2.1 `__construct ( )`

creates a new notification object for receiving notifications

### 6.12.3 Member Function Documentation

#### 6.12.3.1 `getNotification ( $ source = 'php://input' )`

reads the input and tries to read the transaction id

**Returns**

array transactionid=>status

The documentation for this class was generated from the following file:

- `sofortLib_notification.inc.php`

## 6.13 SofortLib\_Refund Class Reference

### Public Member Functions

- [sendRequest](#) ()
- [addRefund](#) (\$transaction, \$amount, \$comment= "")
- [setSenderAccount](#) (\$bankCode, \$accountNumber, \$holder= "")

### 6.13.1 Detailed Description

class for refund/rueckbuchung

Copyright (c) 2012 SOFORT AG

#### Date:

2012-09-05 14:27:56 +0200 (Wed, 05 Sep 2012)

#### Version

[SofortLib](#) 1.5.0

#### Id:

sofortLib\_refund.inc.php 5301 2012-09-05 12:27:56Z dehn

#### Author

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

### 6.13.2 Member Function Documentation

#### 6.13.2.1 addRefund ( \$ transaction, \$ amount, \$ comment = " )

add a new refund to this message

#### Parameters

*string* \$transaction transaction id of transfer you want to refund

*float* \$amount amount of money to refund, less or equal to amount of original transfer

*string* \$comment comment that will be displayed in admin-menu later

#### Returns

[SofortLib\\_Refund](#) \$this

### 6.13.2.2 `sendRequest ( )`

send this message and get response

#### Returns

array transactionid=>status

### 6.13.2.3 `setSenderAccount ( $ bankCode, $ accountNumber, $ holder = " )`

set data of account

#### Parameters

*string* \$bank\_code bank code of bank

*string* \$account\_number account number

*string* \$holder Name/Holder of this account

#### Returns

[SofortLib\\_Multipay](#) \$this

The documentation for this class was generated from the following file:

- `sofortLib_refund.inc.php`

## 6.14 SofortLib\_SofortueberweisungClassic Class Reference

Inherited by [SofortLib\\_iDealClassic](#).

### Public Member Functions

- [setReason](#) (\$arg, \$arg2= '')
- [setSuccessUrl](#) (\$arg)
- [setAbortUrl](#) (\$arg)
- [setNotificationUrl](#) (\$arg)
- [getHashHexValue](#) (\$data, \$hashFunction= 'sha1')
- [getSupportedHashAlgorithm](#) ()
- [getSupportedHashAlgorithms](#) ()

### Static Public Member Functions

- static [generatePassword](#) (\$length=24)

### 6.14.1 Detailed Description

Setup a sofortueberweisung.de session using the classic api after the configuration of the configuration you will receive an url and a transaction id, your customer should be redirected to this url

Called by the `sofortLib.php/sofortLib_ideal_classic.php` etc. `$sofort->new SofortLib_SofortueberweisungClassic( $userid, $projectid, $password [, $hashfunction='sha1'] ); $sofort->set...(); //set params for Hashcalculation $sofort->set...(); //set more params for Hashcalculation $sofort->getPaymentUrl();` Notice: sometimes `getPaymentUrl()` must be overwritten by calling class because of changed hash-params

Copyright (c) 2012 SOFORT AG

#### Date:

2012-09-05 14:27:56 +0200 (Wed, 05 Sep 2012)

#### Version

[SofortLib](#) 1.5.0

#### Id:

`sofortLib_sofortueberweisung_classic.php` 5301 2012-09-05 12:27:56Z dehn

#### Author

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

### 6.14.2 Member Function Documentation

#### 6.14.2.1 `static generatePassword ( $ length = 24 ) [static]`

##### Parameters

*int* [optional] `$length` length of return value, default 24

##### Returns

string

#### 6.14.2.2 `getHashHexValue ( $ data, $ hashFunction = 'sha1' )`

##### Parameters

*string* `$data` string to be hashed

##### Returns

string the hash

### 6.14.2.3 `getSupportedHashAlgorithm ( )`

checks wich hash algorithms are supported by the server and returns the best one

#### Returns

sha512|sha256|sha1|md5|empty string

### 6.14.2.4 `getSupportedHashAlgorithms ( )`

checks wich hash algorithms are supported by the server

#### Returns

array with all supported algorithms, preferred as first one (index 0)

### 6.14.2.5 `setAbortUrl ( $ arg )`

the customer will be redirected to this url if he uses the abort link on the payment form, should redirect him back to his cart or to the payment selection page

#### Parameters

*string* \$arg url for aborting the transaction

#### Returns

[SofortLib\\_Multipay](#)

### 6.14.2.6 `setNotificationUrl ( $ arg )`

set the url where you want notification about status changes being sent to. Use [SofortLib\\_Notification](#) and [SofortLib\\_TransactionData](#) to further process that notification

#### Parameters

*string* \$arg url

#### Returns

[SofortLib\\_Multipay](#)

#### 6.14.2.7 `setReason ( $ arg, $ arg2 = " )`

Set the reason (Verwendungszweck) for sending money

##### Parameters

*string* \$arg

*string* \$arg2

#### 6.14.2.8 `setSuccessUrl ( $ arg )`

the customer will be redirected to this url after a successful transaction, this should be a page where a short confirmation is displayed

##### Parameters

*string* \$arg the url after a successful transaction

##### Returns

[SofortLib\\_Multipay](#)

The documentation for this class was generated from the following file:

- `sofortLib_sofortueberweisung_classic.php`

## 6.15 SofortLib\_TransactionData Class Reference

### Public Member Functions

- [setTransaction](#) (\$arg)
- [addTransaction](#) (\$arg)
- [setTime](#) (\$from, \$to)
- [setNumber](#) (\$number, \$page= '1')
- [getConsumerProtection](#) (\$i=0)
- [getInvoiceAddress](#) (\$i=0)
- [getShippingAddress](#) (\$i=0)
- [getStatus](#) (\$i=0)
- [getStatusReason](#) (\$i=0)
- [getStatusModifiedTime](#) (\$i=0)
- [getLanguageCode](#) (\$i=0)
- [getAmount](#) (\$i=0)
- [getAmountRefunded](#) (\$i=0)
- [getCurrency](#) (\$i=0)
- [getPaymentMethod](#) (\$i=0)
- [getSofortdauerauftragPayments](#) (\$i=0)

- [getSofortdauer AuftragStartDate](#) (\$i=0)
- [getSofortdauer AuftragInterval](#) (\$i=0)
- [getSofortdauer AuftragTotalPayments](#) (\$i=0)
- [getSofortdauer AuftragPaymentsSum](#) (\$i=0)
- [getSofortdauer AuftragNumberOfPaymentsPending](#) (\$i=0)
- [getSofortdauer AuftragNumberOfPaymentsReceived](#) (\$i=0)
- [getSofortdauer AuftragMinimumPayments](#) (\$i=0)
- [getSofortdauer AuftragPaymentsReceived](#) (\$i=0)
- [getSofortdauer AuftragPaymentCount](#) (\$i=0)
- [getSofortdauer AuftragPaymentReceived](#) (\$i=0, \$j=0)
- [getSofortdauer AuftragAllPaymentsReceived](#) (\$i=0)
- [getSofortdauer AuftragLastPaymentReceived](#) (\$i=0)
- [getTransaction](#) (\$i=0)
- [getItems](#) (\$i=0)
- [getReason](#) (\$i=0)
- [getUserVariable](#) (\$n, \$i=0)
- [getTime](#) (\$i=0)
- [getProjectId](#) (\$i=0)
- [getInvoiceUrl](#) (\$i=0)
- [getInvoiceStatus](#) (\$i=0)
- [getInvoiceObjection](#) (\$i=0)
- [isTest](#) (\$i=0)
- [isSofortueberweisung](#) (\$i=0)
- [isSofortvorkasse](#) (\$i=0)
- [isSofortlastschrift](#) (\$i=0)
- [isLastschrift](#) (\$i=0)
- [isSofortdauer Auftrag](#) (\$i=0)
- [isSofortrechnung](#) (\$i=0)
- [isReceived](#) (\$i=0)
- [isLoss](#) (\$i=0)
- [isPending](#) (\$i=0)
- [isRefunded](#) (\$i=0)
- [getRecipientHolder](#) (\$i=0)
- [getRecipientAccountNumber](#) (\$i=0)
- [getRecipientBankCode](#) (\$i=0)
- [getRecipientCountryCode](#) (\$i=0)
- [getRecipientBankName](#) (\$i=0)
- [getRecipientBic](#) (\$i=0)
- [getRecipientIban](#) (\$i=0)
- [getSenderHolder](#) (\$i=0)
- [getSenderAccountNumber](#) (\$i=0)
- [getSenderBankCode](#) (\$i=0)
- [getSenderCountryCode](#) (\$i=0)
- [getSenderBankName](#) (\$i=0)
- [getSenderBic](#) (\$i=0)
- [getSenderIban](#) (\$i=0)

- [getInvoiceReason](#) (\$n=0, \$i=0)
- [getInvoiceDebitorText](#) (\$i=0)
- [getInvoiceDate](#) (\$i=0)
- [getInvoiceDueDate](#) (\$i=0)
- [getInvoiceNumber](#) (\$i=0)
- [getInvoiceBankHolder](#) (\$i=0)
- [getInvoiceBankAccountNumber](#) (\$i=0)
- [getInvoiceBankCode](#) (\$i=0)
- [getInvoiceBankName](#) (\$i=0)
- [getInvoiceType](#) (\$i=0)

### 6.15.1 Detailed Description

This class is for retrieving information about transactions, you can search by transaction-id or by date

```
eg: $transactionDataObj = new SofortLib\_TransactionData('yourapikey');  
$transactionDataObj->setTransaction('1234-456-789654-31321')->sendRequest();  
echo $transactionDataObj->getStatus();
```

Copyright (c) 2012 SOFORT AG

#### Date:

2012-09-10 10:26:54 +0200 (Mon, 10 Sep 2012)

#### Version

[SofortLib](#) 1.3.0

#### Id:

sofortLib\_transaction\_data.inc.php 5341 2012-09-10 08:26:54Z Niehoff

#### Author

SOFORT AG <http://www.sofort.com> ([integration@sofort.com](mailto:integration@sofort.com))

### 6.15.2 Member Function Documentation

#### 6.15.2.1 addTransaction ( \$ arg )

use this function if you want to request detailed information about several transactions at once

#### Parameters

*String* \$arg

#### Returns

[SofortLib\\_TransactionData](#) \$this



### 6.15.2.2 `getAmount ( $ i = 0 )`

returns the total amount of a transaction

#### Parameters

*int* \$i if you request multiple transactions at once you can set the number here

#### Returns

double amount

### 6.15.2.3 `getAmountRefunded ( $ i = 0 )`

refund, if a transaction was refundend. amount = amountRefunded if everything was refunded

#### Parameters

*int* \$i if you request multiple transactions at once you can set the number here

#### Returns

double amount

### 6.15.2.4 `getConsumerProtection ( $ i = 0 )`

returns the state of consumer\_protection if set

#### Parameters

*int* \$i if you request multiple transactions at once you can set the number here

#### Returns

boolean

### 6.15.2.5 `getCurrency ( $ i = 0 )`

returns the currency of a transaction

#### Parameters

*int* \$i if you request multiple transactions at once you can set the number here

#### Returns

string EUR|USD|GBP...

**6.15.2.6 getInvoiceAddress ( \$ i = 0 )**

returns the InvoiceAddress

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

array

**6.15.2.7 getInvoiceBankAccountNumber ( \$ i = 0 )**

invoice receiving bank account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string

**6.15.2.8 getInvoiceBankCode ( \$ i = 0 )**

invoice receiving bank account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string

**6.15.2.9 getInvoiceBankHolder ( \$ i = 0 )**

invoice receiving bank account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string

**6.15.2.10 getInvoiceBankName ( \$ i = 0 )**

invoice receiving bank account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string

**6.15.2.11 getInvoiceDate ( \$ i = 0 )**

date of the invoice

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string

**6.15.2.12 getInvoiceDebitorText ( \$ i = 0 )**

get debtor text (Forderungsabtretung)

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string

**6.15.2.13 getInvoiceDueDate ( \$ i = 0 )**

due date of the invoice, only available for confirmed invoices

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string

**6.15.2.14** `getInvoiceNumber ( $ i = 0 )`

invoice number

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string

**6.15.2.15** `getInvoiceObjection ( $ i = 0 )`

returns the status of an invoice

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string the status can be pending|received|reminder\_1|reminder\_2|reminder\_-3|encashment

**6.15.2.16** `getInvoiceReason ( $ n = 0, $ i = 0 )`

returns the reason the customer needs to use when paying for "Rechnung by sofort"

**Parameters**

*int* \$n specify reason linenumber, can be 1 or 2; us 0 for an array with all reasons

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string|array reason

**6.15.2.17** `getInvoiceStatus ( $ i = 0 )`

returns the status of an invoice

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string the status can be pending|received|reminder\_1|reminder\_2|reminder\_-3|encashment

**6.15.2.18 getInvoiceType ( \$ i = 0 )**

get the invoice type

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string (OR or LS)

**6.15.2.19 getInvoiceUrl ( \$ i = 0 )**

you can request the url to the pdf of a sr-invoice with this function

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string url to the pdf

**6.15.2.20 getItems ( \$ i = 0 )**

Returns an array containing all items of a transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here @  
return array transactions items

**6.15.2.21 getLanguageCode ( \$ i = 0 )**

returns the language code of a transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string language\_code

**6.15.2.22   getPaymentMethod ( \$ i = 0 )**

returns the payment method of a transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string su|sr|sl|sv|ls

**6.15.2.23   getProjectId ( \$ i = 0 )**

returns the project id of a transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

int project id

**6.15.2.24   getReason ( \$ i = 0 )**

Returns an array containing reason of a transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here @  
return array transaction reason

**6.15.2.25   getRecipientAccountNumber ( \$ i = 0 )**

returns the account number of the receiving account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.26 getRecipientBankCode ( \$ i = 0 )**

returns the bank code of the receiving account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.27 getRecipientBankName ( \$ i = 0 )**

returns the bank name of the receiving account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.28 getRecipientBic ( \$ i = 0 )**

returns the BIC of the receiving account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.29 getRecipientCountryCode ( \$ i = 0 )**

returns the country code of the receiving account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.30 getRecipientHolder ( \$ i = 0 )**

returns the holder of the receiving account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.31 getRecipientIban ( \$ i = 0 )**

returns the IBAN of the receiving account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.32 getSenderAccountNumber ( \$ i = 0 )**

returns the account number of the sending account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.33 getSenderBankCode ( \$ i = 0 )**

returns the bank code of the sending account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value



**6.15.2.34 getSenderBankName ( \$ i = 0 )**

returns the bank name of the sending account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.35 getSenderBic ( \$ i = 0 )**

returns the BIC of the sending account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.36 getSenderCountryCode ( \$ i = 0 )**

returns the country code of the sending account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.37 getSenderHolder ( \$ i = 0 )**

returns the holder of the sending account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.38 getSenderIban ( \$ i = 0 )**

returns the IBAN of the sending account

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string value

**6.15.2.39 getShippingAddress ( \$ i = 0 )**

returns the ShippingAddress

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

array

**6.15.2.40 getSofortdauer AuftragAllPaymentsReceived ( \$ i = 0 )**

Only payments made in the past (or the current day) are respected ...

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean

**6.15.2.41 getSofortdauer AuftragInterval ( \$ i = 0 )**

returns the interval for an abo payment

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

int

**6.15.2.42   getSofortdauer AuftragLastPaymentReceived ( \$ i = 0 )**

Get the status (received true|false) of the last payment of the current transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean

**6.15.2.43   getSofortdauer AuftragMinimumPayments ( \$ i = 0 )**

returns the count of minimum payments for an abo payment

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

int

**6.15.2.44   getSofortdauer AuftragNumberOfPaymentsPending ( \$ i = 0 )**

returns the number of received payments of an abo payment

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

int

**6.15.2.45   getSofortdauer AuftragNumberOfPaymentsReceived ( \$ i = 0 )**

returns total sum of received payments of an abo payment

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

int

**6.15.2.46** `getSofortdauer AuftragPaymentCount ( $ i = 0 )`

Enter description here ...

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**6.15.2.47** `getSofortdauer AuftragPaymentReceived ( $ i = 0, $ j = 0 )`

Get the \$j'th payment of \$i'th transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

*int* \$j int current payment

**Returns**

boolean

**6.15.2.48** `getSofortdauer AuftragPayments ( $ i = 0 )`

returns the payments array for an abo payment

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

array

**6.15.2.49** `getSofortdauer AuftragPaymentsReceived ( $ i = 0 )`

returns the count of received payments for an abo payment

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

int

**6.15.2.50** `getSofortdauer AuftragPaymentsSum ( $ i = 0 )`

returns total sum of received payments of an abo payment

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

int

**6.15.2.51** `getSofortdauer AuftragStartDate ( $ i = 0 )`

returns the start date for an abo payment

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

array

**6.15.2.52** `getSofortdauer AuftragTotalPayments ( $ i = 0 )`

returns total of payments of an abo payment

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

int

**6.15.2.53** `getStatus ( $ i = 0 )`

returns the status of a transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string pending|received|loss|refunded

**6.15.2.54 getStatusModifiedTime ( \$ i = 0 )**

returns the time of the last status-change so you can check if sth. changed

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string time e.g. 2011-01-01T12:35:09+01:00 use strtotime() to convert it to unix-time

**6.15.2.55 getStatusReason ( \$ i = 0 )**

returns the detailed status description of a transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string message

**6.15.2.56 getTime ( \$ i = 0 )**

returns the time of a transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string time e.g. 2011-01-01T12:35:09+01:00 use strtotime() to convert it to unix-time

**6.15.2.57 getTransaction ( \$ i = 0 )**

returns the transaction id of a transaction

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string transaction id

**6.15.2.58** `getUserVariable ( $ n, $ i = 0 )`

returns the user variable of a transaction

**Parameters**

*int* \$n number of the variable

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

string the content of this variable

**6.15.2.59** `isLastschrift ( $ i = 0 )`

check if the transaction was a lastschrift by sofort

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean true|false

**6.15.2.60** `isLoss ( $ i = 0 )`

check if status of transaction is loss

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean true|false

**6.15.2.61** `isPending ( $ i = 0 )`

check if status of transaction is pending

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean true|false

**6.15.2.62 isReceived ( \$ i = 0 )**

check if status of transaction is received

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean true|false

**6.15.2.63 isRefunded ( \$ i = 0 )**

check if status of transaction is refunded

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean true|false

**6.15.2.64 isSofortdauerauftrag ( \$ i = 0 )**

check if the transaction was a sofortdauerauftrag

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean true|false

**6.15.2.65 isSofortlastschrift ( \$ i = 0 )**

check if the transaction was a sofortlastschrift

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean true|false



**6.15.2.66 isSofortrechnung ( \$ i = 0 )**

check if the transaction was a sofortrechnung

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean true|false

**6.15.2.67 isSofortueberweisung ( \$ i = 0 )**

check if the transaction was a sofortueberweisung

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean true|false

**6.15.2.68 isSofortvorkasse ( \$ i = 0 )**

check if the transaction was a sofortvorkasse

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

boolean true|false

**6.15.2.69 isTest ( \$ i = 0 )**

checks if the transaction was a test

**Parameters**

*int* \$i if you request multiple transactions at once you can set the number here

**Returns**

bool true|false

### 6.15.2.70 `setNumber ( $ number, $ page = '1' )`

you can limit the number of results

#### Parameters

*int* \$number number of results [0-100]

*int* \$page result page

#### Returns

[SofortLib\\_TransactionData](#) \$this

#### See also

[setTime\(\)](#)

### 6.15.2.71 `setTime ( $ from, $ to )`

you can request all transactions of a certain time period

use [setNumber\(\)](#) to limit the results

#### Parameters

*string* \$from date possible formats: 2011-01-25 or 2011-01-25T19:01:02+02:00

*string* \$to date possible formats: 2011-01-25 or 2011-01-25T19:01:02+02:00

#### Returns

[SofortLib\\_TransactionData](#) \$this

#### See also

[setNumber\(\)](#)

### 6.15.2.72 `setTransaction ( $ arg )`

use this function if you want to request detailed information about a single transaction

#### Parameters

*String* \$arg

#### Returns

[SofortLib\\_TransactionData](#) \$this

The documentation for this class was generated from the following file:

- `sofortLib_transaction_data.inc.php`

# Index

- \_\_construct
  - PnagInvoice, [15](#)
  - SofortLib, [31](#)
  - SofortLib\_CancelSa, [36](#)
  - SofortLib\_CancelSr, [38](#)
  - SofortLib\_ConfirmSr, [41](#)
  - SofortLib\_EditSr, [48](#)
  - SofortLib\_Multipay, [53](#)
  - SofortLib\_Notification, [65](#)
- \_getHashHexValue
  - SofortLib\_ClassicNotification, [40](#)
- \_sendMessage
  - SofortLib, [32](#)
- addInvoiceAddress
  - PnagInvoice, [15](#)
- addItem
  - SofortLib\_ConfirmSr, [41](#)
  - SofortLib\_EditSr, [48](#)
- addItemToInvoice
  - PnagInvoice, [16](#)
- addNotificationEmail
  - SofortLib\_Multipay, [53](#)
- addNotificationUrl
  - SofortLib\_Multipay, [53](#)
- addReason
  - SofortLib\_Debit, [44](#)
- addRefund
  - SofortLib\_Refund, [66](#)
- addShippingAddress
  - PnagInvoice, [16](#)
- addShippingAddresss
  - PnagInvoice, [17](#)
- addSofortrechnungItem
  - SofortLib\_Multipay, [53](#)
- addTransaction
  - SofortLib\_TransactionData, [72](#)
- addUserVariable
  - PnagInvoice, [17](#)
  - SofortLib\_Debit, [44](#)
  - SofortLib\_Multipay, [54](#)
- cancelInvoice
  - PnagInvoice, [17](#)
  - SofortLib\_CancelSr, [38](#)
  - SofortLib\_ConfirmSr, [42](#)
- checkout
  - PnagInvoice, [18](#)
- confirmInvoice
  - PnagInvoice, [18](#)
  - SofortLib\_ConfirmSr, [42](#)
- deleteAllErrors
  - SofortLib, [32](#)
- deleteAllWarnings
  - SofortLib, [32](#)
- disableLog
  - PnagInvoice, [18](#)
  - SofortLib, [32](#)
- enableLog
  - PnagInvoice, [18](#)
  - SofortLib, [32](#)
- error
  - SofortLib, [32](#)
- fatalError
  - SofortLib, [32](#)
- generatePassword
  - SofortLib\_  
SofortueberweisungClassic,  
[68](#)
- getAmount
  - PnagInvoice, [18](#)
  - SofortLib\_TransactionData, [72](#)
- getAmountRefunded
  - SofortLib\_TransactionData, [73](#)
- getConstantById
  - PnagInvoice, [19](#)
- getConstantByName
  - PnagInvoice, [19](#)
- getConsumerProtection
  - SofortLib\_TransactionData, [73](#)

- getCurrency
  - SofortLib\_TransactionData, 73
- getError
  - PnagInvoice, 19
  - SofortLib, 32
- getErrorCodes
  - PnagInvoice, 19
- getErrors
  - PnagInvoice, 19
  - SofortLib, 33
- getHashHexValue
  - SofortLib\_-
    - SofortueberweisungClassic, 68
- getInvoice
  - PnagInvoice, 19
- getInvoiceAddress
  - SofortLib\_TransactionData, 73
- getInvoiceBankAccountNumber
  - SofortLib\_TransactionData, 74
- getInvoiceBankCode
  - SofortLib\_TransactionData, 74
- getInvoiceBankHolder
  - SofortLib\_TransactionData, 74
- getInvoiceBankName
  - SofortLib\_TransactionData, 74
- getInvoiceDate
  - SofortLib\_TransactionData, 75
- getInvoiceDebitorText
  - SofortLib\_TransactionData, 75
- getInvoiceDueDate
  - SofortLib\_TransactionData, 75
- getInvoiceNumber
  - SofortLib\_TransactionData, 75
- getInvoiceObjection
  - PnagInvoice, 20
  - SofortLib\_TransactionData, 76
- getInvoiceReason
  - SofortLib\_TransactionData, 76
- getInvoiceStatus
  - PnagInvoice, 20
  - SofortLib\_TransactionData, 76
- getInvoiceTye
  - PnagInvoice, 20
- getInvoiceType
  - SofortLib\_TransactionData, 76
- getInvoiceUrl
  - PnagInvoice, 20
  - SofortLib\_CancelSr, 39
  - SofortLib\_ConfirmSr, 42
  - SofortLib\_EditSr, 48
  - SofortLib\_TransactionData, 77
- getItems
  - PnagInvoice, 20
  - SofortLib\_TransactionData, 77
- getLanguageCode
  - PnagInvoice, 21
  - SofortLib\_TransactionData, 77
- getNotification
  - SofortLib\_Notification, 65
- getPaymentMethod
  - PnagInvoice, 21
  - SofortLib\_TransactionData, 77
- getPaymentUrl
  - PnagInvoice, 21
  - SofortLib\_Multipay, 54
- getProjectId
  - SofortLib\_TransactionData, 78
- getReason
  - SofortLib\_TransactionData, 78
- getRecipientAccountNumber
  - SofortLib\_TransactionData, 78
- getRecipientBankCode
  - SofortLib\_TransactionData, 78
- getRecipientBankName
  - SofortLib\_TransactionData, 79
- getRecipientBic
  - SofortLib\_TransactionData, 79
- getRecipientCountryCode
  - SofortLib\_TransactionData, 79
- getRecipientHolder
  - SofortLib\_TransactionData, 79
- getRecipientIban
  - SofortLib\_TransactionData, 80
- getRelatedBanks
  - SofortLib\_iDealClassic, 50
- getSenderAccountNumber
  - SofortLib\_TransactionData, 80
- getSenderBankCode
  - SofortLib\_TransactionData, 80
- getSenderBankName
  - SofortLib\_TransactionData, 80
- getSenderBic
  - SofortLib\_TransactionData, 81
- getSenderCountryCode
  - SofortLib\_TransactionData, 81
- getSenderHolder
  - SofortLib\_TransactionData, 81
- getSenderIban
  - SofortLib\_TransactionData, 81

- getShippingAddress
  - SofortLib\_TransactionData, [82](#)
- getSofortdauer AuftragAllPaymentsReceived
  - SofortLib\_TransactionData, [82](#)
- getSofortdauer AuftragInterval
  - SofortLib\_TransactionData, [82](#)
- getSofortdauer AuftragLastPaymentReceived
  - SofortLib\_TransactionData, [82](#)
- getSofortdauer AuftragMinimumPayments
  - SofortLib\_TransactionData, [83](#)
- getSofortdauer AuftragNumberOfPaymentsPending
  - SofortLib\_TransactionData, [83](#)
- getSofortdauer AuftragNumberOfPaymentsReceived
  - SofortLib\_TransactionData, [83](#)
- getSofortdauer AuftragPaymentCount
  - SofortLib\_TransactionData, [83](#)
- getSofortdauer AuftragPaymentReceived
  - SofortLib\_TransactionData, [84](#)
- getSofortdauer AuftragPayments
  - SofortLib\_TransactionData, [84](#)
- getSofortdauer AuftragPaymentsReceived
  - SofortLib\_TransactionData, [84](#)
- getSofortdauer AuftragPaymentsSum
  - SofortLib\_TransactionData, [84](#)
- getSofortdauer AuftragStartDate
  - SofortLib\_TransactionData, [85](#)
- getSofortdauer AuftragTotalPayments
  - SofortLib\_TransactionData, [85](#)
- getState
  - PnagInvoice, [21](#)
- getStatus
  - PnagInvoice, [21](#)
  - SofortLib\_TransactionData, [85](#)
- getStatusModifiedTime
  - SofortLib\_TransactionData, [85](#)
- getStatusOfInvoice
  - PnagInvoice, [21](#)
- getStatusReason
  - PnagInvoice, [22](#)
  - SofortLib\_TransactionData, [86](#)
- getSupportedHashAlgorithm
  - SofortLib\_-
    - SofortueberweisungClassic, [68](#)
- getSupportedHashAlgorithms
  - SofortLib\_-
    - SofortueberweisungClassic, [69](#)
- getTime
  - SofortLib\_TransactionData, [86](#)
- getTransaction
  - SofortLib\_TransactionData, [86](#)
- getTransactionData
  - PnagInvoice, [22](#)
- getTransactionId
  - PnagInvoice, [22](#)
  - SofortLib\_Debit, [45](#)
  - SofortLib\_Multipay, [54](#)
- getUserVariable
  - SofortLib\_TransactionData, [86](#)
- getWarnings
  - PnagInvoice, [22](#)
- getSofortLib
  - SofortLib, [33](#)
- handleErrors
  - SofortLib, [33](#)
- isError
  - PnagInvoice, [22](#)
  - SofortLib, [33](#)
- isLastschrift
  - SofortLib\_TransactionData, [87](#)
- isLoss
  - SofortLib\_TransactionData, [87](#)
- isPending
  - SofortLib\_TransactionData, [87](#)
- isReceived
  - SofortLib\_TransactionData, [87](#)
- isRefunded
  - SofortLib\_TransactionData, [88](#)
- isSofortdauer Auftrag
  - SofortLib\_TransactionData, [88](#)
- isSofortlastschrift
  - SofortLib\_TransactionData, [88](#)
- isSofortrechnung
  - SofortLib\_TransactionData, [88](#)
- isSofortueberweisung
  - SofortLib\_TransactionData, [89](#)
- isSofortvorkasse
  - SofortLib\_TransactionData, [89](#)
- isTest
  - SofortLib\_TransactionData, [89](#)
- isWarning
  - PnagInvoice, [23](#)
  - SofortLib, [34](#)
- log
  - PnagInvoice, [23](#)
  - SofortLib, [34](#)
- logError

- PnagInvoice, [23](#)
  - SofortLib, [34](#)
- logWarning
  - PnagInvoice, [23](#)
  - SofortLib, [34](#)
- PnagInvoice, [13](#)
  - \_\_construct, [15](#)
  - addInvoiceAddress, [15](#)
  - addItemToInvoice, [16](#)
  - addShippingAddress, [16](#)
  - addShippingAddresss, [17](#)
  - addUserVariable, [17](#)
  - cancelInvoice, [17](#)
  - checkout, [18](#)
  - confirmInvoice, [18](#)
  - disableLog, [18](#)
  - enableLog, [18](#)
  - getAmount, [18](#)
  - getConstantById, [19](#)
  - getConstantByName, [19](#)
  - getError, [19](#)
  - getErrorCodes, [19](#)
  - getErrors, [19](#)
  - getInvoice, [19](#)
  - getInvoiceObjection, [20](#)
  - getInvoiceStatus, [20](#)
  - getInvoiceTye, [20](#)
  - getInvoiceUrl, [20](#)
  - getItems, [20](#)
  - getLanguageCode, [21](#)
  - getPaymentMethod, [21](#)
  - getPaymentUrl, [21](#)
  - getState, [21](#)
  - getStatus, [21](#)
  - getStatusOfInvoice, [21](#)
  - getStatusReason, [22](#)
  - getTransactionData, [22](#)
  - getTransactionId, [22](#)
  - getWarnings, [22](#)
  - isError, [22](#)
  - isWarning, [23](#)
  - log, [23](#)
  - logError, [23](#)
  - logWarning, [23](#)
  - refreshTransactionData, [24](#)
  - removeItemfromInvoice, [24](#)
  - setAbortUrl, [24](#)
  - setAmount, [24](#)
  - setBitmask, [24](#)
  - setCustomerId, [25](#)
  - setDebitorVatNumber, [25](#)
  - setEmailCustomer, [25](#)
  - setInvoiceObjection, [25](#)
  - setInvoiceStatus, [25](#)
  - setInvoiceUrl, [26](#)
  - setItems, [26](#)
  - setLanguageCode, [26](#)
  - setNotificationUrl, [26](#)
  - setOrderId, [26](#)
  - setPaymentMethod, [27](#)
  - setPhoneNumberCustomer, [27](#)
  - setReason, [27](#)
  - setSofortrechnung, [27](#)
  - setState, [27](#)
  - setStatus, [28](#)
  - setStatusOfInvoice, [28](#)
  - setStatusReason, [28](#)
  - setSuccessUrl, [28](#)
  - setTime, [29](#)
  - setTimeout, [29](#)
  - setTimeoutUrl, [29](#)
  - setTransaction, [29](#)
  - setTransactionId, [29](#)
  - setVersion, [30](#)
  - updateInvoice, [30](#)
  - updateOrderNumber, [30](#)
- refreshTransactionData
  - PnagInvoice, [24](#)
- removeItem
  - SofortLib\_ConfirmSr, [42](#)
- removeItemfromInvoice
  - PnagInvoice, [24](#)
- removeSofortDauerauftrag
  - SofortLib\_CancelSa, [36](#)
- removeSofortrechnungItem
  - SofortLib\_Multipay, [54](#)
- sendRequest
  - SofortLib\_Debit, [45](#)
  - SofortLib\_Refund, [66](#)
- sendValidationRequest
  - SofortLib\_Multipay, [55](#)
- setAbortUrl
  - PnagInvoice, [24](#)
  - SofortLib\_CancelSa, [36](#)
  - SofortLib\_Multipay, [55](#)
  - SofortLib\_-
    - SofortueberweisungClassic,

- 69
- setAmount
  - PnagInvoice, 24
  - SofortLib\_Debit, 45
  - SofortLib\_Multipay, 55
- setApiVersion
  - SofortLib, 35
- setBitmask
  - PnagInvoice, 24
- setComment
  - SofortLib\_CancelSr, 39
  - SofortLib\_ConfirmSr, 43
  - SofortLib\_EditSr, 48
- setCustomerId
  - PnagInvoice, 25
- setDate
  - SofortLib\_Debit, 45
- setDebitorVatNumber
  - PnagInvoice, 25
  - SofortLib\_Multipay, 55
- setEmailCustomer
  - PnagInvoice, 25
  - SofortLib\_Multipay, 56
- setInvoiceObjection
  - PnagInvoice, 25
- setInvoiceStatus
  - PnagInvoice, 25
- setInvoiceUrl
  - PnagInvoice, 26
- setItems
  - PnagInvoice, 26
- setLanguageCode
  - PnagInvoice, 26
  - SofortLib\_Multipay, 56
- setLastschrift
  - SofortLib\_Multipay, 56
- setLastschriftAddress
  - SofortLib\_Multipay, 56
- setLogDisabled
  - SofortLib, 35
- setLogEnabled
  - SofortLib, 35
- setLogger
  - SofortLib, 35
- setNotificationEmail
  - SofortLib\_Multipay, 57
- setNotificationUrl
  - PnagInvoice, 26
  - SofortLib\_Multipay, 57
- SofortLib\_-
  - SofortueberweisungClassic, 69
- setNumber
  - SofortLib\_TransactionData, 89
- setOrderId
  - PnagInvoice, 26
- setPaymentMethod
  - PnagInvoice, 27
- setPhoneNumberCustomer
  - PnagInvoice, 27
  - SofortLib\_Multipay, 57
- setProjectId
  - SofortLib\_Debit, 45
- setReason
  - PnagInvoice, 27
  - SofortLib\_Debit, 46
  - SofortLib\_Multipay, 58
  - SofortLib\_-
    - SofortueberweisungClassic, 69
- setSenderAccount
  - SofortLib\_Debit, 46
  - SofortLib\_Multipay, 58
  - SofortLib\_Refund, 67
- setSenderAccountNumber
  - SofortLib\_Debit, 46
- setSenderBankCode
  - SofortLib\_Debit, 46
  - SofortLib\_iDealClassic, 50
- setSenderCountryId
  - SofortLib\_iDealClassic, 50
- setSenderHolder
  - SofortLib\_Debit, 47
- setSofortDauerauftrag
  - SofortLib\_Multipay, 58
- setSofortDauerauftragInterval
  - SofortLib\_Multipay, 58
- setSofortDauerauftragMinimumPayments
  - SofortLib\_Multipay, 59
- setSofortDauerauftragStartDate
  - SofortLib\_Multipay, 59
- setSofortDauerauftragTotalPayments
  - SofortLib\_Multipay, 59
- setSofortlastschrift
  - SofortLib\_Multipay, 59
- setSofortlastschriftAddress
  - SofortLib\_Multipay, 60
- setSofortrechnung
  - PnagInvoice, 27

- SofortLib\_Multipay, 60
- setSofortrechnungCustomerId
  - SofortLib\_Multipay, 60
- setSofortrechnungInvoiceAddress
  - SofortLib\_Multipay, 61
- setSofortrechnungOrderId
  - SofortLib\_Multipay, 61
- setSofortrechnungShippingAddress
  - SofortLib\_Multipay, 61
- setSofortueberweisung
  - SofortLib\_Multipay, 62
- setSofortueberweisungCustomerprotection
  - SofortLib\_Multipay, 62
- setSofortvorkasse
  - SofortLib\_Multipay, 62
- setSofortvorkasseCustomerprotection
  - SofortLib\_Multipay, 63
- setState
  - PnagInvoice, 27
- setStatus
  - PnagInvoice, 28
- setStatusOfInvoice
  - PnagInvoice, 28
- setStatusReason
  - PnagInvoice, 28
- setSuccessUrl
  - PnagInvoice, 28
  - SofortLib\_CancelSa, 37
  - SofortLib\_Multipay, 63
  - SofortLib\_-
    - SofortueberweisungClassic, 70
- setTime
  - PnagInvoice, 29
  - SofortLib\_TransactionData, 90
- setTimeout
  - PnagInvoice, 29
  - SofortLib\_Multipay, 63
- setTimeoutUrl
  - PnagInvoice, 29
  - SofortLib\_CancelSa, 37
  - SofortLib\_Multipay, 63
- setTransaction
  - PnagInvoice, 29
  - SofortLib\_CancelSa, 37
  - SofortLib\_CancelSr, 39
  - SofortLib\_ConfirmSr, 43
  - SofortLib\_TransactionData, 90
- setTransactionId
  - PnagInvoice, 29
- setVersion
  - PnagInvoice, 30
  - SofortLib\_Multipay, 64
- SofortLib, 30
  - \_\_construct, 31
  - \_sendMessage, 32
  - deleteAllErrors, 32
  - deleteAllWarnings, 32
  - disableLog, 32
  - enableLog, 32
  - error, 32
  - fatalError, 32
  - getError, 32
  - getErrors, 33
  - getWarnings, 33
  - handleErrors, 33
  - isError, 33
  - isWarning, 34
  - log, 34
  - logError, 34
  - logWarning, 34
  - setApiVersion, 35
  - setLogDisabled, 35
  - setLogEnabled, 35
  - setLogger, 35
- sofortLib, 11
- SofortLib\_CancelSa, 35
  - \_\_construct, 36
  - removeSofortDauerauftrag, 36
  - setAbortUrl, 36
  - setSuccessUrl, 37
  - setTimeoutUrl, 37
  - setTransaction, 37
- SofortLib\_CancelSr, 38
  - \_\_construct, 38
  - cancelInvoice, 38
  - getInvoiceUrl, 39
  - setComment, 39
  - setTransaction, 39
- SofortLib\_ClassicNotification, 39
  - \_getHashHexValue, 40
- SofortLib\_ConfirmSr, 40
  - \_\_construct, 41
  - addItem, 41
  - cancelInvoice, 42
  - confirmInvoice, 42
  - getInvoiceUrl, 42
  - removeItem, 42
  - setComment, 43
  - setTransaction, 43



- updateCart, [43](#)
- SofortLib\_Debit, [44](#)
  - addReason, [44](#)
  - addUserVariable, [44](#)
  - getTransactionId, [45](#)
  - sendRequest, [45](#)
  - setAmount, [45](#)
  - setDate, [45](#)
  - setProjectId, [45](#)
  - setReason, [46](#)
  - setSenderAccount, [46](#)
  - setSenderAccountNumber, [46](#)
  - setSenderBankCode, [46](#)
  - setSenderHolder, [47](#)
- SofortLib\_EditSr, [47](#)
  - \_\_construct, [48](#)
  - addItem, [48](#)
  - getInvoiceUrl, [48](#)
  - setComment, [48](#)
- SofortLib\_iDeal\_Banks, [49](#)
- SofortLib\_iDealClassic, [49](#)
  - getRelatedBanks, [50](#)
  - setSenderBankCode, [50](#)
  - setSenderCountryId, [50](#)
- SofortLib\_Multipay, [51](#)
  - \_\_construct, [53](#)
  - addNotificationEmail, [53](#)
  - addNotificationUrl, [53](#)
  - addSofortrechnungItem, [53](#)
  - addUserVariable, [54](#)
  - getPaymentUrl, [54](#)
  - getTransactionId, [54](#)
  - removeSofortrechnungItem, [54](#)
  - sendValidationRequest, [55](#)
  - setAbortUrl, [55](#)
  - setAmount, [55](#)
  - setDebitorVatNumber, [55](#)
  - setEmailCustomer, [56](#)
  - setLanguageCode, [56](#)
  - setLastschrift, [56](#)
  - setLastschriftAddress, [56](#)
  - setNotificationEmail, [57](#)
  - setNotificationUrl, [57](#)
  - setPhoneNumberCustomer, [57](#)
  - setReason, [58](#)
  - setSenderAccount, [58](#)
  - setSofortDauerauftrag, [58](#)
  - setSofortDauerauftragInterval, [58](#)
  - setSofortDauerauftragMinimumPayments, [59](#)
  - setSofortDauerauftragStartDate, [59](#)
  - setSofortDauerauftragTotalPayments, [59](#)
  - setSofortlastschrift, [59](#)
  - setSofortlastschriftAddress, [60](#)
  - setSofortrechnung, [60](#)
  - setSofortrechnungCustomerId, [60](#)
  - setSofortrechnungInvoiceAddress, [61](#)
  - setSofortrechnungOrderId, [61](#)
  - setSofortrechnungShippingAddress, [61](#)
  - setSofortueberweisung, [62](#)
  - setSofortueberweisungCustomerprotection, [62](#)
  - setSofortvorkasse, [62](#)
  - setSofortvorkasseCustomerprotection, [63](#)
  - setSuccessUrl, [63](#)
  - setTimeout, [63](#)
  - setTimeoutUrl, [63](#)
  - setVersion, [64](#)
  - updateSofortrechnungItem, [64](#)
- SofortLib\_Notification, [64](#)
  - \_\_construct, [65](#)
  - getNotification, [65](#)
- SofortLib\_Refund, [66](#)
  - addRefund, [66](#)
  - sendRequest, [66](#)
  - setSenderAccount, [67](#)
- SofortLib\_SofortueberweisungClassic, [67](#)
  - generatePassword, [68](#)
  - getHashHexValue, [68](#)
  - getSupportedHashAlgorithm, [68](#)
  - getSupportedHashAlgorithms, [69](#)
  - setAbortUrl, [69](#)
  - setNotificationUrl, [69](#)
  - setReason, [69](#)
  - setSuccessUrl, [70](#)
- SofortLib\_TransactionData, [70](#)
  - addTransaction, [72](#)
  - getAmount, [72](#)
  - getAmountRefunded, [73](#)
  - getConsumerProtection, [73](#)
  - getCurrency, [73](#)
  - getInvoiceAddress, [73](#)
  - getInvoiceBankAccountNumber, [74](#)
  - getInvoiceBankCode, [74](#)
  - getInvoiceBankHolder, [74](#)

- getInvoiceBankName, [74](#)
- getInvoiceDate, [75](#)
- getInvoiceDebitorText, [75](#)
- getInvoiceDueDate, [75](#)
- getInvoiceNumber, [75](#)
- getInvoiceObjection, [76](#)
- getInvoiceReason, [76](#)
- getInvoiceStatus, [76](#)
- getInvoiceType, [76](#)
- getInvoiceUrl, [77](#)
- getItems, [77](#)
- getLanguageCode, [77](#)
- getPaymentMethod, [77](#)
- getProjectId, [78](#)
- getReason, [78](#)
- getRecipientAccountNumber, [78](#)
- getRecipientBankCode, [78](#)
- getRecipientBankName, [79](#)
- getRecipientBic, [79](#)
- getRecipientCountryCode, [79](#)
- getRecipientHolder, [79](#)
- getRecipientIban, [80](#)
- getSenderAccountNumber, [80](#)
- getSenderBankCode, [80](#)
- getSenderBankName, [80](#)
- getSenderBic, [81](#)
- getSenderCountryCode, [81](#)
- getSenderHolder, [81](#)
- getSenderIban, [81](#)
- getShippingAddress, [82](#)
- getSofortdauer AuftragAllPaymentsReceived, [82](#)
- getSofortdauer AuftragInterval, [82](#)
- getSofortdauer AuftragLastPaymentReceived, [82](#)
- getSofortdauer AuftragMinimumPayments, [83](#)
- getSofortdauer AuftragNumberOfPaymentsPending, [83](#)
- getSofortdauer AuftragNumberOfPaymentsReceived, [83](#)
- getSofortdauer AuftragPaymentCount, [83](#)
- getSofortdauer AuftragPaymentReceived, [84](#)
- getSofortdauer AuftragPayments, [84](#)
- getSofortdauer AuftragPaymentsReceived, [84](#)
- getSofortdauer AuftragPaymentsSum, [84](#)
- getSofortdauer AuftragStartDate, [85](#)
- getSofortdauer AuftragTotalPayments, [85](#)
- getStatus, [85](#)
- getStatusModifiedTime, [85](#)
- getStatusReason, [86](#)
- getTime, [86](#)
- getTransaction, [86](#)
- getUserVariable, [86](#)
- isLastschrift, [87](#)
- isLoss, [87](#)
- isPending, [87](#)
- isReceived, [87](#)
- isRefunded, [88](#)
- isSofortdauer Auftrag, [88](#)
- isSofortlastschrift, [88](#)
- isSofortrechnung, [88](#)
- isSofortueberweisung, [89](#)
- isSofortvorkasse, [89](#)
- isTest, [89](#)
- setNumber, [89](#)
- setTime, [90](#)
- setTransaction, [90](#)
- updateCart
  - SofortLib\_ConfirmSr, [43](#)
- updateInvoice
  - PnagInvoice, [30](#)
- updateOrderNumber
  - PnagInvoice, [30](#)
- updateSofortrechnungItem
  - SofortLib\_Multipay, [64](#)