



# Chapter 4:

# Deep learning in practice



# Outlines

1. Convolutional networks
2. Recurrent neural networks
3. Commonly used deep learning architectures
4. How to build working deep learning model from scratch
5. Project and lab



# Recurrent neural networks

---

## 1. Support for sequences in neural networks:

- A major characteristic of convolutional neural networks is that they have no memory.
- Each input shown to them is processed independently, with no state kept in between inputs.
- In order to process a sequence or a temporal series of data points, it has to show the entire sequence to the network at once: turn it into a single data point.
- Such networks are called feedforward networks



# Recurrent neural networks

---


## 1. Support for sequences in neural networks:

- As we're reading the present sentence, we're processing it word by word while keeping memories of what came before.
- This method gives us a fluid representation of the meaning conveyed by this sentence.
- Biological intelligence processes information incrementally while maintaining an internal model of what it's processing.
- New information continue to come in.

# Recurrent neural networks

## 1. Support for sequences in neural networks:


- A recurrent neural network (RNN) processes sequences by iterating through the sequence elements and maintaining a state containing information relative to what it has seen so far.
- An RNN is a type of neural network that has an internal loop.



# Recurrent neural networks

## 1. Support for sequences in neural networks:

- The state of the RNN is reset between processing two different.
- One sequence, a single data point:
  - ✓ A single input to the network
- This data point is no longer processed in a single step, but the network internally loops over sequence elements.





# Recurrent neural networks

---


## 2. Architecture of RNN:

- The RNN is a for loop that reuses quantities computed during the previous iteration of the loop.
- There are many different RNNs fitting this definition.
- RNNs are characterized by their step function.

# Recurrent neural networks

## 2. Architecture of RNN:

- The RNN takes as input a sequence of vectors that will be encoded as a 2D tensor of size (**timesteps**, **input\_features**).






# Recurrent neural networks

## 2. Architecture of RNN:

- The RNN loops over **timesteps**, and at each **timestep**, it considers its current state at  $t$  and the input at  $t$  (of shape **(input\_features,)**).
- The input and current state at  $t$  will be combined to obtain the output at  $t$ .





# Recurrent neural networks

---

## 2. Architecture of RNN:

- The next step is to be this previous output.
- For the first **timestep**, the previous output isn't define - there is no current state.
- We can initialize the state as an **zero** vector called the **initial state** of the network.
- The final output is a 2D tensor of shape (timesteps, output\_features), where each timestep is the output of the loop at time t.
- Each timestep t in the output tensor contains information about timesteps 0 to t in the input sequence.
- We don't need the full sequence of outputs; we just need the last output.



# Recurrent neural networks

## 2. Architecture of RNN:

```
import numpy as np
```

```
timesteps = 100 # Number of timesteps in the input sequence
input_features = 32 # Dimensionality of the input feature space
output_features = 64 # Dimensionality of the output feature space
# Input data: random noise for the sake of the example
inputs = np.random.random((timesteps, input_features))
state_t = np.zeros((output_features,)) # Initial state: an all-zero vector
# Creates random weight matrices
W = np.random.random((output_features, input_features))
U = np.random.random((output_features, output_features))
b = np.random.random((output_features,))
successive_outputs = []
for input_t in inputs: # input_t is a vector of shape (input_features,)
    # Combines the input with the current state (the previous output)
    # to obtain the current output
    output_t = np.tanh(np.dot(W, input_t) + np.dot(U, state_t) + b)
    successive_outputs.append(output_t) # Stores this output in a list
    # Updates the state of the network for the next timestep
    state_t = output_t

# The final output is a 2D tensor of shape (timesteps, output_features)
final_output_sequence = np.concatenate(successive_outputs, axis=0)
```



# Recurrent neural networks

---

## 3. Keras for RNN:

- Keras has the `SimpleRNN` layer to build an RNN model.

```
from keras.layers import SimpleRNN
```

- The `SimpleRNN` processes batches of sequences, like all other Keras layers.
- The `SimpleRNN` takes inputs of shape (`batch_size`, `timesteps`, `input_features`), rather than (`timesteps`, `input_features`).



# Recurrent neural networks

---

## 3. Keras for RNN:

- The SimpleRNN can be run in two different modes:
  - ✓ Return the full sequences of successive outputs for each timestep (a 3D tensor of shape (`batch_size`, `timesteps`, `output_features`)).
  - ✓ Return the last output for each input sequence (a 2D tensor of shape (`batch_size`, `output_features`))



# Recurrent neural networks

---

## 3. Keras for RNN:

```
from keras.models import Sequential
from keras.layers import SimpleRNN
from keras.layers import Embedding

model = Sequential()
model.add(Embedding(10000, 32))
model.add(SimpleRNN(32))
model.summary()
```



# Recurrent neural networks

## 3. Keras for RNN:

```
Model: "sequential"
```

Layer (type)	Output Shape	Param #
=====		
embedding (Embedding)	(None, None, 32)	320000
-----		
simple_rnn (SimpleRNN)	(None, 32)	2080
=====		

```
Total params: 322,080
```

```
Trainable params: 322,080
```

```
Non-trainable params: 0
```

```
-----
```



# Recurrent neural networks

---

## 3. Keras for RNN:

```
from keras.models import Sequential
from keras.layers import SimpleRNN
from keras.layers import Embedding

# returns the full state sequence:
model = Sequential()
model.add(Embedding(10000, 32))
model.add(SimpleRNN(32, return_sequences=True))
model.summary()
```





# Recurrent neural networks

## 3. Keras for RNN:

```
Model: "sequential"
```

Layer (type)	Output Shape	Param #
=====		
embedding (Embedding)	(None, None, 32)	320000
-----		
simple_rnn (SimpleRNN)	(None, None, 32)	2080
=====		
Total params: 322,080		
Trainable params: 322,080		
Non-trainable params: 0		
-----		



# Recurrent neural networks

---

## 3. Keras for RNN:

- We can stack several recurrent layers one after the other in order to increase the representational power of a network.
- In such a setup, we have to get all of the intermediate layers to return a full sequence of outputs.

```
model = Sequential()
model.add(Embedding(10000, 32))
model.add(SimpleRNN(32, return_sequences=True))
model.add(SimpleRNN(32, return_sequences=True))
model.add(SimpleRNN(32, return_sequences=True))
model.add(SimpleRNN(32)) # Last layer only returns the last output
model.summary()
```



# Recurrent neural networks

## 3. Keras for RNN:

Model: "sequential"

Layer (type)	Output Shape	Param #
embedding (Embedding)	(None, None, 32)	320000
simple_rnn (SimpleRNN)	(None, None, 32)	2080
simple_rnn_1 (SimpleRNN)	(None, None, 32)	2080
simple_rnn_2 (SimpleRNN)	(None, None, 32)	2080
simple_rnn_3 (SimpleRNN)	(None, 32)	2080

Total params: 328,320  
Trainable params: 328,320  
Non-trainable params: 0



# Recurrent neural networks

---

## 3. Keras for RNN - IMDB:

```
from keras.datasets import imdb
from keras.models import Sequential
from keras.preprocessing import sequence
from keras.layers.embeddings import Embedding
from keras.layers import Dense, SimpleRNN
import matplotlib.pyplot as plt

max_features = 10000 # Number of words to consider as features
# Cuts off texts after this many words (among the max_features most common words)
maxlen = 500
batch_size = 32
```



# Recurrent neural networks

---

## 3. Keras for RNN - IMDB:

```
# Preparing the IMDB data
print('Loading data...')
(input_train, y_train), (input_test, y_test) = imdb.load_data(
    num_words=max_features)
print(len(input_train), 'train sequences')
print(len(input_test), 'test sequences')
print('Pad sequences (samples x time)')
input_train = sequence.pad_sequences(input_train, maxlen=maxlen)
input_test = sequence.pad_sequences(input_test, maxlen=maxlen)
print('input_train shape:', input_train.shape)
print('input_test shape:', input_test.shape)
```



# Recurrent neural networks

---

## 3. Keras for RNN - IMDB:

```
# Training the model with Embedding and SimpleRNN layers
model = Sequential()
model.add(Embedding(max_features, 32))
model.add(SimpleRNN(32))
model.add(Dense(1, activation='sigmoid'))
model.compile(optimizer='rmsprop', loss='binary_crossentropy', metrics=['acc'])
history = model.fit(input_train, y_train,
                    epochs=5,
                    batch_size=128,
                    validation_split=0.2)
```





# Recurrent neural networks


## 3. Keras for RNN - IMDB:

```
# Plotting results
acc = history.history['acc']
val_acc = history.history['val_acc']
loss = history.history['loss']
val_loss = history.history['val_loss']
epochs = range(1, len(acc) + 1)
plt.plot(epochs, acc, 'bo', label='Training acc')
plt.plot(epochs, val_acc, 'b', label='Validation acc')

plt.title('Training and validation accuracy')
plt.legend()
plt.figure()
plt.plot(epochs, loss, 'bo', label='Training loss')
plt.plot(epochs, val_loss, 'b', label='Validation loss')
plt.title('Training and validation loss')
plt.legend()
plt.show()
```

# Recurrent neural networks

## 3. Keras for RNN - IMDB:





# Recurrent neural networks

## 3. Keras for RNN - IMDB:

