

Comment	Description	Designator
Cap Pol	Polarized Capacitor	C1
1000uF/16V	Cap 1000uF/16V - 220uF/50V	C2
100nF	Cap np 1pF - 472pF	C3, C4, C5, C6, C9, C1
22pF	Cap np 1pF - 472pF	C7, C8
PROGRAM	Header IDC, 6 x 1 Pin Vertical 2.54mm Pitch	C10
Diode 1N5404	Default Diode	Diode 1
AOM12864A0-1.54WW	Non-Touch Graphic LCD Display Module - W	DS1
ULN2003A	High-Voltage, High-Current Darlington Array	IC1
LM7805	On ap +, from + 5 to + 24VDC	IC2
Jac DC	Jac DC input	JDC1
JP4	Connector 4	JP1, JP4
JP3	Connector 3	JP2, JP3
LCD16x2A	LCD display 16 char, 2 line	LCD1
LED	LED Single colour Green and Red	LED1, LED2, LED4, LE
LED	LED Single colour Green and Red	LED3
Header 3 - M	Header, 3-Pin, Medium	P1, P2, P3, P4
Header 7	Header, 7-Pin	P5
Header 5	Header, 5-Pin	P6, P7
TIP2955	TIP2955 Series PNP 60 V 15 A Complement	Q1
1k	Resistor 1/4W	R1, R2, R4, R5, R6, R8
1R2/2W	Resistor 2W	R3
10K	Resistor 1/4W	R7
2.2k	Resistor 1/4W	R10
220	Resistor 1/4W	R11
Relay 10A/12V	Relay SPDT, 10A - 12VDC 5 Pin	RL1, RL2, RL3, RL4
SW	Switch button 2 pin	SW1, SW3, SW4, SW5
S POWER	Switch 102 on Broad	SW2
S LCD	Switch 102 on Broad	SW7
PIC16F877A/IP	MCU 8bit 8KB 4-5.5V 20MHz DIP40	U1
ESP32-DEVKITC	ESP32-WROOM-32UE series Transceiver; 8	U2
10K	Var Resistor	VR1
20Mhz	Crystal, 32.768 KHz, -40 to 85 degC, 3.2 x 1.	X1

Footprint	LibRef	Quantity
RADIAL B	Cap Pol	1
CAP_1000UF_16V	CP4	1
CN1	CN1	6
CN1	CN1	2
Header6	Header6	1
Diode 1N4007	Diode	1
LCD_AOM12864A0-1.5	AOM12864A0-1.54WW	1
ULN2003A	ULN2003A	1
QTO-220H3	LM78xx_1	1
DC-IN	DCIN	1
CON4	Con4	2
CON3	Con3	2
LCD16X2N	LCD16x2	1
LED-3	LED	4
LED3R	LED	1
Medium - Header 3	Header 3 - M	4
Header 7	Header 7	1
Header 5	Header 5	2
TOP3AV_TIP2955(Prin	TIP2955	1
R1/4W	R1/4W	7
R2W	R2W	1
R1/4W	R1/4W	1
R1/4W	R1/4W	1
R1/4W	R1/4W	1
RL_10A_5V	Relay 1	4
BUTTON 2PIN TRON	SW2	5
SW102	SW102A	1
SW102	SW102A	1
DIP-40	PIC16F877A/IP	1
MODULE_ESP32-DEV	ESP32-DEVKITC	1
VR	VR	1
XT2	XT2	1