tencontreciterator il 2001/6/A 3:19 DM

```
struct TensorKeyIterator{I<:Sector, F1<:FusionTree{I}, F2<:FusionTree{I}}
    rowr::SectorDict{I, FusionTreeDict{F1, UnitRange{Int}}}
    colr::SectorDict{I, FusionTreeDict{F2, UnitRange{Int}}}
end
struct TensorPairIterator{I<:Sector, F1<:FusionTree{I}, F2<:FusionTree{I},
A<:DenseMatrix}
    rowr::SectorDict{I, FusionTreeDict{F1, UnitRange{Int}}}
    colr::SectorDict{I, FusionTreeDict{F2, UnitRange{Int}}}
    data::SectorDict{I, A}
end
const TensorIterator{I<:Sector, F1<:FusionTree{I}, F2<:FusionTree{I}} =</pre>
Union{TensorKeyIterator{I, F<sub>1</sub>, F<sub>2</sub>}, TensorPairIterator{I, F<sub>1</sub>, F<sub>2</sub>}}
Base.IteratorSize(::Type{<:TensorIterator}) = Base.HasLength()</pre>
Base.IteratorEltype(::Type{<:TensorIterator}) = Base.HasEltype()</pre>
Base.eltype(T::Type{TensorKeyIterator{I, F_1, F_2}) where {I, F_1, F_2} = Tuple{F_1,
F<sub>2</sub>}
function Base.length(t::TensorKeyIterator)
    for (rowdict, coldict) in zip(values(t.rowr), values(t.colr))
        l += length(rowdict) * length(coldict)
    end
    return l
end
function Base.iterate(it::TensorKeyIterator)
    i = 1
    i > length(it.rowr) && return nothing
    rowit, colit = it.rowr.values[i], it.colr.values[i]
    rownext = iterate(rowit)
    colnext = iterate(colit)
    # while rownext === nothing || colnext === nothing: Julia did not infer that
      after while loop, both were not nothing
    while true
        if rownext === nothing
            i += 1
        elseif colnext === nothing
            i += 1
        else
            break
        end
        i > length(it.rowr) && return nothing
        rowit, colit = it.rowr.values[i], it.colr.values[i]
        rownext = iterate(rowit)
        colnext = iterate(colit)
    end
    (f1, r1), rowstate = rownext
    (f2, r2), colstate = colnext
    return (f1, f2), (f2, i, rowstate, colstate)
end
function Base.iterate(it::TensorKeyIterator, state)
```

tensortreeiterstor il 2001/6/4 3:19 PM

```
(f2, i, rowstate, colstate) = state
rowit, colit = it.rowr.values[i], it.colr.values[i]
rownext = iterate(rowit, rowstate)
if rownext !== nothing
    (f1, r1), rowstate = rownext
    return (f1, f2), (f2, i, rowstate, colstate)
colnext = iterate(colit, colstate)
if colnext !== nothing
    rownext = iterate(rowit) # should not be nothing
    @assert rownext !== nothing
    (f1, r1), rowstate = rownext
    (f2, r2), colstate = colnext
    return (f1, f2), (f2, i, rowstate, colstate)
end
while true
    if rownext === nothing
        i += 1
    elseif colnext === nothing
        i += 1
    else
        break
    end
    i > length(it.rowr) && return nothing
    rowit, colit = it.rowr.values[i], it.colr.values[i]
    rownext = iterate(rowit)
    colnext = iterate(colit)
end
(f1, r1), rowstate = rownext
(f2, r2), colstate = colnext
return (f1, f2), (f2, i, rowstate, colstate)
```

end