ENGR–UH 1000 | Lab 0 Report

Pi (pk2269@nyu.edu)

Sep 8, 2020

Contents

1 Problem Identification and Statement

Computing the distance between two given points in a Cartesian plane, given the Cartesian coordinates of the two points.

2 Gathering of Information and Input/Output Description

3 Test Cases and Algorithm Design

- Get input x_1 from user
- Assign x_1 to variable x_1
- Get input y_1 from user
- Assign y_1 to variable y_1
- Get input x_2 from user
- Assign x_2 to variable x_2
- Get input y_2 from user
- Assign y_2 to variable y_2
- Assign $\sqrt{x}$ to distance
- Print Distance

4 Implementation

5 Software Testing and Verification

% Pandoc math demos

$a^2 + b^2 = c^2$

$v(t) = v_0 + \frac{1}{2}at^2$

$\gamma = \frac{1}{\sqrt{1-v^2/c^2}}$

$\exists x \forall y (Rxy \equiv Ryx)$

$p \wedge q \vDash p$

$\Box \diamond p \equiv \diamond p$

$\int_0^1 x dx = \left[\frac{1}{2}x^2\right]_0^1 = \frac{1}{2}$

$e^x = \sum_{n=0}^{\infty} \frac{x^n}{n!} = \lim_{n \to \infty}(1 + x/n)^n$

```
1  /*-----------------------------------------------*/
2  /* Name: Pi, Student Number: N13394469 */
3  /* Date: Sep 8, 2020. */
4  /* Program: distance.cpp */
5  /* Description: This program computes the distance */
6  /* between two points. */
7  /*-----------------------------------------------*/
8  #include <iostream>
9  #include <cmath>
10 using namespace std;
11 int main()
12 {
13 /* Declare and initialize the variables */
14 double x1 = -1, y1 = -3, x2 = 4, y2 = 6;
15 double length1, length2, distance;
16
17 /* Compute the sides of a right triangle */
18 length1 = x2 - x1;
19 length2 = y2 - y1;
20
21 /* Compute the distance between the two points. */
22 distance = sqrt(length1*length1 + length2*length2);
23
24 /* Print the distance */
25 cout << "The distance between the two points is " << distance << endl;
26  return (0);
27 }
28 /*-------------------------End---------------------*/
```